



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



RF EXPOSURE EVALUATION

Applicant: Unitree

Address: 3rd Floor, Building 1, Fengda Creative Park No.88 Dongliu Road,
Binjiang District Hangzhou, Zhejiang China

FCC ID: 2A5PE-YUSHU004

Product Name: Quadruped Robot

Standard(s): 47 CFR §1.1307, 47 CFR §2.1091
447498 D01 General RF Exposure Guidance v06

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR231168373-RF-00H

Date Of Issue: 2024/3/27

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. RF EXPOSURE EVALUATION	5
1.1 APPLICABLE STANDARD.....	5
1.2 EUT WWAN INFORMATION▲:	6
1.3 CALCULATED RESULT:.....	7

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231168373-RF-00H	Original Report	2024/3/27

1. RF EXPOSURE EVALUATION

1.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

1.2 EUT WWAN Information ▲ :

Operation Modes	Operation Frequency (MHz)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	Max Gain Allowed (dBi)
GSM850	824-849	25.81	1.09	8.60
GSM1900	1850-1910	22.81	1.86	10.19
WCDMA B2	1850-1910	25	1.86	8.00
WCDMA B4	1710-1755	25	1.71	5.00
WCDMA B5	824-849	25	1.09	9.42
LTE B2	1850-1910	25	1.86	8.00
LTE B4	1710-1755	25	1.71	5.00
LTE B5	824-849	25	1.09	9.41
LTE B7	2500-2570	25	2.95	8.00
LTE B12	699-716	25	1.09	8.70
LTE B13	777-787	25	1.09	9.16
LTE B25	1850-1915	25	1.86	8.00
LTE B26	814-849	25	1.09	9.36
LTE B38	2570-2620	25	2.95	8.00
LTE B41	2496-2690	25	2.95	8.00
Note: 1. The devices contain certified WWAN Module, FCC ID: XMR201903EG25G. 2. The WWAN Conducted output power comes from module report.				

1.3 Calculated Result:

Mode	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)			
BDR/EDR	2402-2480	1.50	1.41	6	3.98	20	0.0011	1
BLE	2402-2480	1.50	1.41	4	2.51	20	0.0007	1
2.4G SRD	2400.8-2480	2.49	1.77	6	3.98	20	0.0014	1
2.4G Wi-Fi	2412-2462	2.49	1.77	27	501.19	20	0.1765	1
5.2G Wi-Fi	5180-5240	2.72	1.87	15	31.62	20	0.0118	1
5.8G Wi-Fi	5745-5825	3.11	2.05	16	39.81	20	0.0162	1
WBT	6489.6	6	3.98	-12	0.06	20	<<0.0001	1
GSM850	824-849	1.09	1.29	25.81	381.07	20	0.0978	0.549
GSM1900	1850-1910	1.86	1.53	22.81	190.99	20	0.0581	1
WCDMA B2	1850-1910	1.86	1.53	25	316.23	20	0.0963	1
WCDMA B4	1710-1755	1.71	1.48	25	316.23	20	0.0931	1
WCDMA B5	824-849	1.09	1.29	25	316.23	20	0.0812	0.549
LTE B2	1850-1910	1.86	1.53	25	316.23	20	0.0963	1
LTE B4	1710-1755	1.71	1.48	25	316.23	20	0.0931	1
LTE B5	824-849	1.09	1.29	25	316.23	20	0.0812	0.549
LTE B7	2500-2570	2.95	1.97	25	316.23	20	0.1239	1
LTE B12	699-716	1.09	1.29	25	316.23	20	0.0812	0.466
LTE B13	777-787	1.09	1.29	25	316.23	20	0.0812	0.518
LTE B25	1850-1915	1.86	1.53	25	316.23	20	0.0963	1
LTE B26	814-849	1.09	1.29	25	316.23	20	0.0812	0.543
LTE B38	2570-2620	2.95	1.97	25	316.23	20	0.1239	1
LTE B41	2496-2690	2.95	1.97	25	316.23	20	0.1239	1

For WBT, EIRP(dBm/50MHz) is -40.04+34= -6.04dBm, conducted output power is -6.04-6 =-12.04dBm, so conducted output power including Tune-up Tolerance is -12dBm.

The Bluetooth, Wi-Fi, 2.4G SRD, WBT and WWAN can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{Bluetooth}/S_{limit-Bluetooth}+ S_{WWAN}/S_{limit-WWAN}+ S_{2.4G SRD}/S_{limit-2.4G SRD} + S_{2.4G Wi-Fi}/S_{limit-2.4G Wi-Fi} + S_{WBT}/S_{limit-WBT}$$

$$=0.0011/1+0.0978/0.549+0.0014/1+0.1765/1+0.0001/1$$

$$=0.357$$

$$< 1.0$$

Result: The device meets FCC MPE at **20 cm** distance

===== END OF REPORT =====