

Prüfbericht-Nr.: Test report no.:	CN26V9OF 005	Auftrags-Nr.: Order no.:	27200463	Seite 1 von 11 Page 1 of 11	
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2026-01-05		
Auftraggeber: Client:	YuShu Technology Co., Ltd. 306 Room, Building 1, 88 Dongliu Rd, XiXing Street, Binjiang District, Hangzhou, ZheJiang, China				
Prüfgegenstand: Test item:	R1 Humanoid Robot				
Bezeichnung / Typ-Nr.: Identification / Type no.:	R1 AIR, R1, R1 EDU				
Auftrags-Inhalt: Order content:	Test Report				
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 2: Section 2.1091 RSS-102 Issue 6 December 2023				
Wareneingangsdatum: Date of sample receipt:	2026-04-08	Please refer to photo documents			
Prüfmuster-Nr.: Test sample no:	A004171855-001~003 A004260434-001~002				
Prüfzeitraum: Testing period:	2026-04-30 - 2026-05-14				
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: Test result*:	Pass				
geprüft von: tested by:			genehmigt von: authorized by:		
Datum: Date:	2026-05-18	Signed by: Bell Hu		Ausstellungsdatum: Issue date:	2026-05-18
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2A5PE-YUSHU010				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:			Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested					
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Prüfbericht-Nr.: CN26V9OF 005
Test report no.:

Seite 2 von 11
Page 2 of 11

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN26V9OF 005
Test Report No.:

Seite 3 von 11
Page 3 of 11

Test Summary

3.1.1 RF EXPOSURE COMPLIANCE
RESULT: Pass

Contents

1.	TEST SITES.....	5
1.1	TEST FACILITIES	5
1.2	TRACEABILITY	5
1.3	CALIBRATION.....	5
1.4	LOCATION OF ORIGINAL DATA	5
1.5	STATUS OF FACILITY USED FOR TESTING	5
2.	GENERAL PRODUCT INFORMATION	6
2.1	PRODUCT FUNCTION AND INTENDED USE	6
2.2	RATING AND SYSTEM DETAILS	6
3.	TEST RESULTS	9
3.1	RF EXPOSURE EVALUATION	9
3.1.1	RF Exposure Compliance.....	9

1. Test Sites

1.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

FCC Accreditation Designation No.: CN1260

ISED Wireless Device Testing Laboratory: 25069

1.2 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.3 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.4 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.5 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. General Product Information

2.1 Product Function and Intended Use

The product is a Humanoid Robot which supports Bluetooth, 2.4GHz Wi-Fi, 5GHz Wi-Fi, 2.4GHz SRD and Sub-1GHz wireless technologies.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 Rating and System details

Table 1: General Information of EUT

General Information of EUT	Value
Kind of Equipment:	R1 Humanoid Robot
Type Designation:	R1 AIR, R1, R1 EDU* * All models are electrically identical in RF circuits, main boards and constructions. The only differences among them are the Orin board and camera sensor, which have no impact on RF characteristics. Full evaluations on FCC 15B and ICES-003 were performed for all models respectively. As for RF, full test was performed for model R1 EDU and the worst-cases of radiated spurious emissions were re-checked for R1 AIR, and R1.
FCC ID:	2A5PE-YUSHU010
Operating Voltage:	33.12Vdc Battery Powered
Testing Voltage:	Fully charged battery
Technical Specification of Classic Bluetooth	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Channel Number:	79 channels
Channel Separation:	1MHz
Antenna Type:	Integral Antenna
Antenna Gain:	1.5 dBi (Provided by the Client)
Technical Specification of Bluetooth LE	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Channel Number:	40 channels
Channel Separation:	2MHz
Data Rate:	1Mbps, 2Mbps
Antenna Type:	Integral Antenna
Antenna Gain:	1.5 dBi (Provided by the Client)
Technical Specification of 2.4GHz SRD	
Operating Frequency:	2400.8MHz to 2480MHz
Type of Modulation:	GFSK
Channel Separation:	0.8MHz
Antenna Type:	Integral Antenna

Prüfbericht - Nr.: CN26V9OF 005

Test Report No.:

Seite 7 von 11
Page 7 of 11

Antenna Gain:	2.49 dBi (Provided by the Client)	
Technical Specification of Sub-1GHz		
Frequency Range:	920.6MHz to 923.4MHz	
Type of Modulation:	FSK	
Channel Separation:	0.2MHz	
Antenna Type:	Integral Antenna	
Antenna Gain:	-2.0 dBi (Provided by the Client)	
Technical Specification of 2.4GHz Wi-Fi		
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20)/ax(HE20) 2422 - 2452 MHz for 802.11n(HT40)/ax(HE40)	
Type of Modulation:	DSSS, OFDM, OFDMA	
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 for 802.11n MCS0 ~ MCS12 for 802.11ax (All data rates considered, only the Worst-cases reported.)	
Channel Number:	11 channels for 802.11b/g/n(HT20)/ax(HE20) 7 channels for 802.11n(HT40)/ax(HE40)	
Channel Separation:	5 MHz	
Antenna Type:	Integral Antenna	
Antenna Number:	2Tx2Rx	
Antenna Gain:	2.49 dBi for ANT1, 3.0 dBi for ANT2 (Provided by the Client)	
Smart Antenna Systems:	☒ 802.11b/g	☒ SISO
	☒ 802.11n	☒ SISO, ☒ 2*2 CDD,
	☒ 802.11ax	☒ SISO, ☒ 2*2 CDD,
RU Mode for 802.11ax:	☒ Full RU, ☒ Single RU	
Technical Specification of 5GHz Wi-Fi		
Operating Frequency:	5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz	
Protocol:	802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80	
Type of Modulation:	OFDM, OFDMA	
Channel Number:	5180-5240MHz, 7CHs 5260-5320MHz, 7CHs 5500-5700MHz, 18CHs 5745-5825MHz, 8CHs	
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0~MCS7 for 802.11n MCS0~MCS9 for 802.11ac MCS0 ~ MCS11 for 802.11ax (All data rates considered, only the Worst-cases reported.)	
Channel Separation:	20MHz, 40MHz, 80MHz	
Antenna Type:	Integral Antenna	
Antenna Number:	2Tx2Rx	
Antenna Gain:	3.01 dBi for ANT1, 4.2 dBi for ANT2 (Provided by the Client)	
Smart Antenna Systems:	☒ 802.11a	☒ SISO
	☒ 802.11n	☒ SISO, ☒ 2*2 CDD,
	☒ 802.11ac	☒ SISO, ☒ 2*2 CDD,
	☒ 802.11ax	☒ SISO, ☒ 2*2 CDD

Prüfbericht - Nr.: CN26V9OF 005
Test Report No.:

Seite 8 von 11
Page 8 of 11

RU Mode for 802.11ax:

☒ Full RU, ☒ Single RU

3. Test Results

3.1 RF Exposure Evaluation

3.1.1 RF Exposure Compliance

RESULT:
Pass

Test standard : CFR Title 47 FCC Part 2.1091
KDB 447498 D01 General RF Exposure Guidance v06
RSS-102 Issue 6

Limit : Table 1 of CFR Title 47 FCC Part 1.1310
Section 6.6 of RSS-102 Issue 6

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore, MPE measurement or computational modelling should be used to determine compliance.

3.1.1.1 RF Exposure Compliance Requirement for FCC

a) Radio Frequency Exposure Limit

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

b) Radio Frequency Exposure Calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)
P = power input to the antenna (in appropriate units, e.g., mW)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where: EIRP = equivalent (or effective) isotropically radiated power

c) RF Exposure Calculations for FCC, stand-alone mode

Operating Mode	Max. Peak power incl. tune-up (dBm)	Max. EIRP (dBm)	Distance (cm)	MPE P_d (mW/cm ²)	Limit (mW/cm ²)	Verdict
Bluetooth	4.50	6.00	20	0.0008	1.0	Pass
2.4GHz Wi-Fi	24.00	26.75	20	0.0942	1.0	Pass
2.4GHz SRD	17.00	19.49	20	0.0177	1.0	Pass
5GHz Wi-Fi	22.50	25.51	20	0.0708	1.0	Pass
Sub-1GHz	-10.0	-12.00*	20	0.00001	0.6	Pass

Note: Refer to reports CN26FGKC 002~005 for power data.

*For Sub 1GHz Band, the Peak fundamental signal is 83.26dBuV/m@3m (CN26FGKC 005), i.e. -12.0dBm when converted to EIRP.

d) RF Exposure Calculations for FCC, Simultaneous mode

Per KDB 447498 D01 v06, simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is ≤ 1.0 .

Co-location Mode	Sum of the MPE Ratios	Limit	Verdict
Bluetooth+2.4GHz SRD+ Sub-1GHz +2.4GHz Wi-Fi	0.0008/1.0+0.0177/1.0+0.00001/0.6+0.0942/1.0 =0.113	1.0	Pass
Bluetooth+2.4GHz SRD+ Sub-1GHz +5GHz Wi-Fi	0.0008/1.0+0.0177/1.0+0.00001/0.6+0.0708/1.0 =0.089	1.0	Pass

Note: As the sum of MPE ratios for all simultaneous transmitting antennas is ≤ 1.0 , simultaneous transmission MPE test exclusion will be applied.

e) Conclusion

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.

3.1.1.2 RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

The EUT shall comply with the requirement of RSS-102 section 6.6.

Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

a) RF Exposure Calculations for ISSED, Stand-alone mode

Operating Mode	Max. EIRP incl. tune-up (dBm)	Maximum EIRP (W)	Distance (cm)	Threshold power (W)	Verdict
Bluetooth	6.00	0.0040	20	2.68	Pass
2.4GHz Wi-Fi	26.75	0.4732	20	2.68	Pass
2.4GHz SRD	19.49	0.0889	20	2.68	Pass
5GHz Wi-Fi	25.51	0.3556	20	4.53	Pass
Sub-1GHz	-12.00*	0.0001	20	1.39	Pass

Note: Refer to reports CN26FGKC 002~005 for power data.

*For Sub 1GHz Band, the Peak fundamental signal is 83.26dBuV/m@3m (CN26FGKC 005), i.e. -12.0dBm when converted to EIRP.

The maximum EIRP lower than the threshold power in section 6.6, thus compliant.

b) RF Exposure Calculations for ISSED, Simultaneous mode

Co-location Mode	Sum of the MPE Ratios	Limit	Verdict
Bluetooth+2.4GHz SRD+ Sub-1GHz +2.4GHz Wi-Fi	$0.0040/2.68 + 0.0889/2.68 + 0.0001/1.39 + 0.4732/2.68$ =0.21	1.0	Pass
Bluetooth+2.4GHz SRD+ Sub-1GHz +5GHz Wi-Fi	$0.0040/2.68 + 0.0889/2.68 + 0.0001/1.39 + 0.3556/4.53$ =0.11	1.0	Pass

c) Conclusion

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”