

RF EVALUATION TEST REPORT

Applicant..... : Abbingdon Global Limited
Address..... : 79 SCARISBRICK NEW ROAD SOUTHPORT ENGLAND PR&8 6LJ
Manufacturer..... : Abbingdon Global Limited
Address..... : 79 SCARISBRICK NEW ROAD SOUTHPORT ENGLAND PR&8 6LJ
Factory..... : Abbingdon Global Limited
Address..... : 79 SCARISBRICK NEW ROAD SOUTHPORT ENGLAND PR&8 6LJ
Product Name..... : Professional decoder
Brand Name..... : iFi
Model No. : iDSD PHANTOM
FCC ID..... : 2A5QJIDSDPHANTOM
Measurement Standard..... : 47 CFR PART 2, Section 2.1091
Receipt Date of Samples..... : November 06, 2025
Date of Tested..... : November 06, 2025 to May 21, 2026
Date of Report..... : June 04, 2026

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Jenny Liu / Project Engineer



Approved by

Iori Fan / Authorized Signatory

Table of Contents

1. General Description of EUT	4
2. Test Facility and Location	7
3. Applicable Standards and References.....	8
4. Maximum Permissible Exposure Limit	9
5. RF Exposure Evaluation Results	11

Revision History

Report Number	Description	Issued Date
NTC2511033F01	Initial Issue	2026-06-04

1. General Description of EUT

Product Information	
Product Name:	Professional decoder
Main Model Name:	iDSD PHANTOM
Additional Model Name:	N/A
Model Difference:	N/A
S/N:	2511-7042
Brand Name:	iFi
Hardware version:	Not stated
Software version:	Not stated
Rating:	DC Port: DC 15V 3.5A
Typical Arrangement:	Tabletop
I/O Port:	Refer to the user manual
Accessories Information	
Adapter:	Manufacturer: Powertron Technology Co., Ltd. M/N: LN-1550 Input: AC 100-240V 50/60Hz, 1.5A Output: DC 15V 3.5A
Cable:	Power cord: 1.50m, unshielded, undetachable, with a ferrite core
Other:	Remote*1
Additional information	
Note:	N/A
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification (2.4G WLAN)	
Frequency Range:	2412-2462MHz for IEEE 802.11b/g/n(HT20) 2422-2452MHz for IEEE 802.11n(HT40)
Modulation Technology:	DSSS, OFDM
Modulation Type:	CCK, DQPSK, DBPSK, QPSK, BPSK, 16-QAM, 64-QAM,
Number of Channel:	11 for IEEE 802.11b/g/n(HT20) 7 for IEEE 802.11n(HT40)
Channel Space:	5MHz
Antenna Type:	Dipole antenna
Number of Antenna	1
Antenna Gain:	3.99 dBi (Declared by the manufacturer)

Technical Specification (2.4G WLAN) ---IOT module	
Frequency Range:	2412-2462MHz
Modulation Technology:	DSSS, OFDM
Number of Type:	CCK, DQPSK, DBPSK, 64-QAM, 16-QAM, QPSK, BPSK
Number of Channel:	11
Channel Space:	5MHz
Antenna Type:	PCB Antenna
Number of Antenna	1
Antenna Gain:	-1.05 dBi (Declared by the manufacturer)

According to the manufacturer, the EUT integrated a certified module which named as iFi IoT Module. According to the manufacturer, the test data of WIFI refer to the module test reports NTC2302443FV00 which issued by Dongguan Nore Testing Center Co., Ltd on July 06, 2023.

Technical Specification (5G WIFI)	
Frequency Range:	5180-5240MHz 5260-5320MHz, 5500-5700MHz, 5745-5825MHz
Modulation Technology:	DSSS, OFDM
Modulation Type:	BPSK, QPSK for 802.11a 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for 802.11n/ac
Number of Channel:	U-NII-1, U-NII-2A: 4 Channel for 802.11a/n(HT20)/ac(VHT20) 2 Channel for 802.11n(HT40)/ac(VHT40) 1 Channel for 802.11ac(VHT80) U-NII-2C: 11 Channel for 802.11a/n(HT20)/ac(VHT20) 5 Channel for 802.11n(HT40)/ac(VHT40) 2 Channel for 802.11ac(VHT80) U-NII-3: 5 Channel for 802.11a/n(HT20)/ac(VHT20) 2 Channel for 802.11n(HT40)/ac(VHT40) 1 Channel for 802.11ac(VHT80)
Antenna Type:	Dipole antenna
Number of Antenna:	1
Antenna Gain:	4.64 dBi (Declared by the manufacturer)
Beamforming Gain:	Not support

2. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	The Laboratory has been assessed and proved to be in compliance with CNAS/CL01 Listed by CNAS, August 13, 2018 The Certificate Registration Number is L5795. The Certificate is valid until August 13, 2030 The Laboratory has been assessed and proved to be in compliance with ISO17025 Listed by A2LA, November 01, 2017 The Certificate Registration Number is 4429.01 The Certificate is valid until December 31, 2027 Listed by FCC, November 06, 2017 Test Firm Registration Number: 907417 Listed by Industry Canada, June 08, 2017 The Certificate Registration Number. Is 46405-9743A
Test Site Location	:	Room 101, 1101, Building 2, No. 61, Hongmei Section, Wangsha Road, Hongmei Town, Dongguan, Guangdong, People's Republic of China

3. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 1, 1.1307

47 CFR Part 2, 2.1091

KDB 447498 D04 v01

4. Maximum Permissible Exposure Limit

According to 47 CFR Part 1, 1.1307, for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if: 47 CFR Part 1, 1.1307

(A) The available maximum time- averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time- averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where,

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

And,

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the minimum separation distance (cm) in any direction from any part of the device antenna(s) or radiating structure(s) to the body of the device user.

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time- averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where,

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

5. RF Exposure Evaluation Results

Single RF Source								
Mode	Frequency (MHz)	Max. Conducted Power (dBm)	Antenna Gain (dBi)	Max. EIRP (dBm)	Max. ERP (dBm)	Max. ERP (mW)	Separation Distance (cm)	Part 1.1307 Option (B) P_{th} (mW)
2.4G WLAN	2462	16.20	3.99	20.190	18.04	63.68	20	3060
5G WLAN	5320	14.047	4.64	18.687	16.537	45.05	20	3060
2.4G WLAN (IOT module)	2412	23.899	-1.05	22.849	20.699	117.46	20	3060

Multiple RF Source (Simultaneous Transmission)			
2.4G WLAN (IOT module) (P/Pth Ratio)	2.4G WLAN (P/Pth Ratio)	Total Ratio	Limit
0.038386	0.020810	0.059196	1.0

Conclusion:

According to 47 CFR §1.1307 (b)(3)(i)(B), the RF exposure analysis concludes that the product is compliant with the FCC RF exposure requirements in mobile exposure condition.

---End---