



# FCC TEST REPORT

## FCC ID: 2A5UB100-800-B06

|                                                                               |   |                                                                                    |
|-------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------|
| Product                                                                       | : | Digital Caliper IP67 Coolant/Water/Dust Proof Coolant-Cal W/Bluetooth Connectivity |
| Model Name                                                                    | : | 100-800-B06,100-800-B04,100-800-B08,100-800-B12                                    |
| Brand                                                                         | : | iGAGING                                                                            |
| Report No.                                                                    | : | PTC22022303802E-FC01                                                               |
| <b>Prepared for</b>                                                           |   |                                                                                    |
| Internatinal Precision Instrument Corp                                        |   |                                                                                    |
| 1206 Puerta Del Sol, San clement CA 92673 USA                                 |   |                                                                                    |
| <b>Prepared by</b>                                                            |   |                                                                                    |
| Precise Testing & Certification Co., Ltd                                      |   |                                                                                    |
| Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China |   |                                                                                    |
|                                                                               |   |                                                                                    |



## 1 TEST RESULT CERTIFICATION

Applicant's name : Internatinal Precision Instrument Corp

Address : 1206 Puerta Del Sol, San clement CA 92673 USA

Manufacture's name : DONGGUAN CITY TERMA ELECTRONICS CO.,LTD

Address : No. 101, building 28, No. 25, Dongke Road, Dongcheng District, Dong  
guan City, Guangdong Province

Product name : Digital Caliper IP67 Coolant/Water/Dust Proof Coolant-Cal W/  
Bluetooth Connectivity

Model name : 100-800-B06,100-800-B04,100-800-B08,100-800-B12

Standards : FCC CFR47 Part 15 Section 15.247

Test procedure : ANSI C63.10:2013

Test Date : Mar. 10, 2022 to Mar. 21, 2022

Date of Issue : Mar. 21, 2022

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Abel Yu'.

Abel Yu / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Wu Weimin'.

Wu Weimin / Manager



## Contents

|                                                       | Page      |
|-------------------------------------------------------|-----------|
| <b>1 TEST RESULT CERTIFICATION.....</b>               | <b>2</b>  |
| <b>2 TEST SUMMARY.....</b>                            | <b>5</b>  |
| 2.1 TEST SITE.....                                    | 6         |
| <b>3 GENERAL INFORMATION.....</b>                     | <b>7</b>  |
| 3.1 GENERAL DESCRIPTION OF E.U.T.....                 | 7         |
| 3.2 CHANNEL LIST.....                                 | 8         |
| <b>4 EQUIPMENT DURING TEST.....</b>                   | <b>9</b>  |
| 4.1 EQUIPMENTS LIST.....                              | 9         |
| 4.2 MEASUREMENT UNCERTAINTY.....                      | 10        |
| 4.3 DESCRIPTION OF SUPPORT UNITS.....                 | 11        |
| <b>5 CONDUCTED EMISSION.....</b>                      | <b>12</b> |
| 5.1 E.U.T. OPERATION.....                             | 12        |
| 5.2 EUT SETUP.....                                    | 12        |
| 5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... | 13        |
| 5.4 MEASUREMENT PROCEDURE.....                        | 13        |
| 5.5 CONDUCTED EMISSION LIMIT.....                     | 13        |
| 5.6 MEASUREMENT DESCRIPTION.....                      | 13        |
| 5.7 CONDUCTED EMISSION TEST RESULT.....               | 13        |
| <b>6 RADIATED SPURIOUS EMISSIONS.....</b>             | <b>14</b> |
| 6.1 EUT OPERATION.....                                | 14        |
| 6.2 TEST SETUP.....                                   | 15        |
| 6.3 SPECTRUM ANALYZER SETUP.....                      | 16        |
| 6.4 TEST PROCEDURE.....                               | 17        |
| 6.5 SUMMARY OF TEST RESULTS.....                      | 19        |
| <b>7 BAND EDGE MEASUREMENT.....</b>                   | <b>25</b> |
| 7.1 TEST PROCEDURE.....                               | 25        |
| 7.2 TEST RESULT.....                                  | 26        |
| <b>8 6DB BANDWIDTH MEASUREMENT.....</b>               | <b>27</b> |
| 8.1 TEST PROCEDURE.....                               | 27        |



|                                         |           |
|-----------------------------------------|-----------|
| 8.2 TEST RESULT.....                    | 27        |
| <b>9 MAXIMUM PEAK OUTPUT POWER.....</b> | <b>30</b> |
| 9.1 TEST PROCEDURE.....                 | 30        |
| 9.2 TEST RESULT.....                    | 30        |
| <b>10 POWER SPECTRAL DENSITY.....</b>   | <b>33</b> |
| 10.1 TEST PROCEDURE.....                | 33        |
| 10.2 TEST RESULT.....                   | 33        |
| <b>11 ANTENNA APPLICATION.....</b>      | <b>36</b> |
| 11.1 ANTENNA REQUIREMENT.....           | 36        |
| 11.2 RESULT.....                        | 36        |
| <b>12 TEST SET-UP.....</b>              | <b>37</b> |
| <b>13 EUT PHOTOS.....</b>               | <b>38</b> |



## 2 Test Summary

| Test Items                  | Test Requirement                 | Result |
|-----------------------------|----------------------------------|--------|
| Conduct Emission            | 15.207                           | PASS   |
| Radiated Spurious Emissions | 15.205(a)<br>15.209<br>15.247(d) | PASS   |
| Conducted Spurious Emission | 15.247(d)                        | PASS   |
| Band edge                   | 15.247(d)<br>15.205(a)           | PASS   |
| 6dB Bandwidth               | 15.247(a)(2)                     | PASS   |
| Maximum Peak Output Power   | 15.247(b)(1)                     | PASS   |
| Power Spectral Density      | 15.247(e)                        | PASS   |
| Antenna Requirement         | 15.203                           | PASS   |



Report No.: PTC22022303802E-FC01

## 2.1 Test Site

Precise Testing & Certification Co., Ltd

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1



### 3 General Information

#### 3.1 General Description of E.U.T.

|                      |   |                                                                                     |
|----------------------|---|-------------------------------------------------------------------------------------|
| Product Name         | : | Digital Caliper IP67 Coolant/Water/Dust Proof Coolant-Cal W/ Bluetooth Connectivity |
| Model Name           | : | 100-800-B06,100-800-B04,100-800-B08,100-800-B12                                     |
| Bluetooth Version    | : | BT 4.1 BLE                                                                          |
| Operating frequency  | : | 2402-2480MHz                                                                        |
| Number of Channels   | : | 40 channels                                                                         |
| Type of Modulation   | : | GFSK                                                                                |
| Antenna installation | : | PCB Antenna                                                                         |
| Antenna Gain         | : | 0dBi                                                                                |
| Power supply         | : | Battery:DC 3V,220mAh                                                                |
| Hardware Version     | : | N/A                                                                                 |
| Software Version     | : | N/A                                                                                 |



### 3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

| Channel | Frequency (MHz) | Channel   | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|-----------|-----------------|---------|-----------------|
| 00      | <b>2402</b>     | 14        | 2430            | 28      | 2458            |
| 01      | 2404            | 15        | 2432            | 29      | 2460            |
| 02      | 2406            | 16        | 2434            | 30      | 2462            |
| 03      | 2408            | 17        | 2436            | 31      | 2464            |
| 04      | 2410            | 18        | 2438            | 32      | 2466            |
| 05      | 2412            | <b>19</b> | <b>2440</b>     | 33      | 2468            |
| 06      | 2414            | 20        | 2442            | 34      | 2470            |
| 07      | 2416            | 21        | 2444            | 35      | 2472            |
| 08      | 2418            | 22        | 2446            | 36      | 2474            |
| 09      | 2420            | 23        | 2448            | 37      | 2476            |
| 10      | 2422            | 24        | 2450            | 38      | 2478            |
| 11      | 2424            | 25        | 2452            | 39      | <b>2480</b>     |
| 12      | 2426            | 26        | 2454            |         |                 |
| 13      | 2428            | 27        | 2456            |         |                 |

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.



## 4 Equipment During Test

### 4.1 Equipments List

#### RF Conducted Test

| Name of Equipment   | Manufacturer  | Model   | Serial No.   | Last calibration | Calibration Due | Calibration period |
|---------------------|---------------|---------|--------------|------------------|-----------------|--------------------|
| MXG Signal Analyzer | Agilent       | N9020A  | MY56070279   | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Spectrum Analyzer   | Rohde&Schwarz | FSU26   | 1166.1660.26 | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Coaxial Cable       | CDS           | 79254   | 46107086     | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Power Meter         | Anritsu       | ML2495A | 0949003      | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Power Sensor        | Anritsu       | MA2411B | 0917017      | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

#### Radiated Emissions

| Name of Equipment            | Manufacturer  | Model      | Serial No.   | Last calibration | Calibration Due | Calibration period |
|------------------------------|---------------|------------|--------------|------------------|-----------------|--------------------|
| EMI Test Receiver            | Rohde&Schwarz | ESCI       | 101417       | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Loop Antenna                 | Schwarzbeck   | FMZB 1519  | 012          | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Bilog Antenna                | SCHWARZBECK   | VULB9160   | 9160-3355    | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Preamplifier (low frequency) | SCHWARZBECK   | BBV 9475   | 9745-0013    | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Cable                        | Schwarzbeck   | PLF-100    | 549489       | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Spectrum Analyzer            | Agilent       | E4407B     | MY45109572   | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Horn Antenna                 | SCHWARZBECK   | 9120D      | 9120D-1246   | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Power Amplifier              | LUNAR EM      | LNA1G18-40 | J10100000081 | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Horn Antenna                 | SCHWARZBECK   | BBHA 9170  | 9170-181     | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Amplifier                    | SCHWARZBECK   | BBV 9721   | 9721-205     | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Cable                        | H+S           | CBL-26     | N/A          | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| RF Cable                     | R&S           | R204       | R21X         | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |



## Conducted Emissions

| Name of Equipment        | Manufacturer  | Model  | Serial No. | Last calibration | Calibration Due | Calibration period |
|--------------------------|---------------|--------|------------|------------------|-----------------|--------------------|
| EMI Test Receiver        | Rohde&Schwarz | ESCI   | 101417     | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Artificial Mains Network | Rohde&Schwarz | L2-16B | 000WX31025 | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |
| Artificial Mains Network | Rohde&Schwarz | ENV216 | 101342     | Aug. 21, 2021    | Aug. 20, 2022   | 1 year             |

## 4.2 Measurement Uncertainty

| Parameter                                                                                       | Uncertainty              |
|-------------------------------------------------------------------------------------------------|--------------------------|
| RF output power, conducted                                                                      | ±1.0dB                   |
| Power Spectral Density, conducted                                                               | ±2.2dB                   |
| Radio Frequency                                                                                 | ± 1 x 10 <sup>-6</sup>   |
| Bandwidth                                                                                       | ± 1.5 x 10 <sup>-6</sup> |
| Time                                                                                            | ±2%                      |
| Duty Cycle                                                                                      | ±2%                      |
| Temperature                                                                                     | ±1°C                     |
| Humidity                                                                                        | ±5%                      |
| DC and low frequency voltages                                                                   | ±3%                      |
| Conducted Emissions (150kHz~30MHz)                                                              | ±3.64dB                  |
| Radiated Emission(9KHz~30MHz)                                                                   | ±3.15dB                  |
| Radiated Emission(30MHz~1GHz)                                                                   | ±5.03dB                  |
| Radiated Emission(1GHz~25GHz)                                                                   | ±4.74dB                  |
| Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95% |                          |



Report No.: PTC22022303802E-FC01

#### 4.3 Description of Support Units

| Equipment | Model No. | Series No. |
|-----------|-----------|------------|
| N/A       | N/A       | N/A        |

## 5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207

Test Method: : ANSI C63.10: 2013

Test Result: : PASS

Frequency Range: : 150kHz to 30MHz

Class/Severity: : Class B

### 5.1 E.U.T. Operation

Operating Environment :


Temperature: : 25.0 °C

Humidity: : 60 % RH


Atmospheric Pressure: : 101.2kPa

### 5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



### 5.3 Test SET-UP (Block Diagram of Configuration)



### 5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

### 5.5 Conducted Emission Limit

#### Conducted Emission

| Frequency(MHz) | Quasi-peak | Average |
|----------------|------------|---------|
| 0.15-0.5       | 66-56      | 56-46   |
| 0.5-5.0        | 56         | 46      |
| 5.0-30.0       | 60         | 50      |

#### Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.6 Measurement Description

The maximised peak emissions from the EUT was scanned with AC 240V 50Hz and AC 120V 60Hz, and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line. The worst case was recorded by (GFSK TX 2402MHz) with AC 120V 60Hz.

### 5.7 Conducted Emission Test Result

N/A.



## 6 Radiated Spurious Emissions

Test Requirement: : FCC CFR47 Part 15 Section 15.209 & 15.247  
 Test Method: : ANSI C63.10:2013  
 Test Result: : PASS  
 Measurement Distance: : 3m  
 Limit: : See the follow table

| Frequency (MHz) | Field Strength        |              | Field Strength Limit at 3m Measurement Dist |                                       |
|-----------------|-----------------------|--------------|---------------------------------------------|---------------------------------------|
|                 | uV/m                  | Distance (m) | uV/m                                        | dBuV/m                                |
| 0.009 ~ 0.490   | $2400/F(\text{kHz})$  | 300          | $10000 * 2400/F(\text{kHz})$                | $20\log^{(2400/F(\text{kHz}))} + 80$  |
| 0.490 ~ 1.705   | $24000/F(\text{kHz})$ | 30           | $100 * 24000/F(\text{kHz})$                 | $20\log^{(24000/F(\text{kHz}))} + 40$ |
| 1.705 ~ 30      | 30                    | 30           | $100 * 30$                                  | $20\log^{(30)} + 40$                  |
| 30 ~ 88         | 100                   | 3            | 100                                         | $20\log^{(100)}$                      |
| 88 ~ 216        | 150                   | 3            | 150                                         | $20\log^{(150)}$                      |
| 216 ~ 960       | 200                   | 3            | 200                                         | $20\log^{(200)}$                      |
| Above 960       | 500                   | 3            | 500                                         | $20\log^{(500)}$                      |


### 6.1 EUT Operation

Operating Environment :  
 Temperature : 24.5 °C  
 Humidity : 52.0 % RH  
 Atmospheric Pressure : 101.3kPa


## 6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



### 6.3 Spectrum Analyzer Setup

|                      |   |        |        |
|----------------------|---|--------|--------|
| Below 30MHz          |   |        |        |
| IF Bandwidth         | : | 10kHz  |        |
| Resolution Bandwidth | : | 10kHz  |        |
| Video Bandwidth      | : | 10kHz  |        |
| 30MHz ~ 1GHz         |   |        |        |
| Detector             | : | PK     | QP     |
| Resolution Bandwidth | : | 100kHz | 120kHz |
| Video Bandwidth      | : | 300kHz | 300kHz |
| Above 1GHz           |   |        |        |
| Detector             | : | PK     | AV     |
| Resolution Bandwidth | : | 1MHz   | 1MHz   |
| Video Bandwidth      | : | 3MHz   | 10Hz   |



## 6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
  - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
  - 2) Change the antenna polarization and repeat 1) with vertical polarization.
  - 3) Make a hardcopy of the spectrum.
  - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
  - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
  - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
  - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
  - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



For Average Measurement:

VBW=10Hz, when duty cycle is no less than 98 percent.

VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

| Band      | Duty Cycle(%) | T( $\mu$ s) | 1/T(KHz) | Average Correction Factor | VBW Setting |
|-----------|---------------|-------------|----------|---------------------------|-------------|
| 2402-2480 | 100           | -           | -        | 0                         | 10Hz        |



## 6.5 Summary of Test Results

### Test Frequency: 9KHz-30MHz

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission Level<br>(dBuV/m) | Limit 3m<br>(dBuV/m) | Over<br>(dB) |
|----------------|-----------------|----------------------------|----------------------|--------------|
| --             | --              | --                         | --                   | >20          |

#### Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance} / \text{test distance})$  (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


### Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (GFSK (CH00: 2402MHz)).



Antenna Polarization: Horizontal GFSK(CH00: 2402MHz)




| No. | Freq<br>MHz | Cable<br>Loss<br>dB | ANT<br>Factor<br>dB/m | Receiver<br>Reading<br>dBuV | Preamp<br>Factor<br>dB | Emission<br>Level<br>dBuV/m | Limit<br>dBuV/m | Over<br>Limit<br>dB | Remark |
|-----|-------------|---------------------|-----------------------|-----------------------------|------------------------|-----------------------------|-----------------|---------------------|--------|
| 1.  | 39.789      | 1.69                | 12.10                 | 23.65                       | 29.91                  | 7.53                        | 40.00           | -32.47              | QP     |
| 2.  | 78.570      | 2.86                | 9.11                  | 30.63                       | 29.97                  | 12.63                       | 40.00           | -27.37              | QP     |
| 3.  | 122.736     | 3.63                | 12.19                 | 26.28                       | 30.00                  | 12.10                       | 43.50           | -31.40              | QP     |
| 4.  | 188.138     | 4.36                | 11.87                 | 21.88                       | 30.04                  | 8.07                        | 43.50           | -35.43              | QP     |
| 5.  | 334.200     | 5.35                | 14.04                 | 24.62                       | 30.46                  | 13.55                       | 46.00           | -32.45              | QP     |
| 6.  | 560.933     | 6.24                | 18.55                 | 24.17                       | 30.97                  | 17.99                       | 46.00           | -28.01              | QP     |

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



Antenna Polarization: Vertical GFSK(CH00: 2402MHz)



| No. | Freq<br>MHz | Cable<br>Loss<br>dB | ANT<br>Factor<br>dB/m | Receiver<br>Reading<br>dBuV | Preamp<br>Factor<br>dB | Emission<br>Level<br>dBuV/m | Limit<br>dBuV/m | Over<br>Limit<br>dB | Remark |
|-----|-------------|---------------------|-----------------------|-----------------------------|------------------------|-----------------------------|-----------------|---------------------|--------|
| 1.  | 38.888      | 1.65                | 12.12                 | 32.92                       | 29.91                  | 16.78                       | 40.00           | -23.22              | QP     |
| 2.  | 63.983      | 2.50                | 11.14                 | 22.36                       | 29.94                  | 6.06                        | 40.00           | -33.94              | QP     |
| 3.  | 95.093      | 3.18                | 9.11                  | 29.79                       | 29.98                  | 12.10                       | 43.50           | -31.40              | QP     |
| 4.  | 143.830     | 3.90                | 13.46                 | 23.16                       | 30.02                  | 10.50                       | 43.50           | -33.00              | QP     |
| 5.  | 312.179     | 5.23                | 13.51                 | 21.39                       | 30.37                  | 9.76                        | 46.00           | -36.24              | QP     |
| 6.  | 752.743     | 6.75                | 20.74                 | 22.48                       | 31.13                  | 18.84                       | 46.00           | -27.16              | QP     |

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



**Test Frequency 1GHz-25GHz:**

**GFSK Low Channel (2402MHz)**

| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector (PK/AV) |
|-----------------|---------------------|---------------------|-----------------|--------------------------|-------------------------|----------------|-----------------|------|------------------|
| 4804            | 41.23               | 34.04               | 6.58            | 34.09                    | 47.76                   | 74.00          | -26.24          | V    | PK               |
| 7206            | 35.30               | 37.11               | 7.73            | 34.50                    | 45.64                   | 74.00          | -28.36          | V    | PK               |
| 9608            | 37.20               | 39.31               | 9.23            | 34.79                    | 50.95                   | 74.00          | -23.05          | V    | PK               |
| 4804            | 40.52               | 34.04               | 6.58            | 34.09                    | 47.05                   | 74.00          | -26.95          | H    | PK               |
| 7206            | 34.76               | 37.11               | 7.73            | 34.50                    | 45.10                   | 74.00          | -28.90          | H    | PK               |
| 9608            | 32.77               | 39.31               | 9.23            | 34.79                    | 46.52                   | 74.00          | -27.48          | H    | PK               |
| 4804            | 37.68               | 34.04               | 6.58            | 34.09                    | 44.21                   | 54.00          | -9.79           | V    | AV               |
| 7206            | 31.11               | 37.11               | 7.73            | 34.50                    | 41.45                   | 54.00          | -12.55          | V    | AV               |
| 9608            | 32.96               | 39.31               | 9.23            | 34.79                    | 46.71                   | 54.00          | -7.29           | V    | AV               |
| 4804            | 35.82               | 34.04               | 6.58            | 34.09                    | 42.35                   | 54.00          | -11.65          | H    | AV               |
| 7206            | 29.75               | 37.11               | 7.73            | 34.50                    | 40.09                   | 54.00          | -13.91          | H    | AV               |
| 9608            | 27.92               | 39.31               | 9.23            | 34.79                    | 41.67                   | 54.00          | -12.33          | H    | AV               |

**GFSK Middle Channel (2440MHz)**

| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector (PK/AV) |
|-----------------|---------------------|---------------------|-----------------|--------------------------|-------------------------|----------------|-----------------|------|------------------|
| 4880            | 43.53               | 34.38               | 6.69            | 34.09                    | 50.51                   | 74.00          | -23.49          | V    | PK               |
| 7320            | 41.22               | 37.22               | 7.78            | 34.53                    | 51.69                   | 74.00          | -22.31          | V    | PK               |
| 9760            | 34.12               | 39.46               | 9.35            | 34.80                    | 48.13                   | 74.00          | -25.87          | V    | PK               |
| 4880            | 41.70               | 34.38               | 6.69            | 34.09                    | 48.68                   | 74.00          | -25.32          | H    | PK               |
| 7320            | 35.74               | 37.22               | 7.78            | 34.53                    | 46.21                   | 74.00          | -27.79          | H    | PK               |
| 9760            | 35.44               | 39.46               | 9.35            | 34.80                    | 49.45                   | 74.00          | -24.55          | H    | PK               |
| 4880            | 40.39               | 34.38               | 6.69            | 34.09                    | 47.37                   | 54.00          | -6.63           | V    | AV               |
| 7320            | 36.86               | 37.22               | 7.78            | 34.53                    | 47.33                   | 54.00          | -6.67           | V    | AV               |
| 9760            | 29.60               | 39.46               | 9.35            | 34.80                    | 43.61                   | 54.00          | -10.39          | V    | AV               |
| 4880            | 36.81               | 34.38               | 6.69            | 34.09                    | 43.79                   | 54.00          | -10.21          | H    | AV               |
| 7320            | 30.61               | 37.22               | 7.78            | 34.53                    | 41.08                   | 54.00          | -12.92          | H    | AV               |
| 9760            | 30.24               | 39.46               | 9.35            | 34.80                    | 44.25                   | 54.00          | -9.75           | H    | AV               |



GFSK High Channel (2480MHz)

| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamp Factor (dB) | Emission Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector (PK/AV) |
|-----------------|---------------------|---------------------|-----------------|--------------------|-------------------------|----------------|-----------------|------|------------------|
| 4960            | 40.76               | 34.72               | 6.79            | 34.09              | 48.18                   | 74.00          | -25.82          | V    | PK               |
| 7440            | 35.74               | 37.34               | 7.82            | 34.57              | 46.33                   | 74.00          | -27.67          | V    | PK               |
| 9920            | 35.80               | 39.62               | 9.46            | 34.81              | 50.07                   | 74.00          | -23.93          | V    | PK               |
| 4960            | 38.85               | 34.72               | 6.79            | 34.09              | 46.27                   | 74.00          | -27.73          | H    | PK               |
| 7440            | 34.73               | 37.34               | 7.82            | 34.57              | 45.32                   | 74.00          | -28.68          | H    | PK               |
| 9920            | 34.70               | 39.62               | 9.46            | 34.81              | 48.97                   | 74.00          | -25.03          | H    | PK               |
| 4960            | 36.64               | 34.04               | 6.58            | 34.09              | 43.17                   | 54.00          | -10.83          | V    | AV               |
| 7440            | 31.19               | 37.11               | 7.73            | 34.50              | 41.53                   | 54.00          | -12.47          | V    | AV               |
| 9920            | 31.19               | 39.31               | 9.23            | 34.79              | 44.94                   | 54.00          | -9.06           | V    | AV               |
| 4960            | 33.91               | 34.04               | 6.58            | 34.09              | 40.44                   | 54.00          | -13.56          | H    | AV               |
| 7440            | 29.39               | 37.11               | 7.73            | 34.50              | 39.73                   | 54.00          | -14.27          | H    | AV               |
| 9920            | 29.63               | 39.31               | 9.23            | 34.79              | 43.38                   | 54.00          | -10.62          | H    | AV               |

Note: 1. The testing has been conformed to 10\*2480MHz=24800MHz.

2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Preamp Factor  
 Emission Level = Read Level + Factor  
 Over Limit =Emission Level-Limit



## Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

| Test Mode: Low Channel 2402MHz |                   |                       |                 |                    |                |                |           |              |            |
|--------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------|--------------|------------|
| Frequency (MHz)                | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over (dB) | Polarity H/V | Test Value |
| 2390                           | 44.53             | 29.15                 | 3.41            | 34.01              | 43.08          | 74.00          | -30.92    | H            | Peak       |
| 2400                           | 57.50             | 29.16                 | 3.43            | 34.01              | 56.08          | 74.00          | -17.92    | H            | Peak       |
| 2390                           | 44.73             | 29.15                 | 3.41            | 34.01              | 43.28          | 74.00          | -30.72    | V            | Peak       |
| 2400                           | 46.54             | 29.16                 | 3.43            | 34.01              | 45.12          | 74.00          | -28.88    | V            | Peak       |
| 2390                           | 37.15             | 29.15                 | 3.41            | 34.01              | 35.70          | 54.00          | -18.30    | H            | AV         |
| 2400                           | 40.55             | 29.16                 | 3.43            | 34.01              | 39.13          | 54.00          | -14.87    | H            | AV         |
| 2390                           | 35.80             | 29.15                 | 3.41            | 34.01              | 34.35          | 54.00          | -19.65    | V            | AV         |
| 2400                           | 40.50             | 29.16                 | 3.43            | 34.01              | 39.08          | 54.00          | -14.92    | V            | AV         |

| Test Mode: High Channel 2480MHz |                   |                       |                 |                    |                |                |           |              |            |
|---------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------|--------------|------------|
| Frequency (MHz)                 | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over (dB) | Polarity H/V | Test Value |
| 2483.5                          | 48.53             | 29.28                 | 3.53            | 34.03              | 47.31          | 74.00          | -26.69    | H            | Peak       |
| 2500                            | 42.76             | 29.30                 | 3.56            | 34.03              | 41.59          | 74.00          | -32.41    | H            | Peak       |
| 2483.5                          | 46.35             | 29.28                 | 3.53            | 34.03              | 45.13          | 74.00          | -28.87    | V            | Peak       |
| 2500                            | 43.76             | 29.30                 | 3.56            | 34.03              | 42.59          | 74.00          | -31.41    | V            | Peak       |
| 2483.5                          | 41.80             | 29.28                 | 3.53            | 34.03              | 40.58          | 54.00          | -13.42    | H            | AV         |
| 2500                            | 36.57             | 29.30                 | 3.56            | 34.03              | 35.40          | 54.00          | -18.60    | H            | AV         |
| 2483.5                          | 41.53             | 29.28                 | 3.53            | 34.03              | 40.31          | 54.00          | -13.69    | V            | AV         |
| 2500                            | 36.50             | 29.30                 | 3.56            | 34.03              | 35.33          | 54.00          | -18.67    | V            | AV         |



## 7 Band Edge Measurement

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | : Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test Method      | : ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Limit       | : Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |


### 7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold




## 7.2 Test Result

Low Band Edge Plot on Channel 00



High Band Edge Plot on Channel 39





## 8 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013


Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

### 8.2 Test Result

| Channel number | Channel frequency<br>(MHz) | Measurement level<br>(KHz) | Required Limit<br>(KHz) |
|----------------|----------------------------|----------------------------|-------------------------|
| 00             | 2402                       | 665.6                      | >500                    |
| 19             | 2440                       | 595.9                      | >500                    |
| 39             | 2480                       | 696.5                      | >500                    |



2402



2440



2480



## 9 Maximum Peak Output Power

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013


Test Limit : Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

### 9.1 Test Procedure


1. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.

### 9.2 Test Result


| Channel number | Channel | Result[dBm] | Limit[dBm] | Verdict |
|----------------|---------|-------------|------------|---------|
| 00             | 2402    | 1.558       | ≤30        | PASS    |
| 19             | 2440    | 1.482       | ≤30        | PASS    |
| 39             | 2480    | 1.875       | ≤30        | PASS    |



2402



2440



2480



## 10 Power Spectral density

|                  |                                                                                                                                                                                                                                                                                                                                |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | : FCC CFR47 Part 15 Section 15.247                                                                                                                                                                                                                                                                                             |
| Test Method      | : ANSI C63.10:2013                                                                                                                                                                                                                                                                                                             |
| Test Limit       | : Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. |

### 10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

### 10.2 Test Result

| Channel number | Channel frequency (MHz) | Measurement level (dBm) | Required Limit (dBm/3kHz) | Pass/Fail |
|----------------|-------------------------|-------------------------|---------------------------|-----------|
|                |                         | PSD/3kHz                |                           |           |
| 00             | 2402                    | -12.907                 | 8                         | PASS      |
| 19             | 2440                    | -13.155                 | 8                         | PASS      |
| 39             | 2480                    | -9.985                  | 8                         | PASS      |



2402



2440



2480


## 11 Antenna Application

### 11.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


### 11.2 Result

The EUT'S antenna, permanent attached antenna, is PCB antenna. The antenna's gain is 0dBi and meets the requirement.




## 12 Test set-up



Radiated Spurious Emissions  
From 30MHz-1000MHz





Above 1GHz





### 13 EUT PHOTOS

















\*\*\*\*\*THE END REPORT\*\*\*\*\*