

FCC RADIO TEST REPORT

FCC ID: 2A5WH-ME1253C001F0

Product: Air Disinfection Robot

Trade Mark: N/A

Model No.: ME1253C001F0

Family Model: ME1253C001F7, ME1253C001F8,
ME1253C001F9, ME1253C001FA

Report No.: S22030302502003

Issue Date: Apr 18. 2022

Prepared for

Shenzhen CIOT Robotics Co., Ltd

19F, R&D Building, WanDaiheng Hi-Tech Industrial Park, Zhenmei Community, Xinhua Street,
Guangming District, Shenzhen, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090

Website: <http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	4
2	SUMMARY OF TEST RESULTS.....	5
3	FACILITIES AND ACCREDITATIONS	6
3.1	FACILITIES.....	6
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	6
3.3	MEASUREMENT UNCERTAINTY	6
4	GENERAL DESCRIPTION OF EUT	7
5	DESCRIPTION OF TEST MODES	9
6	SETUP OF EQUIPMENT UNDER TEST	11
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	11
6.2	SUPPORT EQUIPMENT.....	12
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	13
7	TEST REQUIREMENTS.....	15
7.1	CONDUCTED EMISSIONS TEST	15
7.1.1	Applicable Standard	15
7.1.2	Conformance Limit	15
7.1.3	Measuring Instruments.....	15
7.1.4	Test Configuration	15
7.1.5	Test Procedure	15
7.1.6	Test Results	16
7.2	RADIATED SPURIOUS EMISSION	20
7.2.1	Applicable Standard	20
7.2.2	Conformance Limit	20
7.2.3	Measuring Instruments.....	21
7.2.4	Test Configuration	21
7.2.5	Test Procedure	22
7.2.6	Test Results	23
7.3	6DB BANDWIDTH.....	35
7.3.1	Applicable Standard	35
7.3.2	Conformance Limit	35
7.3.3	Measuring Instruments.....	35
7.3.4	Test Setup	35
7.3.5	Test Procedure	35
7.3.6	Test Results	36
7.4	DUTY CYCLE.....	37
7.4.1	Applicable Standard	37
7.4.2	Conformance Limit	37
7.4.3	Measuring Instruments.....	37
7.4.4	Test Setup	37
7.4.5	Test Procedure	37
7.4.6	Test Results	37
7.5	MAXIMUM OUTPUT POWER.....	38
7.5.1	Applicable Standard	38
7.5.2	Conformance Limit	38
7.5.3	Measuring Instruments.....	38
7.5.4	Test Setup	38
7.5.5	Test Procedure	38
7.5.6	EUT operation during Test.....	38
7.5.7	Test Results	39
7.6	POWER SPECTRAL DENSITY	40

7.6.1	Applicable Standard	40
7.6.2	Conformance Limit	40
7.6.3	Measuring Instruments	40
7.6.4	Test Setup	40
7.6.5	Test Procedure	40
7.6.6	Test Results	41
7.7	CONDUCTED BAND EDGE MEASUREMENT.....	42
7.7.1	Applicable Standard	42
7.7.2	Conformance Limit	42
7.7.3	Measuring Instruments	42
7.7.4	Test Setup	42
7.7.5	Test Procedure	42
7.7.6	Test Results	43
7.8	SPURIOUS RF CONDUCTED EMISSIONS.....	44
7.8.1	Conformance Limit	44
7.8.2	Measuring Instruments	44
7.8.3	Test Setup	44
7.8.4	Test Procedure	44
7.8.5	Test Results	44
7.9	ANTENNA APPLICATION	45
7.9.1	Antenna Requirement	45
7.9.2	Result	45
8	TEST RESULTS	46
MODULE 1:		46
8.1.1	DUTY CYCLE.....	46
8.1.2	MAXIMUM CONDUCTED OUTPUT POWER	53
8.1.3	OCCUPIED CHANNEL BANDWIDTH	54
8.1.4	MAXIMUM POWER SPECTRAL DENSITY LEVEL	67
8.1.5	BAND EDGE	74
8.1.6	CONDUCTED RF SPURIOUS EMISSION	83
MODULE 2:		96
8.1.7	DUTY CYCLE.....	96
8.1.8	MAXIMUM CONDUCTED OUTPUT POWER	109
8.1.9	OCCUPIED CHANNEL BANDWIDTH	110
8.1.10	MAXIMUM POWER SPECTRAL DENSITY LEVEL	135
8.1.11	BAND EDGE	148
8.1.12	CONDUCTED RF SPURIOUS EMISSION	165

1 TEST RESULT CERTIFICATION

Applicant's name	Shenzhen CIOT Robotics Co., Ltd
Address	19F, R&D Building, WanDaiheng Hi-Tech Industrial Park, Zhenmei Community, Xinhua Street, Guangming District, Shenzhen, China
Manufacturer's Name	Shenzhen CIOT Robotics Co., Ltd
Address	19F, R&D Building, WanDaiheng Hi-Tech Industrial Park, Zhenmei Community, Xinhua Street, Guangming District, Shenzhen, China
Product description	
Product name	Air Disinfection Robot
Model and/or type reference	ME1253C001F0
Family Model	ME1253C001F7, ME1253C001F8, ME1253C001F9, ME1253C001FA

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied


This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : Mar 07 . 2022 ~ Apr 15. 2022

Testing Engineer : 
(Allen Liu)

Authorized Signatory : 
(Alex Li)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Maximum Output Power	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized
International Standard ISO/IEC 17025:2005 General requirements for
the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined
scope and the operation of a laboratory quality management system
(refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$
9	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Air Disinfection Robot
Trade Mark	N/A
FCC ID	2A5WH-ME1253C001F0
Model No.	ME1253C001F0
Family Model	ME1253C001F7, ME1253C001F8, ME1253C001F9, ME1253C001FA
Model Difference	All models are the same circuit and RF module, except the model name.
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20); 2422-2452MHz for 802.11n(HT40);
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Number of Channels	11 channels for 802.11b/g/11n(HT20); 7 channels for 802.11n(HT40);
Antenna Type	Antenna 1: Sucker Antenna(Module 2) Antenna 2: Sucker Antenna(Module 2) Antenna 1: FPCB Antenna(Module 1)
Antenna Gain	Antenna 1: 2dBi(Module 2) Antenna 2: 2dBi(Module 2) Antenna 1: 3.21dBi(Module 1)
Smart system	☒ SISO for 802.11b/g/n20/n40
Adapter	MODEL: XVE248-2940700 INPUT: AC 110-240V 50/60Hz 4.0A MAX OUTPUT: 29.4V---7.0A 205.8W
Battery	DC 25.55V, 20000mAh
Power supply	DC 25.55V from battery or DC 29.4V from Adapter.
HW Version	V1.4
SW Version	Android 7.1.2

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

[illegible]

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20/HT40):

Channel	Frequency(MHz)
1	2412
2	2417
...	...
5	2432
6	2437
...	...
10	2457
11	2462

Note: $f_c = 2412\text{MHz} + (k-1) \times 5\text{MHz}$ $k=1$ to 11

This EUT has two modules, module 2 supports WIFI2.4G, module 2 has two antennas, module 1 supports Bluetooth, WIFI2.4G, module 1 has one antenna.

The module 2 for 2.4G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
802.11b/g/n	1TX, 1RX


Test Mode:

Test Items	Mode	Data Rate	Channel	Ant
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1/2/3
	11g/BPSK	6 Mbps	1/6/11	1/2/3
	11n HT20	MCS0	1/6/11	1/2/3
	11n HT40	MCS0	3/6/9	1/2/3
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1/2/3
	11g/BPSK	6 Mbps	1/6/11	1/2/3
	11n HT20	MCS0	1/6/11	1/2/3
	11n HT40	MCS0	3/6/9	1/2/3
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1/2/3
	11g/BPSK	6 Mbps	1/6/11	1/2/3
	11n HT20	MCS0	1/6/11	1/2/3
	11n HT40	MCS0	3/6/9	1/2/3
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11b/CCK	1 Mbps	1/6/11	1/2/3
	11g/BPSK	6 Mbps	1/6/11	1/2/3
	11n HT20	MCS0	1/6/11	1/2/3
	11n HT40	MCS0	3/6/9	1/2/3
Band Edge Emissions	11b/CCK	1 Mbps	1/6/11	1/2/3
	11g/BPSK	6 Mbps	1/6/11	1/2/3
	11n HT20	MCS0	1/6/11	1/2/3
	11n HT40	MCS0	3/6/9	1/2/3


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	RF Cable	YES	NO	0.1m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2021.04.27	2022.04.26	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2021.07.01	2022.06.30	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2021.07.01	2022.06.30	1 year
4	Test Receiver	R&S	ESPI7	101318	2021.04.27	2022.04.26	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.29 2022/03/30	2022.03.28 2023.03.29	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2021.03.29 2022/03/30	2022.03.28 2023.03.29	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2021.11.07	2022.11.06	1 year
9	Amplifier	EMC	EMC051835SE	980246	2021.07.01	2022.06.30	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2021.11.07	2022.11.06	1 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2021.07.01	2022.06.30	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2019.08.06	2022.08.05	3 year
16	Filter	TRILTHIC	2400MHz	29	2021.07.01	2022.06.30	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2021.04.27	2022.04.26	1 year
2	LISN	R&S	ENV216	101313	2021.04.27	2022.04.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2021.04.27	2022.04.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a)

7.1.2 Conformance Limit


Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


7.1.6 Test Results

EUT:	Air Disinfection Robot	Model Name :	ME1253C001F0
Temperature:	22 °C	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Normal Link- Module 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1932	44.90	9.82	54.72	63.89	-9.17	QP
0.1932	34.20	9.82	44.02	53.89	-9.87	AVG
0.4539	41.38	9.83	51.21	56.80	-5.59	QP
0.4539	31.53	9.83	41.36	46.80	-5.44	AVG
0.9735	38.54	9.92	48.46	56.00	-7.54	QP
0.9735	28.33	9.92	38.25	46.00	-7.75	AVG
1.1717	38.92	9.91	48.83	56.00	-7.17	QP
1.1717	28.78	9.91	38.69	46.00	-7.31	AVG
2.3458	39.96	9.91	49.87	56.00	-6.13	QP
2.3458	29.42	9.91	39.33	46.00	-6.67	AVG
9.4014	43.77	9.98	53.75	60.00	-6.25	QP
9.4014	33.67	9.98	43.65	50.00	-6.35	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Air Disinfection Robot	Model Name :	ME1253C001F0
Temperature:	22℃	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Normal Link- Module 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1932	44.66	9.82	54.48	63.89	-9.41	QP
0.1932	34.83	9.82	44.65	53.89	-9.24	AVG
0.4539	39.01	9.83	48.84	56.80	-7.96	QP
0.4539	29.49	9.83	39.32	46.80	-7.48	AVG
2.3458	39.93	9.91	49.84	56.00	-6.16	QP
2.3458	29.34	9.91	39.25	46.00	-6.75	AVG
3.3814	40.27	10.05	50.32	56.00	-5.68	QP
3.3814	30.20	10.05	40.25	46.00	-5.75	AVG
6.5571	40.47	9.99	50.46	60.00	-9.54	QP
6.5571	30.37	9.99	40.36	50.00	-9.64	AVG
9.5014	43.99	9.98	53.97	60.00	-6.03	QP
9.5014	33.71	9.98	43.69	50.00	-6.31	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Air Disinfection Robot	Model Name :	ME1253C001F0
Temperature:	22 °C	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Normal Link- Module 2

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1932	45.90	9.82	55.72	63.89	-8.17	QP
0.1932	35.87	9.82	45.69	53.89	-8.20	AVG
0.4539	38.38	9.83	48.21	56.80	-8.59	QP
0.4539	28.42	9.83	38.25	46.80	-8.55	AVG
1.1713	37.42	9.91	47.33	56.00	-8.67	QP
1.1713	27.11	9.91	37.02	46.00	-8.98	AVG
1.9489	38.65	9.84	48.49	56.00	-7.51	QP
1.9489	28.27	9.84	38.11	46.00	-7.89	AVG
2.3458	39.46	9.91	49.37	56.00	-6.63	QP
2.3458	29.74	9.91	39.65	46.00	-6.35	AVG
9.4014	41.77	9.98	51.75	60.00	-8.25	QP
9.4014	32.04	9.98	42.02	50.00	-7.98	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Air Disinfection Robot	Model Name :	ME1253C001F0
Temperature:	22°C	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Normal Link- Module 2

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1932	46.16	9.82	55.98	63.89	-7.91	QP
0.1932	35.84	9.82	45.66	53.89	-8.23	AVG
0.4539	38.01	9.83	47.84	56.80	-8.96	QP
0.4539	27.42	9.83	37.25	46.80	-9.55	AVG
0.7157	39.05	9.84	48.89	56.00	-7.11	QP
0.7157	28.31	9.84	38.15	46.00	-7.85	AVG
0.9735	39.07	9.92	48.99	56.00	-7.01	QP
0.9735	28.74	9.92	38.66	46.00	-7.34	AVG
1.2356	38.39	9.91	48.30	56.00	-7.70	QP
1.2356	28.57	9.91	38.48	46.00	-7.52	AVG
9.5014	41.99	9.98	51.97	60.00	-8.03	QP
9.5014	31.67	9.98	41.65	50.00	-8.35	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz:
Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz:
Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz and frequencies above 1GHz,
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

For peak measurement:

Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;

Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz

For average measurement:

VBW = 10 Hz, when duty cycle is no less than 98 percent.

VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n(HT20, HT40)	Test By:	Allen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


- Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT:	Air Disinfection Robot	Model Name :	ME1253C001F0
Temperature:	25 °C	Relative Humidity:	55%
Pressure:	1010hPa	Test Mode:	Normal Link- Module 1
Test Voltage :	DC 25.55V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	46.6664	20.47	15.68	36.15	40.00	-3.85	QP
V	85.8983	22.39	14.38	36.77	40.00	-3.23	QP
V	148.4410	18.64	16.60	35.24	43.50	-8.26	QP
V	247.6819	20.53	19.34	39.87	46.00	-6.13	QP
V	446.4141	14.52	24.75	39.27	46.00	-6.73	QP
V	661.1504	11.53	27.97	39.50	46.00	-6.50	QP

Remark:


Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	59.0251	16.50	14.38	30.88	40.00	-9.12	QP
H	93.1132	22.29	14.72	37.01	43.50	-6.49	QP
H	155.3643	19.87	16.91	36.78	43.50	-6.72	QP
H	247.6819	18.22	19.34	37.56	46.00	-8.44	QP
H	379.9141	16.29	22.76	39.05	46.00	-6.95	QP
H	495.9343	12.79	25.73	38.52	46.00	-7.48	QP

Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit




EUT:	Air Disinfection Robot	Model Name :	ME1253C001F0
Temperature:	25 °C	Relative Humidity:	55%
Pressure:	1010hPa	Test Mode:	Normal Link- Module 2
Test Voltage :	DC 25.55V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	46.0162	18.19	15.94	34.13	40.00	-5.87	QP
V	85.8983	17.39	14.38	31.77	40.00	-8.23	QP
V	148.4410	18.64	16.60	35.24	43.50	-8.26	QP
V	214.5141	21.51	17.78	39.29	43.50	-4.21	QP
V	247.6819	19.03	19.34	38.37	46.00	-7.63	QP
V	446.4141	13.52	24.75	38.27	46.00	-7.73	QP

Remark:


Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	59.0251	17.50	14.38	31.88	40.00	-8.12	QP
H	96.7749	20.81	15.05	35.86	43.50	-7.64	QP
H	155.3642	18.87	16.91	35.78	43.50	-7.72	QP
H	214.5141	17.38	17.78	35.16	43.50	-8.34	QP
H	379.9141	14.29	22.76	37.05	46.00	-8.95	QP
H	744.8659	10.44	29.21	39.65	46.00	-6.35	QP

Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n(HT20, HT40)	Test By:	Allen Liu

Module 1:

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2412 MHz)(802.11b)--Above 1G									
4824.265	63.43	5.21	35.59	44.30	59.93	74.00	-14.07	Pk	Vertical
4824.265	40.23	5.21	35.59	44.30	36.73	54.00	-17.27	AV	Vertical
7236.296	59.74	6.48	36.27	44.60	57.89	74.00	-16.11	Pk	Vertical
7236.296	43.59	6.48	36.27	44.60	41.74	54.00	-12.26	AV	Vertical
4824.414	60.92	5.21	35.55	44.30	57.38	74.00	-16.62	Pk	Horizontal
4824.414	42.67	5.21	35.55	44.30	39.13	54.00	-14.87	AV	Horizontal
7236.428	62.79	6.48	36.27	44.52	61.02	74.00	-12.98	Pk	Horizontal
7236.428	47.03	6.48	36.27	44.52	45.26	54.00	-8.74	AV	Horizontal
Mid Channel (2437 MHz)(802.11b)--Above 1G									
4874.312	63.29	5.21	35.66	44.20	59.96	74.00	-14.04	Pk	Vertical
4874.312	43.24	5.21	35.66	44.20	39.91	54.00	-14.09	AV	Vertical
7311.227	59.51	7.10	36.50	44.43	58.68	74.00	-15.32	Pk	Vertical
7311.227	47.38	7.10	36.50	44.43	46.55	54.00	-7.45	AV	Vertical
4874.529	61.21	5.21	35.66	44.20	57.88	74.00	-16.12	Pk	Horizontal
4874.529	47.78	5.21	35.66	44.20	44.45	54.00	-9.55	AV	Horizontal
7311.313	59.73	7.10	36.50	44.43	58.90	74.00	-15.10	Pk	Horizontal
7311.313	41.82	7.10	36.50	44.43	40.99	54.00	-13.01	AV	Horizontal
High Channel (2462 MHz)(802.11b)--Above 1G									
4924.102	65.36	5.21	35.52	44.21	61.88	74.00	-12.12	Pk	Vertical
4924.102	42.26	5.21	35.52	44.21	38.78	54.00	-15.22	AV	Vertical
7386.425	61.07	7.10	36.53	44.60	60.10	74.00	-13.90	Pk	Vertical
7386.425	45.14	7.10	36.53	44.60	44.17	54.00	-9.83	AV	Vertical
4924.066	66.87	5.21	35.52	44.21	63.39	74.00	-10.61	Pk	Horizontal
4924.066	46.95	5.21	35.52	44.21	43.47	54.00	-10.53	AV	Horizontal
7386.198	60.86	7.10	36.53	44.60	59.89	74.00	-14.11	Pk	Horizontal
7386.198	44.83	7.10	36.53	44.60	43.86	54.00	-10.14	AV	Horizontal

Note:

- (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
- (2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
- (3)"802.11b" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

Module 2:

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2412 MHz)(802.11b)--Above 1G									
4824.265	62.49	5.21	35.59	44.30	58.99	74.00	-15.01	Pk	Vertical
4824.265	41.05	5.21	35.59	44.30	37.55	54.00	-16.45	AV	Vertical
7236.296	60.51	6.48	36.27	44.60	58.66	74.00	-15.34	Pk	Vertical
7236.296	44.28	6.48	36.27	44.60	42.43	54.00	-11.57	AV	Vertical
4824.414	61.29	5.21	35.55	44.30	57.75	74.00	-16.25	Pk	Horizontal
4824.414	42.81	5.21	35.55	44.30	39.27	54.00	-14.73	AV	Horizontal
7236.428	63.06	6.48	36.27	44.52	61.29	74.00	-12.71	Pk	Horizontal
7236.428	46.97	6.48	36.27	44.52	45.20	54.00	-8.80	AV	Horizontal
Mid Channel (2437 MHz)(802.11b)--Above 1G									
4874.312	63.05	5.21	35.66	44.20	59.72	74.00	-14.28	Pk	Vertical
4874.312	43.16	5.21	35.66	44.20	39.83	54.00	-14.17	AV	Vertical
7311.227	59.66	7.10	36.50	44.43	58.83	74.00	-15.17	Pk	Vertical
7311.227	46.87	7.10	36.50	44.43	46.04	54.00	-7.96	AV	Vertical
4874.529	61.04	5.21	35.66	44.20	57.71	74.00	-16.29	Pk	Horizontal
4874.529	48.69	5.21	35.66	44.20	45.36	54.00	-8.64	AV	Horizontal
7311.313	59.50	7.10	36.50	44.43	58.67	74.00	-15.33	Pk	Horizontal
7311.313	41.43	7.10	36.50	44.43	40.60	54.00	-13.40	AV	Horizontal
High Channel (2462 MHz)(802.11b)--Above 1G									
4924.102	65.60	5.21	35.52	44.21	62.12	74.00	-11.88	Pk	Vertical
4924.102	43.05	5.21	35.52	44.21	39.57	54.00	-14.43	AV	Vertical
7386.425	60.49	7.10	36.53	44.60	59.52	74.00	-14.48	Pk	Vertical
7386.425	44.95	7.10	36.53	44.60	43.98	54.00	-10.02	AV	Vertical
4924.066	66.42	5.21	35.52	44.21	62.94	74.00	-11.06	Pk	Horizontal
4924.066	47.25	5.21	35.52	44.21	43.77	54.00	-10.23	AV	Horizontal
7386.198	61.07	7.10	36.53	44.60	60.10	74.00	-13.90	Pk	Horizontal
7386.198	44.34	7.10	36.53	44.60	43.37	54.00	-10.63	AV	Horizontal

Note:

- (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamplifier Factor
- (2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
- (3)"802.11b" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

■ Spurious Emission in Restricted Band 2310MHz -18000MHz

All the modulation modes have been tested, and the worst result was report as below:

Module 1:

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11b									
2310.00	58.05	2.97	27.80	43.80	45.02	74	-28.98	Pk	Horizontal
2310.00	43.95	2.97	27.80	43.80	30.92	54	-23.08	AV	Horizontal
2310.00	58.37	2.97	27.80	43.80	45.34	74	-28.66	Pk	Vertical
2310.00	42.03	2.97	27.80	43.80	29.00	54	-25.00	AV	Vertical
2390.00	57.73	3.14	27.21	43.80	44.28	74	-29.72	Pk	Vertical
2390.00	42.15	3.14	27.21	43.80	28.70	54	-25.30	AV	Vertical
2390.00	57.18	3.14	27.21	43.80	43.73	74	-30.27	Pk	Horizontal
2390.00	41.59	3.14	27.21	43.80	28.14	54	-25.86	AV	Horizontal
2483.50	57.82	3.58	27.70	44.00	45.10	74	-28.90	Pk	Vertical
2483.50	42.93	3.58	27.70	44.00	30.21	54	-23.79	AV	Vertical
2483.50	58.58	3.58	27.70	44.00	45.86	74	-28.14	Pk	Horizontal
2483.50	42.02	3.58	27.70	44.00	29.30	54	-24.70	AV	Horizontal
802.11g									
2310.00	59.17	2.97	27.80	43.80	46.14	74	-27.86	Pk	Horizontal
2310.00	43.88	2.97	27.80	43.80	30.85	54	-23.15	AV	Horizontal
2310.00	57.19	2.97	27.80	43.80	44.16	74	-29.84	Pk	Vertical
2310.00	43.18	2.97	27.80	43.80	30.15	54	-23.85	AV	Vertical
2390.00	57.54	3.14	27.21	43.80	44.09	74	-29.91	Pk	Vertical
2390.00	42.09	3.14	27.21	43.80	28.64	54	-25.36	AV	Vertical
2390.00	58.29	3.14	27.21	43.80	44.84	74	-29.16	Pk	Horizontal
2390.00	43.88	3.14	27.21	43.80	30.43	54	-23.57	AV	Horizontal
2483.50	58.84	3.58	27.70	44.00	46.12	74	-27.88	Pk	Vertical
2483.50	43.71	3.58	27.70	44.00	30.99	54	-23.01	AV	Vertical
2483.50	58.86	3.58	27.70	44.00	46.14	74	-27.86	Pk	Horizontal
2483.50	41.69	3.58	27.70	44.00	28.97	54	-25.03	AV	Horizontal
802.11n20									
2310.00	58.02	2.97	27.80	43.80	44.99	74	-29.01	Pk	Horizontal
2310.00	43.58	2.97	27.80	43.80	30.55	54	-23.45	AV	Horizontal
2310.00	58.80	2.97	27.80	43.80	45.77	74	-28.23	Pk	Vertical
2310.00	42.19	2.97	27.80	43.80	29.16	54	-24.84	AV	Vertical
2390.00	58.07	3.14	27.21	43.80	44.62	74	-29.38	Pk	Vertical
2390.00	42.42	3.14	27.21	43.80	28.97	54	-25.03	AV	Vertical
2390.00	56.77	3.14	27.21	43.80	43.32	74	-30.68	Pk	Horizontal
2390.00	41.82	3.14	27.21	43.80	28.37	54	-25.63	AV	Horizontal
2483.50	58.22	3.58	27.70	44.00	45.50	74	-28.50	Pk	Vertical
2483.50	43.06	3.58	27.70	44.00	30.34	54	-23.66	AV	Vertical
2483.50	58.46	3.58	27.70	44.00	45.74	74	-28.26	Pk	Horizontal
2483.50	42.58	3.58	27.70	44.00	29.86	54	-24.14	AV	Horizontal

802.11n40									
2310.00	59.22	2.97	27.80	43.80	46.19	74	-27.81	Pk	Horizontal
2310.00	44.02	2.97	27.80	43.80	30.99	54	-23.01	AV	Horizontal
2310.00	56.95	2.97	27.80	43.80	43.92	74	-30.08	Pk	Vertical
2310.00	43.82	2.97	27.80	43.80	30.79	54	-23.21	AV	Vertical
2390.00	57.56	3.14	27.21	43.80	44.11	74	-29.89	Pk	Vertical
2390.00	42.29	3.14	27.21	43.80	28.84	54	-25.16	AV	Vertical
2390.00	58.54	3.14	27.21	43.80	45.09	74	-28.91	Pk	Horizontal
2390.00	44.09	3.14	27.21	43.80	30.64	54	-23.36	AV	Horizontal
2483.50	58.41	3.58	27.70	44.00	45.69	74	-28.31	Pk	Vertical
2483.50	43.79	3.58	27.70	44.00	31.07	54	-22.93	AV	Vertical
2483.50	58.71	3.58	27.70	44.00	45.99	74	-28.01	Pk	Horizontal
2483.50	42.48	3.58	27.70	44.00	29.76	54	-24.24	AV	Horizontal

Module 2:

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11b									
2310.00	57.45	2.97	27.80	43.80	44.42	74	-29.58	Pk	Horizontal
2310.00	43.87	2.97	27.80	43.80	30.84	54	-23.16	AV	Horizontal
2310.00	58.46	2.97	27.80	43.80	45.43	74	-28.57	Pk	Vertical
2310.00	42.32	2.97	27.80	43.80	29.29	54	-24.71	AV	Vertical
2390.00	57.61	3.14	27.21	43.80	44.16	74	-29.84	Pk	Vertical
2390.00	41.63	3.14	27.21	43.80	28.18	54	-25.82	AV	Vertical
2390.00	57.23	3.14	27.21	43.80	43.78	74	-30.22	Pk	Horizontal
2390.00	41.50	3.14	27.21	43.80	28.05	54	-25.95	AV	Horizontal
2483.50	58.34	3.58	27.70	44.00	45.62	74	-28.38	Pk	Vertical
2483.50	43.45	3.58	27.70	44.00	30.73	54	-23.27	AV	Vertical
2483.50	58.39	3.58	27.70	44.00	45.67	74	-28.33	Pk	Horizontal
2483.50	41.63	3.58	27.70	44.00	28.91	54	-25.09	AV	Horizontal
802.11g									
2310.00	58.96	2.97	27.80	43.80	45.93	74	-28.07	Pk	Horizontal
2310.00	43.61	2.97	27.80	43.80	30.58	54	-23.42	AV	Horizontal
2310.00	56.48	2.97	27.80	43.80	43.45	74	-30.55	Pk	Vertical
2310.00	43.22	2.97	27.80	43.80	30.19	54	-23.81	AV	Vertical
2390.00	58.13	3.14	27.21	43.80	44.68	74	-29.32	Pk	Vertical
2390.00	42.42	3.14	27.21	43.80	28.97	54	-25.03	AV	Vertical
2390.00	58.33	3.14	27.21	43.80	44.88	74	-29.12	Pk	Horizontal
2390.00	43.47	3.14	27.21	43.80	30.02	54	-23.98	AV	Horizontal
2483.50	58.68	3.58	27.70	44.00	45.96	74	-28.04	Pk	Vertical
2483.50	43.90	3.58	27.70	44.00	31.18	54	-22.82	AV	Vertical
2483.50	58.43	3.58	27.70	44.00	45.71	74	-28.29	Pk	Horizontal
2483.50	41.97	3.58	27.70	44.00	29.25	54	-24.75	AV	Horizontal
802.11n20									
2310.00	57.78	2.97	27.80	43.80	44.75	74	-29.25	Pk	Horizontal
2310.00	43.65	2.97	27.80	43.80	30.62	54	-23.38	AV	Horizontal
2310.00	59.09	2.97	27.80	43.80	46.06	74	-27.94	Pk	Vertical
2310.00	42.36	2.97	27.80	43.80	29.33	54	-24.67	AV	Vertical
2390.00	58.32	3.14	27.21	43.80	44.87	74	-29.13	Pk	Vertical
2390.00	42.34	3.14	27.21	43.80	28.89	54	-25.11	AV	Vertical
2390.00	56.33	3.14	27.21	43.80	42.88	74	-31.12	Pk	Horizontal
2390.00	42.72	3.14	27.21	43.80	29.27	54	-24.73	AV	Horizontal
2483.50	57.76	3.58	27.70	44.00	45.04	74	-28.96	Pk	Vertical
2483.50	42.57	3.58	27.70	44.00	29.85	54	-24.15	AV	Vertical
2483.50	58.42	3.58	27.70	44.00	45.70	74	-28.30	Pk	Horizontal
2483.50	42.25	3.58	27.70	44.00	29.53	54	-24.47	AV	Horizontal

802.11n40									
2310.00	59.52	2.97	27.80	43.80	46.49	74	-27.51	Pk	Horizontal
2310.00	44.07	2.97	27.80	43.80	31.04	54	-22.96	AV	Horizontal
2310.00	57.13	2.97	27.80	43.80	44.10	74	-29.90	Pk	Vertical
2310.00	43.10	2.97	27.80	43.80	30.07	54	-23.93	AV	Vertical
2390.00	57.81	3.14	27.21	43.80	44.36	74	-29.64	Pk	Vertical
2390.00	42.01	3.14	27.21	43.80	28.56	54	-25.44	AV	Vertical
2390.00	58.79	3.14	27.21	43.80	45.34	74	-28.66	Pk	Horizontal
2390.00	43.96	3.14	27.21	43.80	30.51	54	-23.49	AV	Horizontal
2483.50	59.00	3.58	27.70	44.00	46.28	74	-27.72	Pk	Vertical
2483.50	43.81	3.58	27.70	44.00	31.09	54	-22.91	AV	Vertical
2483.50	58.77	3.58	27.70	44.00	46.05	74	-27.95	Pk	Horizontal
2483.50	42.04	3.58	27.70	44.00	29.32	54	-24.68	AV	Horizontal

Spurious Emission in Restricted Bands 3260MHz- 18000MHz

All the modulation modes have been tested, the worst result was report as below:

Module 1:

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	60.08	4.04	29.57	44.70	48.99	74	-25.01	Pk	Vertical
3260	56.17	4.04	29.57	44.70	45.08	54	-8.92	AV	Vertical
3260	62.09	4.04	29.57	44.70	51.00	74	-23.00	Pk	Horizontal
3260	56.35	4.04	29.57	44.70	45.26	54	-8.74	AV	Horizontal
3332	64.50	4.26	29.87	44.40	54.23	74	-19.77	Pk	Vertical
3332	54.09	4.26	29.87	44.40	43.82	54	-10.18	AV	Vertical
3332	63.32	4.26	29.87	44.40	53.05	74	-20.95	Pk	Horizontal
3332	52.37	4.26	29.87	44.40	42.10	54	-11.90	AV	Horizontal
17797	43.23	10.99	43.95	43.50	54.67	74	-19.33	Pk	Vertical
17797	32.62	10.99	43.95	43.50	44.06	54	-9.94	AV	Vertical
17788	43.77	11.81	43.69	44.60	54.67	74	-19.33	Pk	Horizontal
17788	31.95	11.81	43.69	44.60	42.85	54	-11.15	AV	Horizontal

Module 2:

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	60.97	4.04	29.57	44.70	49.88	74	-24.12	Pk	Vertical
3260	55.61	4.04	29.57	44.70	44.52	54	-9.48	AV	Vertical
3260	61.80	4.04	29.57	44.70	50.71	74	-23.29	Pk	Horizontal
3260	56.34	4.04	29.57	44.70	45.25	54	-8.75	AV	Horizontal
3332	64.14	4.26	29.87	44.40	53.87	74	-20.13	Pk	Vertical
3332	53.81	4.26	29.87	44.40	43.54	54	-10.46	AV	Vertical
3332	62.72	4.26	29.87	44.40	52.45	74	-21.55	Pk	Horizontal
3332	53.17	4.26	29.87	44.40	42.90	54	-11.10	AV	Horizontal
17797	43.46	10.99	43.95	43.50	54.90	74	-19.10	Pk	Vertical
17797	32.87	10.99	43.95	43.50	44.31	54	-9.69	AV	Vertical
17788	43.35	11.81	43.69	44.60	54.25	74	-19.75	Pk	Horizontal
17788	31.78	11.81	43.69	44.60	42.68	54	-11.32	AV	Horizontal

"802.11b" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.2.

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

VBW $\geq 3 \times$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.3.6 Test Results

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.4 DUTY CYCLE

7.4.1 Applicable Standard

According to KDB 558074 D01 15.247 Meas Guidance v05r02 Section 6.

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value.
- 3) Set VBW $\geq$ RBW. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

Measure T_{total} and T_{on}

Calculate Duty Cycle = T_{on} / T_{total}

7.4.6 Test Results

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.5 MAXIMUM OUTPUT POWER

7.5.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.3.2.3.

7.5.2 Conformance Limit


The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.5.3 Measuring Instruments

The following table is the setting of the power meter.

Power meter parameter	Setting
Detector	PK

7.5.4 Test Setup



7.5.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.9.1.3 of ANSI C63.10

7.5.6 EUT operation during Test

The EUT was programmed to be in continuously transmitting mode.

7.5.7 Test Results

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.6 POWER SPECTRAL DENSITY

7.6.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.4.

7.6.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 * \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6.6 Test Results

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.7 CONDUCTED BAND EDGE MEASUREMENT

7.7.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

7.7.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

7.7.6 Test Results

EUT:	Air Disinfection Robot	Model No.:	ME1253C001F0
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.8 SPURIOUS RF CONDUCTED EMISSIONS

7.8.1 Conformance Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.3 Test Setup

Please refer to Section 6.1 of this test report.

7.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 26.5GHz.

7.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

Test data reference attachment.

7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 Result

The EUT antenna is permanent attached FPCB Antenna (Gain: 3.21 dBi)(Module 1); Sucker Antenna (Module 2- Antenna 1) (Gain: 2 dBi); Sucker Antenna (Module 2- Antenna 2) (Gain: 2 dBi)It comply with the standard requirement.


8 TEST RESULTS

MODULE 1:


8.1.1 DUTY CYCLE

Condition	Mode	Frequency (MHz)	Duty Cycle (%)
NVNT	802.11b	2412	99.36
NVNT	802.11b	2437	99.3
NVNT	802.11b	2462	98.73
NVNT	802.11g	2412	98.45
NVNT	802.11g	2437	98.28
NVNT	802.11g	2462	98.75
NVNT	802.11n(HT20)	2412	98.84
NVNT	802.11n(HT20)	2437	98.29
NVNT	802.11n(HT20)	2462	98.95
NVNT	802.11n(HT40)	2422	98.28
NVNT	802.11n(HT40)	2437	98.23
NVNT	802.11n(HT40)	2452	98.01


Duty Cycle NVNT 802.11b 2412MHz




Duty Cycle NVNT 802.11b 2437MHz




Duty Cycle NVNT 802.11b 2462MHz




Duty Cycle NVNT 802.11g 2412MHz




Duty Cycle NVNT 802.11g 2437MHz




Duty Cycle NVNT 802.11g 2462MHz




Duty Cycle NVNT 802.11n(HT20) 2412MHz




Duty Cycle NVNT 802.11n(HT20) 2437MHz




Duty Cycle NVNT 802.11n(HT20) 2462MHz




Duty Cycle NVNT 802.11n(HT40) 2422MHz



Duty Cycle NVNT 802.11n(HT40) 2437MHz



Duty Cycle NVNT 802.11n(HT40) 2452MHz




8.1.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	802.11b	2412	Ant 1	14.94	30	Pass
NVNT	802.11b	2437	Ant 1	15.51	30	Pass
NVNT	802.11b	2462	Ant 1	15.66	30	Pass
NVNT	802.11g	2412	Ant 1	13.37	30	Pass
NVNT	802.11g	2437	Ant 1	12.64	30	Pass
NVNT	802.11g	2462	Ant 1	12.4	30	Pass
NVNT	802.11n(HT20)	2412	Ant 1	11.03	30	Pass
NVNT	802.11n(HT20)	2437	Ant 1	10.7	30	Pass
NVNT	802.11n(HT20)	2462	Ant 1	10.68	30	Pass
NVNT	802.11n(HT40)	2422	Ant 1	10.25	30	Pass
NVNT	802.11n(HT40)	2437	Ant 1	9.59	30	Pass
NVNT	802.11n(HT40)	2452	Ant 1	9.78	30	Pass


8.1.3 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	802.11b	2412	Ant 1	15.1049	9.52	0.5	Pass
NVNT	802.11b	2437	Ant 1	15.025	9.6	0.5	Pass
NVNT	802.11b	2462	Ant 1	14.7852	10.04	0.5	Pass
NVNT	802.11g	2412	Ant 1	16.8631	16.28	0.5	Pass
NVNT	802.11g	2437	Ant 1	16.8232	15.76	0.5	Pass
NVNT	802.11g	2462	Ant 1	16.6234	16.04	0.5	Pass
NVNT	802.11n(HT20)	2412	Ant 1	17.9021	17.2	0.5	Pass
NVNT	802.11n(HT20)	2437	Ant 1	18.0619	16.56	0.5	Pass
NVNT	802.11n(HT20)	2462	Ant 1	17.8621	16.36	0.5	Pass
NVNT	802.11n(HT40)	2422	Ant 1	37.003	35.36	0.5	Pass
NVNT	802.11n(HT40)	2437	Ant 1	36.044	35.28	0.5	Pass
NVNT	802.11n(HT40)	2452	Ant 1	35.8841	35.12	0.5	Pass


OBW NVNT 802.11b 2412MHz Ant1




-6 dB BW NVNT 802.11b 2412MHz Ant1




OBW NVNT 802.11b 2437MHz Ant1




-6 dB BW NVNT 802.11b 2437MHz Ant1




OBW NVNT 802.11b 2462MHz Ant1




-6 dB BW NVNT 802.11b 2462MHz Ant1




OBW NVNT 802.11g 2412MHz Ant1




-6 dB BW NVNT 802.11g 2412MHz Ant1




OBW NVNT 802.11g 2437MHz Ant1




-6 dB BW NVNT 802.11g 2437MHz Ant1




OBW NVNT 802.11g 2462MHz Ant1




-6 dB BW NVNT 802.11g 2462MHz Ant1




OBW NVNT 802.11n(HT20) 2412MHz Ant1




-6 dB BW NVNT 802.11n(HT20) 2412MHz Ant1




OBW NVNT 802.11n(HT20) 2437MHz Ant1




-6 dB BW NVNT 802.11n(HT20) 2437MHz Ant1




OBW NVNT 802.11n(HT20) 2462MHz Ant1




-6 dB BW NVNT 802.11n(HT20) 2462MHz Ant1




OBW NVNT 802.11n(HT40) 2422MHz Ant1




-6 dB BW NVNT 802.11n(HT40) 2422MHz Ant1




OBW NVNT 802.11n(HT40) 2437MHz Ant1




-6 dB BW NVNT 802.11n(HT40) 2437MHz Ant1



OBW NVNT 802.11n(HT40) 2452MHz Ant1







8.1.4 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	802.11b	2412	Ant 1	-6.772	8	Pass
NVNT	802.11b	2437	Ant 1	-5.933	8	Pass
NVNT	802.11b	2462	Ant 1	-5.857	8	Pass
NVNT	802.11g	2412	Ant 1	-12.216	8	Pass
NVNT	802.11g	2437	Ant 1	-13.206	8	Pass
NVNT	802.11g	2462	Ant 1	-12.881	8	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-12.93	8	Pass
NVNT	802.11n(HT20)	2437	Ant 1	-15.175	8	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-15.685	8	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-17.831	8	Pass
NVNT	802.11n(HT40)	2437	Ant 1	-17.503	8	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-17.597	8	Pass


PSD NVNT 802.11b 2412MHz Ant1




PSD NVNT 802.11b 2437MHz Ant1




PSD NVNT 802.11b 2462MHz Ant1




PSD NVNT 802.11g 2412MHz Ant1




PSD NVNT 802.11g 2437MHz Ant1




PSD NVNT 802.11g 2462MHz Ant1




PSD NVNT 802.11n(HT20) 2412MHz Ant1




PSD NVNT 802.11n(HT20) 2437MHz Ant1




PSD NVNT 802.11n(HT20) 2462MHz Ant1




PSD NVNT 802.11n(HT40) 2422MHz Ant1



PSD NVNT 802.11n(HT40) 2437MHz Ant1




PSD NVNT 802.11n(HT40) 2452MHz Ant1




8.1.5 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	802.11b	2412	Ant 1	-53.52	-20	Pass
NVNT	802.11b	2462	Ant 1	-58.57	-20	Pass
NVNT	802.11g	2412	Ant 1	-45.77	-20	Pass
NVNT	802.11g	2462	Ant 1	-52.09	-20	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-44.14	-20	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-49.59	-20	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-36.6	-20	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-47.38	-20	Pass


Band Edge NVNT 802.11b 2412MHz Ant1 Ref



Band Edge NVNT 802.11b 2412MHz Ant1 Emission




Band Edge NVNT 802.11b 2462MHz Ant1 Ref




Band Edge NVNT 802.11b 2462MHz Ant1 Emission




Band Edge NVNT 802.11g 2412MHz Ant1 Ref




Band Edge NVNT 802.11g 2412MHz Ant1 Emission




Band Edge NVNT 802.11g 2462MHz Ant1 Ref




Band Edge NVNT 802.11g 2462MHz Ant1 Emission




Band Edge NVNT 802.11n(HT20) 2412MHz Ant1 Ref




Band Edge NVNT 802.11n(HT20) 2412MHz Ant1 Emission



Band Edge NVNT 802.11n(HT20) 2462MHz Ant1 Ref



Band Edge NVNT 802.11n(HT20) 2462MHz Ant1 Emission



Band Edge NVNT 802.11n(HT40) 2422MHz Ant1 Ref

