TCT 通测检测
TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID. ..... :	2A5XB-D600PRO	
Test Report No..... :	TCT240617E020	
Date of issue..... :	Jul. 03, 2024	
Testing laboratory ..... :	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Shenzhen Yutu Technology Co., Ltd.	
Address..... :	1301, Block A, Building 1, Shenzhen International, Innovation Valley, Xili Street, Nanshan District, Shenzhen, China	
Manufacturer's name ... :	Shenzhen Yutu Technology Co., Ltd.	
Address..... :	1301, Block A, Building 1, Shenzhen International, Innovation Valley, Xili Street, Nanshan District, Shenzhen, China	
Standard(s) ..... :	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name..... :	Dash cam	
Trade Mark ..... :	N/A	
Model/Type reference..... :	D600Pro, D100, D100Pro, D200Pro, D1000Pro, D400, E100, E200, E300, E400, E500, E600, E700, E800, E900, E1000	
Rating(s)..... :	DC 12V	
Date of receipt of test item ..... :	Jun. 17, 2024	
Date (s) of performance of test..... :	Jun. 17, 2024 ~ Jul. 03, 2024	
Tested by (+signature) ... :	Onnado YE	Onnado YE
Check by (+signature).... :	Beryl ZHAO	Beryl Zhao
Approved by (+signature):	Tomsin	Tomsin

SHENZHEN TONGCE TESTING LAB TCT

General disclaimer:
This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information 3
1.1. EUT description 3
1.2. Model(s) list 3
1.3. Test Frequency 3
2. Test Result Summary 4
3. General Information 5
3.1. Test environment and mode 5
3.2. Description of Support Units 6
4. Facilities and Accreditations 7
4.1. Facilities 7
4.2. Location 7
4.3. Measurement Uncertainty 7
5. Test Results and Measurement Data 8
5.1. Antenna requirement 8
5.2. Conducted Emission 9
5.3. Maximum Conducted Output Power 13
5.4. 6dB Emission Bandwidth 15
5.5. 26dB Bandwidth and 99% Occupied Bandwidth 16
5.6. Power Spectral Density 17
5.7. Band edge 18
5.8. Unwanted Emissions 25
5.9. Frequency Stability Measurement 33
Appendix A: Test Result of Conducted Test
Appendix B: Photographs of Test Setup
Appendix C: Photographs of EUT

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

1. General Product Information

1.1. EUT description

Product Name.....:	Dash cam
Model/Type reference.....:	D600Pro
Sample Number.....:	TCT240617E020-0101
Operation Frequency.....:	Band 1: 5180 MHz ~ 5240 MHz
Channel Bandwidth.....:	802.11a: 20MHz 802.11n: 20MHz, 40MHz
Modulation Technology.....:	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type.....:	64QAM, 16QAM, BPSK, QPSK
Antenna Type.....:	FPC Antenna
Antenna Gain.....:	4.31dBi
Rating(s).....:	DC 12V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	D600Pro	☒
Other models	D100, D100Pro, D200Pro, D1000Pro, D400, E100, E200, E300, E400, E500, E600, E700, E800, E900, E1000	☐
Note: D600Pro is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of D600Pro can represent the remaining models.		

1.3. Test Frequency

Band 1

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
36	5180	38	5190
40	5200	46	5230
48	5240		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

5.For the band 5.15-5.25GHz,EUT meet the requirements of 15.407(a)(ii).

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. General Information

3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	22.8 °C	24.2 °C
Humidity:	49 % RH	50 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar

Test Software:	
Software Information:	Putty
Power Level:	Default

Test Mode:	
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max duty cycle

The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
  SHENZHEN TONGCE TESTING LAB
  Designation Number: CN1205
  The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A-1
  SHENZHEN TONGCE TESTING LAB
  CAB identifier: CN0031
  The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB
Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The WIFI antenna is FPC antenna which permanently attached, and the best case gain of the antenna is 4.31dBi.	



5.2. Conducted Emission

5.2.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.207</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10:2013</td></tr>
<tr><td>Frequency Range:</td><td>150 kHz to 30 MHz</td></tr>
<tr><td>Receiver setup:</td><td>RBW=9 kHz, VBW=30 kHz, Sweep time=auto</td></tr>
<tr><td>Limits:</td><td>
<table>
<tr><td rowspan="2">Frequency range (MHz)</td><td colspan="2">Limit (dBuV)</td></tr>
<tr><td>Quasi-peak</td><td>Average</td></tr>
<tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr>
<tr><td>0.5-5</td><td>56</td><td>46</td></tr>
<tr><td>5-30</td><td>60</td><td>50</td></tr>
</table>
</td></tr>
<tr><td>Test Setup:</td><td>


Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting Mode</td></tr>
<tr><td>Test Procedure:</td><td>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</td></tr>
<tr><td>Test Result:</td><td>PASS</td></tr>
</table>

5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 31, 2025
Attenuator	N/A	10dB	164080	Jun. 26, 2025
Line-5	TCT	CE-05	/	Jun. 26, 2025
EMI Test Software	EZ_EMC	EMEC-3A1	1.1.4.2	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: *L1* | Temperature: 22.8 (℃) | Humidity: 49 %

Limit: FCC Part 15C Conduction(QP) | Power: DC 12 V

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	38.39	10.02	48.41	66.00	-17.59	QP	
2		0.1500	33.79	10.02	43.81	56.00	-12.19	AVG	
3		0.2859	34.03	9.85	43.88	60.64	-16.76	QP	
4	*	0.2859	33.86	9.85	43.71	50.64	-6.93	AVG	
5		0.4300	29.24	9.41	38.65	57.25	-18.60	QP	
6		0.4300	26.82	9.41	36.23	47.25	-11.02	AVG	
7		0.5700	20.61	9.28	29.89	56.00	-26.11	QP	
8		0.5700	18.14	9.28	27.42	46.00	-18.58	AVG	
9		0.7138	19.37	9.15	28.52	56.00	-27.48	QP	
10		0.7138	18.97	9.15	28.12	46.00	-17.88	AVG	
11		23.3300	37.20	10.71	47.91	60.00	-12.09	QP	
12		23.3300	19.83	10.71	30.54	50.00	-19.46	AVG	

Note:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = LISN factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak
AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: *N* | Temperature: 22.8 (℃) | Humidity: 49 %

Limit: FCC Part 15C Conduction(QP) | Power: DC 12 V

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	38.90	10.00	48.90	66.00	-17.10	QP	
2		0.1500	31.53	10.00	41.53	56.00	-14.47	AVG	
3		0.2860	34.01	9.83	43.84	60.64	-16.80	QP	
4	*	0.2860	33.39	9.83	43.22	50.64	-7.42	AVG	
5		0.4300	28.05	9.39	37.44	57.25	-19.81	QP	
6		0.4300	25.26	9.39	34.65	47.25	-12.60	AVG	
7		0.5738	19.26	9.25	28.51	56.00	-27.49	QP	
8		0.5738	18.76	9.25	28.01	46.00	-17.99	AVG	
9		0.7139	19.54	9.12	28.66	56.00	-27.34	QP	
10		0.7139	19.15	9.12	28.27	46.00	-17.73	AVG	
11		23.3300	36.36	10.64	47.00	60.00	-13.00	QP	
12		23.3300	20.33	10.64	30.97	50.00	-19.03	AVG	

Note:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = LISN factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak
AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*
Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40)) and the worst case Mode (Lowest channel and 802.11a) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046</td></tr>
<tr><td>Test Method:</td><td>KDB662911 D01 Multiple Transmitter Output v02r01
KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E</td></tr>
<tr><td>Limit:</td><td><table>
<tr><td>Frequency Band (MHz)</td><td>Limit</td></tr>
<tr><td>5180 - 5240</td><td>24dBm(250mW) for client device</td></tr>
<tr><td>5260 - 5320</td><td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td></tr>
<tr><td>5470 - 5725</td><td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td></tr>
<tr><td>5745 - 5825</td><td>30dBm(1W)</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting mode with modulation</td></tr>
<tr><td>Test Procedure:</td><td>1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.</td></tr>
<tr><td>Test Result:</td><td>PASS</td></tr>
<tr><td>Remark:</td><td>Conducted output power= measurement power +10log(1/x) X is duty cycle=1, so 10log(1/1)=0
Conducted output power= measurement power</td></tr>
</table>

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Power Meter	Agilent	E4418B	MY45100357	Jun. 26, 2025
Power Sensor	Agilent	8184A	MY41096530	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz The e.i,r,p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.7. Band edge

5.7.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC CFR47 Part 15E Section 15.407</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10 2013</td></tr>
<tr><td>Limit:</td><td>In un-restricted band:
For Band 1&2A&2C: -27dBm/MHz
For Band 3:
<table>
<tr><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td></tr>
<tr><td>< 5650</td><td>-27</td><td>5850~5855</td><td>27~15.6</td></tr>
<tr><td>5650~5700</td><td>-27~10</td><td>5855~5875</td><td>15.6~10</td></tr>
<tr><td>5700~5720</td><td>10~15.6</td><td>5875~5925</td><td>10~-27</td></tr>
<tr><td>5720~5725</td><td>15.6~27</td><td>> 5925</td><td>-27</td></tr>
</table>
E[dBμV/m] = EIRP[dBm] + 95.2 @3m
In restricted band:
<table>
<tr><td>Detector</td><td>Limit@3m</td></tr>
<tr><td>Peak</td><td>74dBμV/m</td></tr>
<tr><td>AVG</td><td>54dBμV/m</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting mode with modulation</td></tr>
<tr><td>Test Procedure:</td><td>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold</td></tr>
</table>

	Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI7	100529	Jan. 31, 2025
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 31, 2025
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 31, 2025
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 26, 2025
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 02, 2025
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025
Antenna Mast	Keleto	RE-AM	/	/
EMI Test Software	EZ_EMC	FA-03A2 RE+	1.1.4.2	/

5.7.3. Test Data

A20-5180



Site: 3m Anechoic Chamber Polarization: *Horizontal* Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	58.29	-9.24	49.05	74.00	-24.95	peak	P	
2 *	5150.000	46.13	-9.24	36.89	54.00	-17.11	AVG	P	



Site: 3m Anechoic Chamber Polarization: *Vertical* Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	60.97	-9.24	51.73	74.00	-22.27	peak	P	
2 *	5150.000	49.35	-9.24	40.11	54.00	-13.89	AVG	P	

A20-5240



Site: 3m Anechoic Chamber Polarization: *Horizontal* Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	52.15	-8.15	44.00	74.00	-30.00	peak	P	
2 *	5350.000	42.15	-8.15	34.00	54.00	-20.00	AVG	P	



Site: 3m Anechoic Chamber Polarization: *Vertical* Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.15	-8.15	43.00	74.00	-31.00	peak	P	
2 *	5350.000	42.06	-8.15	33.91	54.00	-20.09	AVG	P	

N40-5190



Site: 3m Anechoic Chamber Polarization: *Horizontal* Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	59.94	-9.24	50.70	74.00	-23.30	peak	P	
2 *	5150.000	52.69	-9.24	43.45	54.00	-10.55	AVG	P	



Site: 3m Anechoic Chamber Polarization: *Vertical* Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	65.88	-9.24	56.64	74.00	-17.36	peak	P	
2 *	5150.000	58.13	-9.24	48.89	54.00	-5.11	AVG	P	

N40-5230



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	52.38	-8.15	44.23	74.00	-29.77	peak	P	
2 *	5350.000	42.67	-8.15	34.52	54.00	-19.48	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.00	-8.15	42.85	74.00	-31.15	peak	P	
2 *	5350.000	42.97	-8.15	34.82	54.00	-19.18	AVG	P	

Note: *All modulation (802.11a, 802.11n) have been tested, only the worst case in 802.11a, 802.11n(HT40) be reported.*

5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205
Test Method:	KDB 789033 D02 v02r01
Frequency Range:	9kHz to 40GHz
Measurement Distance:	3 m
Antenna Polarization:	Horizontal & Vertical
Operation mode:	Transmitting mode with modulation
Receiver Setup:	

Frequency	Detector	RBW	VBW	Remark
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit:

Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

In restricted bands:

Frequency	Detector	Limit@3m
Above 1G	Peak	74dBμV/m
	AVG	54dBμV/m

Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(KHz)	300
0.49 -1.705	24000/F(KHz)	3
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

In un-restricted bands: 68.2dBuV/m

Test setup:

For radiated emissions below 30MHz



30MHz to 1GHz

	 Above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the groundat a 3 meter camber. The table was rotated 360 degrees todetermine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and thenthe antenna was tuned to heights from 1 meter to 4 meters and the rotatablewas turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and SpecifiedBandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limitspecified, then testing could be stopped and the peak values of the EUT wouldbe reported. Otherwise the emissions that did not have 10dB margin would bere-tested one by one using peak, quasi-peak or average method as specified andthen reported in a data sheet.
Test results:	PASS

5.8.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI7	100529	Jan. 31, 2025
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 31, 2025
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 31, 2025
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 26, 2025
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 02, 2025
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025
Antenna Mast	Keleto	RE-AM	/	/
EMI Test Software	EZ_EMC	FA-03A2 RE+	1.1.4.2	/

5.8.3. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site: 3m Anechoic Chamber1 Polarization: *Horizontal* Temperature: 24.2(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m Power: DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	216.7828	42.54	-14.49	28.05	46.00	-17.95	QP	P	
2 *	374.6225	48.01	-8.89	39.12	46.00	-6.88	QP	P	
3	379.9141	42.17	-8.80	33.37	46.00	-12.63	QP	P	
4	562.6624	41.81	-5.33	36.48	46.00	-9.52	QP	P	
5	647.3856	36.08	-3.31	32.77	46.00	-13.23	QP	P	
6	893.8567	33.90	-0.26	33.64	46.00	-12.36	QP	P	

Vertical:



Site: 3m Anechoic Chamber1 Polarization: *Vertical* Temperature: 24.2(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m Power: DC 12 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	47.6586	45.21	-12.57	32.64	40.00	-7.36	QP	P	
2	162.6106	40.72	-11.12	29.60	43.50	-13.90	QP	P	
3	189.7385	44.96	-13.79	31.17	43.50	-12.33	QP	P	
4	216.7828	47.02	-14.49	32.53	46.00	-13.47	QP	P	
5	374.6225	44.74	-8.89	35.85	46.00	-10.15	QP	P	
6 *	906.4824	40.21	0.00	40.21	46.00	-5.79	QP	P	

Note: *1.The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported*

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40)) and the worst case Mode (Lowest channel and 802.11a) was submitted only.

3.Measurement (dBμV) = Reading level + Correction Factor , correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.12	---	8.02	46.14	---	68.2	---	-22.06
15540	H	38.03	---	9.87	47.9	---	74	54	-6.1
---	H	---	---	---	---	---	---	---	---
10360	V	38.39	---	8.02	46.41	---	68.2	---	-21.79
15540	V	38.66	---	9.87	48.53	---	74	54	-5.47
---	V	---	---	---	---	----	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.47	---	7.97	47.44	---	68.2	---	-20.76
15600	H	39.35	---	9.83	49.18	---	74	54	-4.82
---	H	---	---	---	---	---	---	---	---
10400	V	41.38	---	7.97	49.35	---	68.2	---	-18.85
15600	V	38.61	---	9.83	48.44	---	74	54	-5.56
---	V	---	---	---	---	----	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	38.22	---	7.97	46.19	---	68.2	---	-22.01
15720	H	37.84	---	9.83	47.67	---	74	54	-6.33
---	H	---	---	---	---	---	---	---	---
10480	V	39.56	---	7.97	47.53	---	68.2	---	-20.67
15720	V	36.49	---	9.83	46.32	---	74	54	-7.68
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.23	---	8.02	49.25	---	68.2	---	-18.95
15540	H	38.71	---	9.87	48.58	---	74	54	-5.42
---	H	---	---	---	---	---	---	---	---
10360	V	42.37	---	8.02	50.39	---	68.2	---	-17.81
15540	V	38.16	---	9.87	48.03	---	74	54	-5.97
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.12	---	7.97	48.09	---	68.2	---	-20.11
15600	H	38.31	---	9.83	48.14	---	74	54	-5.86
---	H	---	---	---	---	---	---	---	---
10400	V	40.56	---	7.97	48.53	---	68.2	---	-19.67
15600	V	38.04	---	9.83	47.87	---	74	54	-6.13
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.79	---	7.97	49.76	---	68.2	---	-18.44
15720	H	40.44	---	9.83	50.27	---	74	54	-3.73
---	H	---	---	---	---	---	---	---	---
10480	V	41.62	---	7.97	49.59	---	68.2	---	-18.61
15720	V	40.11	---	9.83	49.94	---	74	54	-4.06
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.03	---	7.75	46.78	---	68.2	---	-21.42
15570	H	37.96	---	9.87	47.83	---	74	54	-6.17
---	H	---	---	---	---	---	---	---	---
10380	V	40.99	---	7.75	48.74	---	68.2	---	-19.46
15570	V	38.18	---	9.87	48.05	---	74	54	-5.95
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.26	---	7.97	49.23	---	68.2	---	-18.97
15690	H	39.84	---	9.83	49.67	---	74	54	-4.33
---	H	---	---	---	---	---	---	---	---
10460	V	42.42	---	7.97	50.39	---	68.2	---	-17.81
15690	V	39.18	---	9.83	49.01	---	74	54	-4.99
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	
Test Procedure:	The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at all models(11a,11n), the worst case (11a) was found and test data was shown in this report.

Test plots as follows:

Test mode:	802.11a	Frequency(MHz):	5180	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	12V	5180.12	120000	PASS
35		5180.12	120000	PASS
25		5180.12	120000	PASS
15		5180.12	120000	PASS
5		5180.10	100000	PASS
0		5180.10	100000	PASS
25	10.2V	5180.12	120000	PASS
	12V	5180.10	100000	PASS
	13.8V	5180.12	120000	PASS

Test mode:	802.11a	Frequency(MHz):	5200	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	12V	5200.10	100000	PASS
35		5200.10	100000	PASS
25		5200.10	100000	PASS
15		5200.10	100000	PASS
5		5200.10	100000	PASS
0		5200.10	100000	PASS
25	10.2V	5200.10	100000	PASS
	12V	5200.10	100000	PASS
	13.8V	5200.10	100000	PASS

Test mode:	802.11a	Frequency(MHz):	5240	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	12V	5200.10	100000	PASS
35		5200.10	100000	PASS
25		5200.10	100000	PASS
15		5200.10	100000	PASS
5		5200.10	100000	PASS
0		5200.10	100000	PASS
25	10.2V	5240.12	120000	PASS
	12V	5240.12	120000	PASS
	13.8V	5240.10	100000	PASS

Appendix A: Test Result of Conducted Test

Duty Cycle

Condition	Mode	Frequency (MHz)	Duty Cycle (%)
NVNT	a	5180	100
NVNT	a	5200	100
NVNT	a	5240	100
NVNT	n20	5180	100
NVNT	n20	5200	100
NVNT	n20	5240	100
NVNT	n40	5190	100
NVNT	n40	5230	100

Test Graphs

Duty Cycle NVNT a 5180MHz



Duty Cycle NVNT a 5200MHz



Duty Cycle NVNT a 5240MHz



Duty Cycle NVNT n20 5180MHz



Duty Cycle NVNT n20 5200MHz



Duty Cycle NVNT n20 5240MHz



Duty Cycle NVNT n40 5190MHz



Duty Cycle NVNT n40 5230MHz



Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	10.41	24	Pass
NVNT	a	5200	9.42	24	Pass
NVNT	a	5240	9.40	24	Pass
NVNT	n20	5180	9.57	24	Pass
NVNT	n20	5200	9.49	24	Pass
NVNT	n20	5240	9.28	24	Pass
NVNT	n40	5190	9.50	24	Pass
NVNT	n40	5230	9.35	24	Pass

Test Graphs

Power NVNT a 5180MHz



Power NVNT a 5200MHz



Power NVNT a 5240MHz



Power NVNT n20 5180MHz



Power NVNT n20 5200MHz



Power NVNT n20 5240MHz



Power NVNT n40 5190MHz



Power NVNT n40 5230MHz



-26dB Bandwidth

Condition	Mode	Frequency (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	25.314	Pass
NVNT	a	5200	20.948	Pass
NVNT	a	5240	21.048	Pass
NVNT	n20	5180	22.001	Pass
NVNT	n20	5200	21.827	Pass
NVNT	n20	5240	21.779	Pass
NVNT	n40	5190	48.584	Pass
NVNT	n40	5230	43.454	Pass

Test Graphs

-26dB Bandwidth NVNT a 5180MHz



-26dB Bandwidth NVNT a 5200MHz



-26dB Bandwidth NVNT a 5240MHz



-26dB Bandwidth NVNT n20 5180MHz



-26dB Bandwidth NVNT n20 5200MHz



-26dB Bandwidth NVNT n20 5240MHz



-26dB Bandwidth NVNT n40 5190MHz



-26dB Bandwidth NVNT n40 5230MHz



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	a	5180	16.573
NVNT	a	5200	16.533
NVNT	a	5240	16.531
NVNT	n20	5180	17.669
NVNT	n20	5200	17.636
NVNT	n20	5240	17.638
NVNT	n40	5190	35.717
NVNT	n40	5230	35.710

Test Graphs

OBW NVNT a 5180MHz



OBW NVNT a 5200MHz



OBW NVNT a 5240MHz



OBW NVNT n20 5180MHz



OBW NVNT n20 5200MHz



OBW NVNT n20 5240MHz



OBW NVNT n40 5190MHz



OBW NVNT n40 5230MHz



Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Conducted PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	-0.92	11	Pass
NVNT	a	5200	-1.83	11	Pass
NVNT	a	5240	-1.82	11	Pass
NVNT	n20	5180	-1.68	11	Pass
NVNT	n20	5200	-1.94	11	Pass
NVNT	n20	5240	-2.17	11	Pass
NVNT	n40	5190	-4.71	11	Pass
NVNT	n40	5230	-4.82	11	Pass

Test Graphs

PSD NVNT a 5180MHz



PSD NVNT a 5200MHz



PSD NVNT a 5240MHz



PSD NVNT n20 5180MHz



PSD NVNT n20 5200MHz



PSD NVNT n20 5240MHz



PSD NVNT n40 5190MHz



PSD NVNT n40 5230MHz



Appendix B: Photographs of Test Setup

Product: Dash cam
Model: D600Pro
Radiated Emission





Conducted Emission



Appendix C: Photographs of EUT

Product: Dash cam
Model: D600Pro
External Photos

Product: Dash cam
Model: D600Pro
Internal Photos












RTL8731BS
N61CWP7
GN26





*******END OF REPORT*******