

Bluetooth antenna specification

一、Antenna introduction

The Bluetooth module antenna is directly used on the PCB board.

二、Antenna size diagram



三、Antenna parameter

PCB Antenna	
Frequency (MHz)	2402 ~ 2480 MHz
VSWR	≤ 1.92
Impedance	50 Ohm Nominal
Return Loss	-10 dB Max
Radiation	Omni-directional
Gain (Peak)	1.08443dBi
Polarization	Linear, Vertical
Admitted Power	2W
Connector	Tin
Antenna type	PCB Antenna
Antenna model	WKZP010EA Antenna

四、Antenna gain detection report

Spectrum Detector:

PK

Test Date :

June 8, 2013

Test By:

Andy

Temperature :

28℃

Test Result:

PASS

Humidity :


55 %

Modulation:


GFSK

Frequency VNA (MHz)	E Total. dB(dB)
2400MHz	0.0403503
2410MHz	0.0886264
2420MHz	0.267381
2430MHz	0.193012
2440MHz	0.26366
2450MHz	0.0723139
2460MHz	0.36895
2470MHz	0.551525
2480MHz	0.640702
2490MHz	1.05232
2500MHz	1.08443


radiation pattern:



PHI 0°




PHI 90°



THETA 90°

VSWR:



Product Description

GSOU TECHNOLOGY(SHENZHEN)Co.,LTD.

1246 Jiaxiye Plaza, No.318 Minzhi Avenue, Minzhi Community, Minzhi Street, Longhua District, Shenzhen