TEST REPORT

Applicant:	Tianjin keepsens Information Technology Co., Ltd
Address:	building 9, Xin'an Chuangye Plaza, No. 399, Huixiang Road, Binhai high tech Zone, Tianjin
Equipment Type:	Cargo sensor
Model Name:	KP-CCXG700-CARGO
Brand Name:	KEEPSENS
FCC ID:	2A64JCCXG700CARGO
Test Standard:	47 CFR Part 15 Subpart C (refer section 3.1)
Test Date:	Jun. 01, 2022 - Jun. 03, 2022
Date of Issue:	Jul. 01, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie zhu **Checked by:** Ye Hongji **Approved by:** Liao Jianming (Technical Director)

Revision History

Version	Issue Date	Revisions
Rev. 01	Jun. 27, 2022	Initial Issue
Rev. 02	Jul. 01, 2022	Update product type in section 2.5 and add a note on page 53

TABLE OF CONTENTS

1 GENERAL INFORMATION 4

1.1 Identification of the Testing Laboratory 4

1.2 Identification of the Responsible Testing Location 4

2 PRODUCT INFORMATION 5

2.1 Applicant Information 5

2.2 Manufacturer Information 5

2.3 Factory Information 5

2.4 General Description for Equipment under Test (EUT) 5

2.5 Technical Information 6

2.6 Additional Instructions 7

3 SUMMARY OF TEST RESULTS 8

3.1 Test Standards 8

3.2 Test Verdict 8

4 GENERAL TEST CONFIGURATIONS 9

4.1 Test Environments 9

4.2 Test Equipment List 9

4.3 Test Software List 9

4.4 Measurement Uncertainty 10

4.5 Description of Test Setup 10

4.6 Measurement Results Explanation Example 13

5 TEST ITEMS 14

5.1 Antenna Requirements 14

5.2 Output Power 15

5.3 Occupied Bandwidth 17
5.4 Conducted Spurious Emission 18
5.5 Band Edge (Authorized-band band-edge) 20
5.6 Conducted Emission 22
5.7 Radiated Spurious Emission 23
5.8 Band Edge (Restricted-band band-edge) 28
5.9 Power Spectral density (PSD) 29
ANNEX A TEST RESULT 30
A.1 Output Power, Duty Cycle 30
A.2 Occupied Bandwidth 34
A.3 Conducted Spurious Emissions 38
A.4 Band Edge (Authorized-band band-edge) 45
A.5 Conducted Emissions 50
A.6 Radiated Spurious Emission 51
A.7 Band Edge (Restricted-band band-edge) 65
A.8 Power Spectral Density (PSD) 69
ANNEX B TEST SETUP PHOTOS 72
ANNEX C EUT EXTERNAL PHOTOS 72
ANNEX D EUT INTERNAL PHOTOS 72

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Tianjin keepsens Information Technology Co., Ltd
Address	building 9, Xin'an Chuangye Plaza, No. 399, Huixiang Road, Binhai high tech Zone, Tianjin

2.2 Manufacturer Information

Manufacturer	Tianjin keepsens Information Technology Co., Ltd
Address	building 9, Xin'an Chuangye Plaza, No. 399, Huixiang Road, Binhai high tech Zone, Tianjin

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Cargo sensor
Model Name Under Test	KP-CCXG700-CARGO
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V1.1
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth BLE

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	GFSK
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate	1 Mbps, 2 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	40 (at intervals of 2 MHz)
Tested Channel	0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	2.02 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

2.6 Additional Instructions

EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	Direct Test Mode Tool		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
GFSK (1 Mbps)	CH0	2402	Power parameter Settings is 0
	CH19	2440	
	CH39	2480	
GFSK (2 Mbps)	CH0	2402	
	CH19	2440	
	CH39	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	--	Pass[Note1]
2	Output Power	15.247(b)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	Low/Middle/High	ANNEX A.5	N/A[Note 3]
7	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Low/Middle/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	Low/Middle/High	ANNEX A.8	Pass
10	Receiver Spurious Emissions	--	--	N/A	N/A[Note2]

Note [1]: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note [2]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

Note [3]: The EUT is powered by battery, so the Conducted Emission test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	3.5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2022.01.04	2023.01.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY50330200	2022.05.19	2023.05.18
Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2022.05.19	2023.05.18
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2021.09.13	2022.09.12
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.10.10	2022.10.09
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.08	2022.06.07
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2021.08.20	2024.08.19
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2022.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.07.02	2024.07.01
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2021.09.04	2024.09.09
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2021.08.15	2024.08.14
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V19.8.28.435	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.82°C
Humidity	4.1%

4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:
Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

4.5.2 For AC Power Supply Port Test



(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = EIRP - 20\log D + 104.8$$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW ≥ DTS bandwidth.

Set VBW ≥ 3 x RBW.

Set span ≥ 3 x RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW ≥ 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW ≥ 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle ≥ 98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ≥ 3 x RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements

for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)

c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).

d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).

e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$E = EIRP – 20\log D + 104.8$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

f) Compare the resultant electric field strength level to the applicable limit.

g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 1.

b) VBW ≥ 3 x RBW.

c) Detector = Peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

a) The EUT shall be configured to operate at the maximum achievable duty cycle.

b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.

c) RBW = 1 MHz (unless otherwise specified).

d) VBW ≥ 3 x RBW.

e) Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

f) Averaging type = power (i.e., RMS).

1) As an alternative, the detector and averaging type may be set for linear voltage averaging.

2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

g) Sweep time = auto.

h) Perform a trace average of at least 100 traces.

i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is 10 log(1/x), where x is the duty cycle.

2) If linear voltage averaging mode was used in step f), then the applicable correction factor is 20 log(1/x), where x is the duty cycle.

3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the

Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.5.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power, Duty Cycle

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low Channel	-2.64	0.54	30	1000	Pass
Middle Channel	-3.09	0.49			Pass
High Channel	-4.47	0.36			Pass

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low Channel	-2.10	0.62	30	1000	Pass
Middle Channel	-3.01	0.50			Pass
High Channel	-3.99	0.40			Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:23:09

GFSK (BLE 1Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:27:58

GFSK (BLE 1Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:31:50

GFSK (BLE 2Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:46:31

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:50:42

GFSK (BLE 2Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:54:01

Duty Cycle Test Data

Band	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)
GFSK (BLE 1Mbps)	0.393	0.626	62.78%
GFSK (BLE 2Mbps)	0.191	0.623	30.66%

Test Plots

GFSK (BLE 1Mbps)



GFSK (BLE 2Mbps)



A.2 Occupied Bandwidth

Test Data

Test Mode	GFSK (BLE 1Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	695.800	1046.310	≥500
Middle Channel	700.200	1046.310	≥500
High Channel	708.740	1046.310	≥500

Test Mode	GFSK (BLE 2Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	1130.620	2028.000	≥500
Middle Channel	1139.160	2052.000	≥500
High Channel	1139.160	2040.000	≥500

Test Plots

6 dB Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:23:14

GFSK (BLE 1Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:28:02

GFSK (BLE 1Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:31:54

GFSK (BLE 2Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:46:35

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:50:46

GFSK (BLE 2Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:54:05

99% Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:23:18

GFSK (BLE 1Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:28:07

GFSK (BLE 1Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:31:59

GFSK (BLE 2Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:46:39

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:50:51

GFSK (BLE 2Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:54:09

A.3 Conducted Spurious Emissions

Test Data

GFSK (BLE 1Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-47.59	-2.28	-22.28	Pass
Middle Channel	-47.43	-3.25	-23.25	Pass
High Channel	-47.27	-4.21	-24.21	Pass

GFSK (BLE 2Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-47.29	-2.29	-22.29	Pass
Middle Channel	-47.17	-3.30	-23.30	Pass
High Channel	-47.16	-3.86	-23.86	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL,
CARRIER LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 1Mbps) LOW CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



GFSK (BLE 1Mbps) MIDDLE CHANNEL,
CARRIER LEVEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 1Mbps) MIDDLE CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



GFSK (BLE 1Mbps) HIGH CHANNEL,
CARRIER LEVEL



Date: 2.JUN.2022 11:02:45

GFSK (BLE 1Mbps) HIGH CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz



Date: 2.JUN.2022 11:03:18

GFSK (BLE 1Mbps) HIGH CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



Date: 2.JUN.2022 11:03:36

GFSK (BLE 2Mbps) LOW CHANNEL,
CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) LOW CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



GFSK (BLE 2Mbps) MIDDLE CHANNEL,
CARRIER LEVEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) MIDDLE CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



GFSK (BLE 2Mbps) HIGH CHANNEL,
CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) HIGH CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Test Data

GFSK (BLE 1Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-59.20	-2.28	-22.28	Pass
High Channel	-60.91	-4.21	-24.21	Pass

GFSK (BLE 2Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-56.66	-2.29	-22.29	Pass
High Channel	-60.41	-3.86	-23.86	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL, REFERENCE LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, REFERENCE LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, REFERENCE LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, REFERENCE LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions

Note: Not applicable.

A.6 Radiated Spurious Emission

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note [4]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 2M-Low channel mode is the worst.

Note [5]: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.668	13.23	-26.19	30.0	-16.77	Peak	75.00	200	Horizontal	Pass
2	55.214	13.97	-26.54	30.0	-16.03	Peak	8.00	100	Horizontal	Pass
3	105.641	11.38	-27.82	33.5	-22.12	Peak	24.00	200	Horizontal	Pass
4	287.956	19.19	-25.38	36.0	-16.81	Peak	140.00	200	Horizontal	Pass
5	311.957	26.99	-24.92	36.0	-9.01	Peak	282.00	200	Horizontal	Pass
6	885.084	25.65	-12.85	36.0	-10.35	Peak	75.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.485	15.51	-29.01	30.0	-14.49	Peak	237.00	200	Vertical	Pass
2	55.214	12.50	-26.54	30.0	-17.50	Peak	14.00	200	Vertical	Pass
3	99.823	11.76	-28.01	33.5	-21.74	Peak	194.00	100	Vertical	Pass
4	199.708	19.08	-27.66	33.5	-14.42	Peak	317.00	200	Vertical	Pass
5	310.017	17.71	-24.79	36.0	-18.29	Peak	189.00	100	Vertical	Pass
6	864.961	25.39	-13.14	36.0	-10.61	Peak	300.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

Note 3: All the configurations were pre tested, and the worst is when the antenna height is 150cm. The report only reflects the data of the antenna height of 150cm.

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1462.500	39.68	-17.40	74.0	-34.32	Peak	74.00	150	Horizontal	Pass
1**	1462.500	28.91	-17.40	54.0	-25.09	AV	74.00	150	Horizontal	Pass
2	2401.700	92.88	-12.26	74.0	18.88	Peak	287.00	150	Horizontal	N/A
2**	2401.700	87.91	-12.26	54.0	33.91	AV	287.00	150	Horizontal	N/A
3	4803.800	50.11	-2.73	74.0	-23.89	Peak	57.00	150	Horizontal	Pass
3**	4803.800	45.87	-2.73	54.0	-8.13	AV	57.00	150	Horizontal	Pass
4	7205.850	48.11	-4.33	74.0	-25.89	Peak	12.00	150	Horizontal	Pass
4**	7205.850	43.53	-4.33	54.0	-10.47	AV	12.00	150	Horizontal	Pass
5	11055.475	52.38	-0.75	74.0	-21.62	Peak	359.00	150	Horizontal	Pass
5**	11055.475	42.60	-0.75	54.0	-11.40	AV	359.00	150	Horizontal	Pass
6	17196.225	54.06	2.12	74.0	-19.94	Peak	326.00	150	Horizontal	Pass
6**	17196.225	47.25	2.12	54.0	-6.75	AV	326.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1661.500	41.80	-17.54	74.0	-32.20	Peak	246.00	150	Vertical	Pass
1**	1661.500	28.51	-17.54	54.0	-25.49	AV	246.00	150	Vertical	Pass
2	2402.100	85.95	-12.26	74.0	11.95	Peak	204.00	150	Vertical	N/A
2**	2402.100	80.38	-12.26	54.0	26.38	AV	204.00	150	Vertical	N/A
3	4804.200	50.54	-2.76	74.0	-23.46	Peak	344.00	150	Vertical	Pass
3**	4804.200	45.65	-2.76	54.0	-8.35	AV	344.00	150	Vertical	Pass
4	7206.425	49.26	-4.32	74.0	-24.74	Peak	45.00	150	Vertical	Pass
4**	7206.425	45.98	-4.32	54.0	-8.02	AV	45.00	150	Vertical	Pass
5	10336.725	52.50	0.07	74.0	-21.50	Peak	282.00	150	Vertical	Pass
5**	10336.725	43.09	0.07	54.0	-10.91	AV	282.00	150	Vertical	Pass
6	17193.075	54.80	2.24	74.0	-19.20	Peak	148.00	150	Vertical	Pass
6**	17193.075	47.80	2.24	54.0	-6.20	AV	148.00	150	Vertical	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1480.800	40.03	-17.58	74.0	-33.97	Peak	50.00	150	Horizontal	Pass
1**	1480.800	28.37	-17.58	54.0	-25.63	AV	50.00	150	Horizontal	Pass
2	2439.700	92.29	-12.64	74.0	18.29	Peak	72.00	150	Horizontal	N/A
2**	2439.700	88.74	-12.64	54.0	34.74	AV	72.00	150	Horizontal	N/A
3	4800.400	51.82	-2.56	74.0	-22.18	Peak	167.00	150	Horizontal	Pass
3**	4800.400	43.28	-2.56	54.0	-10.72	AV	167.00	150	Horizontal	Pass
4	7319.413	50.92	-3.68	74.0	-23.08	Peak	75.00	150	Horizontal	Pass
4**	7319.413	48.43	-3.68	54.0	-5.57	AV	75.00	150	Horizontal	Pass
5	10383.013	52.19	0.15	74.0	-21.81	Peak	75.00	150	Horizontal	Pass
5**	10383.013	42.32	0.15	54.0	-11.68	AV	75.00	150	Horizontal	Pass
6	17410.163	53.92	3.45	74.0	-20.08	Peak	0.00	150	Horizontal	Pass
6**	17410.163	45.85	3.45	54.0	-8.15	AV	0.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1830.500	43.89	-16.67	74.0	-30.11	Peak	83.00	150	Vertical	Pass
1**	1830.500	31.22	-16.67	54.0	-22.78	AV	83.00	150	Vertical	Pass
2	2439.600	91.39	-12.64	74.0	17.39	Peak	213.00	150	Vertical	N/A
2**	2439.600	87.95	-12.64	54.0	33.95	AV	213.00	150	Vertical	N/A
3	4880.800	49.02	-3.45	74.0	-24.98	Peak	202.00	150	Vertical	Pass
3**	4880.800	44.81	-3.45	54.0	-9.19	AV	202.00	150	Vertical	Pass
4	7319.700	47.93	-3.68	74.0	-26.07	Peak	44.00	150	Vertical	Pass
4**	7319.700	43.70	-3.68	54.0	-10.30	AV	44.00	150	Vertical	Pass
5	10654.701	51.99	-0.66	74.0	-22.01	Peak	28.00	150	Vertical	Pass
5**	10654.701	42.55	-0.66	54.0	-11.45	AV	28.00	150	Vertical	Pass
6	15231.938	53.96	0.94	74.0	-20.04	Peak	254.00	150	Vertical	Pass
6**	15231.938	44.71	0.94	54.0	-9.29	AV	254.00	150	Vertical	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1786.800	40.54	-16.90	74.0	-33.46	Peak	88.00	150	Horizontal	Pass
1**	1786.800	28.83	-16.90	54.0	-25.17	AV	88.00	150	Horizontal	Pass
2	2479.800	92.15	-12.43	74.0	18.15	Peak	76.00	150	Horizontal	N/A
2**	2479.800	87.97	-12.43	54.0	33.97	AV	76.00	150	Horizontal	N/A
3	4960.400	48.79	-3.27	74.0	-25.21	Peak	64.00	150	Horizontal	Pass
3**	4960.400	45.06	-3.27	54.0	-8.94	AV	64.00	150	Horizontal	Pass
4	7440.163	48.22	-4.36	74.0	-25.78	Peak	79.00	150	Horizontal	Pass
4**	7440.163	47.46	-4.36	54.0	-6.54	AV	79.00	150	Horizontal	Pass
5	11938.962	53.64	1.69	74.0	-20.36	Peak	145.00	150	Horizontal	Pass
5**	11938.962	43.80	1.69	54.0	-10.20	AV	145.00	150	Horizontal	Pass
6	17422.762	53.79	3.68	74.0	-20.21	Peak	325.00	150	Horizontal	Pass
6**	17422.762	45.88	3.68	54.0	-8.12	AV	325.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1825.300	43.72	-16.65	74.0	-30.28	Peak	79.00	150	Vertical	Pass
1**	1825.300	30.97	-16.65	54.0	-23.03	AV	79.00	150	Vertical	Pass
2	2479.800	91.69	-12.43	74.0	17.69	Peak	217.00	150	Vertical	N/A
2**	2479.800	87.08	-12.43	54.0	33.08	AV	217.00	150	Vertical	N/A
3	4906.600	51.10	-2.58	74.0	-22.90	Peak	110.00	150	Vertical	Pass
3**	4906.600	42.10	-2.58	54.0	-11.90	AV	110.00	150	Vertical	Pass
4	7439.875	48.71	-4.37	74.0	-25.29	Peak	314.00	150	Vertical	Pass
4**	7439.875	46.57	-4.37	54.0	-7.43	AV	314.00	150	Vertical	Pass
5	11389.550	52.59	-0.22	74.0	-21.41	Peak	188.00	150	Vertical	Pass
5**	11389.550	43.74	-0.22	54.0	-10.26	AV	188.00	150	Vertical	Pass
6	17408.850	54.22	3.42	74.0	-19.78	Peak	17.00	150	Vertical	Pass
6**	17408.850	45.70	3.42	54.0	-8.30	AV	17.00	150	Vertical	Pass

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1462.900	39.90	-17.44	74.0	-34.10	Peak	55.00	150	Horizontal	Pass
1**	1462.900	28.71	-17.44	54.0	-25.29	AV	55.00	150	Horizontal	Pass
2	2401.600	92.19	-12.26	74.0	18.19	Peak	289.00	150	Horizontal	N/A
2**	2401.600	86.86	-12.26	54.0	32.86	AV	289.00	150	Horizontal	N/A
3	4823.000	51.18	-3.40	74.0	-22.82	Peak	182.00	150	Horizontal	Pass
3**	4823.000	41.12	-3.40	54.0	-12.88	AV	182.00	150	Horizontal	Pass
4	7204.412	50.26	-4.16	74.0	-23.74	Peak	108.00	150	Horizontal	Pass
4**	7204.412	41.10	-4.16	54.0	-12.90	AV	108.00	150	Horizontal	Pass
5	12231.638	53.41	1.26	74.0	-20.59	Peak	358.00	150	Horizontal	Pass
5**	12231.638	43.93	1.26	54.0	-10.07	AV	358.00	150	Horizontal	Pass
6	17416.200	54.02	3.67	74.0	-19.98	Peak	147.00	150	Horizontal	Pass
6**	17416.200	47.07	3.67	54.0	-6.93	AV	147.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.800	44.39	-17.40	74.0	-29.61	Peak	228.00	150	Vertical	Pass
1**	1330.800	28.79	-17.40	54.0	-25.21	AV	228.00	150	Vertical	Pass
2	2401.900	90.47	-12.26	74.0	16.47	Peak	216.00	150	Vertical	N/A
2**	2401.900	86.78	-12.26	54.0	32.78	AV	216.00	150	Vertical	N/A
3	4804.400	49.74	-2.78	74.0	-24.26	Peak	333.00	150	Vertical	Pass
3**	4804.400	46.69	-2.78	54.0	-7.31	AV	333.00	150	Vertical	Pass
4	7344.138	50.24	-3.56	74.0	-23.76	Peak	239.00	150	Vertical	Pass
4**	7344.138	41.65	-3.56	54.0	-12.35	AV	239.00	150	Vertical	Pass
5	10957.150	52.14	-0.37	74.0	-21.86	Peak	127.00	150	Vertical	Pass
5**	10957.150	41.67	-0.37	54.0	-12.33	AV	127.00	150	Vertical	Pass
6	17413.050	54.17	3.56	74.0	-19.83	Peak	309.00	150	Vertical	Pass
6**	17413.050	45.96	3.56	54.0	-8.04	AV	309.00	150	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1467.900	39.92	-17.53	74.0	-34.08	Peak	57.00	150	Horizontal	Pass
1**	1467.900	28.14	-17.53	54.0	-25.86	AV	57.00	150	Horizontal	Pass
2	2439.400	92.26	-12.64	74.0	18.26	Peak	118.00	150	Horizontal	N/A
2**	2439.400	84.65	-12.64	54.0	30.65	AV	118.00	150	Horizontal	N/A
3	4904.800	51.41	-2.57	74.0	-22.59	Peak	301.00	150	Horizontal	Pass
3**	4904.800	42.41	-2.57	54.0	-11.59	AV	301.00	150	Horizontal	Pass
4	7320.275	51.13	-3.69	74.0	-22.87	Peak	78.00	150	Horizontal	Pass
4**	7320.275	49.33	-3.69	54.0	-4.67	AV	78.00	150	Horizontal	Pass
5	11560.037	53.10	-0.45	74.0	-20.90	Peak	269.00	150	Horizontal	Pass
5**	11560.037	42.83	-0.45	54.0	-11.17	AV	269.00	150	Horizontal	Pass
6	17201.213	53.55	1.83	74.0	-20.45	Peak	215.00	150	Horizontal	Pass
6**	17201.213	45.23	1.83	54.0	-8.77	AV	215.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1827.800	42.14	-16.59	74.0	-31.86	Peak	309.00	150	Vertical	Pass
1**	1827.800	29.15	-16.59	54.0	-24.85	AV	309.00	150	Vertical	Pass
2	2439.500	91.68	-12.64	74.0	17.68	Peak	217.00	150	Vertical	N/A
2**	2439.500	83.03	-12.64	54.0	29.03	AV	217.00	150	Vertical	N/A
3	4809.000	50.92	-2.94	74.0	-23.08	Peak	238.00	150	Vertical	Pass
3**	4809.000	42.61	-2.94	54.0	-11.39	AV	238.00	150	Vertical	Pass
4	7320.275	47.72	-3.69	74.0	-26.28	Peak	59.00	150	Vertical	Pass
4**	7320.275	45.37	-3.69	54.0	-8.63	AV	59.00	150	Vertical	Pass
5	11673.026	52.82	0.25	74.0	-21.18	Peak	152.00	150	Vertical	Pass
5**	11673.026	43.47	0.25	54.0	-10.53	AV	152.00	150	Vertical	Pass
6	17885.813	53.85	3.62	74.0	-20.15	Peak	309.00	150	Vertical	Pass
6**	17885.813	45.56	3.62	54.0	-8.44	AV	309.00	150	Vertical	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1456.800	39.97	-17.48	74.0	-34.03	Peak	53.00	150	Horizontal	Pass
1**	1456.800	27.97	-17.48	54.0	-26.03	AV	53.00	150	Horizontal	Pass
2	2479.500	92.17	-12.44	74.0	18.17	Peak	357.00	150	Horizontal	N/A
2**	2479.500	85.78	-12.44	54.0	31.78	AV	357.00	150	Horizontal	N/A
3	4812.200	51.30	-3.04	74.0	-22.70	Peak	130.00	150	Horizontal	Pass
3**	4812.200	42.10	-3.04	54.0	-11.90	AV	130.00	150	Horizontal	Pass
4	7437.000	45.96	-4.29	74.0	-28.04	Peak	359.00	150	Horizontal	Pass
4**	7437.000	38.78	-4.29	54.0	-15.22	AV	359.00	150	Horizontal	Pass
5	11027.875	52.58	-0.65	74.0	-21.42	Peak	136.00	150	Horizontal	Pass
5**	11027.875	42.55	-0.65	54.0	-11.45	AV	136.00	150	Horizontal	Pass
6	15837.263	53.26	1.45	74.0	-20.74	Peak	36.00	150	Horizontal	Pass
6**	15837.263	45.68	1.45	54.0	-8.32	AV	36.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.600	43.09	-17.50	74.0	-30.91	Peak	237.00	150	Vertical	Pass
1**	1327.600	27.85	-17.50	54.0	-26.15	AV	237.00	150	Vertical	Pass
2	2480.100	91.79	-12.43	74.0	17.79	Peak	213.00	150	Vertical	N/A
2**	2480.100	82.38	-12.43	54.0	28.38	AV	213.00	150	Vertical	N/A
3	4891.800	51.34	-3.27	74.0	-22.66	Peak	132.00	150	Vertical	Pass
3**	4891.800	41.78	-3.27	54.0	-12.22	AV	132.00	150	Vertical	Pass
4	7440.163	47.47	-4.36	74.0	-26.53	Peak	325.00	150	Vertical	Pass
4**	7440.163	45.63	-4.36	54.0	-8.37	AV	325.00	150	Vertical	Pass
5	11448.200	52.40	-0.04	74.0	-21.60	Peak	217.00	150	Vertical	Pass
5**	11448.200	42.00	-0.04	54.0	-12.00	AV	217.00	150	Vertical	Pass
6	17197.801	53.75	2.02	74.0	-20.25	Peak	146.00	150	Vertical	Pass
6**	17197.801	45.52	2.02	54.0	-8.48	AV	146.00	150	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.
Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.
Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
Note [4]: The Level (dBuV/m) has been corrected by factor.

Test Data and Plots

GFSK (BLE 1Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	54.03	-0.50	74.0	-19.97	Peak	215.00	150	Horizontal	Pass
1**	2390.000	43.02	-0.50	54.0	-10.98	AV	215.00	150	Horizontal	Pass
2	2387.500	56.07	-0.53	74.0	-17.93	Peak	201.00	150	Horizontal	Pass
2**	2387.500	43.15	-0.53	54.0	-10.85	AV	201.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	59.83	-0.36	74.0	-14.17	Peak	348.00	150	Horizontal	Pass
1**	2483.500	43.22	-0.36	54.0	-10.78	AV	348.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	53.92	-0.50	74.0	-20.08	Peak	360.00	150	Horizontal	Pass
1**	2390.000	43.19	-0.50	54.0	-10.81	AV	360.00	150	Horizontal	Pass
2	2389.833	55.55	-0.50	74.0	-18.45	Peak	13.00	150	Horizontal	Pass
2**	2389.833	43.10	-0.50	54.0	-10.90	AV	13.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	59.30	-0.36	74.0	-14.70	Peak	74.00	150	Horizontal	Pass
1**	2483.500	43.31	-0.36	54.0	-10.69	AV	74.00	150	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

GFSK (BLE 1Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-17.96	8	Pass
Middle Channel	-18.36	8	Pass
High Channel	-19.75	8	Pass

GFSK (BLE 2Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-20.04	8	Pass
Middle Channel	-20.88	8	Pass
High Channel	-21.96	8	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



Date: 1.JUN.2022 15:49:45

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 1.JUN.2022 15:52:58

GFSK (BLE 2Mbps) HIGH CHANNEL



Date: 1.JUN.2022 15:56:31

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-EC2250673-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-EC2250673-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-EC2250673-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the “inspection and testing dedicated stamp” or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--