

60x60mm

YINUO-LINK® Quick Installation Guide &Warranty Card AC1200 Wi-Fi Nano Router Y7		All rights reserved Without the express written permission of YINUOLINK CO., LTD, no entity or individual shall copy or translate the contents of the Manual in part or in whole, and shall not transmit the contents by any means (electronic, photocopied, recorded, etc.) for profit. YINUO-LINK® is a registered trademark of YINUOLINK CO., LTD. All trademarks mentioned in this manual are the property of their respective owners. Product specification and advice mentioned in this manual are for reference only and are subject to change without prior notice. Unless other wise specified, this manual is intended only as a guide to use and the statements made herein constitute any form of warranty.		1. Multi-Mode Introduction During Travel A. AP Router Mode (Default) Connect to Ethernet to instantly create a private wireless network and share internet access to all your Wi-Fi devices. B. AP Client Router Mode (WISP) Suitable for relay amplification of WiFi hotspot signals provided by operators, such as: CMCC, China Unicom, ChinaNet, etc. <td data-kind="ghost"></td> <td data-cs="2" data-kind="parent"> Public Hotspot At Home C. Access Point Mode Create a wireless network for Wi-Fi enabled devices. D. Client Mode Existing Router </td> <td data-cs="2" data-kind="parent"> Allow devices that require a wired connection to access an existing Wi-Fi network. Note: 5.8G can be used normally for WiFi if you are 2.4G connected to the parent AP, and 2.4G can be used normally for WiFi if you are 5.8G connected to the parent AP. Internet Host AP Host AP Host AP Internet Host AP Host AP Host AP </td>		Public Hotspot At Home C. Access Point Mode Create a wireless network for Wi-Fi enabled devices. D. Client Mode Existing Router	Allow devices that require a wired connection to access an existing Wi-Fi network. Note: 5.8G can be used normally for WiFi if you are 2.4G connected to the parent AP, and 2.4G can be used normally for WiFi if you are 5.8G connected to the parent AP. Internet Host AP Host AP Host AP Internet Host AP Host AP Host AP
---	--	---	--	---	--	--	--