



85*120mm

ACCESSORIES		INSTRUCTIONS		INSTRUCTIONS		DESCRIPTION		Model: SWP-A20															
 Wireless Receiver*1  Microphone*2  USB Cable*1  Anti-slip Rings*2  Foam Covers*2 -01-		 ① Microphone head Section: Including Microphone Cover Net and Microphone Cartridge Module. ② Display Screen: Display working channels, battery power, frequency. ③ Switch button: Press for 3 seconds on/off the microphone. ④ Frequency adjust button. -02-		 ① POWER BUTTON ② USB CHARGING PORT ③ SIGNAL ANTENNA ④ BATTERY INDICATOR ⑤ RF LIGHT LIGHT INSTRUCTION <table><tr><td rowspan="2">Battery indicator ④</td><td>Turns red and flashes quickly</td><td>The power of the receiver is in a low battery status.</td></tr><tr><td>Stays on</td><td>The receiver is in charging model</td></tr><tr><td rowspan="4">RF light ⑤</td><td>Turns off</td><td>The receiver is fully charged.</td></tr><tr><td>Flashes slowly</td><td>The receiver is not connected to the microphone.</td></tr><tr><td>Stays on</td><td>The receiver and microphone are successfully connected.</td></tr><tr><td>Flashes quickly</td><td>The receiver and microphone are successfully connected, and the microphone is transmitting audio signal.</td></tr></table> -03-		Battery indicator ④	Turns red and flashes quickly	The power of the receiver is in a low battery status.	Stays on	The receiver is in charging model	RF light ⑤	Turns off	The receiver is fully charged.	Flashes slowly	The receiver is not connected to the microphone.	Stays on	The receiver and microphone are successfully connected.	Flashes quickly	The receiver and microphone are successfully connected, and the microphone is transmitting audio signal.	The SUDOTACK SWP-A20 is an easy-to-use wireless handheld microphone set. And setup is a snap, thanks to automatic frequency management and remote synchronization. A maximum operating range of 200 feet, and up to 6 hours of use on a single set of batteries. It can use up to 15 systems. The SUDOTACK SWP-A20 is a great handheld wireless microphone for singers, presenters, and hosts. FEATURES • True diversity and up to 15 compatible channels in a stable UHF band • Durable metal-encased receiver • Handheld transmitters pair with the receiver automatically for easy setup • Front display screen for keeping an eye on your signal presence, signal strength, and battery life • Built-in volume buttons allow you to adjust sound levels • Maximum operating range of 200 feet -04-		Technical Support: Support@sudotack.com www.sudotack.com 	
Battery indicator ④	Turns red and flashes quickly	The power of the receiver is in a low battery status.																					
	Stays on	The receiver is in charging model																					
RF light ⑤	Turns off	The receiver is fully charged.																					
	Flashes slowly	The receiver is not connected to the microphone.																					
	Stays on	The receiver and microphone are successfully connected.																					
	Flashes quickly	The receiver and microphone are successfully connected, and the microphone is transmitting audio signal.																					

TRANSMITTER SPECIFICATION

Microphone Core	Dynamic
Frequency Response	50Hz-16kHz
Polar Pattern	Cardioid
Output Impedance	600Ω
Sensitivity	-52dB±1.5dB
S/N Ratio	96dB
Input Sample Rate	48kHz
Bit Rate	24bit
THD+N	0.05%

WORKING PARAMETERS


UHF Carrier frequencies	902.8MHz-926.8MHz
Modulation bandwidth	800kHz
Channel Number	30
Maximum operating range	200ft

RECEIVER SPECIFICATION


Operating temperature	0°C to +55°C
Battery capacity	1500mAh
Output interface	6.35mm
Power supply interface	Micro/USB
Supply voltage	DC 5V
Supply current	500mA

SPECIFICATIONS

Frequency Response



Polar Response



NOTES

①

When using this device, keep it away from water.

②

Use the device in ventilated environment, keep it away from fire.

③

Since it's a wireless device, please keep it away from other interfering sources.

④

Don't take apart the device.

⑤

Please use the standard power supply, high voltage may damage the device.

⑥

Please place the used batteries into the recycle bin, don't litter them.

FCC Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause unintended operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:


- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to the device not explicitly approved by manufacturer could void your authority to operate this equipment.

RF Exposure Information

The device has been evaluated to meet general RF exposure requirements. The device can be used in portable exposure condition without restriction.

SUDOTACK



USER MANUAL

Wireless Microphone