

# TEST REPORT

**Product Name** : Transceiver  
**Brand Mark** : N/A  
**Model No.** : MK02  
**Extension Model** : MK04, MK06, MK07, MK08  
**FCC ID** : 2A6ET-RT6202  
**Report Number** : BLA-EMC-202311-A1403  
**Date of Sample Receipt** : 2023/11/3  
**Date of Test** : 2023/11/4 to 2023/11/10  
**Date of Issue** : 2023/11/13  
**Test Standard** : 47 CFR Part 15, Part1.1307  
47 CFR Part 15, Part2.1093  
KDB447498D04 General RF Exposure  
Guidance v01  
**Test Result** : Pass

Prepared for:

**ShenZhen Ankbit Electronics Limited**  
**Room 401, Building B, Runfeng Industrial Park, No. 4197 Baoan Blvd.,**  
**Xixiang St., Baoan Dist., Shenzhen, China**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**Building C, No. 107, Shihuan Road, Shiyao Sub-District, Baoan District,**  
**Shenzhen, Guangdong Province, China**  
**TEL: +86-755-23059481**

Compiled by:

Lucas

Review by:

Sueels

Approved by:

Blue Zheng

Date:

2023/11/13



## REPORT REVISE RECORD

| Version No. | Date       | Description |
|-------------|------------|-------------|
| 00          | 2023/11/13 | Original    |

BlueAsia

## TABLE OF CONTENTS

|                                                   |          |
|---------------------------------------------------|----------|
| <b>1 TEST SUMMARY .....</b>                       | <b>4</b> |
| <b>2 GENERAL INFORMATION .....</b>                | <b>5</b> |
| <b>3 GENERAL DESCRIPTION OF E.U.T.....</b>        | <b>5</b> |
| <b>4 LABORATORY LOCATION .....</b>                | <b>6</b> |
| <b>5 RF EXPOSURE COMPLIANCE REQUIREMENT .....</b> | <b>7</b> |
| 5.1 STANDARD REQUIREMENT .....                    | 7        |
| 5.2 LIMITS .....                                  | 7        |

## 1 TEST SUMMARY

| Test item   | Test Requirement                               | Test Method        | Class/Severity     | Result |
|-------------|------------------------------------------------|--------------------|--------------------|--------|
| RF Exposure | 47 CFR Part 1.1307,<br>Part 2.1093, KDB 447498 | CFR 47 Part 2.1093 | CFR 47 Part 2.1093 | PASS   |

## 2 GENERAL INFORMATION

|                        |                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>       | ShenZhen Ankbit Electronics Limited                                                                                                                       |
| <b>Address</b>         | Room 401, Building B, Runfeng Industrial Park, No. 4197 Baoan Blvd., Xixiang St., Baoan Dist., Shenzhen, China                                            |
| <b>Manufacturer</b>    | ShenZhen Ankbit Electronics Limited                                                                                                                       |
| <b>Address</b>         | Room 401, Building B, Runfeng Industrial Park, No. 4197 Baoan Blvd., Xixiang St., Baoan Dist., Shenzhen, China                                            |
| <b>Factory</b>         | ShenZhen Ankbit Electronics Limited                                                                                                                       |
| <b>Address</b>         | Room 401, Building B, Runfeng Industrial Park, No. 4197 Baoan Blvd., Xixiang St., Baoan Dist., Shenzhen, China                                            |
| <b>Product Name</b>    | Transceiver                                                                                                                                               |
| <b>Test Model No.</b>  | MK02                                                                                                                                                      |
| <b>Extension Model</b> | MK04, MK06, MK07, MK08                                                                                                                                    |
| <b>Remark</b>          | All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose. |

## 3 GENERAL DESCRIPTION OF E.U.T.

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| <b>Hardware Version</b>     | RT6202-V4                                            |
| <b>Software Version</b>     | 6202_Q16_MK02_QCC3024_SPEAKERv1.8-8db28_MonoRight0Db |
| <b>Operation Frequency:</b> | 2402MHz-2480MHz                                      |
| <b>Modulation Type:</b>     | GFSK,pi/4DQPSK,8DPSK                                 |
| <b>Channel Spacing:</b>     | 1MHz                                                 |
| <b>Number of Channels:</b>  | 79                                                   |
| <b>Antenna Type:</b>        | PCB Antenna                                          |
| <b>Antenna Gain:</b>        | -0.58dBi(Provided by the customer)                   |

#### 4 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

BlueAsia

## 5 RF EXPOSURE COMPLIANCE REQUIREMENT

### 5.1 STANDARD REQUIREMENT

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 5.2 LIMITS

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) |    |    |     |     |     |     |     |     |     |
|-----------------|---------------|----|----|-----|-----|-----|-----|-----|-----|-----|
|                 | 5             | 10 | 15 | 20  | 25  | 30  | 35  | 40  | 45  | 50  |
| 300             | 39            | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
| 450             | 22            | 44 | 67 | 89  | 112 | 135 | 158 | 180 | 203 | 226 |
| 835             | 9             | 25 | 44 | 66  | 90  | 116 | 145 | 175 | 207 | 240 |
| 1900            | 3             | 12 | 26 | 44  | 66  | 92  | 122 | 157 | 195 | 236 |
| 2450            | 3             | 10 | 22 | 38  | 59  | 83  | 111 | 143 | 179 | 219 |
| 3600            | 2             | 8  | 18 | 32  | 49  | 71  | 96  | 125 | 158 | 195 |
| 5800            | 1             | 6  | 14 | 25  | 40  | 58  | 80  | 106 | 136 | 169 |

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

Ant gain = -0.58dBi

Max Output power = -0.928dBm @BR@ 2441MHz

ERP = -0.928dBm - 0.58dBi - 2.15 = -3.658dBm

So

worse case :

$10^{-0.3658} = 0.431\text{mW} < 2.75\text{ mW}$

Comply with RF exposure exemption limit.

Then SAR evaluation is not required

**----END OF REPORT----**

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.