

TEST REPORT

Product Name : Remote control
ZQ02624, ZQ02374, ZQ02375, ZQ02575,
ZQ02576, ZQ02577, ZQ02578, ZQ02627,
ZQ02628, ZQ06136, ZQ07031, ZQ01337,
ZQ01519, ZQ01152, ZQ01148, ZQ01523,

Model Number : ZQ02625, ZQ02798, ZQ02795, ZQ02796,
ZQ02797, ZQ02792, ZQ02793, ZQ02794,
ZQ02623, ZQ02790, ZQ05031, ZQ03229,
ZQ05141, ZQ05201, ZQ06209, ZQ06199,
ZQ06138

FCC ID : 2A6EW-ZQ02624

Prepared for Address : Shenzhen Zhuoqiong Technology Co., Ltd.
: 101-01, No.2 Factory Building, Huanxing Company,
No.4034, Banxuegang Avenue, Xiangjiaotang
Community, Bantian Street, Longgang District,
Shenzhen, China

Prepared by Address : EMTEK (DONGGUAN) CO., LTD.
: -1&2/F., Building 2, Zone A, Zhongda Marine
Biotechnology Research and Development Base,
No.9, Xincheng Avenue, Songshanhu High-technology
Industrial Development Zone, Dongguan, Guangdong,
China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2608030187E00102R
Date of sample receipt : August 03, 2026
Date(s) of Tests : August 03, 2026 to August 21, 2026
Date of issue : August 21, 2026

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Shenzhen Zhuoqiong Technology Co., Ltd.
Address : 101-01, No.2 Factory Building, Huanxing Company, No.4034, Banxuegang Avenue, Xiangjiaotang Community, Bantian Street, Longgang District,
Manufacturer : Shenzhen Zhuoqiong Technology Co., Ltd.
Address : 101-01, No.2 Factory Building, Huanxing Company, No.4034, Banxuegang Avenue, Xiangjiaotang Community, Bantian Street, Longgang District,
Factory : Shenzhen Zhuoqiong Technology Co., Ltd.
Address : 101-01, No.2 Factory Building, Huanxing Company, No.4034, Banxuegang Avenue, Xiangjiaotang Community, Bantian Street, Longgang District,
EUT : Remote control
Model Name : ZQ02624, ZQ02374, ZQ02375, ZQ02575, ZQ02576, ZQ02577, ZQ02578, ZQ02627, ZQ02628, ZQ06136, ZQ07031, ZQ01337, ZQ01519, ZQ01152, ZQ01148, ZQ01523, ZQ02625, ZQ02798, ZQ02795, ZQ02796, ZQ02797, ZQ02792, ZQ02793, ZQ02794, ZQ02623, ZQ02790, ZQ05031, ZQ03229, ZQ05141, ZQ05201, ZQ06209, ZQ06199, ZQ06138
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 2.1091	PASS


The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 2.1091.

The test results of this report relate only to the tested sample identified in this report


Date of Test :

August 03, 2026 to August 21, 2026


Prepared by :


Jessica Zhang /Editor

Reviewer :


Warren Deng /Supervisor

Approve & Authorized Signer :


Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2608030187E00102R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Remote control
Model Number:	ZQ02624, ZQ02374, ZQ02375, ZQ02575, ZQ02576, ZQ02577, ZQ02578, ZQ02627, ZQ02628, ZQ06136, ZQ07031, ZQ01337, ZQ01519, ZQ01152, ZQ01148, ZQ01523, ZQ02625, ZQ02798, ZQ02795, ZQ02796, ZQ02797, ZQ02792, ZQ02793, ZQ02794, ZQ02623, ZQ02790, ZQ05031, ZQ03229, ZQ05141, ZQ05201, ZQ06209, ZQ06199, ZQ06138 Note: All models are the same, only the model name and appearance color are different. Here, model ZQ02624 is selected to complete all the tests.
Sample:	2#
Device Type:	433.92MHz
Modulation:	FSK for 433.92MHz
Operating Frequency Range(s) :	433.92MHz
Number of Channels:	1 channel for 433.92MHz
Transmit Power Max:	433.92MHz: 76.04dBuV@3m
Antenna Type:	PCB antenna
Power supply:	DC3V from Button cell
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

433.92MHz

Channel Freq. (MHz)	Max Field Strength (dBuV/m)	peak output power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
433.92	76.04	-19.12	-20±1	-19	0.00165857	3

According to KDB 447498, no stand-alone required for WIFI antenna, and no simultaneous SAR measurement is required.

*** End of Report ***

