



Radio Frequency Exposure Evaluation Report

For:
Lennox Industries Inc.

Model:
30L27

Product Description:
Smart thermostat to control residential HVAC system

FCC ID: 2A6F9-M4025A
ISED: 28687-M4025A

Applied Rules and Standards:
CFR Part Part1 (1.1307 & 1.1310), Part 2 (2.1091),
FCC KDB 447498 D01 General RF Exposure Guidance v06
ISED RSS-102 Issue 6

Report number: EMC_LEN NX_025_24001_RF_Exposure_Rev1

DATE: 2026-02-06



IC recognized #
3462B

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	Assessment.....	3
2	Administrative Data	4
2.1	Identification of the Testing Laboratory Issuing the EMC Test Report	4
2.2	Identification of the Client	4
2.3	Identification of the Manufacturer.....	4
3	Equipment under Assessment.....	5
3.1	EUT Specifications	5
4	RF Exposure Limits and FCC and ISED Basic Rules	6
	FCC	6
	ISED RSS 102.....	6
5	Evaluations.....	7
5.1	<u>FCC RF Exposure (Standalone)</u>	7
5.2	<u>ISED RF Exposure (Standalone)</u>	7
5.3	<u>RF Exposure Test Exemptions for Simultaneous Transmission Sources</u>	7
6	Revision History	8

1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 &1.1310), Part 2 (2.1091) and ISED standard RSS-102 issue 6 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant).
In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and ISED rule parts based on available specifications for worst-case conditions at 4 cm distance to the body.

Company Name	Product Description	Model No.
Lennox Industries Inc.	Smart thermostat to control residential HVAC system	30L27

Report Authorized by:

Responsible for testing Laboratory:

2026-02-06	Compliance	Alvin, Ilarina (Director of EMC Services)	
Date	Section	Name	Signature

Responsible for the Report:

2026-02-06	Compliance	Art Thammanavarat (Lead Engineer)	Art Thammanavarat Digitally signed by: Art Thammanavarat DN: CN = Art Thammanavarat email = art.thammanavarat@cetecom.com C = AD Date: 2026.02.06 11:01:48 -08'00'
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section3.
CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Alvin, Ilarina
Responsible Project Leader:	Ruby, Hall

2.2 Identification of the Client

Client Firm/Name:	Lennox Industries Inc.
Street Address:	1600 Metrocrest Dr
City/Zip Code	Carrollton, TX 75006
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	
City/Zip Code	
Country	

3 Equipment under Assessment

3.1 EUT Specifications

Product Description:	Smart thermostat to control residential HVAC system
Marketing Name	Lennox M40 Smart Thermostat
Model Name:	30L27
HW Version:	A
SW Version:	04.40.0168
FCC-ID:	2A6F9-M4025A
ISED:	28687-M4025A
FVIN	04.40.0168
HVIN	108750-01
PMN	Lennox M40 Smart Thermostat
Bands/Modes Supported	<u>Wi-Fi & Bluetooth Modules</u> Company Name: Murata Manufacturing Co., Ltd. Model Number: LBEE5KL1YN-814 FCC: VPYLB1DX ISED: 772C-LB1DX <u>Wireless Technologies</u> Wi-Fi 2.4GHz Bluetooth LE
Power Supply/ Rated Operating Voltage Range	Min: 18Vac – Nominal: 24Vac – Max: 30Vac
Operating Temperature Range	Low 0 °C High 40 °C
Sample Revision	☐ Production ☒ Pre-Production
EUT Dimensions	84mm x 84mm x 25mm
EUT Diameter	☒ < 60 cm ☐ Other _____
Note: The information of the EUT specifications in the table above is provided by the client.	

4 RF Exposure Limits and FCC and ISED Basic Rules

FCC

4.1.1 § 2.1093(c)(1)

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than ERP_{20cm} in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

$$P_{th}(\text{mW}) = ERP_{20\text{ cm}}(\text{mW}) = \begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases}$$

4.1.2 § 2.1093(c)(2)

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

4.1.3 § 1.1307(b)(3)(ii)(B)

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

ISED RSS 102

4.1.4 Clause 6.6 Field reference level exposure exemption limits– RF Exposure Evaluation

Field reference level (FRL) RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived

5 Evaluations

5.1 FCC RF Exposure (Standalone)

Radio	Tech-Band	Freq-Low _[GHz]	Pwr _[dBm]	Power _[W]	Ant-G _[dBi]	EIRP _[W]	ERP _[W]	ERP _[mW]	Threshold ERP _[W]	ERP < Threshold ERP _[W]	FCC 2.1093(c)(1) P _{th} _[mW] = ERP _{20cm}	P/P _{th} ratio
BT	LE	2.4020	8.40	0.0069	1.00	0.009	0.005	5.31	0.03	Yes	3060.00	0.002
WLAN	802.11b	2.4120	15.70	0.0372	1.00	0.047	0.029	28.51	0.03	Yes	3060.00	0.012

Conclusion:

- The maximum RF emissions from this equipment fulfills the RF exclusion threshold limits for separation distance between the antenna and the human body greater than 4 cm. No RF Exposure evaluation is required.

5.2 ISED RF Exposure (Standalone)

									SAR	
									RSS-102 6.3 D≤20 cm (300 ≤ Freq ≤ 5800 MHz)	
Radio	Tech-Band	Freq-Low [MHz]	Pwr _[dBm]	Power _[W]	Ant-G [dBi]	EIRP _[W]	ERP _[mW]		Exemption limit for Routine Evaluation	Exemption (Y/N)
BT	LE	2402.00	8.40	0.01	1.00	0.01	8.71		172.09	Yes
WLAN	802.11b	2412.00	15.70	0.04	1.00	0.05	46.77		171.66	Yes

Conclusion:

- The maximum RF emissions from this equipment fulfills the RF exclusion threshold limits for separation distance between the antenna and the human body greater than 4 cm. No RF Exposure evaluation is required.

5.3 RF Exposure Test Exemptions for Simultaneous Transmission Sources

Conclusion:

- The radio complies with routine environmental evaluation requirements for RF exposure. Simultaneous transmission with other radios is not support.

6 Revision History

Date	Report Name	Changes to report	Report prepared by
2025-12-29	EMC_LENXX_025_25001_RF_Exposure	Initial Version	Art Thammanavarat
2026-02-06	EMC_LENXX_025_25001_RF_Exposure_Rev1	Report Revised Section 3.1: Updated HVIN Sections 5.2: Updated Table.	Art Thammanavarat

<<< The End >>>