

TEST REPORT

Product : Thermal printer
Trade mark : N/A
Model/Type reference : FT205, AT205, BT205, CT205,
DT205, ET205, GT205, HT205,
IT205, JT205, KT205, LT205,
MT205, NT205, OT205, PT205,
QT205, RT205, ST205, TT205,
UT205, VT205, WT205, XT205,
YT205, ZT205
Serial Number : N/A
Report Number : EED32S814282
FCC ID : 2A6FW-FT205
Date of Issue : July 29, 2026
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS


Prepared for:

Xiamen Print Future Technology Co.,Ltd.
Room 701, No.55 Dongling Road, Houxi Town, Jimei District, Xiamen City,
Fujian Province, China

Prepared by:

Centre Testing International Group Co., Ltd.
Building C, Hongwei Industrial Park Block 70, Bao'an District,
Shenzhen, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:




Win Wei

Reviewed by:



Keven Tan

Approved by:



Aaron Ma

Date:

July 29, 2026



Check No.: 4212230626

1 Content

1 CONTENT	2
2 TEST SUMMARY	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 TEST CONFIGURATION	6
3.4 TEST ENVIRONMENT	7
3.5 DESCRIPTION OF SUPPORT UNITS	7
3.6 TEST LOCATION	7
3.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
4 EQUIPMENT LIST	9
5 TEST RESULTS AND MEASUREMENT DATA	13
5.1 ANTENNA REQUIREMENT	13
5.2 AC POWER LINE CONDUCTED EMISSIONS	14
5.3 MAXIMUM CONDUCTED OUTPUT POWER	18
5.4 DTS BANDWIDTH	19
5.5 MAXIMUM POWER SPECTRAL DENSITY	20
5.6 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION	21
5.7 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	22
6 APPENDIX A	67
7 PHOTOGRAPHS	68

2 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	PASS
DTS Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
Band edge measurements	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Radiated Spurious Emission & Restricted bands	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

3 General Information

3.1 Client Information

Applicant:	Xiamen Print Future Technology Co.,Ltd.
Address of Applicant:	Room 701, No.55 Dongling Road, Houxi Town, Jimei District, Xiamen City, Fujian Province, China
Manufacturer:	Xiamen Print Future Technology Co.,Ltd.
Address of Manufacturer:	Room 701, No.55 Dongling Road, Houxi Town, Jimei District, Xiamen City, Fujian Province, China
Factory:	Xiamen Print Future Technology Co.,Ltd.
Address of Factory:	Rooms 501, 601, 701, No.55 Dongling Road, Houxi Town, Jimei District, Xiamen City, Fujian Province, China

3.2 General Description of EUT

Product Name:	Thermal printer	
Model No.:	FT205, AT205, BT205, CT205, DT205, ET205, GT205, HT205, IT205, JT205, KT205, LT205, MT205, NT205, OT205, PT205, QT205, RT205, ST205, TT205, UT205, VT205, WT205, XT205, YT205, ZT205	
Test Model No.:	FT205	
Model difference:	That any of production units bearing the following model numbers have same electrical, PCB and layout, only the model names and color are different for marketing requirements.	
Trade mark:	N/A	
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location	
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz	
Modulation Type:	IEEE for 802.11b:DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g:OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM,QPSK,BPSK)	
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels	
Channel Separation:	5MHz	
Function	☒ SISO ☐ 2x2 MIMO ☐ 3x3 MIMO ☐ 4x4MIMO	
Antenna Type:	PCB antenna	
Antenna Gain:	3.01 dBi	
Power Supply:	Battery:	DC3.7V
Test Voltage:	DC3.7V	
Sample Received Date:	Jul. 02, 2026	
Sample tested Date:	Jul. 02, 2026 to Jul. 06, 2026	

Operation Frequency each of channel (802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel (802.11n HT40)							
Channel		Frequency		Channel		Frequency	
3		2422MHz		6		2437MHz	
4		2427MHz		7		2442MHz	
5		2432MHz		8		2447MHz	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/g/n (HT20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The highest channel	2462MHz

802.11n (HT40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The highest channel	2452MHz

3.3 Test Configuration

EUT Test Software Settings:	
Test Software:	EspRFTTestTool_v4.7_Manual.exe
EUT Power Grade:	Default
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, MCS0 for 802.11n(HT20), MCS0 for 802.11n(HT40).	

3.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

3.5 Description of Support Units

The EUT has been tested independently.

3.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164, Test Firm Registration No.: 260439

3.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

4 Equipment List

RF test system					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Communication test set	R&S	CMW500	107929	06-16-2025 06-15-2026	06-15-2026 06-14-2027
Signal Generator	R&S	SMBV100A	262454	08-11-2025	08-10-2026
Spectrum Analyzer	R&S	FSV40	101200	08-11-2025	08-10-2026
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI-42	06-16-2025 05-29-2026	06-15-2026 05-28-2027
high-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-13-2025	11-12-2026
Temperature/Humidity Indicator	biaozhi	HM10	1804186	05-26-2025 05-22-2026	05-15-2026 05-21-2027
BT&Wi-Fi Automatic test software	MWRF-test	MTS 8310	2.0.0.0	---	---
Digital multimeter	FLUKE	17B MAX	59545050WS	10-15-2025	10-14-2026