

RF Exposure Evaluation

FCC ID:2A6IU-TX13

Applicant Name..... : Shenzhen Gaoyi Electronic Co.,Ltd

Address..... : Room 701 7th Floor, Building F, Huafeng Industrial Zone, Hangcheng Road
Xixiang Town, Bao An District, Shenzhen,China

Manufacturer Name..... : Shenzhen Gaoyi Electronic Co.,Ltd

Address..... : Room 701 7th Floor, Building F, Huafeng Industrial Zone, Hangcheng Road
Xixiang Town, Bao An District, Shenzhen,China

Product..... : 3 in 1 Wireless Chargers

Model(s)..... : TX13-i3-Q22, TX13-i3-Q, TX13-i3

Additional Model(s)..... : /

Trademark..... : /

Model Difference..... : TX13-i3-Q22 is tested model, other models are derivative models .
The models are identical in circuit, only different on the model names.
So the test data of TX13-i3-Q22 can represent the remaining models.

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai
Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : Oct. 29, 2025

Date of Test(s)..... : Oct. 29, 2025 to -Jan. 30, 2026

Date of Issue..... : Jan. 30, 2026

Test Requested..... : Select test(s) as requested by the client.

Test Standard(s)..... : KDB 680106 D01 Wireless Power Transfer v04

In the configuration tested, the EUT complied with the standards specified above.

Prepared by

Leon Li

Leon Li/ Engineer

Reviewed by:

Baret Wu

Baret Wu/ Director

Approved by:

Levi Lee

Levi Lee/ Manager

Note: This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report. This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.



Table of Contents

Page

1. GENERAL INFORMATION	4
1.1. GENERAL DESCRIPTION OF EUT	4
1.2. Test Modes	5
1.3. Auxiliary equipment	6
2. RF EXPOSURE TEST	7
2.1. Measuring Standard	7
2.2. Requirements	7
2.3. Limits	8
2.4. Test Setup	8
2.5. Test Procedure	9
2.6. MEASUREMENT UNCERTAINTY	9
2.7. Test Instruments list	10
2.8. Test Result	10
2.9. Test Photos	11



1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	3 in 1 Wireless Chargers
Test Model No.:	TX13-i3-Q22
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	Phone: 115-205kHz, 360kHz Earphone: 115-148kHz Watch: 320-330kHz
Modulation type:	FSK
Antenna Type:	Coil Antenna
Antenna gain:	0dBi
Ratings	Input: 9V  3A, 12V  3A, 15V  3A Power: 32.5W MAX Phone Output: 5W, 7.5W, 10W, 15W, 25W Earphone Output: 5W Watch Output: 2.5W
Sample Number:	251029118YP001
Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	



1.2. TEST MODES

Test Modes:	
Mode 1	AC Mains + Mobile phone charging mode (115-205kHz) + Earphone charging mode + Apple Watch charging mode (Battery Status:≤1%)
Mode 2	AC Mains + Mobile phone charging mode (115-205kHz) + Earphone charging mode + Apple Watch charging mode (Battery Status:50%)
Mode 3	AC Mains + Mobile phone charging mode (115-205kHz) + Earphone charging mode + Apple Watch charging mode (Battery Status:≥98%)
Mode 4	AC Mains + Mobile phone charging mode (360kHz) + Earphone charging mode + Apple Watch charging mode (Battery Status:≤1%)
Mode 5	AC Mains + Mobile phone charging mode (360kHz) + Earphone charging mode + Apple Watch charging mode (Battery Status:50%)
Mode 6	AC Mains + Mobile phone charging mode (360kHz) + Earphone charging mode + Apple Watch charging mode (Battery Status:≥98%)
Mode 7	AC Mains + Mobile phone charging mode (115-205kHz) (Battery Status:≤1%)
Mode 8	AC Mains + Mobile phone charging mode (115-205kHz) (Battery Status:50%)
Mode 9	AC Mains + Mobile phone charging mode (115-205kHz) (Battery Status:≥98%)
Mode 10	AC Mains + Mobile phone charging mode (360kHz) (Battery Status:≤1%)
Mode 11	AC Mains + Mobile phone charging mode (360kHz) (Battery Status:50%)
Mode 12	AC Mains + Mobile phone charging mode (360kHz) (Battery Status:≥98%)
Mode 13	AC Mains + Earphone charging mode (Battery Status:≤1%)
Mode 14	AC Mains + Earphone charging mode (Battery Status:50%)
Mode 15	AC Mains + Earphone charging mode (Battery Status:≥98%)
Mode 16	AC Mains + Watch charging mode (Battery Status:≤1%)
Mode 17	AC Mains + Watch charging mode (Battery Status:50%)
Mode 18	AC Mains + Watch charging mode (Battery Status:≥98%)
Note: All modes were tested, only the worst-case was recorded in the report. Mode 4 is the worst mode.	



1.3. AUXILIARY EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	AC Adapter	Huizhou Jinhu Industrial Development Co., Ltd.	VCBAJACH	/	/
2	Mobile phone	Xiaomi Communications Co., Ltd.	Xiaomi 13	/	/
3	Earphone	Apple Inc.	A2031	/	/
4	Apple Watch	Apple Inc.	ultra 2	/	/
5	Mobile phone	Apple Inc.	iPhone 16 PULS	/	/

2. RF EXPOSURE TEST

2.1. MEASURING STANDARD

KDB 680106 D01 Wireless Power Transfer v04

2.2. REQUIREMENTS

According to the item 5 of KDB 680106 D01 v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

Requirements of section 3 of KDB 680106 D01	Yes/ No	Description
Mobile Device and Portable Device Configurations	Yes	Mobile Device
Equipment Authorization Procedures for Devices Operating at Frequencies Below 4 MHz	Yes	The device operate in the frequency range: Phone: 115-205kHz, 360kHz Earphone: 115-148kHz Watch: 320-330kHz
RF Exposure compliance may be ensured only for a minimum conditions at smaller distances can still be considered unlikely.separation distance that is greater than 20 cm, while use	Yes	The EUT H-field and E-field strengths at 20 cm surrounding the device.

2.3. LIMITS

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)


Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 * =Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

2.4. TEST SETUP

For mobile exposure conditions:



2.5. TEST PROCEDURE

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20 cm from all sides and 20 cm from the top) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

2.6. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	E-field	14.72%
2	H-field	15.48%
3	Temperature	$\pm 0.5^{\circ}\text{C}$
4	Humidity	$\pm 2\%$

Decision Rule

- ☒ Uncertainty is not included
☐ Uncertainty is included

2.7. TEST INSTRUMENTS LIST

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Near-field Electric and Electric Field Sensor System	Schmid & Partner Engineering AG	MAGPy-8H3D+E3D V2	3127	September 09, 2025	September 08, 2026
Near-field Electric and Electric Field Sensor System	Schmid & Partner Engineering AG	MAGPy-DASV2	3121	September 09, 2025	September 08, 2026

2.8. TEST RESULT


H-Filed Strength at 20 cm from the edges surrounding the EUT

Test Mode	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	50%Limits (A/m)	Limits (A/m)	test result
Mode 4	(A/m)	0.23	0.21	0.12	0.19	0.22	0.24	0.815	1.63	PASS

E-Filed Strength at 20 cm from the edges surrounding the EUT

Test Mode	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	50%Limits (V/m)	Limits (V/m)	test result
Mode 4	(V/m)	1.11	1.23	1.21	1.34	1.29	1.04	307	614	PASS

2.9. TEST PHOTOS



***** END OF REPORT *****