

## RF EXPOSURE EVALUATION

### MPE-Based Exemption

#### Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

#### MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts)                  |
|---------------------------|----------------------------------------|
| 0.3-1.34                  | 1,920 R <sup>2</sup> .                 |
| 1.34-30                   | 3,450 R <sup>2</sup> /f <sup>2</sup> . |
| 30-300                    | 3.83 R <sup>2</sup> .                  |
| 300-1,500                 | 0.0128 R <sup>2</sup> f.               |
| 1,500-100,000             | 19.2R <sup>2</sup> .                   |

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

**Result**

| Mode       | Frequency<br>(MHz) | Tune up<br>conducted<br>power <sup>#</sup> (dBm) | Antenna Gain# |       | ERP   |       | Evaluation<br>Distance<br>(m) | ERP<br>Limit<br>(W) |
|------------|--------------------|--------------------------------------------------|---------------|-------|-------|-------|-------------------------------|---------------------|
|            |                    |                                                  | (dBi)         | (dBd) | (dBm) | (W)   |                               |                     |
| 2.4G Wi-Fi | 2412-2462          | 22                                               | 2.93          | 0.78  | 22.78 | 0.190 | 0.2                           | 0.768               |
| 5G Wi-Fi   | 5180-5240          | 14                                               | -0.48         | -2.63 | 11.37 | 0.014 | 0.2                           | 0.768               |
|            | 5260-5320          | 15                                               | 1.92          | -0.23 | 14.77 | 0.030 | 0.2                           | 0.768               |
|            | 5500-5720          | 12                                               | 2.75          | 0.60  | 12.60 | 0.018 | 0.2                           | 0.768               |
|            | 5745-5825          | 13                                               | 0.74          | -1.41 | 11.59 | 0.014 | 0.2                           | 0.768               |

Note: The tune up conducted power and antenna gain was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant**