

Prüfbericht-Nr.: <i>Test report no.:</i>	CN26BJZ5 001	Auftrags-Nr.: <i>Order no.:</i>	48285229	Seite 1 von 29 Page 1 of 29
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2025-12-05	
Auftraggeber: <i>Client:</i>	KAGA FEI Co., Ltd. Gunseisha ANNEX Bldg. 5th floor, 382-1, Kaminamie-machi, Takasaki, Gunma, 370-0801, Japan			
Prüfgegenstand: <i>Test item:</i>	Bluetooth Low Energy Module			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	ES4L15			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (Nordic Original)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2025-12-16			
Prüfmuster-Nr.: <i>Test sample no:</i>	A004165731-009 A004165731-007			
Prüfzeitraum: <i>Testing period:</i>	2026-01-07 - 2026-01-15			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Taiwan Ltd. New Taipei Branch			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
zusammengestellt von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	2026-02-06	Ausstellungsdatum: <i>Issue date:</i>	2026-02-06	
Stellung / Position:	Senior Project Manager	Stellung / Position:	Senior Project Manager	
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN26BJZ5 001

Seite 2 von 29
Page 2 of 29

Anmerkungen
Remarks

- | | |
|----------|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.
Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.
Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i>
<i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:Seite 3 von 29
Page 3 of 29

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
5.1.3	15.247(a)(2)	6 dB Bandwidth	Pass
5.1.3	2.1049	99% Occupied Bandwidth	Pass
5.1.4	15.247(e)	Power Spectral Density	Pass
5.1.5	15.247(d)	Conducted Spurious Emissions and Band Edges	Pass
5.1.6	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:

Seite 4 von 29
Page 4 of 29

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.4 SUBMITTED DOCUMENTS	11
4. TEST SET-UP AND OPERATION MODES	12
4.1 PRINCIPLE OF CONFIGURATION SELECTION	12
4.2 CARRIER FREQUENCY AND CHANNEL	12
4.3 TEST OPERATION AND TEST SOFTWARE	13
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	14
4.5 TEST SETUP DIAGRAM	15
4.6 DUTY CYCLE OF TEST SIGNAL	16
5. TEST RESULTS	17
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	17
5.1.1 Antenna Requirement	17
5.1.2 Peak Output Power	18
5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth	20
5.1.4 Power Spectral Density	21
5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth	22
5.1.6 Radiated Spurious Emissions and Band Edges	23
5.2 MAINS EMISSION	28
5.2.1 Mains Conducted Emission	28

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 5 von 29
Page 5 of 29

APPENDIX A - TEST RESULT OF CONDUCTED

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 6 von 29
Page 6 of 29

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2026-02-06

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:Seite 7 von 29
Page 7 of 29

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 8 von 29
Page 8 of 29

2. Test Sites

2.1 Test Laboratory

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491 (TW3567)
ISED Registration No.: 25563 (TW3567)

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Bluetooth Low Energy Module. It contains a Nordic Original compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Bluetooth Low Energy Module
Type Identification	ES4L15
FCC ID	2A6NFES4L15

Technical Specification of EUT

Item	EUT information
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Number	2Mbps: 79 4Mbps: 76
Data Rate	2Mbps, 4Mbps
Operation Voltage	3.0 Vdc
Modulation	GFSK
Maximum Output Power (mW)	5.38
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 11 von 29
Page 11 of 29

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

Frequency (MHz)	Power Setting
2402	8
2403	8
2441	8
2478	8
2480	8

4.2 Carrier Frequency and Channel

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)
2402	2422	2442	2462
2403	2423	2443	2463
2404	2424	2444	2464
2405	2425	2445	2465
2406	2426	2446	2466
2407	2427	2447	2467
2408	2428	2448	2468
2409	2429	2449	2469
2410	2430	2450	2470
2411	2431	2451	2471
2412	2432	2452	2472
2413	2433	2453	2473
2414	2434	2454	2474
2415	2435	2455	2475
2416	2436	2456	2476
2417	2437	2457	2477
2418	2438	2458	2478
2419	2439	2459	2479
2420	2440	2460	2480
2421	2441	2461	

Note: Nordic original 4Mbps does not support 2402MHz, 2479MHz, and 2480MHz.

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:

Seite 13 von 29
Page 13 of 29

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	Radio Test Tool
---------------	-----------------

The samples were used as follows:

A004165731-009

A004165731-007

Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:

- The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Z-plane**.
- "-" means no effect.

Antenna Port Conducted Measurement

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2441, 2480	2
-	2403 to 2478	2403, 2441, 2478	4

Radiated Spurious Emissions (Above 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2441, 2480	2
-	2403 to 2478	2403, 2441, 2478	4

Radiated Spurious Emissions (Below 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2403 to 2478	2403	4

Mains Conducted Emission

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2403 to 2478	2403	4

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:

Seite 14 von 29
 Page 14 of 29

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	20.5-22.1 °C	60.2-62.4 %	Blake Wang / Andy Chen
Radiated Spurious Emissions above 1 GHz	22.7-25.5 °C	36-40 %	Roger Liao
Radiated Spurious Emissions below 1 GHz	22.7-25.5 °C	36-40 %	Roger Liao
Mains Conducted Emission	23.7 °C	64 %	Chuan Chu

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None

Support Unit


Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
A	Cable	TUV JP	NA	N/A	NO	NO	50	Radiated
1	DC Power Supply	Gwinstek	GPS-3303	N/A	-	-	-	
2	Cable	TUV	TUV-01	N/A	NO	NO	200	
A	Cable	TUV JP	NA	N/A	NO	NO	50	Mains Conducted
1	DC Power Supply	Gwinstek	GPS-3303	N/A	-	-	-	
2	Cable	TUV	TUV-002	N/A	NO	NO	50	
-	Notebook	HP	HP15S-du0007TX	CND93662WV	-	-	-	--
-	Power supply	Radio Tek	KEITHLEY	2303	-	-	-	--
-	USB Cable	TUV JP	N/A	A004165731-001	NO	NO	150	--

4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>



<Mains Conducted Emission mode>




Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 16 von 29
Page 16 of 29

4.6 Duty Cycle of Test Signal

Mode	On + Off Time (ms)	On Time (ms)	Duty Cycle (%)	Duty Factor (dB)
2Mbps	1.315	1.055	80.23	0.96
4Mbps	0.655	0.535	81.68	0.88



Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:Seite 17 von 29
Page 17 of 29

5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the EUT has an antenna with a directional gain of -4.8 dBi. The antenna is monopole antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.
Refer to EUT photo for details.

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 18 von 29
Page 18 of 29

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2025/02/26	2026/02/25	2026/01/07	2026/01/15
Power Sensor	Anritsu	MA2411B	1725269	2025/02/26	2026/02/25	2026/01/07	2026/01/15


Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Gate Setup:

1. Select the [Gates] tab in the software.
2. Check the box (e.g., Gate 1) to display it on the trace.
3. Set Gate Position
 - Drag the gate line with the mouse to the desired point on the waveform, or
 - Enter Values using the [Set] button and input start/stop times.
4. Switch to the next measurement channel and repeat the same gate setup procedure.
5. The instrument calculates average/peak power only within the defined gate interval.



Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:

Seite 19 von 29
Page 19 of 29

Test Result
Peak Output Power
<2Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	7.31	5.38	30
Middle Channel	2441	7.27	5.33	30
High Channel	2480	7.19	5.24	30

<4Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2403	7.31	5.38	30
Middle Channel	2441	7.26	5.32	30
High Channel	2478	7.13	5.16	30

Average Power
<2Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	7.24	5.30
Middle Channel	2441	7.19	5.24
High Channel	2480	7.11	5.14

<4Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2403	7.24	5.30
Middle Channel	2441	7.19	5.24
High Channel	2478	7.03	5.05

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:


Seite 20 von 29
Page 20 of 29

5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth

Limit The minimum 6 dB bandwidth shall be at least 500 kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2026/01/07	2026/01/15

Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- For 99% occupied bandwidth measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A.

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 21 von 29
 Page 21 of 29


5.1.4 Power Spectral Density

Limit

The power spectral density shall not be greater than 8 dBm in any 3 kHz band.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2026/01/07	2026/01/15

Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

Test Results

Please refer to Appendix A.

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:

Seite 22 von 29
Page 22 of 29


5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth

Limit

20dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2026/01/07	2026/01/15

Test Procedure

Measurement procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement procedure OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

Test Results

Please refer to Appendix A.

5.1.6 Radiated Spurious Emissions and Band Edges

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht-Nr.: CN26BJZ5 001
Test report no.:

Seite 25 von 29
Page 25 of 29

Test Instruments

Test Period: 2026-01-08 ~ 2026-01-09

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101508	2025/4/29	2026/4/28
Horn Antenna	ETS-Lindgren	3117	00218929	2025/11/20	2026/11/19
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2025/4/30	2026/4/29
HF-AMP + AC source	EMCI	EMC051845SE	980633	2025/1/15	2026/1/14
HF-AMP + AC source	EMCI	EMC051845SE	980656	2025/1/15	2026/1/14
Microwave Cable	EM	EM102A-KMKM-700	504231101002	2025/5/23	2026/5/22
Microwave Cable	EM	102A-KMKM-200	#01	2025/1/17	2026/1/16
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	801026/2EA	2025/6/6	2026/6/5
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A
30 MHz ~ 1 GHz					
Receiver	R&S	ESR7	102109	2025/02/13	2026/02/12
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2025/04/08	2026/04/07
LF-AMP	Agilent	8447D	2727A05146	2025/01/15	2026/01/14
Microwave Cable	EM	RG 214 U/2*11N/7M	24038601	2025/02/20	2026/02/19
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	802244/4	2025/04/30	2026/04/29
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	MY37203/4	2025/04/30	2026/04/29
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A
Below 30 MHz					
Receiver	R&S	ESR7	102109	2025/02/13	2026/02/12
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2025/12/16	2026/12/15
Microwave Cable	EM	RG 214 U/2*11N/7M	24038601	2025/02/20	2026/02/19
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	802244/4	2025/04/30	2026/04/29
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 27 von 29
Page 27 of 29

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 28 von 29
Page 28 of 29

5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	Rohde & Schwarz	ENV216	101243	2025/08/06	2026/08/05
EMI Test Receiver	R&S	ESCI	101094	2025/11/19	2026/11/18

Prüfbericht-Nr.: **CN26BJZ5 001**
Test report no.:

Seite 29 von 29
Page 29 of 29

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results


Please refer to Appendix B.

Appendix A: Test Results of Conducted Test

Test Result of 6 dB Bandwidth


NORDIC ORIGINAL_2M

Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2402	0.79	0.5	Pass
Middle Channel	2441	0.83	0.5	Pass
High Channel	2480	0.78	0.5	Pass



NORDIC ORIGINAL_4M


Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2403	2.30	0.5	Pass
Middle Channel	2441	2.25	0.5	Pass
High Channel	2478	2.17	0.5	Pass



Test Result of 99% Occupied Bandwidth


NORDIC ORIGINAL_2M

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2402	1.77
Middle Channel	2441	1.86
High Channel	2480	1.81



NORDIC ORIGINAL_4M


Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2403	4.18
Middle Channel	2441	4.20
High Channel	2478	4.23



Test Result of Power Spectral Density


NORDIC ORIGINAL_2M

Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2402	-6.57	8	Pass
Middle Channel	2441	-6.08	8	Pass
High Channel	2480	-6.03	8	Pass




NORDIC ORIGINAL_4M

Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2403	-12.99	8	Pass
Middle Channel	2441	-11.36	8	Pass
High Channel	2478	-12.49	8	Pass




Test Result of Conducted Spurious Emissions

NORDIC ORIGINAL_2M




NORDIC ORIGINAL_4M




Test Result of Conducted Band Edge

NORDIC ORIGINAL_2M



NORDIC ORIGINAL_4M



Appendix B: Test Results of Radiated Spurious Emissions & Mains

Conducted Emission Test


Band Edges, 2.31GHz ~ 2.5GHz

NORDIC ORIGINAL_2M

Low Channel (Horizontal) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2377.925	53.39	16.99	36.40	74.00	-20.61	148	166	Peak	Horizontal		
2	2402.000	99.42	63.87	36.35	74.00	25.42	148	166	Peak	Horizontal		
3	2498.385	55.24	18.13	37.11	74.00	-18.76	148	166	Peak	Horizontal		



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2324.725	53.63	17.17	36.46	74.00	-20.37	272	223	Peak	Vertical		
2	2402.000	97.86	61.51	36.35	74.00	23.86	272	223	Peak	Vertical		
3	2497.482	54.11	17.01	37.10	74.00	-19.89	272	223	Peak	Vertical		

NORDIC ORIGINAL_2M

Low Channel (Horizontal) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2312.897	40.00	3.55	36.45	54.00	-14.00	148	166	Average
2	2402.000	98.13	61.78	36.35	54.00	44.13	148	166	Average
3	2486.272	40.82	3.79	37.03	54.00	-13.18	148	166	Average

Low Channel (Vertical) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2310.617	39.86	3.41	36.45	54.00	-14.14	272	223	Average
2	2402.000	98.53	60.18	36.35	54.00	42.53	272	223	Average
3	2499.525	40.83	3.71	37.12	54.00	-13.17	272	223	Average

NORDIC ORIGINAL_2M

Middle Channel (Horizontal) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2351.563	53.03	16.56	36.47	74.00	-20.97	203	175	Peak	Horizontal	
2	* 2441.000	98.80	62.10	36.70	74.00	24.80	203	175	Peak	Horizontal	
3	2488.885	54.06	17.02	37.04	74.00	-19.94	203	175	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2375.170	53.35	16.94	36.41	74.00	-20.65	300	178	Peak	Vertical	
2	* 2441.000	98.80	61.60	36.70	74.00	24.80	300	178	Peak	Vertical	
3	2499.145	53.93	16.82	37.11	74.00	-20.67	300	178	Peak	Vertical	

NORDIC ORIGINAL_2M

Middle Channel (Horizontal) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2330.995	39.90	3.44	36.46	54.00	-14.10	203	175	Average	Horizontal	
2	* 2441.000	97.57	60.87	36.70	54.00	43.57	203	175	Average	Horizontal	
3	2499.905	41.02	3.90	37.12	54.00	-12.98	203	175	Average	Horizontal	

Middle Channel (Vertical) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2310.760	39.93	3.48	36.45	54.00	-14.07	300	178	Average	Vertical	
2	* 2441.000	97.07	60.37	36.70	54.00	43.07	300	178	Average	Vertical	
3	2496.343	40.89	3.79	37.10	54.00	-13.11	300	178	Average	Vertical	

NORDIC ORIGINAL_2M


High Channel (Horizontal) Peak



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




NORDIC ORIGINAL_4M


Low Channel (Horizontal) Peak



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




NORDIC ORIGINAL_4M

Low Channel (Horizontal) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Peak	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	Level	Line	Limit	dB	cm	deg		
1	2372.695	40.54	4.13	36.41	54.00	-13.46	149	167	Average	Horizontal
2	2403.000	93.04	56.69	36.35	54.00	39.04	149	167	Average	Horizontal
3	2488.552	41.39	4.35	37.04	54.00	-12.61	149	167	Average	Horizontal

Low Channel (Vertical) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Peak	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	Level	Line	Limit	dB	cm	deg		
1	2311.282	40.44	3.99	36.45	54.00	-13.56	274	225	Average	Vertical
2	2403.000	91.64	55.29	36.35	54.00	37.64	274	225	Average	Vertical
3	2498.005	41.46	4.35	37.11	54.00	-12.54	274	225	Average	Vertical

NORDIC ORIGINAL_4M

Middle Channel (Horizontal) Peak



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2313.847	53.54	17.09	36.45	74.00	-20.46		201	174	Peak	Horizontal	
2 *	2441.000	98.77	62.87	36.78	74.00	24.77		201	174	Peak	Horizontal	
3	2485.750	54.73	17.71	37.02	74.00	-19.27		201	174	Peak	Horizontal	

Middle Channel (Vertical) Peak



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2379.160	53.41	17.02	36.39	74.00	-20.59		238	180	Peak	Vertical	
2 *	2441.000	98.79	62.89	36.78	74.00	24.79		238	180	Peak	Vertical	
3	2496.390	53.57	16.47	37.10	74.00	-20.43		238	180	Peak	Vertical	

NORDIC ORIGINAL_4M

Middle Channel (Horizontal) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2362.867	40.93	4.49	36.44	54.00	-13.07	201	174	Average	Horizontal	
2	* 2441.000	92.21	55.51	36.70	54.00	38.21	201	174	Average	Horizontal	
3	2491.925	41.38	4.31	37.07	54.00	-12.62	201	174	Average	Horizontal	

Middle Channel (Vertical) Average



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2326.000	40.45	3.99	36.46	54.00	-13.55	238	180	Average	Vertical	
2	* 2441.000	92.23	55.53	36.70	54.00	38.23	238	180	Average	Vertical	
3	2490.975	41.39	4.32	37.07	54.00	-12.61	238	180	Average	Vertical	

NORDIC ORIGINAL_4M

High Channel (Horizontal) Peak




TÜV Rheinland Taiwan Ltd.
No. 438-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2326.193	53.59	17.04	36.46	74.00	-20.50		246	232	Peak	Horizontal	
2 *	2478.000	97.90	60.93	36.97	74.00	23.90		246	232	Peak	Horizontal	
3	2483.500	55.73	18.72	37.01	74.00	-18.27		246	232	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 438-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2317.220	53.18	16.73	36.45	74.00	-20.82		245	186	Peak	Vertical	
2 *	2478.000	97.07	60.10	36.97	74.00	23.07		245	186	Peak	Vertical	
3	2484.040	55.24	18.23	37.01	74.00	-18.76		245	186	Peak	Vertical	

NORDIC ORIGINAL_4M

High Channel (Horizontal) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2311.093	40.32	3.87	36.45	54.00	-13.68		246	232	Average	Horizontal	
2 *	2478.000	91.86	54.89	36.97	54.00	37.86		246	232	Average	Horizontal	
3	2483.500	44.61	7.60	37.01	54.00	-9.39		246	232	Average	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2347.050	40.43	3.95	36.48	54.00	-13.57		245	186	Average	Vertical	
2 *	2478.000	91.08	54.11	36.97	54.00	37.08		245	186	Average	Vertical	
3	2483.660	44.01	7.00	37.01	54.00	-9.99		245	186	Average	Vertical	


Spurious Emissions, Tx Mode, 9kHz ~ 30MHz

NORDIC ORIGINAL_4M

Low Channel (Open) 9kHz~150kHz




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	0.010	62.08	44.78	17.30	127.60	-65.52	100	39	Peak	Open		
2	0.030	49.10	29.89	19.21	118.05	-68.95	100	39	Peak	Open		
3	0.063	40.75	22.14	18.61	111.55	-70.80	100	191	Peak	Open		
4	0.076	35.21	17.10	18.11	110.00	-74.79	100	40	Peak	Open		
5	0.114	32.32	14.09	18.23	106.49	-74.17	100	226	Peak	Open		
6	0.124	28.37	10.07	18.30	105.71	-77.34	100	247	Peak	Open		



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	0.150	42.42	23.04	19.48	104.00	-61.66	100	12	Peak	Open		
2	0.777	33.28	14.25	19.03	69.80	-36.52	100	162	Peak	Open		
3	4.419	34.15	14.66	19.49	69.50	-35.35	100	232	Peak	Open		
4	17.224	33.79	11.73	22.06	69.50	-35.71	100	337	Peak	Open		
5	22.687	35.00	12.70	22.30	69.50	-34.50	100	136	Peak	Open		
6	26.120	36.16	13.44	22.72	69.50	-33.34	100	223	Peak	Open		


Spurious Emissions, Tx Mode, 30MHz ~ 1GHz

NORDIC ORIGINAL_4M

Low Channel (Horizontal)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	50.378	21.67	27.65	-5.98	40.00	-18.33	100	1 Peak	Horizontal	
2	144.460	21.26	27.96	-6.70	43.50	-22.24	100	1 Peak	Horizontal	
3	653.710	29.43	28.16	1.27	46.00	-16.57	100	144 Peak	Horizontal	
4	735.190	31.21	28.67	2.54	46.00	-14.79	100	358 Peak	Horizontal	
5	845.770	32.70	28.86	3.84	46.00	-13.30	100	5 Peak	Horizontal	
6	945.680	33.23	27.77	5.46	46.00	-12.77	100	4 Peak	Horizontal	

Low Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	37.760	24.24	31.45	-7.21	40.00	-15.76	100	192 Peak	Vertical	
2	163.860	21.36	27.48	-6.12	43.50	-22.14	100	10 Peak	Vertical	
3	612.000	28.40	27.79	0.61	46.00	-17.60	100	215 Peak	Vertical	
4	729.370	32.33	29.80	2.53	46.00	-13.67	100	298 Peak	Vertical	
5	845.770	33.06	29.22	3.84	46.00	-12.94	100	201 Peak	Vertical	
6	933.070	33.31	28.16	5.15	46.00	-12.69	100	276 Peak	Vertical	

Spurious Emissions, Tx Mode, 1GHz ~ 26.5GHz


NORDIC ORIGINAL_2M

Low Channel (Horizontal)


Low Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322




NORDIC ORIGINAL_2M

Middle Channel (Horizontal)




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Penliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4882.000	32.81	43.91	-11.10	54.00	-21.19	214	0 Average	Horizontal	
2	4882.000	44.00	55.10	-11.10	74.00	-30.00	214	0 Peak	Horizontal	
3	7323.000	45.30	54.32	-9.02	54.00	-8.70	100	302 Average	Horizontal	
4	7323.000	55.95	64.97	-9.02	74.00	-18.05	100	302 Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Penliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4882.000	33.98	45.08	-11.10	54.00	-20.02	300	0 Average	Vertical	
2	4882.000	44.57	55.67	-11.10	74.00	-29.43	300	0 Peak	Vertical	
3	7323.000	44.46	53.48	-9.02	54.00	-9.54	300	196 Average	Vertical	
4	7323.000	55.10	64.12	-9.02	74.00	-18.90	300	196 Peak	Vertical	

NORDIC ORIGINAL_2M

High Channel (Horizontal)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4960.000	37.00	47.79	-10.79	54.00	-17.00	300	0 Average	Horizontal	
2	4960.000	47.24	58.03	-10.79	74.00	-26.76	300	0 Peak	Horizontal	
3	7440.000	44.53	53.57	-9.04	54.00	-9.47	300	207 Average	Horizontal	
4	7440.000	55.40	64.44	-9.04	74.00	-18.60	300	207 Peak	Horizontal	

High Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4960.000	34.41	45.20	-10.79	54.00	-19.59	200	295 Average	Vertical	
2	4960.000	45.38	56.17	-10.79	74.00	-28.62	200	295 Peak	Vertical	
3	7440.000	42.08	51.12	-9.04	54.00	-11.92	300	191 Average	Vertical	
4	7440.000	53.64	62.68	-9.04	74.00	-20.36	300	191 Peak	Vertical	


NORDIC ORIGINAL_4M

Low Channel (Horizontal)

Low Channel (Vertical)




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Penliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 4896.000	33.56	44.67	-11.11	54.00	-20.44	100	146 Average	Horizontal	
2 4896.000	44.71	55.82	-11.11	74.00	-29.29	100	146 Peak	Horizontal	
3 12015.000	43.31	45.82	-2.51	54.00	-10.69	100	324 Average	Horizontal	
4 12015.000	54.86	57.37	-2.51	74.00	-19.14	100	324 Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Penliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 4896.000	32.94	44.05	-11.11	54.00	-21.06	300	191 Average	Vertical	
2 4896.000	43.80	54.91	-11.11	74.00	-30.20	300	191 Peak	Vertical	
3 12015.000	36.92	39.43	-2.51	54.00	-17.08	200	313 Average	Vertical	
4 12015.000	49.45	51.96	-2.51	74.00	-24.55	200	313 Peak	Vertical	

NORDIC ORIGINAL_4M

Middle Channel (Horizontal)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 4882.000	31.68	42.70	-11.10	54.00	-22.40	200	101 Average	Horizontal	
2 4882.000	43.04	54.14	-11.10	74.00	-30.96	200	101 Peak	Horizontal	
3 7323.000	46.29	55.31	-9.02	54.00	-7.71	100	212 Average	Horizontal	
4 7323.000	56.10	65.12	-9.02	74.00	-17.90	100	212 Peak	Horizontal	

Middle Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 4882.000	32.63	43.73	-11.10	54.00	-21.37	200	360 Average	Vertical	
2 4882.000	43.86	54.96	-11.10	74.00	-30.14	200	360 Peak	Vertical	
3 7323.000	42.78	51.80	-9.02	54.00	-11.22	300	166 Average	Vertical	
4 7323.000	53.19	62.21	-9.02	74.00	-20.81	300	166 Peak	Vertical	

NORDIC ORIGINAL_4M

High Channel (Horizontal)




TÜV Rheinland Taiwan Ltd.
No. 438-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4956.000	35.85	46.64	-10.79	54.00	-18.15	300	171	Average	Horizontal	
2	4956.000	45.89	56.68	-10.79	74.00	-28.11	300	171	Peak	Horizontal	
3	7434.000	47.82	56.86	-9.04	54.00	-6.18	100	199	Average	Horizontal	
4	7434.000	57.49	66.53	-9.04	74.00	-16.51	100	199	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 438-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



	Freq	Level	Read	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4956.000	32.67	43.46	-10.79	54.00	-21.33	296	356	Average	Vertical	
2	4956.000	43.60	54.39	-10.79	74.00	-30.40	296	356	Peak	Vertical	
3	7434.000	45.73	54.77	-9.04	54.00	-8.27	300	168	Average	Vertical	
4	7434.000	55.69	64.73	-9.04	74.00	-18.31	300	168	Peak	Vertical	

Mains Conducted Emission, TX 150kHz ~ 30MHz


Worst Band

(Line)

(Neutral)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




Trace: 1

	Freq	Level	Read Level Factor	Limit Line	Over Limit Remark	Pol/Phase	Note
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.254	6.85	-2.79	9.64	51.61	-44.76	Average line1
2	0.254	10.13	0.49	9.64	61.61	-51.48	QP line1
3	0.411	5.74	-3.90	9.64	47.64	-41.90	Average line1
4	0.411	8.70	-0.94	9.64	57.64	-48.94	QP line1
5	2.361	5.37	-4.31	9.68	46.00	-40.63	Average line1
6	2.361	18.65	8.97	9.68	56.00	-37.35	QP line1
7	4.210	5.36	-4.34	9.70	46.00	-40.64	Average line1
8	4.210	15.14	5.44	9.70	56.00	-40.86	QP line1
9	5.242	5.22	-4.50	9.72	50.00	-44.78	Average line1
10	5.242	15.62	5.90	9.72	60.00	-44.38	QP line1
11	23.499	13.96	4.18	9.78	50.00	-36.04	Average line1
12	23.499	19.19	9.41	9.78	60.00	-40.81	QP line1



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Trace: 1

	Freq	Level	Read Level Factor	Limit Line	Over Limit Remark	Pol/Phase	Note
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.153	7.65	-1.99	9.64	55.83	-48.18	Average neutral
2	0.153	11.83	2.19	9.64	65.83	-54.00	QP neutral
3	0.186	7.13	-2.50	9.63	54.22	-47.09	Average neutral
4	0.186	10.60	0.97	9.63	64.22	-53.62	QP neutral
5	2.797	5.16	-4.53	9.69	46.00	-40.84	Average neutral
6	2.797	17.29	7.60	9.69	56.00	-38.71	QP neutral
7	4.210	5.37	-4.33	9.70	46.00	-40.63	Average neutral
8	4.210	15.54	5.84	9.70	56.00	-40.46	QP neutral
9	5.242	5.15	-4.57	9.72	50.00	-44.85	Average neutral
10	5.242	15.69	5.97	9.72	60.00	-44.31	QP neutral
11	24.577	13.58	3.70	9.88	50.00	-36.42	Average neutral
12	24.577	18.96	9.08	9.88	60.00	-41.04	QP neutral