

Prüfbericht-Nr.: <i>Test report no.:</i>	CN25PDKP 001	Auftrags-Nr.: <i>Order no.:</i>	48274748	Seite 1 von 52 Page 1 of 52
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2025-03-27	
Auftraggeber: <i>Client:</i>	KAGA FEI Co., Ltd. Gunseisha ANNEX Bldg. 5th floor, 382-1, Kaminamie-machi, Takasaki, Gunma, 370-0801 Japan			
Prüfgegenstand: <i>Test item:</i>	Wireless LAN Module			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	WKI611			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15E Test report (WiFi 5GHz)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart E Section 15.407			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2025-06-05			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A0004012392-001 A0004012392-015, 016			
Prüfzeitraum: <i>Testing period:</i>	2025-07-11 - 2025-09-18			
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Taipei Testing Site			
Prüflaboratorium: <i>Testing laboratory:</i>	Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
zusammengestellt von: <i>compiled by:</i>	<i>Pei-Shan Tsai</i>		genehmigt von: <i>authorized by:</i>	<i>Brenda Chen</i>
Datum: <i>Date:</i>	2025-09-30	Ausstellungsdatum: <i>Issue date:</i>	2025-09-30	
Stellung / Position:	Section Manager	Stellung / Position:	Senior Project Manager	
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN25PDKP 001

Seite 2 von 52
Page 2 of 52

Anmerkungen
Remarks

- | | |
|----------|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.407(a) & 15.203	Antenna Requirement	Pass
5.1.2	15.407(a)	Maximum Conducted Output Power	Pass
5.1.3	15.407(h)(1)	Transmit Power Control (TPC)	Pass
5.1.3	15.407(a)	26 dB Bandwidth	Pass
5.1.3	2.1049	99% Occupied Bandwidth	Pass
5.1.5	15.407(e)	6 dB Bandwidth (U-NII-3 Band only)	Pass
5.1.6	15.407(g)	Frequency Stability	Pass
5.1.7	15.407(a)	Power Spectral Density	Pass
5.1.8	15.407(b) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.1.9	15.407(h) & KDB 905462 D02	Dynamic Frequency Selection	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	12
3.4 SUBMITTED DOCUMENTS	12
4. TEST SET-UP AND OPERATION MODES	13
4.1 PRINCIPLE OF CONFIGURATION SELECTION	13
4.2 CARRIER FREQUENCY AND CHANNEL	15
4.3 TEST OPERATION AND TEST SOFTWARE	16
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	20
4.5 TEST SETUP DIAGRAM	21
4.6 DUTY CYCLE OF TEST SIGNAL	22
5. TEST RESULTS	24
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	24
5.1.1 Antenna Requirement	24
5.1.2 Maximum Conducted Output Power	25
5.1.3 Transmit Power Control (TPC)	34
5.1.4 26 dB Bandwidth and 99% Occupied Bandwidth	35
5.1.5 6 dB Bandwidth (5725-5850MHz)	36
5.1.6 Frequency Stability Measurement	37
5.1.7 Power Spectral Density	39
5.1.8 Radiated Spurious Emissions	41
5.1.9 Dynamic Frequency Selection	46
5.2 MAINS EMISSION	51
5.2.1 Mains Conducted Emission	51

Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 5 von 52
Page 5 of 52

APPENDIX A - TEST RESULT OF CONDUCTED

**APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION FOR
MONOPOLE ANTENNA OF KAGA FEI**

**APPENDIX C - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION FOR
DIPOLE ANTENNA OF MOLEX**

**APPENDIX D - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION FOR
DIPOLE ANTENNA OF TE CONNECTIVITY**

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: **CN25PDKP 001**
Test Report No.

Seite 6 von 52
Page 6 of 52

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2025-09-30

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission for Monopole Antenna of Kaga FEI

Appendix C - Test Result of Radiated Emissions & Mains Conducted Emission for Dipole Antenna of Molex

Appendix D - Test Result of Radiated Emissions & Mains Conducted Emission for Dipole Antenna of TE Connectivity

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart E Section 15.407
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10-2020
KDB 789033 D02 General UNII Test Procedures New Rules v02r01
KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
KDB 662911 D01 Multiple Transmitter Output v02r01

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491
ISED Registration No.: 25563

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless LAN Module. It contains a WLAN compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Wireless LAN Module
Type Identification	WKI611
FCC ID	2A6NFWKI611

Technical Specification of EUT

Item	EUT information
Operating Frequency	Band 1: 5180 MHz ~ 5240 MHz Band 2: 5260 MHz ~ 5320 MHz Band 3: 5500 MHz ~ 5720 MHz Band 4: 5745 MHz ~ 5825 MHz
Channel Number	Band 1: 4 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20 2 for 802.11n HT40/802.11ac VHT40/802.11ax HE40 1 for 802.11ac VHT80/802.11ax HE80 Band 2: 4 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20 2 for 802.11n HT40/802.11ac VHT40/802.11ax HE40 1 for 802.11ac VHT80/802.11ax HE80 Band 3: 12 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20 6 for 802.11n HT40/802.11ac VHT40/802.11ax HE40 3 for 802.11ac VHT80/802.11ax HE80 Band 4: 5 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20 2 802.11n HT40/802.11ac VHT40/802.11ax HE40 1 for 802.11ac VHT80/802.11ax HE80
Data Rate	802.11a: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7 802.11ac: up to MCS9 802.11ax: up to MCS11
Operation Voltage	3.14 ~ 3.46 Vdc (Typical: 3.3 Vdc), 1.71 ~ 1.89 Vdc (Typical: 1.8 Vdc)
Modulation	OFDM (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Maximum Output Power (mW)	5180 ~ 5240 MHz: 19.41 5260 ~ 5320 MHz: 18.07 5500 ~ 5720 MHz: 18.97 5745 ~ 5825 MHz: 18.24

Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 11 von 52
Page 11 of 52

Maximum EIRP (mW)	5260 ~ 5320 MHz: 55.85 5500 ~ 5720 MHz: 58.61
DFS Mode	Slave without radar detection
TPC	Supported
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

<Full RU>

802.11a		802.11n HT20 802.11ac VHT20 802.11ax HE20		802.11n HT40 802.11ac VHT40 802.11ax HE40		802.11ac VHT80 802.11ax HE80	
Channel	Power Setting	Channel	Power Setting	Channel	Power Setting	Channel	Power Setting
36	13	36	11	38	10	42	9
40	13	40	11	46	10	58	9
48	13	48	11	54	10	106	9
52	13	52	11	62	10	122	9
60	13	60	11	102	10	138	9
64	13	64	11	110	10	138	9
100	13	100	11	134	10	155	9
116	13	116	11	142	10		
140	13	140	11	142	10		
144	13	144	11	151	10		
144	13	144	11	159	10		
149	13	149	11				
157	13	157	11				
165	13	165	11				

<Partial RU>

802.11ax HE20 26-Tone		802.11ax HE20 52-Tone		802.11ax HE20 106-Tone		802.11ax HE40 242-Tone		802.11ax HE80 484-Tone	
Channel	Power Setting	Channel	Power Setting	Channel	Power Setting	Channel	Power Setting	Channel	Power Setting
36	-14	36	-10	36	-7	38	-5	42	-1
40	-14	40	-10	40	-7	46	-5	58	-1
48	-14	48	-10	48	-7	54	-5	106	-1
52	-14	52	-10	52	-7	62	-5	122	-1
60	-14	60	-10	60	-7	102	-5	138	-1
64	-14	64	-10	64	-7	110	-5	138	-1
100	-14	100	-10	100	-7	134	-5	155	-1
116	-14	116	-10	116	-7	142	-5		
140	-14	140	-10	140	-7	142	-5		
144	-14	144	-10	144	-7	151	-5		
144	-14	144	-10	144	-7	159	-5		
149	-14	149	-10	149	-7				
157	-14	157	-10	157	-7				
165	-14	165	-10	165	-7				

4.2 Carrier Frequency and Channel

Band	Channel	Frequency (MHz)	802.11a 802.11n HT20 802.11ac VHT20 802.11ax HE20	802.11n HT40 802.11ac VHT40 802.11ax HE40	802.11ac VHT80 802.11ax HE80
U-NII-1 (Band 1)	36	5180	V		
	38	5190		V	
	40	5200	V		
	42	5210			V
	44	5220	V		
	46	5230		V	
	48	5240	V		
U-NII-2A (Band 2)	52	5260	V		
	54	5270		V	
	56	5280	V		
	58	5290			V
	60	5300	V		
	62	5310		V	
	64	5320	V		
U-NII-2C (Band 3)	100	5500	V		
	102	5510		V	
	104	5520	V		
	106	5530			V
	108	5540	V		
	110	5550		V	
	112	5560	V		
	116	5580	V		
	118	5590		V	
	120	5600	V		
	122	5610			V
	124	5620	V		
	126	5630		V	
	128	5640	V		
	132	5660	V		
	134	5670		V	
	136	5680	V		
	140	5700	V		
Straddle Channel	138	5690			V
	142	5710		V	
	144	5720	V		
U-NII-3 (Band 4)	149	5745	V		
	151	5755		V	
	153	5765	V		
	155	5775			V
	157	5785	V		
	159	5795		V	
	161	5805	V		
	165	5825	V		

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	DutApiSisoApApp_W9177.exe
---------------	---------------------------

The samples were used as follows:

A0004012392-001

A0004012392-015, 016

Full test was applied on all test modes, but only worst case was shown.

Modulation Mode	Tx Function
802.11a	1TX (SISO)
802.11n HT20	1TX (SISO)
802.11n HT40	1TX (SISO)
802.11ac VHT20	1TX (SISO)
802.11ac VHT40	1TX (SISO)
802.11ac VHT80	1TX (SISO)
802.11ax HE20	1TX (SISO)
802.11ax HE40	1TX (SISO)
802.11ax HE80	1TX (SISO)

* The modulation and bandwidth are similar for 802.11n mode HT20/HT40 and 802.11ac mode VHT20/VHT40 and 802.11ax HE20/40/80, therefore investigated worse case as representative mode in test report.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
Full RU	-	√	√	√	Ant No.: 1
	-	√	√	√	Ant No.: 2
	√	√	√	√	Ant No.: 3
Partial RU	-	√	-	-	Ant No.: 1
	-	√	-	-	Ant No.: 2
	√	√	-	-	Ant No.: 3

Note:

- The EUT had been pre-tested on the position of each 3 axis. The worst case was found when position on **Z-plane**.
- "-" means no effect.
- ANT No.: 3 is selected for the worst-case of conducted test.

Antenna Port Conducted Measurement
☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)	Description
Full RU	802.11a	5180-5240	36 to 48	36, 40, 48	6.0	ANT No.: 3
		5260-5320	52 to 64	52, 60, 64		
		5500-5720	100 to 144	100, 116, 140, 144		
		5745-5825	149 to 165	149, 157, 165		
	802.11n HT20 802.11ac VHT20 802.11ax HE20	5180-5240	36 to 48	36, 40, 48	6.5	
		5260-5320	52 to 64	52, 60, 64		
		5500-5720	100 to 144	100, 116, 140, 144		
		5745-5825	149 to 165	149, 157, 165		
	802.11n HT40 802.11ac VHT40 802.11ax HE40	5180-5240	38 to 46	38, 46	MCS0 for n mode NSS1 MCS0 for ac/ax mode	
		5260-5320	54 to 62	54, 62		
		5500-5720	102 to 142	102, 110, 134, 142		
		5745-5825	151 to 159	151, 159		
	802.11ac VHT80 802.11ax HE80	5180-5240	42	42	MCS0 for n mode NSS1 MCS0 for ac/ax mode	
		5260-5320	58	58		
		5500-5720	106 to 138	106, 122, 138		
		5745-5825	155	155		
Partial RU (Power & PSD only)	802.11ax HE20, 26-Tone	5180-5240	36 to 48	36, 40, 48	NSS1 MCS0	
		5260-5320	52 to 64	52, 60, 64		
		5500-5720	100 to 144	100, 116, 140, 144		
		5745-5825	149 to 165	149, 157, 165		
	802.11ax HE20, 52-Tone	5180-5240	38 to 46	38, 46		
		5260-5320	54 to 62	54, 62		
		5500-5720	102 to 142	102, 110, 134, 142		
		5745-5825	151 to 159	151, 159		
	802.11ax HE20, 106-Tone	5180-5240	42	42		
		5260-5320	58	58		
		5500-5720	106 to 138	106, 122, 138		
		5745-5825	155	155		
	802.11ax HE40, 242-Tone	5180-5240	38 to 46	38, 46		
		5260-5320	54 to 62	54, 62		
		5500-5720	102 to 142	102, 110, 134, 142		
		5745-5825	151 to 159	151, 159		
	802.11ax HE80, 484-Tone	5180-5240	42	42		
		5260-5320	58	58		
		5500-5720	106 to 138	106, 122, 138		
		5745-5825	155	155		

Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 18 von 52
Page 18 of 52

Radiated Spurious Emissions (Above 1 GHz)
☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)	Description
Full RU	802.11a	5180-5240	36 to 48	36, 40, 48	6.0	ANT No.: 1, 2 ,3
		5260-5320	52 to 64	52, 60, 64		
		5500-5720	100 to 144	100, 116, 140, 144		
		5745-5825	149 to 165	149, 157, 165		
	802.11ax HE20	5180-5240	36 to 48	36, 40, 48	6.5	
		5260-5320	52 to 64	52, 60, 64		
		5500-5720	100 to 144	100, 116, 140, 144		
		5745-5825	149 to 165	149, 157, 165		
	802.11ax HE40	5180-5240	38 to 46	38, 46	NSS1 MCS0	
		5260-5320	54 to 62	54, 62		
		5500-5720	102 to 142	102, 110, 134, 142		
		5745-5825	151 to 159	151, 159		
	802.11ax HE80	5180-5240	42	42	NSS1 MCS0	
		5260-5320	58	58		
		5500-5720	106 to 138	106, 122, 138		
		5745-5825	155	155		
Partial Ru (Power & PSD only)	802.11ax HE20, 26-Tone	5180-5240	36 to 48	48	NSS1 MCS0	ANT No.: 1, 2, 3
		5260-5320	52 to 64	60		
		5500-5720	100 to 144	144		
		5745-5825	149 to 165	165		
	802.11ax HE20, 52-Tone	5180-5240	36 to 48	48		
		5260-5320	52 to 64	60		
		5500-5720	100 to 144	144		
		5745-5825	149 to 165	165		
	802.11ax HE20, 106-Tone	5180-5240	36 to 48	48		
		5260-5320	52 to 64	60		
		5500-5720	100 to 144	144		
		5745-5825	149 to 165	165		
	802.11ax HE40, 242-Tone	5180-5240	38 to 46	46		
		5260-5320	54 to 62	62		
		5500-5720	102 to 142	142		
		5745-5825	151 to 159	159		
	802.11ax HE80, 484-Tone	5180-5240	42	42		
		5260-5320	58	58		
		5500-5720	106 to 138	122		
		5745-5825	155	155		

Radiated Spurious Emissions (Below 1 GHz)
☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)	Description
Full RU	802.11a	5180-5240	36 to 48	48	6.0	Ant No.: 1
	802.11a	5180-5240	36 to 48	36	6.0	Ant No.: 2
	802.11a	5180-5240	36 to 48	48	6.0	Ant No.: 3

Mains Conducted Emission Test

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)	Description
Full RU	802.11a	5180-5240	36 to 48	48	6.0	Ant No.: 1
	802.11a	5180-5240	36 to 48	36	6.0	Ant No.: 2
	802.11a	5180-5240	36 to 48	48	6.0	Ant No.: 3

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	18.3-18.8 °C	51-65 %	Nick Hsu
Radiated Spurious Emissions above 1 GHz	23.4-24.7 °C	53-55 %	Ivan Chiang & Peter Chiou
Radiated Spurious Emissions below 1 GHz	23.4-24.7 °C	53-55 %	Ivan Chiang & Peter Chiou
Mains Conducted Emission	22.1 °C	65 %	Roger Liao

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None.

Support Unit


Support Unit					
No.	Description	Brand	Model	S/N	Remark
Radiated and Mains Conducted Test					
1	Power Supply	GWINSTEK	GPS-3303	-	--
Conducted Test					
-	Notebook	DELL	E7450	457YR32	--
-	Power Supply	GWINSTEK	GPS-3303	GEU915620	--
-	RJ45-2M Cable	Kaga FEI	KAGA FEI-Cable-001	-	--
-	MicoUSB To USB Type-A-1M Cable	Kaga FEI	KAGA FEI-Cable-002	-	--
-	USB Type-C to Type-C-2M Cable	Kaga FEI	KAGA FEI-Cable-003	-	--
-	Adapter	Buffalo	BSACPD4500 Series	A10909	--
DFS Test					
-	Notebook	Lenovo	20CLS3P606	PC0DH09R	--
-	Notebook	Acer	N20C4	NXA1UTA00114210 D5C3400	--
-	Signalling Unit	NetGear	RAXE500	6JX62477A03CE	--

4.5 Test Setup Diagram

<Radiated Spurious Emissions Mode>





<Mains Conducted Emission Mode>



4.6 Duty Cycle of Test Signal

	Mode	On + Off Time (ms)	On Time (ms)	Duty Cycle (%)	Duty Factor (dB)
Full RU	802.11n	1.450	1.425	98.28	0.08
	802.11ax HE20	1.060	1.04	98.11	0.08
	802.11ax HE40	0.565	0.545	96.46	0.16
	802.11ax HE80	0.310	0.292	94.19	0.26
Partial RU	802.11ax HE20 26-Tone	1.425	1.355	95.09	0.22
	802.11ax HE20 52-Tone	1.425	1.355	95.09	0.22
	802.11ax HE20 106-Tone	1.425	1.355	95.09	0.22
	802.11ax HE40 242-Tone	1.425	1.355	95.09	0.22
	802.11ax HE80 484-Tone	1.430	1.355	94.76	0.23





5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the EUT's antenna specifications are described as below.
The antenna is used with no possibility of replacement with a non-approved antenna by the end-user.
Therefore, the EUT is considered to comply with this provision.

ANT No.:	Manufacturer	Antenna Type	Antenna Gain (dBi)
1	Kaga FEI	Monopole	1.4
2	Molex	Dipole	4.5
3	TE Connectivity	Dipole	4.9

Refer to EUT photo for details.

5.1.2 Maximum Conducted Output Power

Limit

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125 mW (21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	Fixed point-to-point Access Point	1 Watt (30 dBm)
	Indoor Access Point	1 Watt (30 dBm)
	Mobile and Portable client device	250 mW (24 dBm)
U-NII-2A	---	250 mW (24 dBm) or 11 dBm + 10 log B*
U-NII-2C	---	250 mW (24 dBm) or 11 dBm + 10 log B*
U-NII-3	---	1 Watt (30 dBm)

Note: B* is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20 MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

Kind of Test Site Shielded room

Test Setup



Test Instruments


Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2025/2/26	2026/2/25	2025/7/11	2025/8/27
Power Sensor	Anritsu	MA2411B	1725269	2025/2/26	2026/2/25	2025/7/11	2025/8/27

Test Procedures

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to AVERAGE. Duty factor is not added to measured value.

Gate Setup:

- 1) Select the [Gates] tab in the software.
- 2) Check the box (e.g., Gate 1) to display it on the trace.
- 3) Set Gate Position
 - Drag the gate line with the mouse to the desired point on the waveform, or
 - Enter Values using the [Set] button and input start/stop times.
- 4) Switch to the next measurement channel and repeat the same gate setup procedure.
- 5) The instrument calculates average/peak power only within the defined gate interval.



Test Result for Full RU

<802.11a>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
36	5180	12.68	18.54	24.00
40	5200	12.75	18.84	24.00
48	5240	12.88	19.41	24.00
52	5260	12.57	18.07	24.00
60	5300	12.56	18.03	24.00
64	5320	12.53	17.91	24.00
100	5500	12.26	16.83	24.00
116	5580	12.78	18.97	24.00
140	5700	12.33	17.10	24.00
144	5720 (U-NII-2C)	12.18	16.52	22.84
144	5720 (U-NII-3)	12.18	16.52	30.00
149	5745	12.61	18.24	30.00
157	5785	12.49	17.74	30.00
165	5825	12.51	17.82	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(20.38) = 24.09 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(20.30) = 24.07 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(20.50) = 24.12 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(20.42) = 24.10 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(20.34) = 24.08 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(20.34) = 24.08 \text{ dBm} > 24 \text{ dBm}$.
7. $11 \text{ dBm} + 10\log(15.27) = 22.84 \text{ dBm} < 24 \text{ dBm}$.

<802.11n HT20>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
36	5180	10.64	11.59	24.00
40	5200	10.69	11.72	24.00
48	5240	10.79	11.99	24.00
52	5260	10.52	11.27	24.00
60	5300	10.56	11.38	24.00
64	5320	10.42	11.02	24.00
100	5500	10.23	10.54	24.00
116	5580	10.71	11.78	24.00
140	5700	10.29	10.69	24.00
144	5720 (U-NII-2C)	10.12	10.28	22.89
144	5720 (U-NII-3)	10.12	10.28	30.00
149	5745	10.37	10.89	30.00
157	5785	10.39	10.94	30.00
165	5825	10.29	10.69	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(20.98) = 24.22 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(20.90) = 24.20 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(20.98) = 24.22 \text{ dBm} > 24 \text{ dBm}$.
7. $11 \text{ dBm} + 10\log(15.47) = 22.89 \text{ dBm} < 24 \text{ dBm}$.

<802.11n HT40>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
38	5190	9.65	9.23	24.00
46	5230	9.83	9.62	24.00
54	5270	9.47	8.85	24.00
62	5310	9.51	8.93	24.00
102	5510	9.22	8.36	24.00
110	5550	9.52	8.95	24.00
134	5670	9.18	8.28	24.00
142	5710 (U-NII-2C)	9.13	8.18	24.00
142	5710 (U-NII-3)	9.13	8.18	30.00
151	5755	9.36	8.63	30.00
159	5795	9.37	8.65	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(40.76) = 27.10 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(41.00) = 27.13 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(40.28) = 27.05 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(40.44) = 27.07 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(40.76) = 27.10 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(35.70) = 26.53 \text{ dBm} > 24 \text{ dBm}$.

<802.11ac VHT20>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
36	5180	10.69	11.72	24.00
40	5200	10.73	11.83	24.00
48	5240	10.86	12.19	24.00
52	5260	10.55	11.35	24.00
60	5300	10.58	11.43	24.00
64	5320	10.51	11.25	24.00
100	5500	10.29	10.69	24.00
116	5580	10.74	11.86	24.00
140	5700	10.32	10.76	24.00
144	5720 (U-NII-2C)	10.15	10.35	22.89
144	5720 (U-NII-3)	10.15	10.35	30.00
149	5745	10.39	10.94	30.00
157	5785	10.41	10.99	30.00
165	5825	10.32	10.76	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(20.98) = 24.22 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(20.90) = 24.20 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(20.98) = 24.22 \text{ dBm} > 24 \text{ dBm}$.
7. $11 \text{ dBm} + 10\log(15.47) = 22.89 \text{ dBm} < 24 \text{ dBm}$.

<802.11ac VHT40>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
38	5190	9.67	9.27	24.00
46	5230	9.86	9.68	24.00
54	5270	9.52	8.95	24.00
62	5310	9.55	9.02	24.00
102	5510	9.25	8.41	24.00
110	5550	9.56	9.04	24.00
134	5670	9.20	8.32	24.00
142	5710 (U-NII-2C)	9.16	8.24	24.00
142	5710 (U-NII-3)	9.16	8.24	30.00
151	5755	9.38	8.67	30.00
159	5795	9.39	8.69	30.00

Note:
For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(40.76) = 27.10 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(41.00) = 27.13 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(40.28) = 27.05 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(40.44) = 27.07 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(40.76) = 27.10 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(35.70) = 26.53 \text{ dBm} > 24 \text{ dBm}$.

<802.11ac VHT80>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
42	5210	8.79	7.57	24.00
58	5290	8.62	7.28	24.00
106	5530	8.34	6.82	24.00
122	5610	8.89	7.74	24.00
138	5690 (U-NII-2C)	8.31	6.78	24.00
138	5690 (U-NII-3)	8.31	6.78	30.00
155	5775	8.53	7.13	30.00

Note:
For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(75.44) = 29.78 \text{ dBm} > 24 \text{ dBm}$.

<802.11ax HE20>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
36	5180	10.91	12.33	24.00
40	5200	10.99	12.56	24.00
48	5240	11.12	12.94	24.00
52	5260	10.76	11.91	24.00
60	5300	10.81	12.05	24.00
64	5320	10.75	11.89	24.00
100	5500	10.53	11.30	24.00
116	5580	10.96	12.47	24.00
140	5700	10.57	11.40	24.00
144	5720 (U-NII-2C)	10.34	10.81	22.89
144	5720 (U-NII-3)	10.34	10.81	30.00
149	5745	10.63	11.56	30.00
157	5785	10.66	11.64	30.00
165	5825	10.54	11.32	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(20.98) = 24.22 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(20.90) = 24.20 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(20.86) = 24.19 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(20.98) = 24.22 \text{ dBm} > 24 \text{ dBm}$.
7. $11 \text{ dBm} + 10\log(15.47) = 22.89 \text{ dBm} > 24 \text{ dBm}$.

<802.11ax HE40>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
38	5190	10.05	10.12	24.00
46	5230	10.14	10.33	24.00
54	5270	9.86	9.68	24.00
62	5310	9.95	9.89	24.00
102	5510	9.56	9.04	24.00
110	5550	9.85	9.66	24.00
134	5670	9.52	8.95	24.00
142	5710 (U-NII-2C)	9.46	8.83	24.00
142	5710 (U-NII-3)	9.46	8.83	30.00
151	5755	9.71	9.35	30.00
159	5795	9.64	9.20	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(40.76) = 27.10 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(41.00) = 27.13 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(40.28) = 27.05 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(40.44) = 27.07 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(40.76) = 27.10 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(35.70) = 26.53 \text{ dBm} > 24 \text{ dBm}$.

<802.11ax HE80>

Channel	Channel Frequency (MHz)	Average Output Power		Limit (dBm)
		(dBm)	(mW)	
42	5210	9.32	8.55	24.00
58	5290	9.09	8.11	24.00
106	5530	8.88	7.73	24.00
122	5610	9.49	8.89	24.00
138	5690 (U-NII-2C)	8.59	7.23	24.00
138	5690 (U-NII-3)	8.59	7.23	30.00
155	5775	8.85	7.67	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(75.44) = 29.78 \text{ dBm} > 24 \text{ dBm}$.

Test Result for Partial RU

<802.11ax HE20, 26-Tone>

Channel	Channel Frequency (MHz)	RU Index	Average Output Power		Limit (dBm)
			(dBm)	(mW)	
36	5180	0	-13.59	0.04	24.00
40	5200	0	-13.38	0.05	24.00
48	5240	8	-13.01	0.05	24.00
52	5260	0	-13.51	0.04	24.00
60	5300	0	-13.41	0.05	24.00
64	5320	8	-13.42	0.05	24.00
100	5500	0	-13.89	0.04	24.00
116	5580	0	-13.22	0.05	24.00
140	5700	8	-13.38	0.05	24.00
144	5720 (U-NII-2C)	0	-13.41	0.05	22.89
144	5720 (U-NII-3)	8	-13.41	0.05	30.00
149	5745	0	-12.81	0.05	30.00
157	5785	0	-12.76	0.05	30.00
165	5825	8	-12.85	0.05	30.00

<802.11ax HE20, 52-Tone>

Channel	Channel Frequency (MHz)	RU Index	Average Output Power		Limit (dBm)
			(dBm)	(mW)	
36	5180	37	-9.39	0.12	24.00
40	5200	37	-9.21	0.12	24.00
48	5240	40	-8.92	0.13	24.00
52	5260	37	-9.44	0.11	24.00
60	5300	37	-9.33	0.12	24.00
64	5320	40	-9.35	0.12	24.00
100	5500	37	-9.87	0.10	24.00
116	5580	37	-9.13	0.12	24.00
140	5700	40	-9.26	0.12	24.00
144	5720 (U-NII-2C)	37	-9.33	0.12	22.89
144	5720 (U-NII-3)	40	-9.33	0.12	30.00
149	5745	37	-8.81	0.13	30.00
157	5785	37	-8.71	0.13	30.00
165	5825	40	-8.78	0.13	30.00

<802.11ax HE20, 106-Tone>

Channel	Channel Frequency (MHz)	RU Index	Average Output Power		Limit (dBm)
			(dBm)	(mW)	
36	5180	53	-6.12	0.24	24.00
40	5200	53	-5.86	0.26	24.00
48	5240	54	-5.57	0.28	24.00
52	5260	53	-6.41	0.23	24.00
60	5300	53	-6.34	0.23	24.00
64	5320	54	-6.35	0.23	24.00
100	5500	53	-6.59	0.22	24.00
116	5580	53	-5.74	0.27	24.00
140	5700	54	-5.89	0.26	24.00
144	5720 (U-NII-2C)	53	-5.96	0.25	22.89
144	5720 (U-NII-3)	54	-5.96	0.25	30.00
149	5745	53	-5.41	0.29	30.00
157	5785	53	-5.40	0.29	30.00
165	5825	54	-5.69	0.27	30.00

<802.11ax HE40, 242-Tone>

Channel	Channel Frequency (MHz)	RU Index	Average Output Power		Limit (dBm)
			(dBm)	(mW)	
38	5190	61	-3.93	0.40	24.00
46	5230	62	-3.51	0.45	24.00
54	5270	61	-4.18	0.38	24.00
62	5310	62	-4.22	0.38	24.00
102	5510	61	-4.41	0.36	24.00
110	5550	61	-4.02	0.40	24.00
134	5670	62	-3.77	0.42	24.00
142	5710 (U-NII-2C)	61	-3.86	0.41	24.00
142	5710 (U-NII-3)	62	-3.86	0.41	30.00
151	5755	61	-3.23	0.48	30.00
159	5795	62	-3.26	0.47	30.00

<802.11ax HE80, 484-Tone>

Channel	Channel Frequency (MHz)	RU Index	Average Output Power		Limit (dBm)
			(dBm)	(mW)	
42	5210	65	0.05	1.01	24.00
58	5290	66	0.09	1.02	24.00
106	5530	65	-0.22	0.95	24.00
122	5610	66	0.58	1.14	24.00
138	5690 (U-NII-2C)	65	0.08	1.02	24.00
138	5690 (U-NII-3)	66	0.08	1.02	30.00
155	5775	65	0.51	1.12	30.00

5.1.3 Transmit Power Control (TPC)

Requirement U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p of less than 500 mW.

Maximum EIRP of this device is 59.98mW which is less than 500mW, therefore it's not required TPC function.

TPC	E.I.R.P	15.407(h)(1)
	> 500mW	The TPC mechanism is required for system with an E.I.R.P. of above 500mW
V	< 500mW	-


Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 35 von 52
 Page 35 of 52

5.1.4 26 dB Bandwidth and 99% Occupied Bandwidth

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/7/11	2025/8/27
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/7/11	2025/8/27

Test Procedure

- a. Set RBW = approximately 1% of the emission bandwidth.
- b. Set the VBW > RBW.
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- f. For 99% Bandwidth Measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A


Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 36 von 52
 Page 36 of 52

5.1.5 6 dB Bandwidth (5725-5850MHz)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/7/11	2025/8/27
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/7/11	2025/8/27

Test Procedure

MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Test Results

Please refer to Appendix A

5.1.6 Frequency Stability Measurement

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/7/11	2025/8/27
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/7/11	2025/8/27

Test Procedure

- To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
- The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10 dB lower than the measured peak value.
- The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

 Seite 38 von 52
 Page 38 of 52

Test Results

Frequency (MHz)	5180			
Voltage (V)	Measurement Frequency (MHz)			Max. Deviation (ppm)
3.46 / 1.89	5179.96585			6.593
3.3 / 1.8	5179.96673			6.423
3.14 / 1.71	5179.96614			6.537
Temperature (°C)	Measurement Frequency (MHz)			
	0 Minute	2 Minute	5 Minute	10 Minute
50	5179.95977	5179.95948	5179.95948	5179.95948
40	5179.96353	5179.96353	5179.96353	5179.96353
30	5179.97598	5179.97511	5179.97511	5179.97511
20	5179.96673	5179.96614	5179.96614	5179.96585
10	5180.00608	5180.00666	5180.00695	5180.00695
0	5179.98958	5179.98611	5179.98437	5179.98408
-10	5179.99132	5179.99305	5179.99392	5179.99392
-20	5179.99624	5179.99624	5179.99624	5179.99624
Max. Deviation (ppm)	7.766	7.822	7.822	7.822

5.1.7 Power Spectral Density

Limit

For the 5.15~5.25GHz Bands:

For mobile and portable client devices in the 5.15~5.25GHz band, the Maximum Power spectral density shall not exceed 11dBm/MHz. For an indoor access point operating in the band 5.15~5.25GHz, the maximum power spectral density shall not exceed 17dBm/MHz.

For the 5.25~5.35GHz and 5.47~5.725GHz Bands:


The maximum power spectral density shall not exceed 11dBm/MHz.

For the 5.745~5.85GHz Bands:

The maximum power spectral density shall not exceed 30dBm/500kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/7/11	2025/8/27
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/7/11	2025/8/27

Test Procedure

For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-1 for Full RU

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value

Using method SA-2 for Partial RU

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value and add 10 log (1/duty cycle)

※For U-NII-3:

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
4. Sweep time = auto, trigger set to "free run".
5. Trace average at least 100 traces in power averaging mode.
6. Record the max value and add $10 \log (1/\text{duty cycle})$

For MIMO mode, calculation method follows FCC KDB 662911 Method 2) a) of power density measurement using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

Test Results

Please refer to Appendix A

5.1.8 Radiated Spurious Emissions

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.407(b).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 43 von 52
Page 43 of 52

Test Instruments

Test Date: 2025/8/1 ~ 2025/9/18

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101508	2025/5/7	2026/5/6
Wireless Test	R&S	CBT	100866	2025/4/9	2026/4/8
Horn Antenna	ETS-Lindgren	3117	00218929	2024/11/21	2025/11/20
HF-AMP + AC source	EMCI	EMC051845SE	980635	2025/4/2	2026/4/1
HF-AMP + AC source	EMCI	EMC184045SE	980656	2025/1/15	2026/1/14
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2025/4/30	2026/4/29
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
30 MHz – 1 GHz					
Receiver	R&S	ESR7	102109	2025/2/13	2026/2/12
Wireless Test	R&S	CBT	100866	2025/4/9	2026/4/8
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2025/4/8	2026/4/7
LF-AMP	Agilent	8447D	2727A05146	2025/1/15	2026/1/14
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
Below 30 MHz					
Receiver	R&S	ESR7	102109	2025/2/13	2026/2/12
Wireless Test	R&S	CBT	100866	2025/4/9	2026/4/8
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2024/12/11	2025/12/10
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht - Nr.: **CN25PDKP 001**
Test Report No.

Seite 45 von 52
Page 45 of 52

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B ~ D.

5.1.9 Dynamic Frequency Selection

Limit

<DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection>

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

<DFS Response Requirement Values>


Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time and the Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Kind of Test Site


Shielded room

Test Setup


<Setup for Master with injection at the Master>



<Setup for Client with injection at the Master>



<Setup for Client with injection at the Client>



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Keysight	N9000B	MY62361339	2025/02/13	2026/02/12	2025/7/16	2025/7/16
EXG Vector Signal Generator	Keysight	N5172B	MY61253270	2024/12/24	2025/12/23	2025/7/16	2025/7/16
Frequency Extender	Keysight	N5182BX07	MY61500182	2024/12/24	2025/12/23	2025/7/16	2025/7/16

Requirement

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

Prüfbericht - Nr.: CN25PDKP 001
Test Report No.

Seite 49 von 52
Page 49 of 52

Test Results
<802.11ax HT80>

Non-Occupancy Period:



Channel (MHz)	Limit (minute)	Result
5290	30	Pass
5530	30	Pass



Channel Moving Time:

Channel (MHz)	Channel Move Time (s)	Limit (s)	Result
5290	0.510	10	Pass
5530	0.552	10	Pass

Channel Closing Transmission Time:

Channel (MHz)	Channel Closing Transmission Time (ms)	Limit (ms)	Result
5290	0.012	60	Pass
5530	0.012	60	Pass





5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted emissions as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Test Date: 2025/9/18

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	Rohde & Schwarz	ENV216	101938	2024/10/22	2025/10/21
EMI Test Receiver	R&S	ESCI	101094	2024/11/25	2025/11/24

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results

Please refer to Appendix B ~ D.