

FCC TEST REPORT

FCC ID: 2A6P9-WCPAA-2S

Report No. : SSP26030288-4E

Applicant : Promaster Electronic LLC

Product Name : Wireless CPAA adaptor

Model Name : WCPAA-2S

Test Standard : FCC Part 15 Subpart E

Date of Issue : 2026-03-24

Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Promaster Electronic LLC		
Address of Applicant:	25275 Budde Rd Suite 31, Spring, Texas, United States, 77380		
Manufacturer:	Huizhou Funnavi Electronics Co., Ltd		
Address of Manufacturer:	3rd floor, No.:25 Xiangda road Xiao Jin kou street, Huicheng district, Huizhou city, China		
Product Name:	Wireless CPAA adaptor		
Brand Name:	Autosky		
Main Model:	WCPAA-2S		
Series Models:	WCPAA-2S-O, WCPAA-2S-MB, WCPAA-2S-B, WCPAA-2S-BR, WCPAA-2S-S, WCPAA-2S-C		
Test Standard:	FCC Part 15 Subpart E KDB 789033 D02 v02r01 ANSI C63.4-2014 ANSI C63.10-2020		
Date of Test	2026-03-14 to 2026-03-20		
Test Result:	PASS		
Tested By		(Colin Chen)	
Reviewed By:		(Lorzix Luo)	
Authorized Signatory:		(Lahm Peng)	
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.			

CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	7
1.3 Compliance Standards.....	8
1.4 Test Facilities.....	8
1.5 List of Measurement Instruments	9
1.6 Measurement Uncertainty.....	10
2. Summary of Test Results.....	11
3. Antenna Requirement.....	12
3.1 Standard and Limit.....	12
3.2 Test Result.....	12
4. Conducted Emissions	13
4.1 Standard and Limit.....	13
4.2 Test Procedure.....	13
4.3 Test Data and Results	14
5. Radiated Emissions(Below 1GHz).....	17
5.1 Standard and Limit.....	17
5.2 Test Procedure.....	17
5.3 Test Data and Results	18
6. Spurious Emissions(Above 1GHz).....	21
6.1 Standard and Limit.....	21
6.2 Test Procedure.....	21
6.3 Test Data and Results	22
7. Band-edge Emissions(Radiated).....	25
7.1 Standard and Limit.....	25
7.2 Test Procedure.....	25
7.3 Test Data and Results	25
8. Maximum Conducted Output Power	28
8.1 Standard and Limit.....	28
8.2 Test Procedure.....	28
8.3 Test Data and Results	28
9. Occupied Bandwidth	29
9.1 Standard and Limit.....	29
9.2 Test Procedure.....	29
9.3 Test Data and Results	29
10. Maximum Power Spectral Density.....	30
10.1 Standard and Limit.....	30
10.2 Test Procedure.....	30
10.3 Test Data and Results	30
11. Frequency Stability	31
11.1 Standard and Limit.....	31
11.2 Test Procedure.....	31
11.3 Test Data and Results	31

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2026-03-24	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Wireless CPAA adaptor
Trade Name:	Autosky
Test Model:	WCPAA-2S
Series Models:	WCPAA-2S-O, WCPAA-2S-MB, WCPAA-2S-B, WCPAA-2S-BR, WCPAA-2S-S, WCPAA-2S-C
Rated Voltage:	USB 5V by Adapter
Battery:	-
Test Sample No:	SSP26030288-1
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The manufacturer declares that the listed series models have different appearance colors and model names from the main model, but the circuits and electronic structures are the same.	

Wireless Specification	
Wireless Standard:	802.11a(HT20) 802.11n(HT20/HT40)
Operating Frequency:	802.11a/n (HT20): U-NII Band 1: 5180MHz to 5240MHz U-NII Band 4: 5745MHz to 5825MHz 802.11n (HT40): U-NII Band 1: 5190MHz to 5230MHz U-NII Band 4: 5755MHz to 5795MHz
Number of Channel:	802.11a/n (HT20): 4 for Band 1, 5 for Band 4 802.11n (HT40): 2 for Band 1, 2 for Band 4
Modulation:	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Antenna Gain:	2.54dBi
Type of Antenna:	PCB Antenna
Type of Device:	☐ Portable Device ☒ Mobile Device ☐ Modular Device

Channel List for UNII Band 1 (5150-5250MHz)							
802.11a/n(20MHz)				802.11n (40MHz)		--	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	--	--
36	<u>5180</u>	44	5220	38	<u>5190</u>	--	--
40	<u>5200</u>	48	<u>5240</u>	46	<u>5230</u>	--	--

Channel List for UNII Band 4 (5725-5850MHz)							
802.11a/n(20MHz)		802.11n(40MHz)		--		--	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	--	--	--	--
149	<u>5745</u>	151	<u>5755</u>	--	--	--	--
153	5765	159	<u>5795</u>	--	--	--	--
157	<u>5785</u>	--	--	--	--	--	--
161	5805	--	--	--	--	--	--
165	<u>5825</u>	--	--	--	--	--	--

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	UNII Band 1_802.11a(HT20)	5180MHz/5200MHz/5240MHz	
TM2	UNII Band 1_802.11n(HT20)	5180MHz/5200MHz/5240MHz	
TM3	UNII Band 1_802.11n(HT40)	5190MHz/5230MHz	
TM4	UNII Band 4_802.11a(HT20)	5745MHz/5785MHz/5825MHz	
TM5	UNII Band 4_802.11n(HT20)	5745MHz/5785MHz/5825MHz	
TM6	UNII Band 4_802.11n(HT40)	5755MHz/5795MHz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
USB cable	100cm	Unshielded	Without Ferrite
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	XIAOMI	MDY-14-EU	HC78E2N6A23645
-	-	-	-

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart E	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Unlicensed National Information Infrastructure Devices
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart E	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Unlicensed National Information Infrastructure Devices
KDB 789033 D02 v02r01	GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6983.01
FCC Registration No.:	583813
FCC Designation No.:	CN1373
ISED Registration No.:	CN0164

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2025-07-15	2026-07-14
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2025-07-15	2026-07-14
Test Cable	N/A	Cable 5	N/A	2025-07-15	2026-07-14
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2025-07-15	2026-07-14
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2025-07-15	2026-07-14
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2025-07-15	2026-07-14
Amplifier	SCHWARZBECK	BBV 9743B	00251	2025-07-15	2026-07-14
Amplifier	HUABO	YXL0518-2.5-45	--	2025-07-15	2026-07-14
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2025-07-15	2026-07-14
Loop Antenna	DAZE	ZN30900C	21104	2025-07-12	2026-07-11
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2025-07-12	2026-07-11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2025-07-12	2026-07-11
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2025-07-12	2026-07-11
Attenuator	QUANJUDA	6dB	220731	2025-07-15	2026-07-14
Test Cable	N/A	Cable 1	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 2	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 3	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 4	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 8	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 9	N/A	2025-07-15	2026-07-14
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2025-07-16	2026-07-15
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2025-07-16	2026-07-15
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThlnkPad E15 Gen 3	SPPOZ22485	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB
Power Spectrum Density	9kHz ~ 26GHz	±0.62 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(f)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207, 15.407(b)(9)	Conducted Emissions	Passed
FCC Part 15.209, 15.407(b)(9), (10)	Radiated Emissions	Passed
FCC Part 15.407(b)(10)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.407(a)(1), (2), (3)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.407(a)(2), (e)	Occupied Bandwidth	Passed
FCC Part 15.407(a)(1), (2), (3)	Maximum Power Spectral Density	Passed
FCC Part 15.407 (g)	Frequency Stability	Passed
FCC Part 15.407 (h)	Transmit Power Control (TPC)	N/A
FCC Part 15.407 (h)	Dynamic Frequency Selection (DFS)	N/A
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an PCB antenna, and the maximum antenna gain is 2.54dBi, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10-2020 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz


c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.


- d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f) LISN is at least 80 cm from nearest part of EUT chassis.
- g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

Both band1 and band4 all of the 802.11a, 802.11n and 802.11ac modes have been tested, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case 802.11a_5180MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit





5. Radiated Emissions(Below 1GHz)

5.1 Standard and Limit

According to FCC Part 15.407(b)(9), Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in FCC Part 15.209.

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of Emission (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: The more stringent limit applies at transition frequencies.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure

Test is conducting under the description of ANSI C63.10-2020 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz




Block Diagram of Radiated Emission From 30MHz to 1GHz


- The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz.
- EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 100 kHz
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

Both band1 and band4 all of the 802.11a, 802.11n modes have been tested, the EUT complied with the FCC Part 15.209 standard limit for a wireless device, and with the worst case 802.11a_5180MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit





Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to 1GHz. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

6. Spurious Emissions(Above 1GHz)


6.1 Standard and Limit

According to FCC Part 15.407(b), Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: All emissions outside of the 5.47–5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725–5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (5) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (6) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10-2020 section 6.3 to 6.6.



- a) The EUT is placed on a turntable, which is 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) For the actual test configuration, please refer to the related item - EUT test photos.

6.3 Test Data and Results

Both band1 and band4 all of the 802.11a, 802.11n and modes have been tested, the EUT complied with the FCC Part 15.407 standard limit, and with the worst case 802.11a-HT20, 802.11n-HT20 as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

UNII Band 1

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
802.11a_20MHz_Lowest Channel (5180MHz)							
10360	68.68	-6.22	53.2	68.2	-15	H	Peak
15540	55.27	-5.4	49.87	74	-24.13	H	Peak
10360	58.66	-6.22	52.44	68.2	-15.76	V	Peak
15540	54.51	-5.4	49.11	74	-24.89	V	Peak
802.11a_20MHz_Highest Channel (5240MHz)							
10480	62.19	-5.99	53.2	68.2	-15	H	Peak
15720	50.01	-5.53	53.3	74	-20.7	H	Peak
10480	62.3	-5.99	52.2	68.2	-16	V	Peak
15720	58.5	-5.53	52.97	74	-21.03	V	Peak
802.11n_20MHz_Lowest Channel (5180MHz)							
10360	61.87	-6.22	53.2	68.2	-15	H	Peak
15540	51.18	-5.4	45.78	74	-28.22	H	Peak
10360	66.15	-6.22	52.1	68.2	-16.1	V	Peak
15540	55.73	-5.4	50.33	74	-23.67	V	Peak
802.11n_20MHz_Highest Channel (5240MHz)							
10480	63.26	-5.99	53.2	68.2	-15	H	Peak
15720	52.39	-5.53	46.86	74	-27.14	H	Peak
10480	58.01	-5.99	52.2	68.2	-16	V	Peak
15720	51.05	-5.53	45.52	74	-28.48	V	Peak

UNII Band 4

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
802.11a_20MHz_Lowest Channel (5745MHz)							
11490	58.12	-4.34	53.78	74	-20.22	H	Peak
17235	50.14	-3.29	46.85	68.2	-21.35	H	Peak
11490	57.65	-4.34	53.31	74	-20.69	V	Peak
17235	55.29	-3.29	52	68.2	-16.2	V	Peak
802.11a_20MHz_Highest Channel (5825MHz)							
11650	56.27	-4.16	52.11	74	-21.89	H	Peak
17475	54.83	-2.53	52.3	68.2	-15.9	H	Peak
11650	57.26	-4.16	53.1	74	-20.9	V	Peak
17475	51.62	-2.53	49.09	68.2	-19.11	V	Peak
802.11n_20MHz_Lowest Channel (5745MHz)							
11490	56.16	-4.34	51.82	74	-22.18	H	Peak
17235	51.25	-3.29	47.96	68.2	-20.24	H	Peak
11490	56.07	-4.34	51.73	74	-22.27	V	Peak
17235	60.26	-3.29	56.97	68.2	-11.23	V	Peak
802.11n_20MHz_Highest Channel (5825MHz)							
11650	57.93	-4.16	53.77	74	-20.23	H	Peak
17475	55.29	-2.53	52.76	68.2	-15.44	H	Peak
11650	57.44	-4.16	53.28	74	-20.72	V	Peak
17475	50.23	-2.53	47.7	68.2	-20.5	V	Peak

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 1GHz to the tenth harmonics, If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit, so there is no record.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, above 18GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

7. Band-edge Emissions(Radiated)


7.1 Standard and Limit

According to §15.407(b), Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: All emissions outside of the 5.47–5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725–5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

7.2 Test Procedure

Test is conducting under the description of ANSI C63.10-2020 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

7.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.407 standard limit, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

UNII Band 1_ 802.11a_20MHz_Lowest Channel (5180MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5150	62.67	-13.96	48.71	74	-25.29	H	Peak
5150	65.49	-13.96	51.53	74	-22.47	V	Peak

UNII Band 1_ 802.11a_20MHz_Highest Channel (5240MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5350	54.54	-13.26	41.28	74	-32.72	H	Peak
5460	55.82	-12.88	42.94	74	-31.06	H	Peak
5350	55.01	-13.26	41.75	74	-32.25	V	Peak
5460	54.21	-12.88	41.33	74	-32.67	V	Peak

UNII Band 1_802.11n_40MHz_Lowest Channel (5190MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5150	67.46	-13.96	53.5	74	-20.5	H	Peak
5150	58.76	-13.96	44.8	74	-29.2	V	Peak

UNII Band 1_ 802.11n_40MHz_Highest Channel (5230MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5350	56.2	-13.26	42.94	74	-31.06	H	Peak
5460	54.22	-12.88	41.34	74	-32.66	H	Peak
5350	54.58	-13.26	41.32	74	-32.68	V	Peak
5460	51.72	-12.88	38.84	74	-35.16	V	Peak

UNII Band 4_ 802.11a_20MHz_Lowest Channel (5745MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5650	51.68	-12.3	39.38	68.2	-28.82	H	Peak
5700	51.3	-12.16	39.14	105.6	-66.46	H	Peak
5720	74.97	-12.09	62.88	110.8	-47.92	H	Peak
5650	52.68	-12.3	40.38	68.2	-27.82	V	Peak
5700	52.05	-12.16	39.89	105.6	-65.71	V	Peak
5720	68.23	-12.09	56.14	110.8	-54.66	V	Peak

UNII Band 4_ 802.11a_20MHz_Highest Channel (5825MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5850	70.67	-11.72	58.95	122.2	-63.25	H	Peak
5875	56.86	-11.64	45.22	110.8	-65.58	H	Peak
5925	52.01	-11.5	40.51	68.2	-27.69	H	Peak
5850	64.28	-11.72	52.56	122.2	-69.64	V	Peak
5875	60.92	-11.64	49.28	110.8	-61.52	V	Peak
5925	50.95	-11.5	39.45	68.2	-28.75	V	Peak

UNII Band 4_802.11n_40MHz_Lowest Channel (5755MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5650	55.73	-12.3	43.43	68.2	-24.77	H	Peak
5700	50.8	-12.16	38.64	105.6	-66.96	H	Peak
5720	69.03	-12.09	56.94	110.8	-53.86	H	Peak
5650	50.27	-12.3	37.97	68.2	-30.23	V	Peak
5700	50.56	-12.16	38.4	105.6	-67.2	V	Peak
5720	69.61	-12.09	57.52	110.8	-53.28	V	Peak

UNII Band 4_ 802.11n_40MHz_Highest Channel (5795MHz)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	Peak
5850	72.92	-11.72	61.2	122.2	-61	H	Peak
5875	57.82	-11.64	46.18	110.8	-64.62	H	Peak
5925	51.54	-11.5	40.04	68.2	-28.16	H	Peak
5850	66.93	-11.72	55.21	122.2	-66.99	V	Peak
5875	62.24	-11.64	50.6	110.8	-60.2	V	Peak
5925	55.43	-11.5	43.93	68.2	-24.27	V	Peak

8. Maximum Conducted Output Power

8.1 Standard and Limit

According to 15.407(a): (1) For the band 5.15–5.25 GHz.

For an outdoor or indoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band..

For client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

(2) For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725–5.895 GHz: the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500–kHz band.

8.2 Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the modulated transmitter's radio frequency power output.

- 1) A measurement instrument with an integrated channel bandwidth function may be used to automate the test process.
- 2) Set center of frequency = operating frequency.
- 3) Connect the EUT to the RF input of the spectrum analyzer via a low loss RF cable
- 4) Set the RBW = 1MHz, VBW = 3MHz, Detector = RMS, Sweep = Auto.
- 5) Set the SPAN to 40MHz/80MHz/160MHz for 20MHz/40MHz/80MHz emission bandwidth mode.
- 6) Measure the highest amplitude appearing on spectral display and mark the value.
- 7) Repeat the above procedures until all frequency measured was complete.



Test Setup Block Diagram

8.3 Test Data and Results

Please refer to the appendix for details.

9. Occupied Bandwidth

9.1 Standard and Limit

According to 15.407(a), Within the 5.250–5.350 GHz and 5.470–5.725 GHz bands the 26 dB bandwidth shall be tested.

According to 15.407(e), Within the 5.725–5.850 GHz and 5.850–5.895 GHz bands, the minimum 6 dB bandwidth of U–NII devices shall be at least 500 kHz.

9.2 Test Procedure

According to the ANSI C63.10-2020, section 12.5.1&12.5.2, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) 6dB: Set RBW = 100kHz, VBW $\geq [3 \times \text{RBW}]$, Sweep = Auto.
26dB: Set RBW = shall be in the range of 1% to 5% of the emission bandwidth, VBW>RBW, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 6dB or 26dB from the reference level. Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

9.3 Test Data and Results

Please refer to the appendix for details.

10. Maximum Power Spectral Density

10.1 Standard and Limit

According to 15.407(a):

(1) For the band 5.15–5.25 GHz.

For an outdoor or indoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band..

For client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

(2) For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725–5.895 GHz: the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

10.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Band 1: Set RBW = 1MHz, VBW = 3MHz, Sweep = Auto, Detector = RMS.
- Band 4: Set RBW = 510kHz, VBW = 1.5MHz, Sweep = Auto, Detector = RMS.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

10.3 Test Data and Results

Please refer to the appendix for details.


11. Frequency Stability

11.1 Standard and Limit

According to 15.407(g), Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

11.2 Test Procedure

Test is conducting under the description of ANSI C63.10-2020 section 6.8.



Test Setup Block Diagram

11.3 Test Data and Results

Mode	Frequency (MHz)	Temperature (°C)	Voltage (VDC)	Measured Frequency (MHz)	Limit (MHz)	Verdict
Carrier Wave	5180	20	4.5	5179.975	5150 to 5250	Pass
			5	5179.958	5150 to 5250	Pass
			5.5	5179.968	5150 to 5250	Pass
		-30	5	5179.961	5150 to 5250	Pass
		-20	5	5179.966	5150 to 5250	Pass
		-10	5	5179.958	5150 to 5250	Pass
		0	5	5179.971	5150 to 5250	Pass
		10	5	5179.967	5150 to 5250	Pass
		30	5	5179.969	5150 to 5250	Pass
		40	5	5179.966	5150 to 5250	Pass
		50	5	5179.964	5150 to 5250	Pass
	5200	20	4.5	5199.917	5150 to 5250	Pass
			5	5199.923	5150 to 5250	Pass
			5.5	5199.915	5150 to 5250	Pass
		-30	5	5199.917	5150 to 5250	Pass
		-20	5	5199.916	5150 to 5250	Pass

		-10	5	5199.933	5150 to 5250	Pass
		0	5	5199.918	5150 to 5250	Pass
		10	5	5199.917	5150 to 5250	Pass
		30	5	5199.914	5150 to 5250	Pass
		40	5	5199.914	5150 to 5250	Pass
		50	5	5199.914	5150 to 5250	Pass
	5240	20	4.5	5239.933	5150 to 5250	Pass
			5	5239.943	5150 to 5250	Pass
			5.5	5239.932	5150 to 5250	Pass
		-30	5	5239.932	5150 to 5250	Pass
		-20	5	5239.931	5150 to 5250	Pass
		-10	5	5239.933	5150 to 5250	Pass
		0	5	5239.935	5150 to 5250	Pass
		10	5	5239.946	5150 to 5250	Pass
		30	5	5239.938	5150 to 5250	Pass
		40	5	5239.945	5150 to 5250	Pass
		50	5	5239.942	5150 to 5250	Pass
	5745	20	4.5	5744.911	5725 to 5850	Pass
			5	5744.916	5725 to 5850	Pass
			5.5	5744.918	5725 to 5850	Pass
		-30	5	5744.921	5725 to 5850	Pass
		-20	5	5744.922	5725 to 5850	Pass
		-10	5	5744.926	5725 to 5850	Pass
		0	5	5744.935	5725 to 5850	Pass
		10	5	5744.932	5725 to 5850	Pass
		30	5	5744.919	5725 to 5850	Pass
		40	5	5744.922	5725 to 5850	Pass
		50	5	5744.926	5725 to 5850	Pass
	5785	20	4.5	5784.932	5725 to 5850	Pass
			5	5784.937	5725 to 5850	Pass
			5.5	5784.933	5725 to 5850	Pass
		-30	5	5784.933	5725 to 5850	Pass
		-20	5	5784.932	5725 to 5850	Pass
		-10	5	5784.931	5725 to 5850	Pass
		0	5	5784.937	5725 to 5850	Pass
		10	5	5784.932	5725 to 5850	Pass
		30	5	5784.931	5725 to 5850	Pass
		40	5	5784.934	5725 to 5850	Pass
		50	5	5784.932	5725 to 5850	Pass
	5825	20	4.5	5824.911	5725 to 5850	Pass
			5	5824.911	5725 to 5850	Pass
			5.5	5824.926	5725 to 5850	Pass
		-30	5	5824.922	5725 to 5850	Pass

		-20	5	5824.934	5725 to 5850	Pass
		-10	5	5824.931	5725 to 5850	Pass
		0	5	5824.927	5725 to 5850	Pass
		10	5	5824.921	5725 to 5850	Pass
		30	5	5824.919	5725 to 5850	Pass
		40	5	5824.916	5725 to 5850	Pass
		50	5	5824.914	5725 to 5850	Pass

******* END OF REPORT *******