

RF TEST REPORT

For

SHENZHEN HAIJIXING TECHNOLOGY CO., LTD

Product Name: digital camera

Test Model(s): WD05-8K

Report Reference No. : DACE260831024RL001

FCC ID : 2A6Q7-WD05-8K

Applicant's Name : SHENZHEN HAIJIXING TECHNOLOGY CO., LTD

Address : No. 105, Tianwan Road, Tianliao Community, Yutang Subdistrict,
Guangming District, Shenzhen City, Guangdong Province, China

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park,
Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen,
Guangdong, China

Test Specification Standard : 47 CFR Part 15.247


Date of Receipt : August 31, 2026

Date of Test : August 31, 2026 to September 11, 2026

Date of Issue : September 11, 2026

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Apply for company information

Applicant's Name	:	SHENZHEN HAIJIXING TECHNOLOGY CO., LTD
Address	:	No. 105, Tianwan Road, Tianliao Community, Yutang Subdistrict, Guangming District, Shenzhen City, Guangdong Province, China
Product Name	:	digital camera
Test Model(s)	:	WD05-8K
Series Model(s)	:	WD05-8K Pro
Test Specification Standard(s)	:	47 CFR Part 15.247

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Lucy Mo

Lucy Mo / Test Engineer

September 11, 2026

Supervised by:

Arron Liu

Arron Liu / Project Engineer

September 11, 2026

Approved by:

Tom Chen

Tom Chen / Manager

September 11, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260831024RL001	September 11, 2026

CONTENTS

1	TEST SUMMARY	6
1.1	TEST STANDARDS	6
1.2	SUMMARY OF TEST RESULT	6
2	GENERAL INFORMATION	8
2.1	CLIENT INFORMATION	8
2.2	DESCRIPTION OF DEVICE (EUT)	8
2.3	DESCRIPTION OF TEST MODES	8
2.4	DESCRIPTION OF SUPPORT UNITS	8
2.5	OPERATION FREQUENCY EACH OF CHANNEL	9
2.6	EQUIPMENTS USED DURING THE TEST	10
2.7	STATEMENT OF THE MEASUREMENT UNCERTAINTY	12
3	EVALUATION RESULTS (EVALUATION)	13
3.1	ANTENNA REQUIREMENT	13
3.1.1	Conclusion:	13
4	RADIO SPECTRUM MATTER TEST RESULTS (RF)	14
4.1	CONDUCTED EMISSION AT AC POWER LINE	14
4.1.1	E.U.T. Operation:	14
4.1.2	Test Setup Diagram:	14
4.1.3	Test Data:	15
4.2	6DB BANDWIDTH	17
4.2.1	E.U.T. Operation:	17
4.2.2	Test Setup Diagram:	17
4.2.3	Test Data:	18
4.3	MAXIMUM CONDUCTED OUTPUT POWER	19
4.3.1	E.U.T. Operation:	19
4.3.2	Test Setup Diagram:	19
4.3.3	Test Data:	19
4.4	POWER SPECTRAL DENSITY	20
4.4.1	E.U.T. Operation:	20
4.4.2	Test Setup Diagram:	20
4.4.3	Test Data:	20
4.5	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	21
4.5.1	E.U.T. Operation:	21
4.5.2	Test Setup Diagram:	21
4.5.3	Test Data:	21
4.6	BAND EDGE EMISSIONS (RADIATED)	22
4.6.1	E.U.T. Operation:	22
4.6.2	Test Setup Diagram:	22
4.6.3	Test Data:	23
4.7	EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz)	27
4.7.1	E.U.T. Operation:	27
4.7.2	Test Setup Diagram:	27
4.7.3	Test Data:	29
4.8	EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz)	31
4.8.1	E.U.T. Operation:	31
4.8.2	Test Setup Diagram:	32

	4.8.3 Test Data:	33
5	TEST SETUP PHOTOS	39
6	PHOTOS OF THE EUT	41
	APPENDIX	42
	1. -6dB Bandwidth	43
	2. 99% Occupied Bandwidth	50
	3. Duty Cycle	57
	4. MAX. Output Power	64
	5. Power Spectral Density	65
	6. Bandedge	72
	7. Spurious Emission	81

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.247	---	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2	47 CFR 15.207(a)	Pass
6dB Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10 KDB 558074 D01	47 CFR 15.247(d), 15.209, 15.205	Pass

		15.247 Meas Guidance v05r02		
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a- 2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a- 2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : SHENZHEN HAIJIXING TECHNOLOGY CO., LTD
Address : No. 105, Tianwan Road, Tianliao Community, Yutang Subdistrict, Guangming District, Shenzhen City, Guangdong Province, China

Manufacturer : SHENZHEN HAIJIXING TECHNOLOGY CO., LTD
Address : No. 105, Tianwan Road, Tianliao Community, Yutang Subdistrict, Guangming District, Shenzhen City, Guangdong Province, China

2.2 Description of Device (EUT)

Product Name:	digital camera
Model/Type reference:	WD05-8K
Series Model:	WD05-8K Pro
Model Difference:	All the model are the same circuit and RF module, only for model name are different. Test sample model: WD05-8K
Trade Mark:	N/A
Power Supply:	DC 5V charging from adapter DC 3.7V by battery
Operation Frequency:	2412-2462MHz
Number of Channels:	IEEE 802.11b/g/n(HT20): 11 Channels; IEEE 802.11n(HT40): 7 Channels
Modulation Type:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK); IEEE 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); IEEE 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type:	PCB Antenna
Antenna Gain:	0.52dBi
Hardware Version:	V1.0
Software Version:	V1.0

2.3 Description of Test Modes

No	Title	Description
TM1	2.4GWIFI TX Mode	Keep the EUT in TX mode
Test Environment		Normal Voltage(DC): 5V

2.4 Description of Support Units

Title	Manufacturer	Model No.	Serial No.
Adapter	PHOTON	ATXC-069AC65B	/

2.5 Operation Frequency each of channel

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	/	/

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	802.11b/g/n(HT20)	802.11n(HT40)
	Frequency (MHz)	Frequency (MHz)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

2.6 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2026-04-14	2027-04-13
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	2026-04-14	2027-04-13
Cable	SCHWARZ BECK	/	/	2026-04-14	2027-04-13
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Attenuation	561-G071	2025-12-02	2026-12-01
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	1164.6607K03 -102109-MH	2026-04-14	2027-04-13
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2026-04-14	2027-04-13
L.I.S.N	SCHWARZ BECK	NSLK 8126	05055	2026-04-14	2027-04-13
Pulse Limiter	CYBERTEK	EM5010A	/	2026-04-14	2027-04-13
EMI test software	Farad	EZ -EMC	EMEC-3A1.1	/	/

Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(she nzhn) Co.,Ltd.	RTS-01	V1.0.0	/	/
RF Power Sensor Unit	Tachoy Information Technology(she nzhn) Co.,Ltd.	TR1029-2	20220428P005	/	/
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Vector Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01
RF Control Unit	Tachoy Information Technology(she nzhn) Co.,Ltd.	TR1029-1	20220428C005	/	/

Band edge emissions (Radiated)
Emissions in frequency bands (below 1GHz)
Emissions in frequency bands (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	FA-03A2 RE+	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2026-04-14	2027-04-13
Cable(LF)#2	Schwarzbeck	/	/	2026-04-13	2027-04-12
Cable(LF)#1	Schwarzbeck	/	/	2026-04-14	2027-04-13
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2026-04-14	2027-04-13
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2026-04-14	2027-04-13
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2026-04-14	2027-04-13
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2026-04-14	2027-04-13
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2026-04-14	2027-04-13
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2026-04-14	2027-04-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2026-04-14	2027-04-13
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2026-04-29	2028-04-28

2.7 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	$\pm 3.41\text{dB}$
Occupied Bandwidth	$\pm 3.63\%$
RF conducted power	$\pm 0.733\text{dB}$
RF power density	$\pm 0.234\%$
Conducted Spurious emissions	$\pm 1.98\text{dB}$
Radiated Emission (Above 1GHz)	$\pm 5.46\text{dB}$
Radiated Emission (Below 1GHz)	$\pm 5.79\text{dB}$
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)


4.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2		
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

4.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	23.2 °C	Humidity:	46 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.1.2 Test Setup Diagram:




4.1.3 Test Data:

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4420	40.38	10.09	50.47	57.02	-6.55	QP	
2		0.4420	26.68	10.09	36.77	47.02	-10.25	AVG	
3		0.5580	43.38	10.10	53.48	56.00	-2.52	QP	
4	*	0.5580	33.84	10.10	43.94	46.00	-2.06	AVG	
5		1.1019	41.24	10.10	51.34	56.00	-4.66	QP	
6		1.1019	22.89	10.10	32.99	46.00	-13.01	AVG	
7		1.7220	38.72	10.12	48.84	56.00	-7.16	QP	
8		1.7220	30.81	10.12	40.93	46.00	-5.07	AVG	
9		2.3300	37.04	10.15	47.19	56.00	-8.81	QP	
10		2.3300	19.62	10.15	29.77	46.00	-16.23	AVG	
11		3.1940	35.86	10.15	46.01	56.00	-9.99	QP	
12		3.1940	22.08	10.15	32.23	46.00	-13.77	AVG	

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3100	37.50	10.10	47.60	59.97	-12.37	QP	
2		0.3100	14.50	10.10	24.60	49.97	-25.37	AVG	
3		0.4420	39.43	10.09	49.52	57.02	-7.50	QP	
4		0.4420	16.09	10.09	26.18	47.02	-20.84	AVG	
5	*	0.5540	43.46	10.10	53.56	56.00	-2.44	QP	
6		0.5540	23.35	10.10	33.45	46.00	-12.55	AVG	
7		1.1100	39.71	10.10	49.81	56.00	-6.19	QP	
8		1.1100	20.05	10.10	30.15	46.00	-15.85	AVG	
9		1.7220	39.23	10.12	49.35	56.00	-6.65	QP	
10		1.7220	20.80	10.12	30.92	46.00	-15.08	AVG	
11		2.3860	36.76	10.15	46.91	56.00	-9.09	QP	
12		2.3860	15.15	10.15	25.30	46.00	-20.70	AVG	

Remark: Factor = Cable loss + LISN factor, Margin = Measurement – Limit

All modes have been tested, and the test results show that b-mode data is the worst, only b-mode test chart is put. Test Mode: 802.11b20 low channel (the worst)

4.2 6dB Bandwidth


Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.9 °C	Humidity:	48 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.2.2 Test Setup Diagram:

--



4.2.3 Test Data:

Please Refer to Appendix for Details.


4.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 11.9.2 Maximum conducted (average) output power

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.1 °C	Humidity:	48 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 11.10, Maximum power spectral density level in the fundamental emission

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	54 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.


4.5 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.11.1, Section 11.11.2, Section 11.11.3

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	47 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.


4.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10.5.2		

4.6.1 E.U.T. Operation:


Operating Environment:			
Temperature:	22.6 °C	Humidity:	46 %
Atmospheric Pressure:	101.4 kPa		
Pretest mode:	TM1		
Final test mode:	TM1		

4.6.2 Test Setup Diagram:




4.6.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	2310.000	40.70	6.35	47.05	74.00	-26.95	peak		P	
2	2310.000	29.49	6.35	35.84	54.00	-18.16	AVG		P	
3	2390.000	40.36	6.56	46.92	74.00	-27.08	peak		P	
4 *	2390.000	30.30	6.56	36.86	54.00	-17.14	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2310.000	40.69	6.35	47.04	74.00	-26.96	peak			P	
2	2310.000	29.40	6.35	35.75	54.00	-18.25	AVG			P	
3	2390.000	41.69	6.56	48.25	74.00	-25.75	peak			P	
4 *	2390.000	29.47	6.56	36.03	54.00	-17.97	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2483.500	41.78	6.80	48.58	74.00	-25.42	peak			P	
2 *	2483.500	31.95	6.80	38.75	54.00	-15.25	AVG			P	
3	2500.000	41.78	6.84	48.62	74.00	-25.38	peak			P	
4	2500.000	29.76	6.84	36.60	54.00	-17.40	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2483.500	42.21	6.80	49.01	74.00	-24.99	peak			P	
2 *	2483.500	33.31	6.80	40.11	54.00	-13.89	AVG			P	
3	2500.000	40.54	6.84	47.38	74.00	-26.62	peak			P	
4	2500.000	29.67	6.84	36.51	54.00	-17.49	AVG			P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be of 802.11b mode recorded in the test report.


4.7 Emissions in frequency bands (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4		

4.7.1 E.U.T. Operation:

Operating Environment:			
Temperature:	22.3 °C	Humidity:	46 %
Atmospheric Pressure:	101.4 kPa		
Pretest mode:	TM1		
Final test mode:	TM1		


4.7.2 Test Setup Diagram:






4.7.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	312.1794	31.42	-2.04	29.38	46.00	-16.62	QP			P	
2 *	383.9318	42.18	-0.29	41.89	46.00	-4.11	QP			P	
3	572.6144	35.96	3.74	39.70	46.00	-6.30	QP			P	
4 !	721.7258	34.83	5.69	40.52	46.00	-5.48	QP			P	
5	815.9678	32.24	7.64	39.88	46.00	-6.12	QP			P	
6 !	903.3093	32.43	8.69	41.12	46.00	-4.88	QP			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 !	285.9777	43.43	-3.14	40.29	46.00	-5.71	QP			P	
2 !	360.4476	42.36	-1.12	41.24	46.00	-4.76	QP			P	
3 !	428.0192	41.15	0.62	41.77	46.00	-4.23	QP			P	
4 !	572.6144	36.90	3.74	40.64	46.00	-5.36	QP			P	
5 *	721.7258	36.19	5.69	41.88	46.00	-4.12	QP			P	
6 !	857.0246	33.36	7.99	41.35	46.00	-4.65	QP			P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be of 802.11b mode recorded in the test report.


4.8 Emissions in frequency bands (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4		

4.8.1 E.U.T. Operation:


Operating Environment:			
Temperature:	22.4 °C	Humidity:	52 %
		Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1		
Final test mode:	TM1		

4.8.2 Test Setup Diagram:




4.8.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	4818.750	48.49	13.16	61.65	74.00	-12.35	peak	P	
2	4818.750	35.07	13.16	48.23	54.00	-5.77	AVG	P	
3	7239.250	39.52	19.93	59.45	74.00	-14.55	peak	P	
4 *	7239.250	29.98	19.93	49.91	54.00	-4.09	AVG	P	
5	9448.250	37.52	24.32	61.84	74.00	-12.16	peak	P	
6	9448.250	25.11	24.32	49.43	54.00	-4.57	AVG	P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4818.750	42.44	13.16	55.60	74.00	-18.40	peak			P	
2	4818.750	30.34	13.16	43.50	54.00	-10.50	AVG			P	
3	7239.250	38.83	19.93	58.76	74.00	-15.24	peak			P	
4	7239.250	29.21	19.93	49.14	54.00	-4.86	AVG			P	
5	9366.000	38.20	24.28	62.48	74.00	-11.52	peak			P	
6 *	9366.000	26.24	24.28	50.52	54.00	-3.48	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	46.39	13.36	59.75	74.00	-14.25	peak			P	
2	4877.500	31.06	13.36	44.42	54.00	-9.58	AVG			P	
3	7309.750	39.45	20.00	59.45	74.00	-14.55	peak			P	
4	7309.750	29.69	20.00	49.69	54.00	-4.31	AVG			P	
5	9319.000	38.33	24.24	62.57	74.00	-11.43	peak			P	
6 *	9319.000	25.81	24.24	50.05	54.00	-3.95	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	5429.750	38.24	14.96	53.20	74.00	-20.80	peak			P	
2	5429.750	26.00	14.96	40.96	54.00	-13.04	AVG			P	
3	8778.500	37.03	23.48	60.51	74.00	-13.49	peak			P	
4	8778.500	24.18	23.48	47.66	54.00	-6.34	AVG			P	
5	11927.500	38.24	26.12	64.36	74.00	-9.64	peak			P	
6 *	11927.500	25.60	26.12	51.72	54.00	-2.28	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4924.500	41.45	13.50	54.95	74.00	-19.05	peak			P	
2	4924.500	28.38	13.50	41.88	54.00	-12.12	AVG			P	
3	7697.500	37.17	20.83	58.00	74.00	-16.00	peak			P	
4	7697.500	25.03	20.83	45.86	54.00	-8.14	AVG			P	
5	9401.250	38.88	24.30	63.18	74.00	-10.82	peak			P	
6 *	9401.250	25.83	24.30	50.13	54.00	-3.87	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4924.500	40.69	13.50	54.19	74.00	-19.81	peak			P	
2	4924.500	28.17	13.50	41.67	54.00	-12.33	AVG			P	
3	7603.500	36.52	20.55	57.07	74.00	-16.93	peak			P	
4	7603.500	24.94	20.55	45.49	54.00	-8.51	AVG			P	
5	9354.250	37.78	24.27	62.05	74.00	-11.95	peak			P	
6 *	9354.250	26.24	24.27	50.51	54.00	-3.49	AVG			P	


- Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor
- Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the noise floor test chart was not uploaded.
- All modes have been tested, and the test results show that b-mode data is the worst, only b-mode test chart is put. Test Mode: 802.11b low channel (the worst)

5 TEST SETUP PHOTOS

Conducted Emission at AC power line



Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)



6 PHOTOS OF THE EUT


Refer to Appendix - EUT Photos for EUT External Photo and Internal Photo.

Appendix



1. -6dB Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	8.04	500	Pass
NVNT	ANT1	802.11b	2437.00	7.99	500	Pass
NVNT	ANT1	802.11b	2462.00	8.11	500	Pass
NVNT	ANT1	802.11g	2412.00	16.08	500	Pass
NVNT	ANT1	802.11g	2437.00	16.22	500	Pass
NVNT	ANT1	802.11g	2462.00	16.19	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	17.41	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.46	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.42	500	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	34.74	500	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	34.70	500	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	35.11	500	Pass



-6dB_Bandwidth_NVNT_ANT1_802_11b_2412




-6dB_Bandwidth_NVNT_ANT1_802_11b_2437



-6dB_Bandwidth_NVNT_ANT1_802_11g_2412





-6dB_Bandwidth_NVNT_ANT1_802_11g_2462






-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412



-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437











2. 99% Occupied Bandwidth




Condition	Antenna	Modulation	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	802.11b	2412.00	12.785
NVNT	ANT1	802.11b	2437.00	12.765
NVNT	ANT1	802.11b	2462.00	12.786
NVNT	ANT1	802.11g	2412.00	16.496
NVNT	ANT1	802.11g	2437.00	16.479
NVNT	ANT1	802.11g	2462.00	16.512
NVNT	ANT1	802.11n(HT20)	2412.00	17.591
NVNT	ANT1	802.11n(HT20)	2437.00	17.593
NVNT	ANT1	802.11n(HT20)	2462.00	17.593
NVNT	ANT1	802.11n(HT40)	2422.00	35.980
NVNT	ANT1	802.11n(HT40)	2437.00	36.016
NVNT	ANT1	802.11n(HT40)	2452.00	36.003


99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2437









99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412





99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462



99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT40)_2422




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT40)_2452




3. Duty Cycle

Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	99.08	0.00
NVNT	ANT1	802.11b	2437.00	98.62	0.00
NVNT	ANT1	802.11b	2462.00	99.08	0.00
NVNT	ANT1	802.11g	2412.00	84.62	0.73
NVNT	ANT1	802.11g	2437.00	83.33	0.79
NVNT	ANT1	802.11g	2462.00	84.62	0.73
NVNT	ANT1	802.11n(HT20)	2412.00	75.00	1.25
NVNT	ANT1	802.11n(HT20)	2437.00	75.00	1.25
NVNT	ANT1	802.11n(HT20)	2462.00	72.73	1.38
NVNT	ANT1	802.11n(HT40)	2422.00	75.00	1.25
NVNT	ANT1	802.11n(HT40)	2437.00	75.00	1.25
NVNT	ANT1	802.11n(HT40)	2452.00	75.00	1.25


Duty_Cycle_NVNT_ANT1_802_11b_2412




Duty_Cycle_NVNT_ANT1_802_11b_2437




Duty_Cycle_NVNT_ANT1_802_11b_2462





Duty_Cycle_NVNT_ANT1_802_11g_2412





Duty_Cycle_NVNT_ANT1_802_11g_2437





Duty_Cycle_NVNT_ANT1_802_11g_2462




Duty_Cycle_NVNT_ANT1_802_11n(HT20)_2437



Duty_Cycle_NVNT_ANT1_802_11n(HT40)_2422



Duty_Cycle_NVNT_ANT1_802_11n(HT40)_2452




4. MAX. Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	N/A	8.93	30	Pass
NVNT	ANT1	802.11b	2437.00	N/A	8.83	30	Pass
NVNT	ANT1	802.11b	2462.00	N/A	8.40	30	Pass
NVNT	ANT1	802.11g	2412.00	N/A	7.22	30	Pass
NVNT	ANT1	802.11g	2437.00	N/A	7.08	30	Pass
NVNT	ANT1	802.11g	2462.00	N/A	7.51	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	N/A	6.68	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	N/A	6.38	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	N/A	6.00	30	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	N/A	5.81	30	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	N/A	5.70	30	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	N/A	5.66	30	Pass

5. Power Spectral Density

Condition	Antenna	Modulation	Frequency (MHz)	SA_PSD(dBm/30kHz)	Duty factor(dB)	RB factor(dB)	PSD(dBm/3kHz)	limit(dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	-7.37	N/A	-10.00	-17.37	8	Pass
NVNT	ANT1	802.11b	2437.00	-7.75	N/A	-10.00	-17.75	8	Pass
NVNT	ANT1	802.11b	2462.00	-7.21	N/A	-10.00	-17.21	8	Pass
NVNT	ANT1	802.11g	2412.00	-15.32	N/A	-10.00	-25.32	8	Pass
NVNT	ANT1	802.11g	2437.00	-15.54	N/A	-10.00	-25.54	8	Pass
NVNT	ANT1	802.11g	2462.00	-15.16	N/A	-10.00	-25.16	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	-17.10	N/A	-10.00	-27.10	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-17.47	N/A	-10.00	-27.47	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-15.73	N/A	-10.00	-25.73	8	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	-17.20	N/A	-10.00	-27.20	8	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	-19.24	N/A	-10.00	-29.24	8	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	-18.80	N/A	-10.00	-28.80	8	Pass

Power_Spectral_Density_NVNT_ANT1_802_11b_2412





Power_Spectral_Density_NVNT_ANT1_802_11b_2437





Power_Spectral_Density_NVNT_ANT1_802_11b_2462





Power_Spectral_Density_NVNT_ANT1_802_11g_2412





Power_Spectral_Density_NVNT_ANT1_802_11g_2462




Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2437



Power_Spectral_Density_NVNT_ANT1_802_11n(HT40)_2422




Power_Spectral_Density_NVNT_ANT1_802_11n(HT40)_2452





6. Bandedge

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2399.264	-3.382	-54.900	-23.382	Pass
NVNT	ANT1	802.11b	2462.00	2485.600	-3.415	-58.069	-23.415	Pass
NVNT	ANT1	802.11g	2412.00	2384.704	-10.246	-62.687	-30.246	Pass
NVNT	ANT1	802.11g	2462.00	2492.656	-10.932	-62.764	-30.932	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2378.432	-12.748	-63.467	-32.748	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2498.224	-12.086	-61.740	-32.086	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	2398.308	-14.029	-63.586	-34.029	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	2487.692	-13.539	-62.999	-33.539	Pass

1_Reference_Level_NVNT_ANT1_802_11b_2412




2_Bandedge_NVNT_ANT1_802_11b_2412




2_Bandedge_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Bandedge_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Bandedge_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2422




2_Bandedge_NVNT_ANT1_802_11n(HT40)_2422



1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2452




2_Bandedge_NVNT_ANT1_802_11n(HT40)_2452





7. Spurious Emission



Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	24887.635	-3.382	-51.143	-23.382	Pass
NVNT	ANT1	802.11b	2437.00	25000.000	-3.656	-50.889	-23.656	Pass
NVNT	ANT1	802.11b	2462.00	24525.570	-3.415	-47.276	-23.415	Pass
NVNT	ANT1	802.11g	2412.00	24460.648	-10.246	-52.787	-30.246	Pass
NVNT	ANT1	802.11g	2437.00	24975.030	-11.379	-53.776	-31.379	Pass
NVNT	ANT1	802.11g	2462.00	24970.036	-10.932	-56.789	-30.932	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	24987.515	-12.748	-54.787	-32.748	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24528.067	-13.177	-55.695	-33.177	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	24990.012	-12.086	-55.230	-32.086	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	24972.533	-14.029	-57.589	-34.029	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	24960.048	-14.495	-57.784	-34.495	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	24458.151	-13.539	-57.613	-33.539	Pass


1_Reference_Level_NVNT_ANT1_802_11b_2412




2_Spurious_Emission_NVNT_ANT1_802_11b_2412











1_Reference_Level_NVNT_ANT1_802_11g_2412





2_Spurious_Emission_NVNT_ANT1_802_11g_2412




2_Spurious_Emission_NVNT_ANT1_802_11g_2437







2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2437




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2422




2_Spurious_Emission_NVNT_ANT1_802_11n(HT40)_2422




1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT40)_2437



1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2452



2_Spurious_Emission_NVNT_ANT1_802_11n(HT40)_2452



***** End of Report *****