



TEST REPORT

Application No.: BTEK231024009AE
Applicant: Shenzhen Haijixing Technology Co., Ltd
Address of Applicant: 2/F, No. 97 of Tianwan Road, Tianliao Community, Guangming New District, Shenzhen, China
Manufacturer: Shenzhen Haijixing Technology Co., Ltd
Address of Manufacturer: 2/F, No. 97 of Tianwan Road, Tianliao Community, Guangming New District, Shenzhen, China
Factory: Shenzhen Haijixing Technology Co., Ltd
Address of Factory: 2/F, No. 97 of Tianwan Road, Tianliao Community, Guangming New District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Digital Camera
Model No.: WD05
Trade Mark: NA
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2023-10-24
Date of Test: 2023-10-24 to 2023-11-10
Date of Issue: 2023-11-10

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Damon Su

Damon Su
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-11-10		Original

Authorized for issue by			
			
		Carl Yang /Project Engineer	
			
		Keven Tan /Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Average Output Power		ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location.....	7
4.5 Deviation from Standards.....	7
4.6 Abnormalities from Standard Conditions	7
5 Equipment List.....	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description.....	11
7.1.3 Test Setup Diagram.....	12
7.1.4 Measurement Procedure and Data.....	12
7.2 Conducted Average Output Power	15
7.2.1 E.U.T. Operation	15
7.2.2 Test Mode Description.....	15
7.2.3 Test Setup Diagram.....	16
7.2.4 Measurement Procedure and Data.....	16
7.3 Minimum 6dB Bandwidth	17
7.3.1 E.U.T. Operation	17
7.3.2 Test Mode Description.....	17
7.3.3 Test Setup Diagram.....	17
7.3.4 Measurement Procedure and Data.....	17
7.4 Power Spectrum Density.....	18
7.4.1 E.U.T. Operation	18
7.4.2 Test Mode Description.....	18
7.4.3 Test Setup Diagram.....	18
7.4.4 Measurement Procedure and Data.....	18
7.5 Conducted Band Edges Measurement.....	19
7.5.1 E.U.T. Operation	19
7.5.2 Test Mode Description.....	19
7.5.3 Test Setup Diagram.....	20
7.5.4 Measurement Procedure and Data.....	20
7.6 Conducted Spurious Emissions	21
7.6.1 E.U.T. Operation	21
7.6.2 Test Mode Description.....	21
7.6.3 Test Setup Diagram.....	22
7.6.4 Measurement Procedure and Data.....	22



7.7	Radiated Emissions which fall in the restricted bands	23
7.7.1	E.U.T. Operation	23
7.7.2	Test Mode Description	23
7.7.3	Test Setup Diagram	24
7.7.4	Measurement Procedure and Data	24
7.8	Radiated Spurious Emissions (Below 1GHz)	28
7.8.1	E.U.T. Operation	28
7.8.2	Test Mode Description	28
7.8.3	Test Setup Diagram	29
7.8.4	Measurement Procedure and Data	29
7.9	Radiated Spurious Emissions (Above 1GHz)	32
7.9.1	E.U.T. Operation	32
7.9.2	Test Mode Description	32
7.9.3	Test Setup Diagram	33
7.9.4	Measurement Procedure and Data	34
8	Test Setup Photo	40
9	EUT Constructional Details (EUT Photos)	40
10	Appendix	41



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.7V by Rechargeable Lithium-Ion Battery(3000mAh/11.1 Wh) and recharged by usb port.
Cable(s):	NA
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Channel Numbers:	802.11b/g, 802.11n HT20: 11 Channels
Channel Spacing:	5MHz
Antenna Type:	PCB Antenna
Antenna Gain:	1.9dBi
Hardware Version:	WD05_V1.4
Software and Firmware Version:	V1.4
Remark: The information in this section is provided by the applicant or manufacturer, BANTEK is not liable to the accuracy, suitability, reliability or/and integrity of the information.	
Sample No.:	BTEK231024009AE-01

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
adapter	FUSHIGANG	AS1201A0502000USU	--

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	±3.12dB
Conducted Peak Output Power	± 0.75dB
Minimum 6dB Bandwidth	± 3%
Power Spectrum Density	± 2.84dB
Conducted Band Edges Measurement	± 0.75dB
Conducted Spurious Emissions	± 0.75dB
Radiated Emissions which fall in the restricted bands	±5.08dB (1GHz-6GHz);±5.14dB(above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	±5.06dB (3m); ±4.46dB (10m)
Radiated Spurious Emissions (Above 1GHz)	±5.08dB (1GHz-6GHz);±5.14dB(above 6GHz)



4.4 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.,

A5&A6, Building B1&B2, No.45 Gangtuo Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518103

Tel: 0755-2334 4200

Fax: 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Shielding Room	YIHENG EN ELECTRONIC	9*5*3.3	YH-BT-220304-04	2022-03-03	2025-03-02
EMI Test Receiver	Rohde&Schwarz	ESCI	101021	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	N/A	N/A
LISN	Rohde&Schwarz	ENV216	101472	2023-06-12	2024-06-11
LISN	Schwarzbeck	NSLK 8128	05127	2023-06-12	2024-06-11

RF Conducted					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Shielding Room	YIHENG EN ELECTRONIC	5.5*3.1*3	YH-BT-220304-03	2022-03-03	2025-03-02
EXA Signal Analyzer	KEYSIGHT	N9020A	MY54230486	2023-06-12	2024-06-11
DC Power Supply	E3632A	E3642A	KR75304416	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-6dB	N/A	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-3dB	N/A	2023-06-12	2024-06-11
RF Control Unit	Techy	TR1029-1	N/A	2023-06-12	2024-06-11
RF Sensor Unit	Techy	TR1029-2	N/A	2023-06-12	2024-06-11
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	141258	2023-06-12	2024-06-11
MXG Vector Signal Generator	Agilent	N5182A	US46240522	2023-06-12	2024-06-11
Programmable Temperature&Humidity Chamber	GRT	GR-HWX1000	GR22051001	2023-06-12	2024-06-11
Measurement Software	TACHOY	RF TestSoft	N/A	N/A	N/A

RSE					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	YIHENG EN ELECTRONIC	966	YH-BT-220304-01	2022-05-06	2025-05-05
EMI Test Receiver	Rohde&Schwarz	ESCI	100694	2023-06-12	2024-06-11
TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	01324	2022-06-15	2025-06-14
Pre-Amplifier	Schwarzbeck	BBV 9745	#180	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	2023-06-12	2024-06-11
EXA Signal Analyzer	Keysight	N9020A	MY54440290	2023-06-12	2024-06-11
Horn Antenna	Schwarzbeck	BBHA 9120D	02695	2022-06-15	2025-06-14
Pre-Amplifier	Tonscend	TAP0118045	AP20K806109	2023-06-12	2024-06-11
Horn Antenna	SCHWARZBECK	BBHA9170	1157	2022-06-15	2025-06-14
Low Noise Pre-amplifier	SKET	LNPA-1840G-	SK2022032902	2023-06-12	2024-06-11





		50			
Signal analyzer	ROHDE&SCHWARZ	FSQ40	100010	2023-06-12	2024-06-11
Loop Antenna	ETS	6502	00201177	2022-06-15	2025-06-14

General used equipment					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Humidity/Temperature/B arometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11
Humidity/Temperature/B arometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.


15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.9Bi.

Please refer to internal photos.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.2 °C

Humidity: 60.5 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
--------------------------	--------------	-------------

Final test	01
------------	----

Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $\text{LISN} = \text{Read Level} + \text{Cable Loss} + \text{LISN Factor}$




Test Mode: 01; Line: Live line; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	30.48	19.74	50.22	66.00	-15.78	QP	P	
2	0.1500	14.22	19.74	33.96	56.00	-22.04	AVG	P	
3	0.3428	10.02	19.82	29.84	49.14	-19.30	AVG	P	
4	0.3435	21.24	19.82	41.06	59.12	-18.06	QP	P	
5	0.6090	9.68	19.87	29.55	46.00	-16.45	AVG	P	
6	0.6108	21.38	19.87	41.25	56.00	-14.75	QP	P	
7 *	1.1085	23.13	20.02	43.15	56.00	-12.85	QP	P	
8	1.1085	9.39	20.02	29.41	46.00	-16.59	AVG	P	
9	2.7869	18.09	20.17	38.26	56.00	-17.74	QP	P	
10	2.7869	6.44	20.17	26.61	46.00	-19.39	AVG	P	
11	24.8550	19.57	22.61	42.18	60.00	-17.82	QP	P	
12	24.8550	6.90	22.61	29.51	50.00	-20.49	AVG	P	



Test Mode: 01; Line: Neutral Line; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	30.24	19.76	50.00	66.00	-16.00	QP	P	
2	0.1500	13.74	19.76	33.50	56.00	-22.50	AVG	P	
3	0.1725	13.61	19.79	33.40	54.84	-21.44	AVG	P	
4	0.1770	28.93	19.79	48.72	64.63	-15.91	QP	P	
5	0.4875	20.56	19.84	40.40	56.21	-15.81	QP	P	
6	0.4875	10.15	19.84	29.99	46.21	-16.22	AVG	P	
7	0.7350	21.45	19.93	41.38	56.00	-14.62	QP	P	
8	0.7350	8.97	19.93	28.90	46.00	-17.10	AVG	P	
9	1.1265	8.74	20.03	28.77	46.00	-17.23	AVG	P	
10 *	1.1310	22.75	20.03	42.78	56.00	-13.22	QP	P	
11	2.5935	6.70	20.13	26.83	46.00	-19.17	AVG	P	
12	2.6070	19.11	20.13	39.24	56.00	-16.76	QP	P	

Note:

- 1) Pre-scan all modes and recorded the worst case results in this report(Low Channel).
- 2) Level= Reading+ Factor; Margin=Level-limit.



7.2 Conducted Average Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 20.5 °C

Humidity: 50.0 % RH


Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.3 Minimum 6dB Bandwidth

Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥500 kHz


7.3.1 E.U.T. Operation

Operating Environment:			
Temperature:	20.5 °C	Humidity:	50.0 % RH
		Atmospheric Pressure:	1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 20.5 °C


Humidity: 50.0 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 20.5 °C Humidity: 50.0 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20.5 °C

Humidity: 50.0 % RH


Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C

Humidity: 54.3 % RH


Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.99	-30.59	38.40	74.00	-35.60	peak	P
2	2390.000	69.38	-30.49	38.89	74.00	-35.11	peak	P
3	2400.000	79.15	-30.48	48.67	74.00	-25.33	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	67.73	-30.59	37.14	74.00	-36.86	peak	P
2	2390.000	70.33	-30.49	39.84	74.00	-34.16	peak	P
3	2400.000	78.28	-30.48	47.80	74.00	-26.20	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	80.63	-30.39	50.24	74.00	-23.76	peak	P
2	2500.000	71.68	-30.37	41.31	74.00	-32.69	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.63	-30.39	49.24	74.00	-24.76	peak	P
2	2500.000	70.08	-30.37	39.71	74.00	-34.29	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.32	-30.59	37.73	74.00	-36.27	peak	P
2	2390.000	69.84	-30.49	39.35	74.00	-34.65	peak	P
3	2400.000	78.57	-30.48	48.09	74.00	-25.91	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.54	-30.59	37.95	74.00	-36.05	peak	P
2	2390.000	69.92	-30.49	39.43	74.00	-34.57	peak	P
3	2400.000	77.93	-30.48	47.45	74.00	-26.55	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	80.02	-30.39	49.63	74.00	-24.37	peak	P
2	2500.000	70.80	-30.37	40.43	74.00	-33.57	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	80.18	-30.39	49.79	74.00	-24.21	peak	P
2	2500.000	71.23	-30.37	40.86	74.00	-33.14	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.77	-30.59	38.18	74.00	-35.82	peak	P
2	2390.000	69.36	-30.49	38.87	74.00	-35.13	peak	P
3	2400.000	79.33	-30.48	48.85	74.00	-25.15	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	67.10	-30.59	36.51	74.00	-37.49	peak	P
2	2390.000	69.00	-30.49	38.51	74.00	-35.49	peak	P
3	2400.000	77.60	-30.48	47.12	74.00	-26.88	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	80.93	-30.39	50.54	74.00	-23.46	peak	P
2	2500.000	71.62	-30.37	41.25	74.00	-32.75	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.98	-30.39	49.59	74.00	-24.41	peak	P
2	2500.000	71.47	-30.37	41.10	74.00	-32.90	peak	P

Note: Level = Reading level + Factor

Factor= Antenna Factor+ Cable Loss-Preamp Factor



7.8 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C

Humidity: 68.6 % RH


Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.




Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	36.1269	43.56	-17.38	26.18	40.00	-13.82	QP	100	135	P	
2	150.0107	47.33	-16.76	30.57	43.50	-12.93	QP	100	126	P	
3	400.4318	51.78	-15.34	36.44	46.00	-9.56	QP	126	125	P	
4 *	451.1350	56.11	-14.15	41.96	46.00	-4.04	QP	125	123	P	
5	750.1082	44.89	-8.86	36.03	46.00	-9.97	QP	132	100	P	
6 !	900.1472	49.67	-7.96	41.71	46.00	-4.29	QP	200	100	P	



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	37.1550	49.14	-17.19	31.95	40.00	-8.05	QP	125	123	P	
2	150.0107	52.17	-16.76	35.41	43.50	-8.09	QP	126	26	P	
3 !	451.1350	55.21	-14.15	41.06	46.00	-4.94	QP	256	17	P	
4	541.3723	50.64	-12.85	37.79	46.00	-8.21	QP	124	100	P	
5 !	750.1082	51.18	-8.86	42.32	46.00	-3.68	QP	100	100	P	
6 *	900.1472	50.31	-7.96	42.35	46.00	-3.65	QP	128	126	P	

Note:

- 1) Pre-scan all modes and recorded the worst case results in this report (Low Channel).
- 2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3) Level= Reading+ Factor, Margin= Level- Limit, Factor= Antenna Factor Cable Loss-Preamp Factor



7.9 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C

Humidity: 54.3 % RH


Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.843	69.71	-29.16	40.56	74.00	-33.44	peak	P
2	4276.152	67.31	-27.92	39.39	74.00	-34.61	peak	P
3	6084.559	65.87	-26.20	39.67	74.00	-34.33	peak	P
4	8645.289	70.52	-25.82	44.70	74.00	-29.30	peak	P
5	11048.315	68.07	-23.47	44.59	74.00	-29.41	peak	P
6	14217.742	71.18	-20.76	50.42	74.00	-23.58	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2973.791	67.55	-30.26	37.28	74.00	-36.72	peak	P
2	4312.208	68.86	-29.01	39.85	74.00	-34.15	peak	P
3	6353.477	68.25	-26.00	42.25	74.00	-31.75	peak	P
4	8577.057	70.77	-25.27	45.50	74.00	-28.50	peak	P
5	11286.266	67.94	-23.14	44.79	74.00	-29.21	peak	P
6	14955.086	70.27	-19.33	50.94	74.00	-23.06	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.949	69.33	-29.63	39.70	74.00	-34.30	peak	P
2	4277.410	68.25	-28.97	39.28	74.00	-34.72	peak	P
3	6085.027	63.97	-25.43	38.54	74.00	-35.46	peak	P
4	8645.768	70.48	-24.52	45.96	74.00	-28.04	peak	P
5	11048.282	67.79	-23.81	43.98	74.00	-30.02	peak	P
6	14217.648	70.36	-21.93	48.44	74.00	-25.56	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.726	67.79	-29.62	38.17	74.00	-35.83	peak	P
2	4313.776	68.59	-28.17	40.42	74.00	-33.58	peak	P
3	6352.813	67.57	-26.14	41.43	74.00	-32.57	peak	P
4	8576.658	70.27	-26.07	44.20	74.00	-29.80	peak	P
5	11286.503	68.68	-22.37	46.32	74.00	-27.68	peak	P
6	14956.669	71.43	-20.01	51.42	74.00	-22.58	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.276	69.33	-29.89	39.45	74.00	-34.55	peak	P
2	4278.111	68.54	-28.39	40.16	74.00	-33.84	peak	P
3	6085.859	65.60	-24.63	40.96	74.00	-33.04	peak	P
4	8645.649	69.26	-25.97	43.29	74.00	-30.71	peak	P
5	11047.235	67.32	-22.58	44.73	74.00	-29.27	peak	P
6	14218.517	70.50	-20.78	49.72	74.00	-24.28	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.333	67.26	-30.37	36.89	74.00	-37.11	peak	P
2	4312.755	69.28	-29.32	39.96	74.00	-34.04	peak	P
3	6353.852	67.21	-25.00	42.21	74.00	-31.79	peak	P
4	8577.168	68.84	-24.68	44.16	74.00	-29.84	peak	P
5	11286.705	68.57	-23.88	44.69	74.00	-29.31	peak	P
6	14955.744	71.85	-20.21	51.65	74.00	-22.35	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.411	68.68	-30.01	38.68	74.00	-35.32	peak	P
2	4276.315	67.32	-29.11	38.21	74.00	-35.79	peak	P
3	6084.571	65.88	-26.26	39.62	74.00	-34.38	peak	P
4	8646.481	69.78	-24.30	45.48	74.00	-28.52	peak	P
5	11046.911	67.72	-23.77	43.95	74.00	-30.05	peak	P
6	14218.874	71.40	-21.72	49.68	74.00	-24.32	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2974.243	66.19	-29.27	36.92	74.00	-37.08	peak	P
2	4313.341	67.92	-29.79	38.13	74.00	-35.87	peak	P
3	6352.497	66.90	-24.74	42.16	74.00	-31.84	peak	P
4	8576.183	69.73	-25.68	44.06	74.00	-29.94	peak	P
5	11286.493	68.91	-23.94	44.97	74.00	-29.03	peak	P
6	14956.744	71.21	-20.16	51.05	74.00	-22.95	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.385	70.41	-29.37	41.04	74.00	-32.96	peak	P
2	4278.013	68.10	-29.19	38.91	74.00	-35.09	peak	P
3	6085.318	64.73	-25.06	39.66	74.00	-34.34	peak	P
4	8646.648	69.64	-25.37	44.27	74.00	-29.73	peak	P
5	11047.475	67.31	-22.63	44.68	74.00	-29.32	peak	P
6	14217.869	71.58	-20.30	51.28	74.00	-22.72	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.334	67.70	-30.05	37.65	74.00	-36.35	peak	P
2	4313.030	67.87	-28.29	39.58	74.00	-34.42	peak	P
3	6353.770	66.74	-25.43	41.30	74.00	-32.70	peak	P
4	8576.295	68.91	-25.76	43.16	74.00	-30.84	peak	P
5	11286.157	68.45	-23.11	45.34	74.00	-28.66	peak	P
6	14956.138	71.15	-20.82	50.34	74.00	-23.66	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.262	69.36	-29.22	40.14	74.00	-33.86	peak	P
2	4277.631	68.43	-28.41	40.02	74.00	-33.98	peak	P
3	6085.396	64.79	-24.44	40.36	74.00	-33.64	peak	P
4	8646.511	69.19	-25.00	44.19	74.00	-29.81	peak	P
5	11047.839	67.07	-24.39	42.69	74.00	-31.31	peak	P
6	14219.098	69.96	-21.23	48.73	74.00	-25.27	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.761	66.78	-29.04	37.74	74.00	-36.26	peak	P
2	4313.981	68.96	-28.17	40.79	74.00	-33.21	peak	P
3	6352.736	67.20	-24.91	42.28	74.00	-31.72	peak	P
4	8575.826	69.49	-25.08	44.41	74.00	-29.59	peak	P
5	11285.434	67.44	-23.59	43.85	74.00	-30.15	peak	P
6	14956.369	70.65	-21.26	49.39	74.00	-24.61	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.787	70.02	-28.83	41.19	74.00	-32.81	peak	P
2	4276.195	67.63	-29.17	38.46	74.00	-35.54	peak	P
3	6084.641	65.23	-25.11	40.12	74.00	-33.88	peak	P
4	8646.355	69.79	-25.11	44.68	74.00	-29.32	peak	P
5	11046.745	68.77	-24.05	44.72	74.00	-29.28	peak	P
6	14218.250	69.92	-22.03	47.89	74.00	-26.11	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.533	67.84	-28.76	39.07	74.00	-34.93	peak	P
2	4312.567	69.38	-28.72	40.66	74.00	-33.34	peak	P
3	6353.626	68.06	-25.01	43.05	74.00	-30.95	peak	P
4	8576.847	70.59	-26.06	44.53	74.00	-29.47	peak	P
5	11285.687	68.66	-23.32	45.34	74.00	-28.66	peak	P
6	14954.805	70.44	-20.87	49.56	74.00	-24.44	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.765	69.72	-29.94	39.78	74.00	-34.22	peak	P
2	4277.156	67.37	-28.77	38.59	74.00	-35.41	peak	P
3	6085.397	64.72	-25.20	39.51	74.00	-34.49	peak	P
4	8645.603	70.50	-25.20	45.30	74.00	-28.70	peak	P
5	11047.671	67.20	-24.04	43.16	74.00	-30.84	peak	P
6	14218.804	71.27	-22.03	49.24	74.00	-24.76	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2973.817	66.59	-29.66	36.93	74.00	-37.07	peak	P
2	4313.775	68.96	-29.73	39.23	74.00	-34.77	peak	P
3	6353.895	67.59	-24.82	42.77	74.00	-31.23	peak	P
4	8576.317	68.92	-24.28	44.64	74.00	-29.36	peak	P
5	11285.731	67.58	-24.19	43.39	74.00	-30.61	peak	P
6	14955.914	71.15	-20.46	50.69	74.00	-23.31	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.005	69.13	-29.44	39.69	74.00	-34.31	peak	P
2	4277.997	69.14	-29.36	39.78	74.00	-34.22	peak	P
3	6086.267	65.50	-25.00	40.50	74.00	-33.50	peak	P
4	8645.499	69.81	-24.66	45.15	74.00	-28.85	peak	P
5	11047.739	68.28	-22.53	45.75	74.00	-28.25	peak	P
6	14218.670	70.85	-20.80	50.04	74.00	-23.96	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.480	66.45	-30.26	36.19	74.00	-37.81	peak	P
2	4313.019	68.29	-29.19	39.10	74.00	-34.90	peak	P
3	6352.336	67.25	-26.00	41.25	74.00	-32.75	peak	P
4	8576.414	69.28	-25.68	43.60	74.00	-30.40	peak	P
5	11286.745	67.15	-24.20	42.95	74.00	-31.05	peak	P
6	14956.757	71.50	-21.14	50.35	74.00	-23.65	peak	P

Notes:

- 1).Measuring frequencies from 9 KHz~10th harmonic(ex.26GHz),at least have 20dB margin found between lowest internal used/generated frequency to 30 MHz.
- 2).Radiated emissions measured in frequency range from 9 KHz~10th harmonic (ex.26GHz)were made with an instrument using Peak detector mode.
- 3).18-25GHz at least have 20dB margin.No recording in the test report.
- 4) Level=Reading +Factor
Factor= Antenna Factor+ Cable Loss-Preamp Factor



8 Test Setup Photo

Please Refer to appendix – Test Setup Photos for BTEK231024009AE.

9 EUT Constructional Details (EUT Photos)


Please Refer to appendix - External and Internal Photos for BTEK231024009AE







10 Appendix



1. -6dB Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	9.06	500	Pass
NVNT	ANT1	802.11b	2437.00	10.07	500	Pass
NVNT	ANT1	802.11b	2462.00	9.05	500	Pass
NVNT	ANT1	802.11g	2412.00	13.88	500	Pass
NVNT	ANT1	802.11g	2437.00	15.75	500	Pass
NVNT	ANT1	802.11g	2462.00	15.07	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	13.88	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.04	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	15.08	500	Pass











-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437




-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462




2. 99% Occupied Bandwidth


Condition	Antenna	Modulation	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	802.11b	2412.00	12.162
NVNT	ANT1	802.11b	2437.00	13.035
NVNT	ANT1	802.11b	2462.00	12.088
NVNT	ANT1	802.11g	2412.00	16.667
NVNT	ANT1	802.11g	2437.00	17.614
NVNT	ANT1	802.11g	2462.00	16.608
NVNT	ANT1	802.11n(HT20)	2412.00	17.547
NVNT	ANT1	802.11n(HT20)	2437.00	18.311
NVNT	ANT1	802.11n(HT20)	2462.00	17.531




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2462





99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2437






99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437






99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462







3. Duty Cycle



Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	100	0.00
NVNT	ANT1	802.11b	2437.00	100	0.00
NVNT	ANT1	802.11b	2462.00	100	0.00
NVNT	ANT1	802.11g	2412.00	98.59	0.00
NVNT	ANT1	802.11g	2437.00	98.59	0.00
NVNT	ANT1	802.11g	2462.00	98.59	0.00
NVNT	ANT1	802.11n(HT20)	2412.00	98.51	0.00
NVNT	ANT1	802.11n(HT20)	2437.00	98.51	0.00
NVNT	ANT1	802.11n(HT20)	2462.00	99.25	0.00














4. MAX. Output Power



Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	RMS	8.25	0.00	8.25	30	Pass
NVNT	ANT1	802.11b	2437.00	RMS	8.26	0.00	8.26	30	Pass
NVNT	ANT1	802.11b	2462.00	RMS	8.01	0.00	8.01	30	Pass
NVNT	ANT1	802.11g	2412.00	RMS	8.12	0.00	8.12	30	Pass
NVNT	ANT1	802.11g	2437.00	RMS	8.63	0.00	8.63	30	Pass
NVNT	ANT1	802.11g	2462.00	RMS	8.46	0.00	8.46	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	RMS	8.56	0.00	8.56	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	RMS	8.37	0.00	8.37	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	RMS	8.17	0.00	8.17	30	Pass



5. Power Spectral Density

Condition	Antenna	Modulation	Frequency (MHz)	PSD(dBm/30kHz)	Duty factor(dB)	RB factor(dB)	PSD(dBm/3kHz)	limit(dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	-13.86	0.00	-10.00	-23.86	8	
NVNT	ANT1	802.11b	2437.00	-14.26	0.00	-10.00	-24.26	8	
NVNT	ANT1	802.11b	2462.00	-13.98	0.00	-10.00	-23.98	8	
NVNT	ANT1	802.11g	2412.00	-14.84	0.00	-10.00	-24.84	8	
NVNT	ANT1	802.11g	2437.00	-15.26	0.00	-10.00	-25.26	8	
NVNT	ANT1	802.11g	2462.00	-14.54	0.00	-10.00	-24.54	8	
NVNT	ANT1	802.11n(HT20)	2412.00	-14.72	0.00	-10.00	-24.72	8	
NVNT	ANT1	802.11n(HT20)	2437.00	-15.31	0.00	-10.00	-25.31	8	
NVNT	ANT1	802.11n(HT20)	2462.00	-14.62	0.00	-10.00	-24.62	8	











Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2437






Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2462







6. Bandedge



Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_frequency(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2399.040	-49.473	-26.729	Pass
NVNT	ANT1	802.11b	2462.00	2486.992	-60.235	-27.204	Pass
NVNT	ANT1	802.11g	2412.00	2398.368	-47.167	-31.768	Pass
NVNT	ANT1	802.11g	2462.00	2488.048	-55.881	-30.158	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2399.824	-46.873	-31.157	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2483.680	-53.454	-30.297	Pass




















7. Spurious Emission

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_frequency(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	24285.858	-55.137	-26.729	Pass
NVNT	ANT1	802.11b	2437.00	888.968	-36.282	-27.541	Pass
NVNT	ANT1	802.11b	2462.00	24865.162	-55.195	-27.204	Pass
NVNT	ANT1	802.11g	2412.00	24760.288	-59.529	-31.768	Pass
NVNT	ANT1	802.11g	2437.00	24800.240	-59.682	-31.625	Pass
NVNT	ANT1	802.11g	2462.00	24428.187	-53.370	-30.158	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	24752.797	-59.384	-31.157	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24782.761	-53.181	-31.030	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	898.956	-34.068	-30.297	Pass

1 Reference_Level_NVNT_ANT1_802_11b_2412





2_Spurious_Emission_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2437






2_Spurious_Emission_NVNT_ANT1_802_11b_2462



1_Reference_Level_NVNT_ANT1_802_11g_2412







2_Spurious_Emission_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2437









2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2437



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462





- End of the Report -

