



## FCC RF Exposure

EUT Description: digital camera  
ModelNo.: WD08-A  
FCC ID: 2A6Q7-WD08-A  
Equipment type: Portable devices

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numericasimulation, is not required when the corresponding SAR Test Exclusion Thresholdocondition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR testexclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

| TestMode   | Frequency(MHz) | Conductedpower (dBm) | Max tune-up(mW) | Min. distance(mm) | Result | limit |
|------------|----------------|----------------------|-----------------|-------------------|--------|-------|
| 802.11b    | 2412           | 4.04                 | 2.54            | 5                 | 0.787  | 3.0   |
| 802.11g    | 2437           | 4.09                 | 2.56            | 5                 | 0.801  | 3.0   |
| 802.11n 20 | 2462           | 4.05                 | 2.54            | 5                 | 0.797  | 3.0   |

Conclusion: No SAR is required