

TEST REPORT

Product Name : IP Camera
Brand Mark : N/A
Model No. : JY-683-IPC
Extension model : JY-679-IPC, IP TRUCK CAMERA PRO
FCC ID : 2A6VD-JY683IPC
Report Number : BLA-EMC-202204-A6502
Date of Sample Receipt : 2022/4/19
Date of Test : 2022/4/19 to 2022/5/10
Date of Issue : 2022/5/10
Test Standard : 47 CFR Part 1.1307, Part 2.1093, KDB
447498
Test Result : Pass

Prepared for:

Shenzhen LUVIEW Co.,Ltd

**E Building, Huayi Liwei Industrial Park, 308 huanguan Middle Road,
Guanlan,Longhua District, Shenzhen, China, 518110**

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481

Compiled by:

Jozu

Approved by:

Blue Zhong

Review by:

Sueels

Date:

2022/5/10



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/5/10	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	4
2	GENERAL INFORMATION	5
3	GENERAL DESCRIPTION OF E.U.T.	5
4	LABORATORY LOCATION	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1	LIMITS	7
5.2	TEST PROCEDURE	7
5.3	EUT RF EXPOSURE EVALUATION	8

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	Pass

2 GENERAL INFORMATION

Applicant	Shenzhen LUVIEW Co.,Ltd
Address	E Building, Huayi Liwei Industrial Park, 308 huanguan Middle Road, Guanlan,Longhua District, Shenzhen, China, 518110
Manufacturer	Shenzhen LUVIEW Co.,Ltd
Address	E Building, Huayi Liwei Industrial Park, 308 huanguan Middle Road, Guanlan,Longhua District, Shenzhen, China, 518110
Factory	Shenzhen LUVIEW Co.,Ltd
Address	E Building, Huayi Liwei Industrial Park, 308 huanguan Middle Road, Guanlan,Longhua District, Shenzhen, China, 518110
Product Name	IP Camera
Test Model No.	JY-683-IPC
Extension model	JY-679-IPC, IP TRUCK CAMERA PRO
Note	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	676-A0-A
Software Version	V1.6.2_20211224
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Antenna Type:	External Antenna
Antenna Gain:	5dBi(Provided by the applicant)

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 LIMITS

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.2 TEST PROCEDURE

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5.3 EUT RF EXPOSURE EVALUATION

Antenna Gain: 5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.162 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

worse case 802.11b:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
middle	2437	14.859	0.030613	0.019267	1.0	PASS

Note: Refer to report No. BLA-EMC-202204-A6501 for EUT test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation Requirement

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.