

**MEASUREMENT REPORT**  
**FCC PART 15 Subpart C (15.225) NFC**

**Applicant Name:**

BH EVS CO., LTD.  
35, Magokjungang 8-ro 3-gil,  
Gangseo-gu, Seoul,  
07793 Republic of Korea

**Date of Testing:**

2/04/2026 – 2/05/2026

**Test Report Issue Date:**

3/20/2026

**Test Site/Location:**

ELEMENT Lab. Yongin-Si, Gyeonggi-do, South Korea

**Test Report Serial No.:**

1K2512080010-03.2A6WX

**FCC ID:**

**2A6WXWCGMA35AA**

**APPLICANT:**

**BH EVS CO., LTD.**

**Application Type:**

Certification

**Model:**

WCGMA35A

**EUT Type:**

Wireless Charger

**Frequency:**

13.56MHz

**FCC Classification:**

Low Power Communications Device Transmitter (DXX)

**FCC Rule Part(s):**

Part 15 Subpart C (15.225)

**Test Procedure(s):**

ANSI C63.10-2020

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Prepared by



Reviewed by

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 1 of 24                             |

## TABLE OF CONTENTS

|     |                                                           |    |
|-----|-----------------------------------------------------------|----|
| 1.0 | Introduction .....                                        | 3  |
| 1.1 | Scope.....                                                | 3  |
| 1.2 | Element Test Location .....                               | 3  |
| 1.3 | Test Facility / Accreditations .....                      | 3  |
| 2.0 | RODUCT INFORMATION.....                                   | 4  |
| 2.1 | Equipment Description.....                                | 4  |
| 2.2 | Device Capabilities .....                                 | 4  |
| 2.3 | Test Configuration .....                                  | 4  |
| 2.4 | EMI Suppression Device(s)/Modifications.....              | 4  |
| 3.0 | DESCRIPTION OF TEST .....                                 | 5  |
| 3.1 | Evaluation Procedure.....                                 | 5  |
| 3.2 | Radiated Emissions .....                                  | 5  |
| 3.3 | Environmental Conditions .....                            | 5  |
| 4.0 | ANTENNA REQUIREMENTS .....                                | 6  |
| 5.0 | MEASUREMENT UNCERTAINTY .....                             | 7  |
| 6.0 | TEST EQUIPMENT CALIBRATION DATA.....                      | 8  |
| 7.0 | TEST DATA .....                                           | 9  |
| 7.1 | Summary .....                                             | 9  |
| 7.2 | Occupied Bandwidth Measurement .....                      | 10 |
| 7.3 | Frequency Stability Test Data.....                        | 12 |
| 7.4 | In-Band Radiated Spurious Emission Measurements.....      | 15 |
| 7.5 | Radiated Spurious Emission Measurements, Out-of-Band..... | 18 |
| 8.0 | CONCLUSION .....                                          | 24 |

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 2 of 24                             |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory(ies) indicated in Section 1.3 below. All measurement facilities are compliant with the test site requirements specified in ANSI C63.10-2020.

### 1.3 Test Facility / Accreditations

**Measurements were performed at Element Materials Technology Suwon, Ltd. located in Yongin-si, Gyeonggi-do, 16954, South Korea.**

- Element Materials Technology Suwon, Ltd. is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation(A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology Suwon, Ltd. facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 3 of 24                             |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **BH EVS Wireless Charger FCC ID: 2A6WXWCGMA35AA**. The EUT is designed to operate with a DC input voltage of 14 VDC. The test data contained in this report pertains only to the emissions due to the NFC transmitter of the EUT.

### 2.2 Device Capabilities

This device contains the following capabilities:

NFC, WPT

### 2.3 Test Configuration

The EUT was set to continuously transmit at 13.56MHz. This was performed using manufacturer software loaded on the phone to allow for continuous transmission. This device was tested in accordance with the guidance of ANSI C63.10-2020. See Sections 3.2 of this test report for a description of the radiated emissions test setup.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 4 of 24                             |

## 3.0 DESCRIPTION OF TEST

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

### 3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 5 of 24                      |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the EUT are **permanently attached**.
- This unit was tested while powered by an DC power source.

### Conclusion:

The EUT complies with the requirement of §15.203.

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 6 of 24                             |

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2020. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                 | Expanded Uncertainty ( $\pm$ dB) |
|------------------------------|----------------------------------|
| Line Conducted Disturbance   | 3.09                             |
| Radiated Disturbance (<1GHz) | 4.10                             |

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 7 of 24                             |

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer    | Model    | Description                | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-----------------|----------|----------------------------|------------|--------------|------------|---------------|
| Agilent         | N9030A   | PXA Signal Analyzer        | 2025-05-23 | Annual       | 2026-05-22 | MY49432391    |
| Com-Power       | AL-130R  | Active Loop Antenna        | 2024-10-10 | Biennial     | 2026-10-09 | 10160045      |
| ESPEC           | SH-242   | Environmental Chamber      | 2025-09-17 | Annual       | 2026-09-16 | 93011064      |
| Rohde & Schwarz | ESW      | EMI Test Receiver          | 2025-09-15 | Annual       | 2026-09-14 | 103550        |
| Rohde & Schwarz | FSW      | SIGNAL & SPECTRUM Analyzer | 2025-09-15 | Annual       | 2026-09-14 | 103295        |
| Schwarzbeck     | VULB9162 | Broadband TRILOG Antenna   | 2025-06-05 | Biennial     | 2026-06-04 | 9162-217      |

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 8 of 24                             |

## 7.0 TEST DATA

### 7.1 Summary

Company Name: BH EVS CO., LTD.  
 FCC ID: 2A6WXWCGMA35AA  
 FCC Classification: Low Power Communications Device Transmitter (DXX)  
 Frequencies Examined: 13.56MHz

| FCC Part Section(s)  | RSS Section(s) | Test Description              | Test Limit                                                                                                                                                                    | Test Condition      | Test Result | Reference   |
|----------------------|----------------|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-------------|-------------|
| 2.1049               | RSS-Gen [6.7]  | Occupied Bandwidth            | N/A                                                                                                                                                                           | RADIATED            | PASS        | Section 7.2 |
| 15.225 (a)(b)(c)     | RSS-210 [B.6]  | In-Band Emissions             | 15,848µV/m @ 30m<br>13.553 – 13.567 MHz<br><br>334µV/m @ 30m<br>13.410 – 13.553 MHz<br>13.567 – 13.710 MHz<br><br>106µV/m @ 30m<br>13.110 – 13.410 MHz<br>13.710 – 14.010 MHz |                     | PASS        | Section 7.4 |
| 15.225 (d)<br>15.209 | RSS-Gen [8.9]  | Out-of-Band Emissions         | Emissions outside of the specified band (13.110 – 14.010 MHz) must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])                                                |                     | PASS        | Section 7.5 |
| 15.225 (e)           | RSS-210 [B.6]  | Frequency Stability Tolerance | ± 0.01% of Operating Frequency                                                                                                                                                | Temperature Chamber | PASS        | Section 7.3 |

**Table 7-1. Summary of Test Results**

**Note:**

This unit was tested while powered by an DC power source.

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 9 of 24                      |

## 7.2 Occupied Bandwidth Measurement

§2.1049; RSS-Gen (6.6)

### Test Overview and Limit

The occupied bandwidth is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequency.

### Test Procedure Used


ANSI C63.10-2020 – Section 6.9.3

### Test Settings

1. Spectrum analyzer frequency is set to the nominal EUT channel center frequency.
2. RBW = 1 – 5% OBW
3. VBW  $\geq 3 \times$  RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. Using the 99% power bandwidth function of the instrument and report the measured bandwidth.

### Test Notes

None.




**Figure 7-1. Test Instrument & Measurement Setup**

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 10 of 24                            |

| Frequency | Occupied Bandwidth |
|-----------|--------------------|
| 13.56MHz  | 559.31kHz          |

**Table 7-2. Occupied Bandwidth Measurement**



**Figure 7-2. Occupied Bandwidth Plot**

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 11 of 24                     |

### 7.3 Frequency Stability Test Data

§15.225; RSS-210 (B.6)

#### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.10-2020. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -20°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 15.225, the frequency stability of the transmitter shall be maintained within  $\pm 0.01\%$  of the center frequency.***

#### Test Procedure Used

ANSI C63.10-2020 – Section 6.8

#### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -20°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

#### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

#### Test Notes

None.

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 12 of 24                            |

## Frequency Stability Test Data

§15.225; RSS-210 (B.6)

OPERATING FREQUENCY: 13,560,000 Hz  
REFERENCE VOLTAGE: 14.00 VDC

| VOLTAGE (%) | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|-------------|-------------|------------|----------------|-----------------|---------------|
| 85 %        | 11.90       | + 20       | 13,560,018     | -18             | -0.0001327    |
| 100 %       | 14.00       | + 20 (Ref) | 13,560,009     | -9              | -0.0000664    |
| 100 %       |             | - 30       | 13,560,041     | -41             | -0.0003024    |
| 100 %       |             | - 20       | 13,560,022     | -22             | -0.0001622    |
| 100 %       |             | - 10       | 13,560,113     | -113            | -0.0008333    |
| 100 %       |             | 0          | 13,560,006     | -6              | -0.0000442    |
| 100 %       |             | + 10       | 13,560,048     | -48             | -0.0003540    |
| 100 %       |             | + 20       | 13,560,009     | -9              | -0.0000664    |
| 100 %       |             | + 30       | 13,560,128     | -128            | -0.0009440    |
| 100 %       |             | + 40       | 13,560,066     | -66             | -0.0004867    |
| 100 %       |             | + 50       | 13,560,073     | -73             | -0.0005383    |
| 115 %       | 16.10       | + 20       | 13,560,029     | -29             | -0.0002139    |

Table 7-3. Frequency Stability Test Data

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 13 of 24                     |

## Frequency Stability Test Data

§15.225; RSS-210 (B.6)




Figure 7-3. Frequency Stability Plot

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 14 of 24                     |

## 7.4 In-Band Radiated Spurious Emission Measurements

§15.225(a)(b)(c); RSS-210 (B.6)

### Test Overview and Limit

The EUT was tested from 13.110 – 14.010 MHz. All in-band radiated spurious emissions are measured with a spectrum analyzer connected to a loop antenna while the EUT is operating at appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All in-band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table 7-4.***

| Frequency [MHz]                            | Field Strength [ $\mu$ V/m] | Measured Distance [Meters] |
|--------------------------------------------|-----------------------------|----------------------------|
| 13.553-13.567 MHz                          | 15,848                      | 30                         |
| 13.410-13.553 MHz and<br>13.567-13.710 MHz | 334                         | 30                         |
| 13.110-13.410 MHz and<br>13.710-14.010 MHz | 106                         | 30                         |

**Table 7-4. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2020 – Section 6.4.7


### Test Settings

1. RBW = 9kHz
2. VBW  $\geq 3 \times$  RBW
3. Detector = peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 15 of 24                     |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Radiated Test Setup**

## Test Notes:

1. All emissions lying in restricted bands specified in §15.225 and RSS-210 are below the limit shown in Table 7-4.
2. All measurements were performed using a loop antenna. The antenna was positioned in three orthogonal positions (X front, Y side, Z top) and the position with the highest emission level was recorded.
3. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
4. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2). Extrapolation Factor =  $20 \log_{10}(30/3)^2 = 40\text{dB}$ .
5. The spectrum was investigated from 9kHz up to 30MHz using the loop antenna. Only the emissions shown in the table below were found to be significant.
6. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

## Sample Calculation

- Field Strength Level  $[\text{dB}\mu\text{V/m}] = \text{Analyzer Level} [\text{dBm}] + 107 + \text{AFCL} [\text{dB/m}]$
- $\text{AFCL} [\text{dB/m}] = \text{Antenna Factor} [\text{dB/m}] + \text{Cable Loss} [\text{dB}]$
- $\text{Margin} [\text{dB}] = \text{Field Strength Level} [\text{dB}\mu\text{V/m}] - \text{Limit} [\text{dB}\mu\text{V/m}]$

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 16 of 24                     |

## In-Band Radiated Spurious Emission Measurements

§15.225(a)(b)(c); RSS-210 (B.6)

Frequency: 13.56MHz

Measurement Distance: 3 Meters

| Frequency [MHz] | Ant. Pol. [X/Y/Z] | Antenna Height [cm] | Turntable Azimuth [degree] | Level [dBm] | AFCL [dB/m] | 3m Field Strength [dBµV/m] | 30m Field Strength [dBµV/m] | Limit [µV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|-------------------|---------------------|----------------------------|-------------|-------------|----------------------------|-----------------------------|--------------|----------------|-------------|
| 13.143          | X                 | 100                 | 234                        | -79.22      | 13.27       | 41.05                      | 1.05                        | 106.00       | 40.51          | -39.45      |
| 13.226          | X                 | 100                 | 234                        | -79.34      | 13.26       | 40.92                      | 0.92                        | 106.00       | 40.51          | -39.59      |
| 13.389          | X                 | 100                 | 234                        | -78.65      | 13.23       | 41.58                      | 1.58                        | 106.00       | 40.51          | -38.92      |
| 13.547          | X                 | 100                 | 234                        | -69.28      | 13.21       | 50.93                      | 10.93                       | 334.00       | 50.47          | -39.55      |
| 13.562          | X                 | 100                 | 234                        | -68.67      | 13.20       | 51.53                      | 11.53                       | 15848.00     | 84.00          | -72.46      |
| 13.579          | X                 | 100                 | 234                        | -69.37      | 13.20       | 50.83                      | 10.83                       | 334.00       | 50.47          | -39.64      |
| 13.718          | X                 | 100                 | 234                        | -79.00      | 13.18       | 41.18                      | 1.18                        | 106.00       | 40.51          | -39.33      |

**Table 7-5. In-Band Radiated Measurements**

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 17 of 24                     |

## 7.5 Radiated Spurious Emission Measurements, Out-of-Band

§15.209 §15.225(d); RSS-Gen (8.9)

### Test Overview and Limit

The EUT was tested from 9kHz up to the 1GHz excluding the band 13.110 – 14.010 MHz.

***All out-of-band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table 7-6 per Section 15.209.***

| Frequency         | Field Strength<br>[μV/m] | Measured Distance<br>[Meters] |
|-------------------|--------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)             | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)            | 30                            |
| 1.705 – 30.00 MHz | 30                       | 30                            |
| 30.00 – 88.00 MHz | 100                      | 3                             |
| 88.00 – 216.0 MHz | 150                      | 3                             |
| 216.0 – 960.0 MHz | 200                      | 3                             |
| Above 960.0 MHz   | 500                      | 3                             |

**Table 7-6. Radiated Limits – Out of band**

### Test Procedures Used

ANSI C63.10-2020 – Section 6.5.4


### Test Settings

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 9kHz for emissions below 30MHz and 100kHz for emissions between 30MHz and 1GHz
3. VBW ≥ 3 x RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 18 of 24                     |

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup < 30MHz**



**Figure 7-6. Radiated Test Setup > 30MHz**

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 19 of 24                            |

### Test Notes:

1. A loop antenna was used to investigate emissions below 30MHz.
2. Both Vertical and Horizontal polarities of the receive antenna were evaluated with the worst case emissions being reported. Below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
4. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
5. No spurious emissions levels were found to be greater than the level of the fundamental.
6. The "-" shown in the following RSE tables are used to denote a noise floor measurement.


### Sample Calculation

- Field Strength Level  $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 20 of 24                            |

## Radiated Spurious Emission Measurements, Out-of-Band


§15.209 §15.225(d); RSS-Gen (8.9)



Plot 7-1. Radiated Spurious Plot 9kHz – 30MHz (Pol. X)




Plot 7-2. Radiated Spurious Plot 9kHz – 30MHz (Pol. Y)



Plot 7-3. Radiated Spurious Plot 9kHz – 30MHz (Pol. Z)

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 21 of 24                     |



Plot 7-4. Radiated Spurious Plot 30MHz – 1GHz

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 22 of 24                            |

# Radiated Spurious Emission Measurements, Out-of-Band §15.209 §15.225(d); RSS-Gen (8.9)

Tx Frequency 13.56MHz

Measurement Distance: 3 Meters

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level [dBm] | AFCL [dB/m] | 3m Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|-------------|-------------|----------------------------|----------------|-------------|
| 27.12           | H               | -                   | -                          | -82.17      | 11.50       | 36.33                      | 69.54          | -33.21      |
| 40.68           | H               | 109                 | 180                        | -101.73     | 19.75       | 25.02                      | 40.00          | -14.98      |
| 54.24           | H               | -                   | -                          | -107.34     | 19.98       | 19.64                      | 40.00          | -20.36      |
| 67.80           | H               | 105                 | 174                        | -97.57      | 17.18       | 26.61                      | 40.00          | -13.39      |
| 81.36           | H               | 100                 | 173                        | -100.69     | 13.85       | 20.16                      | 40.00          | -19.84      |
| 94.92           | H               | -                   | -                          | -105.71     | 18.05       | 19.34                      | 43.52          | -24.18      |
| 108.48          | H               | -                   | -                          | -105.83     | 18.07       | 19.24                      | 43.52          | -24.28      |
| 122.04          | H               | -                   | -                          | -106.17     | 16.06       | 16.89                      | 43.52          | -26.63      |
| 135.60          | H               | 126                 | 127                        | -97.46      | 15.15       | 24.69                      | 43.52          | -18.83      |
| 149.16          | H               | 120                 | 133                        | -102.07     | 14.95       | 19.88                      | 43.52          | -23.64      |
| 162.72          | H               | 122                 | 127                        | -103.72     | 15.70       | 18.98                      | 43.52          | -24.54      |
| 203.40          | H               | 120                 | 125                        | -101.47     | 16.07       | 21.60                      | 43.52          | -21.93      |
| 216.96          | H               | 110                 | 112                        | -95.30      | 17.63       | 29.33                      | 46.02          | -16.69      |
| 230.52          | H               | 124                 | 101                        | -99.51      | 18.04       | 25.53                      | 46.02          | -20.49      |
| 447.48          | H               | 125                 | 120                        | -104.75     | 18.32       | 20.57                      | 46.02          | -25.45      |
| 596.64          | H               | 124                 | 165                        | -99.94      | 19.09       | 26.15                      | 46.02          | -19.87      |
| 732.24          | H               | 119                 | 132                        | -103.68     | 19.66       | 22.98                      | 46.02          | -23.04      |

**Table 7-7. Radiated Measurements**

|                                           |                                                                                     |                                                                                                                                                                                                                  |                            |                                   |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------|
| FCC ID:<br>2A6WXWCGMA35AA                 |  | Test Dates: 2/04/2026 – 2/05/2026                                                                                                                                                                                | EUT Type: Wireless Charger | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                            | Page 23 of 24                     |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **BH EVS Wireless Charger FCC ID: 2A6WXWCGMA35AA** has been tested to show compliance with Part 15 Subpart C (15.225) of the FCC Rules and RSS-210 of the ISED Rules.

|                                                  |                                                                                     |                                                                                                                                                                                                                  |                                   |                                          |
|--------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------|
| <b>FCC ID:</b><br>2A6WXWCGMA35AA                 |  | <b>Test Dates:</b> 2/04/2026 – 2/05/2026                                                                                                                                                                         | <b>EUT Type:</b> Wireless Charger | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1K2512080010-03.2A6WX |  | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo. |                                   | Page 24 of 24                            |