

APPENDIX A: RF EXPOSURE TEST PLOTS

Plot A-1 Verification Test Data

cDASY6 Module WPT Measurement Report

Device under test

Info:
85kHz Verification

Serial number:
1031

Scenario:
85kHz Verification

Tool info

DASY software version:
cDASY6 Module WPT 2.8.0.5184

Probe model, serial no. and configuration date:
MAGPy-0H3D+E3Dv2, WP000261, 2024/08/14

Software version:
2.8.8, backend: 2.2.36

Scan info

Center location:
x: -7.08 mm, y: -125.20 mm, z: 50.22 mm

Dimensions:
x: 433.0 mm, y: 520.0 mm, z: 36.7 mm

Resolution:
x: 7.33 mm, y: 7.33 mm, z: 7.33 mm

Completed on:
2025/03/18 13:32:20

Measurement results

Maximum H-field [RMS]:
MAGNITUDE: 127.21 A/m
x: 105.22 A/m, y: 31.03 A/m, z: 64.41 A/m

Maximum H-field location relative to DUT:
x: 84.33 mm, y: 99.00 mm, z: 8.50 mm


Maximum E-field [RMS]:
MAGNITUDE: 127.51 V/m
x: 6.63 V/m, y: 5.61 V/m, z: 127.21 V/m

Maximum E-field location relative to DUT:
x: 14.67 mm, y: -176.00 mm, z: 0.00 mm


Distance to -20.0 dB boundary:
66.41 mm

Offset relative to DUT:
x: 0.00 m, y: 0.00 m, z: 1.00 mm

H-field magnitude [RMS] at center location



H-field magnitude [RMS] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 85.00 kHz, $\sigma = 0.750$ S/m, tissue density = 1,000 kg/m³)

Distance [mm]	Peak incident fields [RMS]		Peak E _{ind} [V/m, RMS]			Peak J _{ind} [A/m ² , RMS]		psSAR [mW/kg]		H-field extent		Warnings	
	H _{inc} [A/m]	E _{inc} [V/m]	Cube avg.	Local	Line avg.	Surface avg.	1g avg.	10g avg.		-20 dB radius [mm]	Sign	Vector potential	Boundary effect
0.00	205	128	3.29	3.33	3.34	2.31	6.28	4.67		181	2%	108%	32%
2.00	185	117	3.10	3.13	3.14	2.18	5.62	4.23		184	2%	108%	33%

Compliance evaluation (Field values at the peak frequency) (f=85.00 kHz, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	PH _{inc}	PE _{inc}	PE _{ind}	psSAR	PH _{inc}	PE _{inc}	PJ _{ind}	psSAR	PH _{inc}	PE _{inc}	PE _{ind}	psSAR	PH _{inc}	PE _{inc}	PE _{ind}	psSAR	PH _{inc}	PE _{inc}	PE _{ind}	psSAR
0.00	205	128	3.30	4.67	205	128	2.32	4.67	205	128	3.34	4.67	205	128	N/A	6.28	205	128	3.33	6.28
2.00	185	117	3.10	4.23	185	117	2.18	4.23	185	117	3.14	4.23	185	117	N/A	5.62	185	117	3.14	5.62

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	PH _{inc}	PE _{inc}	PE _{ind}	psSAR	PH _{inc}	PE _{inc}	PJ _{ind}	psSAR	PH _{inc}	PE _{inc}	PE _{ind}	psSAR	PH _{inc}	PE _{inc}	PE _{ind}	psSAR	PH _{inc}	PE _{inc}	PE _{ind}	psSAR
0.00	9.74	N/A	3.78	N/A	0.29	N/A	40.9	3.22	13.6	N/A	1.26	N/A	0.51	N/A	0.19	N/A	2.27	2.33	N/A	N/A
2.00	8.79	N/A	3.47	N/A	0.27	N/A	36.9	2.95	12.9	N/A	1.13	N/A	0.47	N/A	0.18	N/A	2.05	2.14	N/A	N/A

Document generated at 2025/03/18 13:44:53, simulation performed at 2025/03/18 13:41:49 using Sim4Life version 8.0.1.15737

1 / 1

FCC ID: 2A6WXCNIS31S		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 3/18/2025 – 3/28/2025	Apparatus/Device: Wireless Charger		APPENDIX A: Page 1 of 3

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Plot A-2 Worst Case Test Data

cDASY6 Module WPT Measurement Report

Device under test	Tool info	Scan info
Info: 2A6WXWCNIS31S	DASY software version: cDASY6 Module WPT 2.8.0.5184	Center location: x: 17.69 mm, y: -144.66 mm, z: 78.92 mm
Serial number: Sample 1	Probe model, serial no. and configuration date: MAGPy-8H3D+E3Dv2, WP000261, 2024/08/14	Dimensions: x: 124.7 mm, y: 125.0 mm, z: 36.6 mm
Scenario: Standby (Ping) Signal Front Side	Software version: 2.8.8, backend: 2.2.36	Resolution: x: 7.33 mm, y: 7.33 mm, z: 7.33 mm
		Completed on: 2025/03/19 12:04:44

Measurement results

Maximum H-field [rms]:
MAGNITUDE: 101.75 A/m
x: 13.98 A/m, y: 15.52 A/m, z: 99.58 A/m

Maximum H-field location relative to DUT:
x: -3.63 mm, y: -3.63 mm, z: 8.50 mm


Maximum E-field [rms]:
MAGNITUDE: 49.91 V/m
x: 2.39 V/m, y: 60.72 mV/m, z: 49.85 V/m

Maximum E-field location relative to DUT:
x: 7.37 mm, y: 33.33 μ m, z: 0.00 m


Distance to -20.0 dB boundary:
26.44 mm

Offset relative to DUT:
x: 36.70 mm, y: 36.70 mm, z: 1.00 mm

H-field magnitude [rms] at center location



H-field magnitude [rms] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 81.81 kHz, $\sigma = 0.750$ S/m, tissue density = 1,000 kg/m³)

	Peak incident fields [E_{rms}]		Peak E_{ind} [V/m, E_{rms}]			Peak J_{ind} [A/m^2 , E_{rms}]	psSAR [mW/kg]		H-field extent			Warnings
Distance [mm]	H_{inc} [A/m]	E_{inc} [V/m]	Cube avg.	Local	Line avg.	Surface avg.	1g avg.	10g avg.	-20 dB radius [mm]	Sign	Vector potential	Boundary effect
0.00	230	49.9	0.529	0.550	0.545	0.310	0.0869	0.0355	29.9	3%	11%	8%
2.00	199	44.2	0.433	0.451	0.451	0.248	0.0556	0.0229	29.8	3%	11%	9%

Compliance evaluation (Field values at the peak frequency) (f = 81.81 kHz, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL [rms]	BR [rms]	RL [rms]	BR [rms]	ERL [rms]	DRL [rms]	MPE [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[A/m ²]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]
0.00	230	49.9	0.530	0.0355	230	49.9	0.311	0.0355	230	49.9	0.546	0.0355	230	49.9	N/A	0.0869	230	49.9	0.551	0.0869
2.00	199	44.2	0.434	0.0229	199	44.2	0.248	0.0229	199	44.2	0.452	0.0229	199	44.2	N/A	0.0556	199	44.2	0.452	0.0556

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL	BR	RL	BR	ERL	DRL	MPE	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH
0.00	10.9	N/A	16.6	N/A	0.05	N/A	46.0	26.9	2.04	N/A	1.41	N/A	2.24	N/A	0.03	N/A	2.55	5.55	N/A	N/A
2.00	9.48	N/A	14.7	N/A	0.04	N/A	39.8	23.9	1.64	N/A	1.22	N/A	1.99	N/A	0.03	N/A	2.21	4.91	N/A	N/A

Document generated at 2025/04/14 12:06:07, simulation performed at 2025/04/14 12:06:02 using Sim4Life version 8.0.1.15737

1/1

FCC ID: 2A6WXWCNIS31S		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 3/18/2025 – 3/28/2025	Apparatus/Device: Wireless Charger		APPENDIX A: Page 2 of 3

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Plot A-2 Worst Case Test Data at 15cm

cDASY6 Module WPT Measurement Report

Device under test

Info:
2A6WXCNIS31S

Serial number:
Sample 1

Scenario:
Standby (Ping) Signal Front Side

Tool info

DASY software version:
cDASY6 Module WPT 2.8.0.5184

Probe model, serial no. and configuration date:
MAGPy-8H3D+E3Dv2, WP000261, 2024/08/14

Software version:
2.8.8, backend: 2.2.36

Scan info

Center location:
x: 13.05 mm, y: -143.37 mm, z: 228.57 mm

Dimensions:
x: 124.6 mm, y: 124.0 mm, z: 37.0 mm

Resolution:
x: 7.33 mm, y: 7.33 mm, z: 7.33 mm

Completed on:
2025/03/20 15:53:45

Measurement results

Maximum H-field [RMS]:
MAGNITUDE: 183.05 mA/m
x: 130.38 mA/m, y: 45.15 mA/m, z: 120.29 mA/m

Maximum H-field location relative to DUT:
x: -3.63 mm, y: 40.37 mm, z: 195.17 mm


Maximum E-field [RMS]:
MAGNITUDE: 294.16 mV/m
x: 50.48 mV/m, y: 169.22 mV/m, z: 235.26 mV/m

Maximum E-field location relative to DUT:
x: -43.97 mm, y: 7.37 mm, z: 0.00 m


Distance to -20.0 dB boundary:
NaN

Offset relative to DUT:
x: 36.70 mm, y: 36.70 mm, z: 151.00 mm

H-field magnitude [RMS] at center location



H-field magnitude [RMS] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 82.88 kHz, $\sigma = 0.750$ S/m, tissue density = 1,000 kg/m³)

Distance [mm]	Peak incident fields [<i>RMS</i>]		Peak <i>E</i> _{ind} [V/m, <i>RMS</i>]			Peak <i>J</i> _{ind} [A/m ² , <i>RMS</i>]		psSAR [mW/kg]		H-field extent	Sign	Vector potential	Warnings
	<i>H</i> _{inc} [A/m]	<i>E</i> _{inc} [V/m]	Cube avg.	Local	Line avg.	Surface avg.	1g avg.	10g avg.	-20 dB radius [mm]	Boundary effect			
150	0.332	0.294	1.44e-3	1.48e-3	1.48e-3	9.49e-4	9.91e-7	6.46e-7	68.0	73%	217%	100%	
152	0.245	0.278	1.32e-3	1.35e-3	1.35e-3	8.89e-4	8.95e-7	6.03e-7	69.5	73%	217%	100%	

Compliance evaluation (Field values at the peak frequency) (f = 82.88 kHz, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
150	0.332	0.294	1.45e-3	6.46e-7	0.332	0.294	9.54e-4	6.46e-7	0.332	0.294	1.49e-3	6.46e-7	0.332	0.294	N/A	9.91e-7	0.332	0.294	1.49e-3	9.91e-7
152	0.245	0.278	1.33e-3	6.03e-7	0.245	0.278	8.94e-4	6.03e-7	0.245	0.278	1.35e-3	6.03e-7	0.245	0.278	N/A	8.95e-7	0.245	0.278	1.36e-3	8.95e-7

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
150	0.02	N/A	0.16	N/A	<0.01	N/A	0.07	0.24	<0.01	N/A	<0.01	N/A	<0.01	0.05	N/A	N/A	<0.01	N/A	0.16	N/A
152	0.01	N/A	0.15	N/A	<0.01	N/A	0.05	0.22	<0.01	N/A	<0.01	N/A	<0.01	0.05	N/A	N/A	<0.01	N/A	0.15	N/A

Document generated at 2025/04/14 11:02:13, simulation performed at 2025/04/14 11:01:44 using Sim4Life version 8.0.1.15737

1/1

FCC ID: 2A6WXCNIS31S		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 3/18/2025 – 3/28/2025	Apparatus/Device: Wireless Charger		APPENDIX A: Page 3 of 3

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.