



Choose Scandinavian trust

RF Exposure Compliance – MPE Calculation Report

Applicant company:	Trellisware Technologies
Model number (HVIN):	TW-750W
Product:	802.11a/b/g/n/ac Module with Bluetooth 5.0
FCC Identification:	FCC ID: 2A6X2-750W
ISED certification number:	IC: 28565-750W
Product type:	Mobile or Fixed Device
Device category	Consumer Device for General Population/Uncontrolled Exposure
Date of issue:	April 8, 2026
Compliance	FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
Specifications:	FCC 47 CFR Part 2 Subpart J, §§2.1091, 2.1093 FCC KDB 447498 D01 General RF Exposure Guidance v06 FCC KDB 865664 D01 RF Exposure Procedures and Equipment Authorization Policies ISED Canada RSS-102 Issue 6 December 15, 2023

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).
The test results included in this report are within the scope of this accreditation.
The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.





Test locations of Nemko Canada Inc.

	Ottawa site	Montréal site	GTA Cambridge site
Facility address	303 River Road Ottawa, Ontario Canada K1V 1H2 Tel: +1 613 737 9680 Fax: +1 613 737 9691	292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8 Tel: +1 514 694 2684 Fax: +1 514 694 3528	1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2 Tel: +1 519 650 4811
Test site identifier - FCC	CA2040	CA2041	CA0101
Test site identifier – ISED Canada	2040A-4	2040G-5	24676
ANAB File Number	AT-3195	AT-3193	AT-3194

Andrey Adelberg

Senior EMC/Wireless Specialist

Prepared by

Signature

Limits of responsibility

The results presented in this report apply solely to the specific device model tested and are valid only for the operating conditions and installation requirements specified herein. Testing was conducted in accordance with ISO/IEC 17025:2017 requirements, and all results fall within the scope of Nemko Canada's accreditation.

This MPE evaluation is based on the maximum power levels and operating conditions specified. Any modifications to the device hardware, software, or installation that could affect RF output power or antenna characteristics may invalidate this compliance demonstration.

Copyright notification

This report may be reproduced by the applicant in its entirety for regulatory submission and internal use. Any use of this report by third parties, including reliance on its contents or decisions made based on it, is solely at the risk of those third parties. Nemko Canada Inc. assumes no responsibility for any damages incurred by third parties as a result of actions taken based on this report.

© Nemko Canada Inc. All rights reserved.



1. Executive Summary

This report presents the Maximum Permissible Exposure (MPE) analysis to demonstrate compliance with FCC and ICED RF exposure requirements. The evaluation considers both single transmitter operation and simultaneous multi-transmitter scenarios where applicable.

2. Key Findings

Compliance status	Complies
Critical separation distances	20 cm
Special conditions or limitations	N/A

MPE calculations for stand-alone transmission

Device Classification Requirements

Portable Device Definition (§2.1093)	Devices designed for use by a person where the radiating structure is within 20 cm of the user's body require SAR evaluation rather than MPE calculation.
Mobile Device Definition	Devices installed in vehicles or with permanently installed antennas may use MPE calculations if minimum separation distances can be established.
Fixed/Base Station Definition	Stationary transmitters with controlled access to antenna locations may use MPE calculations for both occupational and general population exposure scenarios.

3. References, definitions and limits for FCC

FCC §2.1091(d)

- (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1: §1.1310(e)(1)—Power Density Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure		
0.3–3.0	*(100)	≤6
3.0–30	*(900 / f ²)	<6
30–300	1.0	<6
300–1500	f / 300	<6
1500–100000	5	<6
(ii) Limits for General Population/Uncontrolled Exposure		
0.3–1.34	*(100)	<30
1.34–30	*(180 / f ²)	<30
30–300	0.2	<30
300–1500	f / 1500	<30
1500–100000	1.0	<30

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

4. References, definitions and limits for ISED

RSS-102

Section 5.3.2 The power density reference levels, and associated reference period for devices employed by the general public (uncontrolled environment) and controlled-use devices (controlled environment) are specified in table below. Note that the power density limits specified in this table apply to whole body exposure conditions.

Table 2: RSS-102— Power density limits

Frequency range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)	Reference Period (minutes)
Limits for controlled-use devices (controlled environment)			
10–20	10	1	6
20–48	$44.72 / f^{0.5}$	$4.472 / f^{0.5}$	6
48–100	6.455	0.6455	6
100–6000	$0.6455 f^{0.5}$	$0.06455 f^{0.5}$	6
6000–15000	50	5	$616000 / f^{1.2}$
15000–30000	$3.33 \times 10^{-4} f$	$0.333 \times 10^{-4} f$	$616000 / f^{1.2}$
Limits for devices used by the general public (uncontrolled environment)			
10–20	2	0.2	6
20–48	$8.944 / f^{0.5}$	$0.8944 / f^{0.5}$	6
48–300	1.291	0.1291	6
300–6000	$0.02619 f^{0.6834}$	$0.002619 f^{0.6834}$	6
6000–15000	10	1	$616000 / f^{1.2}$
15000–30000	$6.67 \times 10^{-5} / f$	$0.667 \times 10^{-5} / f$	$616000 / f^{1.2}$

Notes: f = frequency in MHz.

The above table refers to Health Canada's Safety Code 6 for relevant notes and additional information.

Additional ISED Considerations

Routine Evaluation Thresholds	ISED requires routine evaluation when predicted or measured field strength exceeds certain thresholds, even for equipment that would otherwise be categorically excluded.
Environmental Classification	Clear distinction must be made between controlled and uncontrolled environments based on RF awareness and access control measures.

5. Power density calculation formula

The fundamental equation (from page 18 of OET Bulletin 65, Edition 97-01) for calculating power density at a specified distance from an RF source is derived from the far-field assumption:

$$S = \frac{PG}{4\pi R^2}$$

where:

- S = Power density (mW/cm² or W/m²)
- P = Power input to antenna (mW or W)
- G = Antenna gain (linear ratio, not dB)
- R = Distance from radiation center (cm or m)

This equation assumes:

- Far-field conditions ($R > 2D^2/\lambda$, where D is largest antenna dimension) are assumed at the evaluation distance of 20 cm
- Isotropic power distribution (conservative approach)
- Free-space propagation conditions
- Worst-case antenna orientation

Multiple Transmitter Analysis (if applicable)

Total Exposure Ratio (TER) Calculation: $TER = \sum (S_i/L_i) \leq 1.0$

Where:

- S_i = Power density from transmitter i
- L_i = Applicable limit for transmitter i

6. EUT technical information for a single/simultaneous transmitter operation

	2.4 GHz Wi-Fi	UNII-1	UNII-2a	UNII-2c	UNII-3	BT EDR	BT LE
Prediction frequency (MHz)	2462	5250	5350	5725	5850	2480	2480
Antenna gain (dBi)	2.79	4.0	4.0	4.0	4.0	2.79	2.79
Number of antennas	1	1	1	1	1	1	1
Maximum transmitter power (dBm)	18.44	17.82	19.51	19.87	20.03	7.52	8.89
Declared separation distance (cm)	20	20	20	20	20	20	20
Duty cycle (%)	100	100	100	100	100	100	100

7. Test report references

Transmitter maximum output power measurement result was taken from the following RF test reports:

	Report 1	Report 2	Report 3	Report 4
Report ID	FR061103AN	FR061103AD	FR061103AE	FR061103AC
Issue date	10-Nov-20	10-Nov-20	10-Nov-20	10-Nov-20
Test standard	FCC 15.407, RSS-247	FCC 15.247, RSS-247	FCC 15.247, RSS-247	FCC 15.247, RSS-247

8. Verdict

The calculated power density at the declared separation distance is below the applicable regulatory limits. Therefore, the product **COMPLIES** with FCC and ISED RF exposure requirements for single transmitter operation.

The calculated Total Exposure Ratio (TER) is less than 1.0, indicating that the combined RF exposure from simultaneous transmission does not exceed regulatory limits. Therefore, the product **COMPLIES** with FCC and ISED RF exposure requirements for simultaneous multi-transmitter operation.

9. MPE calculation (conducted method) for FCC Uncontrolled environment (General population)

Band, type	Frequency, MHz	Conducted power (measured), dBm	Cable loss, dB	Maximum power at antenna terminal, dBm	Duty cycle, %	Average power adjusted for duty cycle, mW	Antenna gain, dBi	Number of antennas	Total system gain, dBi	Declared distance, cm	Average power density at declared distance, mW/cm ²	MPE limit, mW/cm ²	Exposure ratio	Minimum calculated prediction distance for compliance, cm	Margin of Compliance, dB	Maximum permitted total system gain, dBi
2.4G Wi-Fi	2462	18.44	0	18.44	100	69.823	2.79	1	2.79	20	0.026408	1.000000	0.026408	20	15.78	18.57
UNII-1	5250	17.82	0	17.82	100	60.534	4.00	1	4.00	20	0.030250	1.000000	0.030250	20	15.19	19.19
UNII-2a	5350	19.51	0	19.51	100	89.331	4.00	1	4.00	20	0.044641	1.000000	0.044641	20	13.50	17.50
UNII-2c	5725	19.87	0	19.87	100	97.051	4.00	1	4.00	20	0.048499	1.000000	0.048499	20	13.14	17.14
UNII-3	5850	20.03	0	20.03	100	100.693	4.00	1	4.00	20	0.050319	1.000000	0.050319	20	12.98	16.98
BT EDR	2480	7.52	0	7.52	100	5.649	2.79	1	2.79	20	0.002137	1.000000	0.002137	20	26.70	29.49
BT LE	2480	8.89	0	8.89	100	7.745	2.79	1	2.79	20	0.002929	1.000000	0.002929	20	25.33	28.12

Total exposure ratio for simultaneous operation	0.205182	<1 = Pass
---	----------	-----------

10. MPE calculation (conducted method) for ISD Uncontrolled environment (General population)

Band, type	Frequency, MHz	Conducted power (measured), dBm	Cable loss, dB	Maximum power at antenna terminal, dBm	Duty cycle, %	Average power adjusted for duty cycle, mW	Antenna gain, dBi	Number of antennas	Total system gain, dBi	Declared distance, cm	Average power density at declared distance, mW/cm ²	MPE limit, mW/cm ²	Exposure ratio	Minimum calculated prediction distance for compliance, cm	Margin of Compliance, dB	Maximum permitted total system gain, dBi
2.4G Wi-Fi	2462	18.44	0	18.44	100	69.823	2.79	1	2.79	20	0.026408	0.544179	0.048528	20	13.14	15.93
UNII-1	5250	17.82	0	17.82	100	60.534	4.00	1	4.00	20	0.030250	0.913045	0.033131	20	14.80	18.80
UNII-2a	5350	19.51	0	19.51	100	89.331	4.00	1	4.00	20	0.044641	0.924895	0.048266	20	13.16	17.16
UNII-2c	5725	19.87	0	19.87	100	97.051	4.00	1	4.00	20	0.048499	0.968722	0.050065	20	13.00	17.00
UNII-3	5850	20.03	0	20.03	100	100.693	4.00	1	4.00	20	0.050319	0.983127	0.051182	20	12.91	16.91
BT EDR	2480	7.52	0	7.52	100	5.649	2.79	1	2.79	20	0.002137	0.546895	0.003907	20	24.08	26.87
BT LE	2480	8.89	0	8.89	100	7.745	2.79	1	2.79	20	0.002929	0.546895	0.005356	20	22.71	25.50

Maximum single power density	0.50319	W/m ²
Total simultaneous power density	2.05182	W/m ²
Total exposure ratio for simultaneous operation	0.24043	<1 = Pass

End of the test report