

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 1 of 62

Applicant : PETKIT Network Technology (Shanghai) Co., Ltd.
Address of Applicant : Room 4139, Building 2, 588 Zixing Road, Minhang District, Shanghai

Product Name : PETKIT EVERSWEET ULTRA AI HEALTH CARE PET WATER FOUNTAIN

Brand Name : PETKIT

Model Name : P4117

Sample Acquisition Method : Sent by Client

Sample No. : E25120030-01#02
E25120030-01#03

FCC ID : 2A72N-P4117

Standards : FCC CFR47 Part 15.247, Subpart C

Date of Receipt : 2025-12-15


Date of Test : 2026-01-17~ 2026-03-24

Date of Issue : 2026-03-24

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by:



(Erik Yang)

Reviewed by:



(Jennifer Zhou)

Approved by:



(Authorized signatory: Echo Mu)

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 2 of 62

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	DETAILS OF TEST MODE	8
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
3.3	SUPPORT SOFTWARE	9
3.4	TEST SETUP DIAGRAM	9
4	TEST RESULTS	11
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
4.1.1	<i>Antenna Requirement.....</i>	<i>11</i>
4.1.2	<i>Maximum conducted (average) output power</i>	<i>12</i>
4.1.3	<i>6dB Bandwidth</i>	<i>13</i>
4.1.4	<i>Maximum conducted output power spectral density.....</i>	<i>19</i>
4.1.5	<i>Conducted Spurious Emission & Authorized-band band-edge.....</i>	<i>25</i>
4.1.6	<i>Radiated Emission</i>	<i>42</i>
4.1.7	<i>Band Edge (Restricted-band band-edge).....</i>	<i>43</i>
4.2	MAINS EMISSIONS	44
4.2.1	<i>Conducted Emission on AC Mains.....</i>	<i>44</i>
5	APPENDIXES	47
5.1	EXTERNAL PHOTO OF THE SAMPLE	47
5.2	INTERNAL PHOTO OF THE SAMPLE	52
5.3	SET-UP FOR CONDUCTED EMISSIONS	61
5.4	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	61
5.5	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	62
5.6	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	62

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 3 of 62

1 General Information

1.1 Testing Laboratory

Company Name	Shanghai Ingeer Testing Technology Co., Ltd.
Address	No.1298, Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999

1.2 Details of Application

Applicant Company Name	PETKIT Network Technology (Shanghai) Co., Ltd.
Applicant Company Address	Room 4139, Building 2, 588 Zixing Road, Minhang District, Shanghai
Contact Person	TingHe
Telephone	+86 13916991059
Email	ting.he@petkit.com
Manufacturer Company Name	Dongguan Zhihang Electronic Technology Co., LTD.
Manufacturer Company Address	Room 701, Building 15, No.1, Pushi Road I, Qiaotou Town, Dongguan City,Guangdong Province, China.
Factory Company Name	Dongguan Zhihang Electronic Technology Co., LTD.
Factory Company Address	Room 701, Building 15, No.1, Pushi Road I, Qiaotou Town, Dongguan City,Guangdong Province, China.

1.3 Details of EUT

Product Name	PETKIT EVERSWEET ULTRA AI HEALTH CARE PET WATER FOUNTAIN
Brand Name	PETKIT
Test Model Name	P4117
FCC ID	2A72N-P4117
Mode of Operation	WLAN 802.11b/g/n(HT20)
Max RF Output Power	IEEE 802.11b: 16.33dBm IEEE 802.11g: 15.78dBm IEEE 802.11n(20): 14.82dBm
Frequency Range	2400MHz ~ 2483.5MHz
Channel Separation	5 MHz
Number of channels	11
Modulation Type	DSSS, OFDM
Antenna Type	Internal Antenna
Antenna Gain	3.26dBi
Extreme Temperature Range	0°C~ +40°C
Test Voltage	DC 12V 2A by adapter
WIFI Hardware Version	V1.0
WIFI Software Version	V1.360

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 4 of 62

RF power setting in TEST SW	802.11b: SecureCRT Version 7.0.4 and rtwpriv command_Power setting_patha=78 802.11g: SecureCRT Version 7.0.4 and rtwpriv command_Power setting_patha=68 802.11n(HT20): SecureCRT Version 7.0.4 and rtwpriv command_Power setting_patha=62
------------------------------------	--

Note:

1. The above information was declared by the manufacture.
2. For more details, please refer to the User's manual of the EUT.

Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2.412GHz	5	2.432GHz	9	2.452GHz
2	2.417GHz	6	2.437GHz	10	2.457GHz
3	2.422GHz	7	2.442GHz	11	2.462GHz
4	2.427GHz	8	2.447GHz		

Note: For 20MHz bandwidth system use Channel 1 to Channel 11

1.4 Test Methodology

47 CFR Part 15, Subpart C	Telecommunication-Radio Frequency Devices-Intentional Radiators
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
ANSI C63.10-2020+Cor.1-2023	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 5 of 62

1.5 Test Summary

Test Item	FCC Rules	Result
Antenna Requirement	FCC Part 15.247(b)(4), Part 15.203	PASS
Maximum conducted (average) output power	FCC Part 15.247(b)(3)	PASS
6dB Bandwidth	FCC Part 15.247(a)(2)	PASS
Maximum conducted output power spectral density	FCC Part 15.247(e)	PASS
Conducted Spurious Emission & Authorized-band band-edge	FCC Part 15.247(d)	PASS
Radiated Emission	FCC Part 15.247(d), 15.205, 15.209	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.247(d), 15.205, 15.209	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	PASS

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 6 of 62

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	15-35
Humidity (%RH)	30-60
Barometric Pressure (mbar)	860-1060

Note: Actual values will be recorded during the test.

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020B	MY59260184	2025-06-30	2026-06-29
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2025-06-10	2026-06-09
Signal Generator	Rohde & Schwarz	SMR27	100184	2025-06-30	2026-06-29
USB Wideband Power Sensor	Keysight	U2021XA	MY57200011	2025-11-10	2026-11-09
USB Wideband Power Sensor	Keysight	U2021XA	MY56090008	2025-11-10	2026-11-09
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2025-06-09	2026-06-08
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2025-06-09	2026-06-08
V-network	SCHWARZBECK	NSLK 8127	8127-902	2025-06-09	2026-06-08
Attenuator	SCHWARZBECK	VTSD 9561-FN	/	2025-06-09	2026-06-08
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2025-03-24	2027-03-23
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2025-06-22	2027-06-21
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2025-06-23	2027-06-22
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2025-06-22	2027-06-21
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2025-06-09	2026-06-08
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2025-06-10	2028-06-09
Shielded Enclosure 8*5*4(L*W*H)	CHANGNING	854	N/A	2025-06-10	2028-06-09
Test Software	BL	BL410_E	Version:1.0.0.122	N/A	N/A
Test Software	BL	BL410_R	Version:3.5.2.642	N/A	N/A

TEST REPORT

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in measurement” (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission		$\pm 1.04\text{dB}$
Radiated Emission	30MHz-1GHz	$\pm 5.00\text{dB}$
	1GHz-40GHz	$\pm 5.46\text{dB}$
Conducted Emission on AC Mains	150KHz-30MHz	$\pm 3.36\text{dB}$
Occupied Channel Bandwidth		$\pm 39.26\text{KHz}$
Maximum Conducted Output Power		$\pm 1.06\text{dB}$
Maximum Conducted Output Power Spectral Density		$\pm 1.12\text{dB}$

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 8 of 62

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software (SecureCRT Version 7.0.4 and rtwpriv command) to control EUT work in continuous transmitting and receiving mode. Select test channel as below:

For 802.11b/g/n (HT20)

Channel	Frequency
The lowest channel (CH1)	2412MHz
The middle channel (CH6)	2437MHz
The highest channel (CH11)	2462MHz

Through Pre-scan under all rate at lowest channel, the data rate as below table described is the worst case, so we choose these data rate for test.

Type	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(20M)	MCS0

The basic operation modes are:

- A. On
 - 1. WLAN mode
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - b. Receiving
- B. Standby
- C. Off

TEST REPORT

3.2 Special Accessories and Auxiliary Equipment


Description	Manufacturer	Model Name	Serial No.
Laptop 1	HP	HP ZHAN 66 Pro G1	5CD7438R1J
Laptop 2	Lenovo	TP00083A	PF-0PRDGN
USB Cable	N/A	N/A	1.00m Unshielded
Switching Adapter	N/A	GQ24-120200-AX	Input: AC 100-240V 50/60Hz 1.0A Max; Output: DC 12V 2A 24W

3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	SecureCRT Version 7.0.4 and rtwpriv command

3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

TEST REPORT

Diagram of Measurement Equipment Configuration for Conduction Measurement




Diagram of Measurement Equipment Configuration for Transmitter Measurement





Diagram of Measurement Equipment Configuration for conducted output power setup



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 11 of 62

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT: **PASS**

Test standard	: FCC Part 15.247(b)(4), Part 15.203
Requirement	: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.26dBi. The antenna is an Internal antenna with no possibility of replacement with a non-approved antenna by the end-user.

Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 12 of 62

4.1.2 Maximum conducted (average) output power

RESULT:

PASS

Test standard : FCC Part 15.247(b)(3)
Requirement : ANSI C63.10 Clause 11.9.2.3.1
KDB 558074 D01 v05r02, Clause 8.3.2
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.6-24.8°C
Relative humidity : 43.8-46.7%

Table 1: Maximum conducted (average) output power

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum conducted (average) output power		Limit (W)
			(dBm)	(mW)	
802.11b	96.88	2412	16.31	42.76	≤1
		2437	16.33	42.95	
		2462	14.95	31.26	
802.11g	41.34	2412	15.78	37.84	
		2437	15.25	33.50	
		2462	14.27	26.73	
802.11n(HT20)	38.25	2412	14.82	30.34	
		2437	13.85	24.27	
		2462	13.08	20.32	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 13 of 62

4.1.3 6dB Bandwidth

RESULT:

PASS

Test standard : FCC Part 15.247(a)(2)

Requirement : ANSI C63.10 Clause 11.8.2
KDB 558074 D01 v05r02, Clause 8.2

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 23.6-24.8℃

Relative humidity : 43.8-46.7%

Table 2: 6dB Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Applicable Limit (MHz)
802.11b	2412	9.60	≥0.5
	2437	9.57	
	2462	9.58	
802.11g	2412	13.70	
	2437	10.39	
	2462	11.75	
802.11n(HT20)	2412	12.64	
	2437	14.23	
	2462	15.71	

TEST REPORT

Report No.: SHE25120030-02CE


Date: 2026-03-24

Page 14 of 62

Figure 1: 6dB Bandwidth, 802.11b, 2412MHz



Figure 2: 6dB Bandwidth, 802.11b, 2437MHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 15 of 62

Figure 3: 6dB Bandwidth, 802.11b, 2462MHz





Figure 4: 6dB Bandwidth, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 16 of 62

Figure 5: 6dB Bandwidth, 802.11g, 2437MHz





Figure 6: 6dB Bandwidth, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE25120030-02CE


Date: 2026-03-24

Page 17 of 62

Figure 7: 6dB Bandwidth, 802.11n(HT20), 2412MHz



Figure 8: 6dB Bandwidth, 802.11n(HT20), 2437MHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 18 of 62

Figure 9: 6dB Bandwidth, 802.11n(HT20), 2462MHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 19 of 62

4.1.4 Maximum conducted output power spectral density

RESULT:

PASS

Test standard : FCC Part 15.247(e)
Requirement : ANSI C63.10 Clause 11.10.5
KDB 558074 D01 v05r02, Clause 8.4
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.6-24.8°C
Relative humidity : 43.8-46.7%

Table 3: Maximum (average) conducted output power spectral density

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum (average) conducted output power spectral density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	96.88	2412	-16.95	≤8
		2437	-16.04	
		2462	-17.51	
802.11g	41.34	2412	-18.37	
		2437	-19.07	
		2462	-20.25	
802.11n(HT20)	38.25	2412	-21.06	
		2437	-21.36	
		2462	-21.23	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured PSD to compute the average PSD during the actual transmission time

TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 20 of 62

Figure 10: Power Spectral Density, 802.11b, 2412MHz





Figure 11: Power Spectral Density, 802.11b, 2437MHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 21 of 62

Figure 12: Power Spectral Density, 802.11b, 2462MHz





Figure 13: Power Spectral Density, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25120030-02CE Date: 2026-03-24 Page 22 of 62

Figure 14: Power Spectral Density, 802.11g, 2437MHz





Figure 15: Power Spectral Density, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE25120030-02CE Date: 2026-03-24 Page 23 of 62

Figure 16: Power Spectral Density, 802.11n(HT20), 2412MHz





Figure 17: Power Spectral Density, 802.11n(HT20), 2437MHz




TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 24 of 62

Figure 18: Power Spectral Density, 802.11n(HT20), 2462MHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 25 of 62

4.1.5 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard

Requirement

Kind of test site

: FCC Part 15.247(d), 15.209

: ANSI C63.10 Clause 11.11.1

: KDB 558074 D01 v05r02, Clause 8.5

: Shielded room

Test setup

Test Channel

Operation Mode

Ambient temperature

Relative humidity

: Low/Middle/High for spurious, Low/High for Band Edge


: A.1.a

: 23.6-24.8°C

: 43.8-46.7%

For details refer to following test plot.

Figure 19: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2412MHz Carrier Level



TEST REPORT

Report No.: SHE25120030-02CE


Date: 2026-03-24

Page 26 of 62

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 27 of 62



Figure 20: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2437MHz Carrier Level




TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 28 of 62

Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 29 of 62

Figure 21: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2462MHz Carrier Level



Band Edge





TEST REPORT

Report No.: SHE25120030-02CE

Date: 2026-03-24

Page 30 of 62


Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25120030-02CE Date: 2026-03-24 Page 31 of 62

Figure 22: Conducted Spurious Emission & Authorized-band band-edge, 802.11g, 2412MHz Carrier Level



Band Edge

