

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 1 of 59

Applicant : PETKIT Network Technology (Shanghai) Co., Ltd.
Address of Applicant : Room 4139, Building 2, 588 Zixing Road, Minhang District, Shanghai

Product Name : PETKIT YUMSHARE DUAL-HOPPER 2 WITH CAMERA SMART PET FEEDER
Brand Name : PETKIT
Model Name : P592
Sample Acquisition Method : Sent by Client

Sample No. : E25110009-01#03
E25110009-01#04

FCC ID : 2A72N-P592

Standards : FCC CFR47 Part 15.247, Subpart C

Date of Receipt : 2025-11-06
Date of Test : 2025-11-18~ 2026-01-20
Date of Issue : 2026-01-21

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by:



(Erik Yang)

Reviewed by:



(Jennifer Zhou)

Approved by:



(Authorized signatory: Echo Mu)

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 2 of 59

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	DETAILS OF TEST MODE	8
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
3.3	SUPPORT SOFTWARE	9
3.4	TEST SETUP DIAGRAM	9
4	TEST RESULTS	11
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
4.1.1	<i>Antenna Requirement</i>	11
4.1.2	<i>Maximum conducted (average) output power</i>	12
4.1.3	<i>6dB Bandwidth</i>	13
4.1.4	<i>Maximum conducted output power spectral density</i>	19
4.1.5	<i>Conducted Spurious Emission & Authorized-band band-edge</i>	25
4.1.6	<i>Radiated Emission</i>	42
4.1.7	<i>Band Edge (Restricted-band band-edge)</i>	43
4.2	MAINS EMISSIONS	44
4.2.1	<i>Conducted Emission on AC Mains</i>	44
5	APPENDIXES	47
5.1	EXTERNAL PHOTO OF THE SAMPLE	47
5.2	INTERNAL PHOTO OF THE SAMPLE	51
5.3	SET-UP FOR CONDUCTED EMISSIONS	57
5.4	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	58
5.5	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	58
5.6	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	59

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 3 of 59

1 General Information

1.1 Testing Laboratory

Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd
Address	No.1298, Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Applicant Company Name	PETKIT Network Technology (Shanghai) Co., Ltd.
Applicant Company Address	Room 4139, Building 2, 588 Zixing Road, Minhang District, Shanghai
Contact Person	TingHe
Telephone	+86 13916991059
Email	ting.he@petkit.com
Manufacturer Company Name	Dongguan Zhihang Electronic Technology Co., LTD.
Manufacturer Company Address	Room 701, Building 15, No.1, Pushi Road I, Qiaotou Town, Dongguan City,Guangdong Province, China.
Factory Company Name	Dongguan Zhihang Electronic Technology Co., LTD.
Factory Company Address	Room 701, Building 15, No.1, Pushi Road I, Qiaotou Town, Dongguan City,Guangdong Province, China.

1.3 Details of EUT

Product Name	PETKIT YUMSHARE DUAL-HOPPER 2 WITH CAMERA SMART PET FEEDER
Brand Name	PETKIT
Test Model Name	P592
FCC ID	2A72N-P592
Mode of Operation	WLAN 802.11b/g/n(HT20)
Max RF Output Power	IEEE 802.11b: 15.27dBm IEEE 802.11g: 11.10dBm IEEE 802.11n(20): 10.60dBm
Frequency Range	2400MHz ~ 2483.5MHz
Channel Separation	5 MHz
Number of channels	11
Modulation Type	DSSS, OFDM
Antenna Type	Internal Antenna
Antenna Gain	3.70dBi

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 4 of 59

Extreme Temperature Range	0°C~ +40°C
Test Voltage	DC 5.9V 2A by adapter Adapter (Manufacturer: TEKA; Model: TEKA-TB059200US; Input: AC 100-240V 50/60Hz 0.35A max; Output: DC 5.9V 2A)
WIFI Hardware Version	V1.1
WIFI Software Version	V2.841
RF power setting in TEST SW	802.11b: SecureCRT Version 7.0.4 and rtwpriv command_Power setting_patha=69 802.11g: SecureCRT Version 7.0.4 and rtwpriv command_Power setting_patha=45 802.11n(HT20): SecureCRT Version 7.0.4 and rtwpriv command_Power setting_patha=42

Note:

1. The above information was declared by the manufacture.
2. For more details, please refer to the User's manual of the EUT.

Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2.412GHz	5	2.432GHz	9	2.452GHz
2	2.417GHz	6	2.437GHz	10	2.457GHz
3	2.422GHz	7	2.442GHz	11	2.462GHz
4	2.427GHz	8	2.447GHz		

Note: For 20MHz bandwidth system use Channel 1 to Channel 11

1.4 Test Methodology

47 CFR Part 15, Subpart C	Telecommunication-Radio Frequency Devices-Intentional Radiators
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 5 of 59

1.5 Test Summary

Test Item	FCC Rules	Result
Antenna Requirement	FCC Part 15.247(b)(4), Part 15.203	PASS
Maximum conducted (average) output power	FCC Part 15.247(b)(3)	PASS
6dB Bandwidth	FCC Part 15.247(a)(2)	PASS
Maximum conducted output power spectral density	FCC Part 15.247(e)	PASS
Conducted Spurious Emission & Authorized-band band-edge	FCC Part 15.247(d)	PASS
Radiated Emission	FCC Part 15.247(d), 15.205, 15.209	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.247(d), 15.205, 15.209	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	PASS

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 6 of 59

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	15-35
Humidity (%RH)	30-60
Barometric Pressure (mbar)	860-1060

Note: Actual values will be recorded during the test.

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020A	MY54101709	2025-06-30	2026-06-29
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2025-06-10	2026-06-09
Signal Generator	Rohde & Schwarz	SMR27	100184	2025-06-30	2026-06-29
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2025-06-09	2026-06-08
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2025-06-09	2026-06-08
V-network	SCHWARZBECK	NSLK 8127	8127-902	2025-06-09	2026-06-08
Attenuator	SCHWARZBECK	VTSD 9561-FN	/	2025-06-09	2026-06-08
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2025-03-24	2027-03-23
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2025-06-22	2027-06-21
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2025-06-23	2027-06-22
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2025-06-22	2027-06-21
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2025-06-09	2026-06-08
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2025-06-10	2028-06-09
Shielded Enclosure 8*5*4(L*W*H)	CHANGNING	854	N/A	2025-06-10	2028-06-09
Test Software	BL	BL410_E	Version:2.1.1.436	N/A	N/A
Test Software	BL	BL410_R	Version:2.1.1.409	N/A	N/A

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 7 of 59

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in measurement” (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission		$\pm 1.04\text{dB}$
Radiated Emission	30MHz-1GHz	$\pm 5.00\text{dB}$
	1GHz-40GHz	$\pm 5.46\text{dB}$
Conducted Emission on AC Mains	150KHz-30MHz	$\pm 3.36\text{dB}$
Occupied Channel Bandwidth		$\pm 39.26\text{KHz}$
Maximum Conducted Output Power		$\pm 1.06\text{dB}$
Maximum Conducted Output Power Spectral Density		$\pm 1.12\text{dB}$

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 8 of 59

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software (SecureCRT Version 7.0.4 and rtwpriv command) was control EUT work in continuous transmitter and receiver mode. Select test channel as below:

For 802.11b/g/n (HT20)

Channel	Frequency
The lowest channel (CH1)	2412MHz
The middle channel (CH6)	2437MHz
The highest channel (CH11)	2462MHz

Through Pre-scan under all rate at lowest channel, the data rate as below table described is the worst case, so we choose these data rate for test.

Type	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(20M)	MCS0

The basic operation modes are:

- A. On
 - 1. WLAN mode
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - b. Receiving
- B. Standby
- C. Off

TEST REPORT

3.2 Special Accessories and Auxiliary Equipment


Description	Manufacturer	Model Name	Serial No.
Laptop 1	HP	HP ZHAN 66 Pro G1	5CD7438R1J
Laptop 2	Lenovo	TP00083A	PF-0PRDGN
USB Cable	N/A	N/A	1.00m Unshielded
Adapter	TEKA	TEKA-TB059200US	Input: AC 100-240V 50/60Hz 0.35A max; Output: DC 5.9V 2A

3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	SecureCRT Version 7.0.4 and rtwpriv command

3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

TEST REPORT

Diagram of Measurement Equipment Configuration for Conduction Measurement




Diagram of Measurement Equipment Configuration for Transmitter Measurement





Diagram of Measurement Equipment Configuration for conducted output power setup



TEST REPORT

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard	: FCC Part 15.247(b)(4), Part 15.203
Requirement	: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.70dBi. The antenna is an Internal antenna with no possibility of replacement with a non-approved antenna by the end-user.

Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 12 of 59

4.1.2 Maximum conducted (average) output power

RESULT:

PASS

Test standard : FCC Part 15.247(b)(3)
Requirement : ANSI C63.10-2020, Clause 11.9.2.3.1
KDB 558074 D01 v05r02, Clause 8.3.2
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 24.0°C
Relative humidity : 45.3%

Table 1: Maximum conducted (average) output power

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum conducted (average) output power		Limit (W)
			(dBm)	(mW)	
802.11b	97.83	2412	15.27	33.65	≤1
		2437	14.98	31.48	
		2462	13.52	22.49	
802.11g	43.58	2412	11.10	12.88	
		2437	10.22	10.52	
		2462	9.34	8.59	
802.11n(HT20)	39.75	2412	10.60	11.48	
		2437	9.73	9.40	
		2462	9.08	8.09	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 13 of 59

4.1.3 6dB Bandwidth

RESULT:

PASS

Test standard : FCC Part 15.247(a)(2)

Requirement : ANSI C63.10-2020, Clause 11.8.2
KDB 558074 D01 v05r02, Clause 8.2

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 24.0°C

Relative humidity : 45.3%

Table 2: 6dB Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Applicable Limit (MHz)
802.11b	2412	9.11	≥0.5
	2437	9.56	
	2462	9.55	
802.11g	2412	16.28	
	2437	16.08	
	2462	12.63	
802.11n(HT20)	2412	12.69	
	2437	16.69	
	2462	11.31	

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 14 of 59

Figure 1: 6dB Bandwidth, 802.11b, 2412MHz





Figure 2: 6dB Bandwidth, 802.11b, 2437MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 15 of 59

Figure 3: 6dB Bandwidth, 802.11b, 2462MHz





Figure 4: 6dB Bandwidth, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 16 of 59

Figure 5: 6dB Bandwidth, 802.11g, 2437MHz





Figure 6: 6dB Bandwidth, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 17 of 59

Figure 7: 6dB Bandwidth, 802.11n(HT20), 2412MHz





Figure 8: 6dB Bandwidth, 802.11n(HT20), 2437MHz




TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 18 of 59

Figure 9: 6dB Bandwidth, 802.11n(HT20), 2462MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 19 of 59

4.1.4 Maximum conducted output power spectral density

RESULT:

PASS

Test standard : FCC Part 15.247(e)
Requirement : ANSI C63.10-2020, Clause 11.10.5
KDB 558074 D01 v05r02, Clause 8.4
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 24.0°C
Relative humidity : 45.3%

Table 3: Maximum (average) conducted output power spectral density

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum (average) conducted output power spectral density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	97.83	2412	-18.15	≤8
		2437	-18.05	
		2462	-19.17	
802.11g	43.58	2412	-23.52	
		2437	-24.66	
		2462	-25.38	
802.11n(HT20)	39.75	2412	-24.68	
		2437	-24.72	
		2462	-25.77	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured PSD to compute the average PSD during the actual transmission time

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 20 of 59

Figure 10: Power Spectral Density, 802.11b, 2412MHz




Figure 11: Power Spectral Density, 802.11b, 2437MHz



TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 21 of 59

Figure 12: Power Spectral Density, 802.11b, 2462MHz



Figure 13: Power Spectral Density, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 22 of 59

Figure 14: Power Spectral Density, 802.11g, 2437MHz





Figure 15: Power Spectral Density, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 23 of 59

Figure 16: Power Spectral Density, 802.11n(HT20), 2412MHz





Figure 17: Power Spectral Density, 802.11n(HT20), 2437MHz




TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 24 of 59

Figure 18: Power Spectral Density, 802.11n(HT20), 2462MHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 25 of 59

4.1.5 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard

Requirement

Kind of test site

: FCC Part 15.247(d), 15.209

: ANSI C63.10-2020, Clause 11.11.1

: KDB 558074 D01 v05r02, Clause 8.5

: Shielded room

Test setup

Test Channel

Operation Mode

Ambient temperature

Relative humidity

: Low/Middle/High for spurious, Low/High for Band Edge


: A.1.a

: 24.0°C

: 45.3%

For details refer to following test plot.

Figure 19: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2412MHz Carrier Level




TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 26 of 59

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 27 of 59





Figure 20: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2437MHz Carrier Level





TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 28 of 59

Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 29 of 59

Figure 21: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2462MHz Carrier Level



Band Edge





TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 30 of 59

Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 31 of 59

Figure 22: Conducted Spurious Emission & Authorized-band band-edge, 802.11g, 2412MHz Carrier Level



Band Edge





TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 32 of 59

Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 33 of 59

Figure 23: Conducted Spurious Emission & Authorized-band band-edge, 802.11g, 2437MHz Carrier Level



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 34 of 59





Figure 24: Conducted Spurious Emission & Authorized-band band-edge, 802.11g, 2462MHz Carrier Level




TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 35 of 59

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 36 of 59





Figure 25: Conducted Spurious Emission & Authorized-band band-edge, 802.11n(HT20), 2412MHz Carrier Level



TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 37 of 59

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 38 of 59





Figure 26: Conducted Spurious Emission & Authorized-band band-edge, 802.11n(HT20), 2437MHz Carrier Level





TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 39 of 59

Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 40 of 59

Figure 27: Conducted Spurious Emission & Authorized-band band-edge, 802.11n(HT20), 2462MHz Carrier Level



Band Edge





TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 41 of 59

Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 42 of 59

4.1.6 Radiated Emission

RESULT:

PASS

Test standard	: FCC Part 15.247(d), 15.205, 15.209
Requirement	: ANSI C63.10-2020, Clause 11.12.1 KDB 558074 D01 v05r02, Clause 8.6
Kind of test site	: 3m Semi-Anechoic Chamber

Test setup

Test Channel	: Low/Middle/High
Operation Mode	: A.1.a
Ambient temperature	: 22.6-23.1°C
Relative humidity	: 45-51%

Notes

Test plots please refer to the annex document "SHE25110009-02CE DATA WIFI 2.4GHz-TX EXHIBIT A".

- 1. For 9 kHz ~ 30 MHz, the amplitude of spurious emissions that are attenuated by more than 20dB below the permissible. The value has no need to be reported.*
- 2. The spurious above 18GHz is noise only and 20dB below the limit. The value has no need to be reported.*
- 3. All test modes had been pre-tested, but only the 802.11b at low channel of below 1 GHz is the worst case and recorded in the report.*
- 4. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement -X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.*

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 43 of 59

4.1.7 Band Edge (Restricted-band band-edge)

RESULT:

PASS

Test standard	: FCC Part 15.247(d), 15.205, 15.209
Requirement	: ANSI C63.10-2020, Clause 11.12.3 KDB 558074 D01 v05r02, Clause 8.7
Kind of test site	: 3m Semi-Anechoic Chamber

Test setup

Test Channel	: Low/Middle/High
Operation Mode	: A.1.a
Ambient temperature	: 22.6-23.1°C
Relative humidity	: 45-51%

Notes:

1. Test plots please refer to the annex document "SHE25110009-02CE DATA WIFI 2.4GHz-TX EXHIBIT A".
2. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 44 of 59

4.2 Mains Emissions

4.2.1 Conducted Emission on AC Mains

RESULT:

PASS

Test standard	: FCC Part 15.207(a)
Requirement	: ANSI C63.10-2020, Clause 6.2
Kind of test site	: Shielded room

Test setup

Input Voltage	: DC 5.9V 2A supply by AC adapter (which received AC 120V, 60Hz)
Operation Mode	: A.1.a
Earthing	: Disconnected to GND
Ambient temperature	: 22.9°C
Relative humidity	: 53%

For details refer to following test plot.

TEST REPORT


Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 45 of 59

Note: All test modes had been pre-tested, but only the 802.11b at low channel is the worst case and recorded in the report.

Figure 28: Conducted Emission on AC Mains, L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	55.37	10.25	65.57	10.20	Peak	L	Pass
1*	0.158	45.49	10.25	65.57	20.08	QP	L	Pass
1**	0.158	31.76	10.25	55.57	23.81	AV	L	Pass
2	0.688	43.72	10.33	56.00	12.28	Peak	L	Pass
2*	0.688	38.60	10.33	56.00	17.40	QP	L	Pass
2**	0.688	31.68	10.33	46.00	14.32	AV	L	Pass
3	2.064	40.89	10.10	56.00	15.11	Peak	L	Pass
3*	2.064	37.14	10.10	56.00	18.86	QP	L	Pass
3**	2.064	32.19	10.10	46.00	13.81	AV	L	Pass
4	3.442	39.77	10.13	56.00	16.23	Peak	L	Pass
4*	3.442	37.54	10.13	56.00	18.46	QP	L	Pass
4**	3.442	32.57	10.13	46.00	13.43	AV	L	Pass
5	16.526	42.39	10.64	60.00	17.61	Peak	L	Pass
5*	16.526	40.42	10.64	60.00	19.58	QP	L	Pass
5**	16.526	37.09	10.64	50.00	12.91	AV	L	Pass
6	28.924	48.14	11.36	60.00	11.86	Peak	L	Pass
6*	28.924	45.74	11.36	60.00	14.26	QP	L	Pass
6**	28.924	39.94	11.36	50.00	10.06	AV	L	Pass


TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 46 of 59

Figure 29: Conducted Emission on AC Mains, N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.174	54.57	10.15	64.77	10.20	Peak	N	Pass
1*	0.174	43.56	10.15	64.77	21.21	QP	N	Pass
1**	0.174	31.95	10.15	54.77	22.82	AV	N	Pass
2	0.690	43.86	10.27	56.00	12.14	Peak	N	Pass
2*	0.690	41.69	10.27	56.00	14.31	QP	N	Pass
2**	0.690	38.25	10.27	46.00	7.75	AV	N	Pass
3	2.062	43.78	10.03	56.00	12.22	Peak	N	Pass
3*	2.062	41.73	10.03	56.00	14.27	QP	N	Pass
3**	2.062	39.06	10.03	46.00	6.94	AV	N	Pass
4	3.438	43.70	10.08	56.00	12.30	Peak	N	Pass
4*	3.438	41.81	10.08	56.00	14.19	QP	N	Pass
4**	3.438	38.79	10.08	46.00	7.21	AV	N	Pass
5	7.566	42.56	10.20	60.00	17.44	Peak	N	Pass
5*	7.566	40.54	10.20	60.00	19.46	QP	N	Pass
5**	7.566	37.65	10.20	50.00	12.35	AV	N	Pass
6	26.144	46.22	11.18	60.00	13.78	Peak	N	Pass
6*	26.144	44.67	11.18	60.00	15.33	QP	N	Pass
6**	26.144	36.89	11.18	50.00	13.11	AV	N	Pass

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 47 of 59

5 Appendixes

5.1 External Photo of the Sample



All of the sample



Adapter of the sample

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 48 of 59



Front of the sample



Rear of the sample

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 49 of 59



Left of the sample



Right of the sample

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 50 of 59



Top of the sample



Bottom of the sample

TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 51 of 59



Port of the sample

5.2 Internal Photo of the Sample



Open-1 of the sample

TEST REPORT


Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 52 of 59



Open-2 of the sample




Internal-1 of the sample

TEST REPORT


Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 53 of 59



Internal-2 of the sample




Internal-3 of the sample

TEST REPORT


Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 54 of 59




Internal-4 of the sample




Internal-5 of the sample

TEST REPORT



Internal-6 of the sample




Bluetooth Antenna position

TEST REPORT


Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 56 of 59



WIFI Antenna position




WIFI Antenna-Front

TEST REPORT

Report No.: SHE25110009-02CE


Date: 2026-01-21

Page 57 of 59



WiFi Antenna-Back

5.3 Set-up for Conducted Emissions




TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 58 of 59

5.4 Set-up for Conducted RF test at Antenna Port



5.5 Set-up for Spurious Emissions below 1GHz




TEST REPORT

Report No.: SHE25110009-02CE

Date: 2026-01-21

Page 59 of 59

5.6 Set-up for Spurious Emissions above 1GHz



End of the report