

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2A73PCF-010

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
EDR 8DPSK& MCH	2±1	3	1.9953	1.1668 (0.67dBi)	0.0005	1	Pass
2.4G WIFI 802.11n(HT 40)&2452	14±1	15	31.6228	0.9772 (-0.1dBi)	0.0062	1	Pass
LTE BAND 2	25±1	26	398.107 2	1.7140 (2.34dBi)	0.1358	1	Pass
LTE BAND 4	25±1	26	398.107 2	2.4946 (3.97dBi)	0.1977	1	Pass
LTE BAND 5	25±1	26	398.107 2	0.8204 (-0.86dBi)	0.065	0.5	Pass
LTE BAND 7	25±1	26	398.107 2	2.1727 (3.37dBi)	0.1722	1	Pass
LTE BAND 12	25±1	26	398.107 2	1.1220 (0.5dBi)	0.0889	0.5	Pass

BT+WIFI +LTE supported simultaneous transmission:

BLE+2.4GWIFI+LTE : $\sum$ MPE Ratio =0.0005/1+0.0062/1+0.1977/1

=0.2044≤1, So passed.