



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN2450-FPC327BX

Product Name: Antenna

Specification For Approval

Date: 2025.3.12

Version: 1.0

客户名称

Customer:

九安

客户料号

Customer P/N:

腾祥料号

T X P/N:

AN2450-FPC327BX

规格描述

Description:

2.4G/5G FPC 天线 1.13mm 黑色线 L=120mm +IPEX

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制作	路婷	TESTED BY 检测	
CHECKED BY 审核	胡超	CHECKED BY 审核	
Q.C.DEPT. 品管	江美如	Q.C.DEPT. 品管	
APPROVED BY 核准	韦佳	APPROVED BY 核准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN2450-FPC327BX

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)

Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2025.3.12	初版	

Product Number: AN2450-FPC327BX

Product Name: Antenna

1. Specification

Sample Photo



A. Electrical Characteristics

Frequency 频率	2400-2500 MHz/5150-5850MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	2.63dBi /3.00dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm

B. Material & Mechanical Characteristics

Cable Type 线材规格	OD1.13mm , Black
Connector Type 连接器规格	I-PEX

C. Environmental

Storage Temperature 存储温度	- 40°C ~ +80 °C
Operation Temperature 工作温度	- 40°C ~ +80 °C

Product Number: AN2450-FPC327BX

Product Name: Antenna



2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C;Duration: 5 seconds 温度 260±5° C;持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待测物规范;频率偏移≤5%	PASS
6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面处理	Directive DUT specification 符合待测物规范	PASS
7	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN2450-FPC327BX

Product Name: Antenna

3. Antenna - S Parameter Test Data



Product Number: AN2450-FPC327BX

Product Name: Antenna

4. Antenna - Radiation Pattern Test Data





Frequency/Mhz	MaxGain/dBi	Efficiency / %	Frequency/Mhz	MaxGain/dBi	Efficiency / %
2400	3.6	48.53	5250	3.49	44.36
2410	3.36	45.6	5300	4.11	46.13
2420	2.89	41.02	5350	3.91	44.57
2430	2.8	40.74	5400	3.9	44.06
2440	3.09	42.17	5450	3.85	46.03
2450	3.02	43.15	5500	3.75	43.25
2460	2.87	41.02	5550	4.28	46.13
2470	2.97	43.05	5600	4.6	45.71
2480	3.12	41.11	5650	4.86	46.13
2490	3.08	39.36	5700	5.11	46.56
2500	3.74	39.63	5750	5.1	47.86
5150	3.48	44.46	5800	5.01	48.31
5200	2.83	42.46	5850	5.69	48.31

2400MHz

XZ

YZ





XY







Product Number: AN2450-FPC327BX

Product Name: Antenna





2450MHz







2500MHz



5150MHz







5550MHz



Product Number: AN2450-FPC327BX


Product Name: Antenna

5850MHz



5. Mechanical Drawing See attached files

SIGN	DATE	DESCRIPTION	APPROVER
			
			
			



1. Mark* is important dimension;"Cpk "Identify for process control($CpK \geq 1.33$).
2. Tolerance: Unmarked tolerance refer to the standard tolerance please.
3. Pay attention to the direction of the connector.

3	CR-113-ZP-A	I-PEX	Cu	Au Plated	1
2	CB-113BS	Coaxial Cable	OD1.13	Black	1
1	AN2450-FPC296204	FPC		Black	1
No.	Part Number	Name	Material	Finish	Q'ty

 Tengxiang Electronics Co., Ltd.						
TITLE: Antenna						
PART NO.: AN2450-FPC327BX				CUSTOMER P/N: /		
APP BY	CHK BY	RF BY	DES BY			Tolerance
YCX	HC	WJ	SY			UNITS: mm
2025.03.12	2025.03.12	2025.03.12	2025.03.12	SCALE: 1/1		X.XX ±0.2
				REVISION: A		X° ±1

产品包装规范


PACKING CRITERION

Date: 2025.03.12

Page: 1 of 1


Part Number : AN2450-FPC327BX	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。




8000pcs/Carton



3. SEALING。



SIDE



FRONT



APPROVED BY : YCX CHECKED BY : HC DESIGNED BY : SY Y