


π/4-DQPSK_2441_30~1000




π/4-DQPSK_2441_1000~26500




π/4-DQPSK_2480_0~Reference




π/4-DQPSK_2480_30~1000




π/4-DQPSK_2480_1000~26500




8-DPSK_2402_0~Reference




8-DPSK_2402_30~1000




8-DPSK_2402_1000~26500




8-DPSK_2441_0~Reference




8-DPSK_2441_30~1000




8-DPSK_2441_1000~26500




8-DPSK_2480_0~Reference




8-DPSK_2480_30~1000




8-DPSK_2480_1000~26500



## 3.5. 20DB Bandwidth

**Limit**

N/A

**Test Configuration**




**Test Procedure**

5. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
6. OCB and 20dB Spectrum Setting:
   (1) Set RBW = 1% ~ 5% occupied bandwidth.
   (2) Set the video bandwidth (VBW) ≥ 3 RBW.
   (3) Detector = Peak.
   (4) Trace mode = Max hold.
   (5) Sweep = Auto couple.

Note: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

**Test Mode**

Please refer to the clause 2.4.

**Test Results**

| Test Mode | Frequency[MHz] | 20db EBW[MHz] | 20dB Bandwidth *2/3 (kHz) | Verdict |
|---|---|---|---|---|
| GFSK | 2402 | 0.942 | 628 | PASS |
| | 2441 | 0.945 | 630 | PASS |
| | 2480 | 0.936 | 624 | PASS |
| π/4-DQPSK | 2402 | 1.290 | 860 | PASS |
| | 2441 | 1.290 | 860 | PASS |
| | 2480 | 1.314 | 876 | PASS |
| 8-DPSK | 2402 | 1.302 | 868 | PASS |
| | 2441 | 1.302 | 868 | PASS |
| | 2480 | 1.302 | 868 | PASS |

GFSK_2402




GFSK_2441




GFSK_2480





中国国家认证认可监督管理委员会
Certification and Accreditation Administration of the People's Republic of China
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

π/4-DQPSK_2402




π/4-DQPSK_2441




π/4-DQPSK_2480




8-DPSK_2402




8-DPSK_2441




8-DPSK_2480



## 3.6. Channel Separation

**Limit**

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)/ RSS-247 5.1 b :**

| Test Item | Limit | Frequency Range(MHz) |
|---|---|---|
| Channel Separation | >25KHz or >two-thirds of the 20 dB bandwidth Which is greater | 2400~2483.5 |

**Test Configuration**




**Test Procedure**

7. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
8. Spectrum Setting:
   (1) Set RBW = 100 kHz.
   (2) Set the video bandwidth (VBW) ≥ 3 RBW.
   (3) Detector = Peak.
   (4) Trace mode = Max hold.
   (5) Sweep = Auto couple.

**Test Mode**

Please refer to the clause 2.4.

**Test Results**

| Test Mode | Frequency[MHz] | Result[MHz] | Limit[kHz] | Verdict |
|---|---|---|---|---|
| GFSK | Hop_2441 | 1.000 | >630 | PASS |
| π/4-DQPSK | Hop_2441 | 1.008 | >860 | PASS |
| 8-DPSK | Hop_2441 | 1.000 | >868 | PASS |

GFSK_Hop_2441




π/4-DQPSK_Hop_2441

8-DPSK_Hop_2441

## 3.7. Number of Hopping Channel

**Limit**

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)/ RSS-247 5.1 d:**

| Section | Test Item | Limit |
|---|---|---|
| 15.247 (a)(iii)/ RSS-247 5.1 d: | Number of Hopping Channel | >15 |

**Test Configuration**




**Test Procedure**

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
   (1) Peak Detector: RBW=100 kHz, VBW≥RBW, Sweep time= Auto.

**Test Mode**

Please refer to the clause 2.4.

**Test Result**

| Modulation type | Channel number | Limit | Result |
|---|---|---|---|
| GFSK | 79 | ≥15.00 | Pass |
| π/4-DQPSK | 79 | | |
| 8DPSK | 79 | | |

GFSK




π/4-DQPSK




8-DPSK



## 3.8. Dwell Time

**Limit**

| Section | Test Item | Limit |
|---|---|---|
| 15.247(a)(iii)/ RSS-247 5.1 d | Average Time of Occupancy | 0.4 sec |

**Test Configuration**




**Test Procedure**

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
   (1) Spectrum Setting: RBW=1MHz, VBW≥RBW.
   (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
   (3) Sweep Time is more than once pulse time.
   (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
   (5) Measure the maximum time duration of one single pulse.
   (6) Set the EUT for packet transmitting.

**Test Mode**

Please refer to the clause 2.4.

**Test Result**

| Modulation type | Channel | Frequency [MHz] | Pulse Time (ms) | Total of Dwell (ms) | Period Time (ms) | Limit (Second) | Result |
|---|---|---|---|---|---|---|---|
| GFSK | DH1 | 2441 | 0.38 | 121.60 | 31.60 | ≤ 0.40 | Pass |
| | DH3 | 2441 | 1.64 | 262.40 | 31.60 | | |
| | DH5 | 2441 | 2.88 | 307.20 | 31.60 | | |
| π/4-DQPSK | 2DH1 | 2441 | 0.38 | 121.60 | 31.60 | ≤ 0.40 | Pass |
| | 2DH3 | 2441 | 1.64 | 262.40 | 31.60 | | |
| | 2DH5 | 2441 | 2.89 | 308.27 | 31.60 | | |
| 8-DPSK | 3DH1 | 2441 | 0.38 | 121.60 | 31.60 | ≤ 0.40 | Pass |
| | 3DH3 | 2441 | 1.64 | 262.40 | 31.60 | | |
| | 3DH5 | 2441 | 2.89 | 308.27 | 31.60 | | |

*Note: 1DH1/2DH1/3DH1Total of Dwell= Pulse Time*(1600/2)*31.6/79*
*1DH3/2DH3/3DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79*
*1DH5/2DH5/3DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79*

GFSK_2402




GFSK_2441




GFSK_2480



π/4-DQPSK_2402




π/4-DQPSK_2441




π/4-DQPSK_2480




8-DPSK_2402


中国国家认证认可监督管理委员会
Certification and Accreditation Administration of the People's Republic of China
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




8-DPSK_2441




8-DPSK_2480



## 3.9. Peak Output Power

**Limit**

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1) / RSS-247 5.4 b:**

| Test Item | Limit | Frequency Range(MHz) |
|---|---|---|
| Maximum Conducted Peak Output Power | Hopping Channels>75 Power<1W(30dBm)<br>Other <125mW(21dBm) | 2400~2483.5 |
| E.I.R.P | 4 Watt or 36dBm | 2400~2483.5 |

**Test Configuration**




**Test Procedure**

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
   (1) Set RBW> 20DB Bandwidth.
   (2) Set the video bandwidth (VBW) ≥ RBW.
   (3) Detector = Peak.
   (4) Trace mode = Max hold.
   (5) Sweep = Auto couple.

**Test Mode**

Please refer to the clause 2.4.

**Test Result**

| Test Mode | Frequency[MHz] | Result[dBm] | Limit[dBm] | Verdict |
|---|---|---|---|---|
| GFSK | 2402 | 9.86 | <=30 | PASS |
| | 2441 | 10.33 | <=30 | PASS |
| | 2480 | 9.66 | <=30 | PASS |
| π/4-DQPSK | 2402 | 9.60 | <=30 | PASS |
| | 2441 | 10.03 | <=30 | PASS |
| | 2480 | 9.26 | <=30 | PASS |
| 8-DPSK | 2402 | 9.70 | <=30 | PASS |
| | 2441 | 10.15 | <=30 | PASS |
| | 2480 | 9.49 | <=30 | PASS |

GFSK_2402




GFSK_2441




GFSK_2480



π/4-DQPSK_2402




π/4-DQPSK_2441




π/4-DQPSK_2480




8-DPSK_2402




8-DPSK_2441




8-DPSK_2480



## 3.10. Duty Cycle

**Limit**

None, for report purposes only.

**Test Configuration**




**Test Procedure**

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:

Set analyzer center frequency to test channel center frequency.
Set the span to 0Hz
Set the RBW to 10MHz
Set the VBW to 10MHz
Detector: Peak
Sweep time: Auto
Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

**Test Mode**

Please refer to the clause 2.4.

**Test Result**

| Test Mode | Frequency [MHz] | Transmission Duration [ms] | Transmission Period [ms] | Duty Cycle [%] | 1/T Minimum VBW (kHz) | Final setting For VBW (kHz) |
|---|---|---|---|---|---|---|
| GFSK | 2402 | 2.88 | 3.75 | 76.80 | 0.35 | 1 |
| | 2441 | 2.88 | 3.75 | 76.80 | 0.35 | 1 |
| | 2480 | 2.88 | 3.75 | 76.80 | 0.35 | 1 |
| π/4-DQPSK | 2402 | 2.89 | 3.75 | 77.07 | 0.35 | 1 |
| | 2441 | 2.88 | 3.74 | 77.01 | 0.35 | 1 |
| | 2480 | 2.88 | 3.75 | 76.80 | 0.35 | 1 |
| 8-DPSK | 2402 | 2.89 | 3.75 | 77.07 | 0.35 | 1 |
| | 2441 | 2.88 | 3.75 | 76.80 | 0.35 | 1 |
| | 2480 | 2.89 | 3.75 | 77.07 | 0.35 | 1 |

GFSK_2402




GFSK_2441




GFSK_2480



π/4-DQPSK_2402




π/4-DQPSK_2441




π/4-DQPSK_2480




8-DPSK_2402


中国国家认证认可监督管理委员会 Certification and Accreditation Administration of the People's Republic of China
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




8-DPSK_2441




8-DPSK_2480



## 3.11. Antenna requirement

**Requirement**

**FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**Test Result**

The directional gain of the antenna less than 6dBi, please refer to the EUT internal photographs antenna photo.

**********THE END**********