



FCC TEST REPORT

FCC ID: 2A77A-JTFLAP12W24K

Product	:	Wireless Bluetooth Music Bulb
Model Name	:	JTFLAP-12W-24K ; JTFL-A31-2121 ; JTFL-A31-212 ; JTFL-A31-212APP; JTFL-A32-212; JTFL-A30-212; JTFL-A30-212APP; JTFL-A30-2121; JTFL-A30-2121; JTFL-A30-2122; JTFL-A30-2123; JTFL-A30-2124; JTFL-E27-6W-01; JTFL-E27-6W-02; JTFL-E27-3W-01; JTFL-E27-3W-02; JTFL-E27-6W; JTFL-A27-218; JTFL-A28-236; JTFL-A29-254; JTFL-A23-241; JTFL-A23-24 ; JTFL-A24-24; JTFL-A25-24 ; JTFL-A44-23 ; JTFL-A40-53 ; JTFL-A40-531 ; JTFL-A40-532; JTFL-A6-54; JTFL-A8-541; JTFL-A8-54 ; JTFL-A8-114; JTFL-A7-54 ; JTFL-A9-56 ; JTFL-A10-215 ; JTFL-A11-215 ; JTFL-A10-2151 ; JTFL-A10-2152 ; JTFL-A15-26 ; JTFL-A14-26 ; JTFL-A14-262; JTFL-A14-261; JTFL-a17-26; JTFL-A18-26; JTFL-A12-215; JTFL-A12-515; JTFL-A13-212; JTFL-A13-512; JTFL-A19-29; JTFL-A19-291; JTFL-A20-29; JTFL-A20-291; JTFL-A20-292; JTFL-A20-293; JTFL-A16-26; JTFL-A16-261; JTFL-A26-261; JTFL-A26-26; JTFL-A42-510 ; JTFL-A43-510 ; JTFL-A22-224 ; JTFL-A21-224 ; JTFL-KX-1688 ; JTFL-A47-58 ; JTFL-4Y-XK-01 ; JTFL-4Y-XK-02 ; JTFL-4Y-SJ-01; JTFL-4Y-SJ-02; JTFL-4Y-TASJ-01; JTFL-4Y-TASJ-02 ; JTFL-4Y-48W ; JTFL-4Y-36W ; JTFL-3Y-SJ-01 ; JTFL-3Y-SJ-02 ; JTFL-3Y-XK-01 ; JTFL-3Y-XK-02 ; JTFL-12W-24K; JTFL-FXP-PM; JTFL-3Y-24K; JTFL-LY-SJ; JTFL-LY-LHFD; JTFL-LY-WXSJ; JTFL-LY-WXXK; JTFL-4Y-4-1; JTFL-3Y-3-1; JTFL-4Y-4-1PC; JTFL-4Y-4-1ABS; JTFL-LY-XFD-01; JTFL-LY-XFD-02; JTFL-LY-MNXFD-01; JTFL-LY-MNXFD-02; JTFL-LY-MNXFD-03; JTFL-LY-CDFD-TA; JTFL-LY-CDFD-XK ; JTFL-LY-ZS-RGB ; JTFL-LY-XFD ; JTFL-LY-CDDMQ-01 ; JTFL-LY-CDDMQ-02 ; JTFL-LY-CDDMQ-03 ; JTFL-QCFSD-60W
Report No.	:	PTC22060201101E-FC01
Sample ID	:	PTC22060201101E-FC01#



Report No.: PTC22060201101E-FC01

Prepared for
shen zhen shi jie teng song ke ji you xian gong si
Room 506,Building 8,Baoshan Industrial Zone,Mizhi Street,Longhua New District,Shenzhen,Guangdong,China
Prepared by
Dongguan Precise Testing & Certification Co., Ltd.
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China



1 TEST RESULT CERTIFICATION

Applicant's name : shen zhen shi jie teng song ke ji you xian gong si

Address : Room 506,Building 8,Baoshan Industrial Zone,Mizhi Street,Longhua New District,Shenzhen,Guangdong,China

Manufacture's name : shen zhen shi jie teng song ke ji you xian gong si

Address : Room 506,Building 8,Baoshan Industrial Zone,Mizhi Street,Longhua New District,Shenzhen,Guangdong,China

Product name : Wireless Bluetooth Music Bulb

Model name : JTFLAP-12W-24K ; JTFL-A31-2121 ; JTFL-A31-212 ; JTFL-A31-212APP ; JTFL-A32-212 ; JTFL-A30-212 ; JTFL-A30-212APP ; JTFL-A30-2121 ; JTFL-A30-2121 ; JTFL-A30-2122 ; JTFL-A30-2123 ; JTFL-A30-2124 ; JTFL-E27-6W-01 ; JTFL-E27-6W-02 ; JTFL-E27-3W-01 ; JTFL-E27-3W-02 ; JTFL-E27-6W ; JTFL-A27-218 ; JTFL-A28-236 ; JTFL-A29-254 ; JTFL-A23-241 ; JTFL-A23-24 ; JTFL-A24-24 ; JTFL-A25-24 ; JTFL-A44-23 ; JTFL-A40-53 ; JTFL-A40-531 ; JTFL-A40-532 ; JTFL-A6-54 ; JTFL-A8-541 ; JTFL-A8-54 ; JTFL-A8-114 ; JTFL-A7-54 ; JTFL-A9-56 ; JTFL-A10-215 ; JTFL-A11-215 ; JTFL-A10-2151 ; JTFL-A10-2152 ; JTFL-A15-26 ; JTFL-A14-26 ; JTFL-A14-262 ; JTFL-A14-261 ; JTFL-a17-26 ; JTFL-A18-26 ; JTFL-A12-215 ; JTFL-A12-515 ; JTFL-A13-212 ; JTFL-A13-512 ; JTFL-A19-29 ; JTFL-A19-291 ; JTFL-A20-29 ; JTFL-A20-291 ; JTFL-A20-292 ; JTFL-A20-293 ; JTFL-A16-26 ; JTFL-A16-261 ; JTFL-A26-261 ; JTFL-A26-26 ; JTFL-A42-510 ; JTFL-A43-510 ; JTFL-A22-224 ; JTFL-A21-224 ; JTFL-KX-1688 ; JTFL-A47-58 ; JTFL-4Y-XK-01 ; JTFL-4Y-XK-02 ; JTFL-4Y-SJ-01 ; JTFL-4Y-SJ-02 ; JTFL-4Y-TASJ-01 ; JTFL-4Y-TASJ-02 ; JTFL-4Y-48W ; JTFL-4Y-36W ; JTFL-3Y-SJ-01 ; JTFL-3Y-SJ-02 ; JTFL-3Y-XK-01 ; JTFL-3Y-XK-02 ; JTFL-12W-24K ; JTFL-FXP-PM ; JTFL-3Y-24K ; JTFL-LY-SJ ; JTFL-LY-LHFD ; JTFL-LY-WXSJ ; JTFL-LY-WXXK ; JTFL-4Y-4-1 ; JTFL-3Y-3-1 ; JTFL-4Y-4-1PC ; JTFL-4Y-4-1ABS ; JTFL-LY-XFD-01 ; JTFL-LY-XFD-02 ; JTFL-LY-MNXFD-01 ; JTFL-LY-MNXFD-02 ; JTFL-LY-MNXFD-03 ; JTFL-LY-CDFD-TA ; JTFL-LY-CDFD-XK ; JTFL-LY-ZS-RGB ; JTFL-LY-XFD ; JTFL-LY-CDDMQ-01 ; JTFL-LY-CDDMQ-02 ; JTFL-LY-CDDMQ-03 ; JTFL-QCFSD-60W

Standards : FCC CFR47 Part 15 Section 15.247



Report No.: PTC22060201101E-FC01

Test procedure : ANSI C63.10:2013
Test Date : Jul. 05, 2022 to Jul. 15, 2022
Date of Issue : Jul. 18, 2022
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads 'Leo Yang'.

Leo Yang / Engineer

Technical Manager:

A handwritten signature in black ink that reads 'Ronnie Liu'.

Ronnie Liu / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	3
2 TEST SUMMARY	7
2.1 TEST SITE	8
3 GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF E.U.T.	9
3.2 CHANNEL LIST	11
4 EQUIPMENT DURING TEST	12
4.1 EQUIPMENTS LIST	12
4.2 MEASUREMENT UNCERTAINTY	14
4.3 DESCRIPTION OF SUPPORT UNITS	15
5 CONDUCTED EMISSION	16
5.1 E.U.T. OPERATION	16
5.2 EUT SETUP	16
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
5.4 MEASUREMENT PROCEDURE	17
5.5 CONDUCTED EMISSION LIMIT	17
5.6 MEASUREMENT DESCRIPTION	17
5.7 CONDUCTED EMISSION TEST RESULT	17
6 RADIATED SPURIOUS EMISSIONS	20
6.1 EUT OPERATION	20
6.2 TEST SETUP	21
6.3 SPECTRUM ANALYZER SETUP	22
6.4 TEST PROCEDURE	23
6.5 SUMMARY OF TEST RESULTS	25
7 BAND EDGE MEASUREMENT	30
7.1 TEST PROCEDURE	30
7.2 TEST RESULT	31
8 6DB BANDWIDTH MEASUREMENT	32
8.1 TEST PROCEDURE	32



8.2 TEST RESULT	32
9 MAXIMUM PEAK OUTPUT POWER	35
9.1 TEST PROCEDURE	35
9.2 TEST RESULT	35
10 POWER SPECTRAL DENSITY	36
10.1 TEST PROCEDURE	36
10.2 TEST RESULT	36
11 ANTENNA APPLICATION	39
11.1 ANTENNA REQUIREMENT	39
11.2 RESULT	39



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS

Remark:

1. The EUT is powered by full-charged battery during the test.



Report No.: PTC22060201101E-FC01

2.1 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1

Designation Number: CN1219



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Wireless Bluetooth Music Bulb
Model Name	:	JTFLAP-12W-24K
Derivative model	:	JTFL-A31-2121; JTFL-A31-212; JTFL-A31-212APP; JTFL-A32-212; JTFL-A30-212; JTFL-A30-212APP; JTFL-A30-2121; JTFL-A30-2121; JTFL-A30-2122; JTFL-A30-2123; JTFL-A30-2124; JTFL-E27-6W-01; JTFL-E27-6W-02; JTFL-E27-3W-01; JTFL-E27-3W-02; JTFL-E27-6W; JTFL-A27-218; JTFL-A28-236; JTFL-A29-254; JTFL-A23-241; JTFL-A23-24; JTFL-A24-24; JTFL-A25-24; JTFL-A44-23; JTFL-A40-53; JTFL-A40-531; JTFL-A40-532; JTFL-A6-54; JTFL-A8-541; JTFL-A8-54; JTFL-A8-114; JTFL-A7-54; JTFL-A9-56; JTFL-A10-215; JTFL-A11-215; JTFL-A10-2151; JTFL-A10-2152; JTFL-A15-26; JTFL-A14-26; JTFL-A14-262; JTFL-A14-261; JTFL-a17-26; JTFL-A18-26; JTFL-A12-215; JTFL-A12-515; JTFL-A13-212; JTFL-A13-512; JTFL-A19-29; JTFL-A19-291; JTFL-A20-29; JTFL-A20-291; JTFL-A20-292; JTFL-A20-293; JTFL-A16-26; JTFL-A16-261; JTFL-A26-261; JTFL-A26-26; JTFL-A42-510; JTFL-A43-510; JTFL-A22-224; JTFL-A21-224; JTFL-KX-1688; JTFL-A47-58; JTFL-4Y-XK-01; JTFL-4Y-XK-02; JTFL-4Y-SJ-01; JTFL-4Y-SJ-02; JTFL-4Y-TASJ-01; JTFL-4Y-TASJ-02; JTFL-4Y-48W; JTFL-4Y-36W; JTFL-3Y-SJ-01; JTFL-3Y-SJ-02; JTFL-3Y-XK-01; JTFL-3Y-XK-02; JTFL-12W-24K; JTFL-FXP-PM; JTFL-3Y-24K; JTFL-LY-SJ; JTFL-LY-LHFD; JTFL-LY-WXSJ; JTFL-LY-WXXK; JTFL-4Y-4-1; JTFL-3Y-3-1; JTFL-4Y-4-1PC; JTFL-4Y-4-1ABS; JTFL-LY-XFD-01; JTFL-LY-XFD-02; JTFL-LY-MNXFD-01; JTFL-LY-MNXFD-02; JTFL-LY-MNXFD-03; JTFL-LY-CDFD-TA; JTFL-LY-CDFD-XK; JTFL-LY-ZS-RGB; JTFL-LY-XFD; JTFL-LY-CDDMQ-01; JTFL-LY-CDDMQ-02; JTFL-LY-CDDMQ-03; JTFL-QCFSD-60W
Differences between the basic and derivative model(s)	:	It is same schematic circuit and pcb layout, just color and model name different.
Version	:	5.1 BLE
Operating frequency	:	2402-2480MHz
Number of Channels	:	40
Type of Modulation	:	GFSK
Antenna installation	:	PCB Antenna



Report No.: PTC22060201101E-FC01

Antenna Gain	:	0dBi
Power supply	:	AC 85-265V 60Hz
Hardware Version	:	V1.0
Software Version	:	V1.0



3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.



4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Last calibration	Calibration Due	Calibration period
MXA Signal Analyzer	Agilent	N9020A	MY56070279	Aug. 21, 2021	Aug. 20, 2022	1 year
Coaxial Cable	CDS	79254	46107086	Aug. 21, 2021	Aug. 20, 2022	1 year
Power Meter	Anritsu	ML2495A	0949003	Aug. 21, 2021	Aug. 20, 2022	1 year
Power Sensor	Anritsu	MA2411B	0917017	Aug. 21, 2021	Aug. 20, 2022	1 year
Spectrum Analyzer	Rohde&Schwarz	FSU26	1166.1660.26	Aug. 21, 2021	Aug. 20, 2022	1 year

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Last calibration	Calibration Due	Calibration period
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	Aug. 21, 2021	Aug. 20, 2022	1 year
Loop Antenna	Schwarzbeck	FMZB 1519	012	Aug. 21, 2021	Aug. 20, 2022	1 year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	Aug. 21, 2021	Aug. 20, 2022	1 year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	Aug. 21, 2021	Aug. 20, 2022	1 year
Cable	Schwarzbeck	PLF-100	549489	Aug. 21, 2021	Aug. 20, 2022	1 year
Spectrum Analyzer	Agilent	E4407B	MY45109572	Aug. 21, 2021	Aug. 20, 2022	1 year
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	Aug. 21, 2021	Aug. 20, 2022	1 year
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	Aug. 21, 2021	Aug. 20, 2022	1 year
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	Aug. 21, 2021	Aug. 20, 2022	1 year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	Aug. 21, 2021	Aug. 20, 2022	1 year
Cable	H+S	CBL-26	N/A	Aug. 21, 2021	Aug. 20, 2022	1 year
RF Cable	R&S	R204	R21X	Aug. 21, 2021	Aug. 20, 2022	1 year



Report No.: PTC22060201101E-FC01

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Last calibration	Calibration Due	Calibration period
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	Aug. 21, 2021	Aug. 20, 2022	1 year
Artificial Mains Network	Rohde&Schwarz	L2-16B	000WX31025	Aug. 21, 2021	Aug. 20, 2022	1 year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	Aug. 21, 2021	Aug. 20, 2022	1 year



4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(9kHz~30MHz)	$\pm 2.54\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	



Report No.: PTC22060201101E-FC01

4.3 Description of Support Units

Equipment	Model No.	Series No.

5 Conducted Emission

Test Requirement	: FCC CFR 47 Part 15 Section 15.207
Test Method	: ANSI C63.10: 2013
Test Result	: PASS
Frequency Range	: 150kHz to 30MHz
Class/Severity	: Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature	: 25.5 °C
Humidity	: 51 % RH
Atmospheric Pressure	: 101.2kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description


The maximised peak emissions from the EUT was scanned and measured AC 120V and 230V for both the Live and Neutral Lines, worst case is AC 120V 60Hz ,CH00:2402MHz. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

Pass




Line:



Final Data List

NO.	Freq. [MHz]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.159	55.71	65.52	9.81	40.98	55.52	14.54	PASS
2	0.393	54.24	58.00	3.76	40.13	48.00	7.87	PASS
3	0.578	52.07	56.00	3.93	40.99	46.00	5.01	PASS
4	1.469	53.00	56.00	3.00	36.91	46.00	9.09	PASS
5	3.116	50.00	56.00	6.00	33.03	46.00	12.97	PASS
6	5.105	45.95	60.00	14.05	26.26	50.00	23.74	PASS

Neutral:



Final Data List

NO.	Freq. [MHz]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.164	57.41	65.28	7.87	48.00	55.28	7.28	PASS
2	0.263	58.09	61.35	3.26	43.10	51.35	8.25	PASS
3	0.501	52.45	56.00	3.55	43.69	46.00	2.31	PASS
4	0.996	52.17	56.00	3.83	39.27	46.00	6.73	PASS
5	1.491	52.06	56.00	3.94	35.99	46.00	10.01	PASS
6	2.499	50.48	56.00	5.52	35.52	46.00	10.48	PASS



6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method : ANSI C63.10:2013
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation


Operating Environment :

Temperature : 23.5 °C
 Humidity : 51.1 % RH
 Atmospheric Pressure : 101.2kPa


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value



6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



For Average Measurement:

VBW=10Hz, when duty cycle is no less than 98 percent.

VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μ s)	1/T(KHz)	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (AC 120V 60Hz, GFSK, CH00: 2402MHz).



Antenna Polarization: Vertical GFSK(CH00: 2402MHz)




Final Data List								
NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	30.24	-18.33	16.13	40.00	23.87	100	288	Vertical
2	65.65	-18.64	13.14	40.00	26.86	100	244	Vertical
3	125.79	-17.57	23.55	43.50	19.95	100	316	Vertical
4	299.90	-15.45	17.76	46.00	28.24	100	247	Vertical
5	312.03	-15.10	22.87	46.00	23.13	100	239	Vertical
6	713.85	-6.31	16.24	46.00	29.76	100	65	Vertical

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



Antenna Polarization: Horizontal GFSK(CH00: 2402MHz)



Final Data List								
NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	30.49	-18.32	11.84	40.00	28.16	100	50	Horizontal
2	68.32	-18.99	12.51	40.00	27.49	100	188	Horizontal
3	133.79	-16.96	15.31	43.50	28.19	100	298	Horizontal
4	299.90	-15.45	27.67	46.00	18.33	100	174	Horizontal
5	312.03	-15.10	29.52	46.00	16.48	100	179	Horizontal
6	728.64	-5.94	20.95	46.00	25.05	100	246	Horizontal

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



Test Frequency 1GHz-18GHz:

GFSK Low Channel (2402MHz)

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4804	28.43	AV	V	16.84	8.22	16.04	37.45	54	-16.55
4804	27.95	AV	H	16.84	8.22	16.04	36.97	54	-17.03
4804	30.42	PK	V	16.84	8.22	16.04	35.2	74	-38.8
4804	31.58	PK	H	16.84	8.22	16.04	36.07	74	-37.93
17358	29.34	AV	V	20.17	8.46	19.34	38.63	54	-15.37
17358	30.11	AV	H	20.17	8.46	19.34	39.4	54	-14.6
17358	31.55	PK	V	20.17	8.46	19.34	38.75	74	-35.25
17358	33.24	PK	H	20.17	8.46	19.34	40.37	74	-33.63

GFSK Middle Channel (2440MHz)

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4880	28.44	AV	V	15.32	7.14	16.34	34.46	54	-19.54
4880	29.06	AV	H	15.32	7.14	16.34	35.17	54	-18.83
4880	31.32	PK	V	15.32	7.14	16.34	36.45	74	-37.55
4880	32.57	PK	H	15.32	7.14	16.34	33.58	74	-40.42
16753	27.49	AV	V	24.08	8.25	21.49	42.1	54	-11.9
16753	28.05	AV	H	24.08	8.25	21.49	38.3	54	-15.7
16753	33.26	PK	V	24.08	8.25	21.49	39.89	74	-34.11
16753	35.08	PK	H	24.08	8.25	21.49	41.52	74	-32.48

GFSK High Channel (2480MHz)

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4960	27.63	AV	V	14.05	7.86	13.64	35.9	54	-18.1
4960	28.04	AV	H	14.05	7.86	13.64	36.31	54	-17.69
4960	30.11	PK	V	14.05	7.86	13.64	37.41	74	-36.59
4960	32.69	PK	H	14.05	7.86	13.64	34.31	74	-39.69
17248	28.49	AV	V	20.47	8.83	20.44	39.04	54	-14.96
17248	29.15	AV	H	20.47	8.83	20.44	38.35	54	-15.65
17248	31.62	PK	V	20.47	8.83	20.44	36.9	74	-37.1
17248	32.57	PK	H	20.47	8.83	20.44	38.04	74	-35.96

Note: 1. The testing has been conformed to 10*2480MHz=24800MHz.

2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit

Test Frequency: From 18GHz to 25GHz

The measurements were more than 20dB below the limit and not reported.



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test Mode: BLE Low Channel 2402MHz									Test Value
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	
2310.00	32.11	28.11	6.73	37.12	29.83	74.00	-44.17	V	Peak
2390.00	34.08	28.04	6.92	38.06	30.98	74.00	-43.02	V	
2310.00	30.15	28.11	6.73	37.12	27.87	74.00	-46.13	H	
2390.00	33.29	28.04	6.92	38.06	30.19	74.00	-43.81	H	
2310.00	28.42	28.11	6.73	37.12	26.14	54.00	-27.86	V	Average
2390.00	29.16	28.04	6.92	38.06	26.06	54.00	-27.94	V	
2310.00	27.46	28.11	6.73	37.12	25.18	54.00	-28.82	H	
2390.00	28.65	28.04	6.92	38.06	25.55	54.00	-28.45	H	

Test Mode: BLE High Channel 2480MHz									Test Value
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	
2483.50	40.29	27.33	6.32	35.69	38.25	74.00	-35.75	V	Peak
2500.00	38.15	26.84	6.42	37.04	34.37	74.00	-39.63	V	
2483.50	41.32	27.33	6.32	35.69	39.28	74.00	-34.72	H	
2500.00	40.69	26.84	6.42	37.04	36.91	74.00	-37.09	H	
2483.50	38.65	27.33	6.32	35.69	36.61	54.00	-17.39	V	Average
2500.00	37.46	26.84	6.42	37.04	33.68	54.00	-20.32	V	
2483.50	36.29	27.33	6.32	35.69	34.25	54.00	-19.75	H	
2500.00	35.04	26.84	6.42	37.04	31.26	54.00	-22.74	H	



7 Band Edge Measurement

Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold



7.2 Test Result

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	1.50	-46.01	≤-18.5	PASS
		High	2480	0.33	-44.68	≤-19.67	PASS





8 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1 Test Procedure

1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100KHz, Set the Video Bandwidth(VBW)= 300KHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500KHz.
4. Measure and record the results in the test report.

8.2 Test Result

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.504	2401.676	2402.180	0.5	PASS
		2440	0.508	2439.672	2440.180	0.5	PASS
		2480	0.532	2479.664	2480.196	0.5	PASS



BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480





9 Maximum Peak Output Power

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

Test Limit : Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

9.1 Test Procedure

1. The RF output of EUT was connected to the power meter by RF cable . The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.

9.2 Test Result

Channel number	Channel Frequency(MHz)	Peak Power Output(dBm)	Peak Power Output(W)	Peak Power Limit(W)	Verdict
00	2402	0.31	0.001074	1	PASS
19	2440	1.01	0.001262	1	PASS
39	2480	1.04	0.001271	1	PASS



10 Power Spectral density

Test Requirement	: FCC CFR47 Part 15 Section 15.247
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

10.1 Test Procedure

1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW0 = 3KHz, Video Bandwidth (VBW) = 10KHz, in order to make an accurate measurement, set the span to 1.5 times DTS channel bandwidth.
4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
5. Measure and record the result in the test report.

10.2 Test Result

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-18.17	≤8.00	PASS
		2440	-18.84	≤8.00	PASS
		2480	-19.7	≤8.00	PASS



BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



Report No.: PTC22060201101E-FC01





11 Antenna Application

11.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2 Result

The EUT'S antenna, permanent attached antenna, is internal PCB antenna. The antenna's gain is dBi and meets the requirement.

*****THE END REPORT*****