



SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community,
Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V06
Report Template Revision Date: 2026-01-30

TEST REPORT

Report No. : CQASZ20260601264E-02
Applicant: Dongguan Yuaochen Technology Co., Ltd
Address of Applicant: Room 801, Building 2, No. 23, Dalingshan Section, Guanchang Road,
Dalingshan Town, Dongguan City, Guangdong Province
Equipment Under Test (EUT):
EUT Name: Action camera
Model No.: X20, X19
Test Model No.: X20
Brand Name: N/A
FCC ID: 2A7A8-X20
47 CFR Part 1.1307
Standards: 47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2026-06-18
Date of Test: 2026-06-18 to 2026-07-16
Date of Issue: 2026-07-22
Test Result : **PASS**

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1. Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260601264E-02	Rev.01	Initial report	2026-07-22

2. Contents

1. VERSION	2
2. CONTENTS	3
3. GENERAL INFORMATION	4
4. CLIENT INFORMATION	4
5. GENERAL DESCRIPTION OF EUT	4
6. GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	4
RF EXPOSURE EVALUATION	5
RF EXPOSURE COMPLIANCE REQUIREMENT	5
<i>Standard Requirement</i>	5
<i>Limits</i>	5
<i>EUT RF Exposure</i>	6

3. General Information

4. Client Information

Applicant:	Dongguan Yuaochen Technology Co., Ltd
Address of Applicant:	Room 801, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province
Manufacturer:	Dongguan Yuaochen Technology Co., Ltd
Address of Manufacturer:	Room 801, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province
Factory:	Dongguan Yuaochen Technology Co., Ltd
Address of Factory:	Room 801, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province

5. General Description of EUT

Product Name:	Action camera
Model No.:	X20, X19
Test Model No.:	X20
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Power Supply:	Li-ion battery DC 3.7V 1000mAh, Charge by DC 5V for adapter
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

6. General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)
Number of Channel:	IEEE 802.11b: 11 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps
Sample Type:	☐ Mobile ☒ Portable
Antenna Type:	PCB antenna
Antenna Gain:	0.41dBi

RF Exposure Evaluation

RF Exposure Compliance Requirement

Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

EUT RF Exposure

1) For 2.4G WIFI

Measurement Data

Worst case: 802.11b				
Test Channel	AV Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	2.19	2.5±1	3.5	2.24
Middle(2437MHz)	2.20	2.5±1	3.5	2.24
Highest(2462MHz)	1.70	2.0±1	3.0	2.00

Worst case: 802.11b			
Channel	Maximum tuneup Power (mW)	Calculated value	Exclusion threshold
Lowest (2412MHz)	2.239	0.695	3.0
Middle (2437MHz)	2.239	0.699	
Highest (2462MHz)	1.995	0.626	
Conclusion: the calculated value ≤3.0, SAR is exempted.			

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20260601264E-01

*** END OF REPORT ***