

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	Antenna Gain (dBi)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	32.88	-1.1	29.63	38.45	PASS
GSM850	190	5	33.04	-1.1	29.79	38.45	PASS
GSM850	251	5	33.00	-1.1	29.75	38.45	PASS
GSM1900	512	0	29.66	0.2	29.86	33.00	PASS
GSM1900	661	0	29.97	0.2	30.17	33.00	PASS
GSM1900	810	0	29.67	0.2	29.87	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	Antenna Gain (dBi)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	32.97	-1.1	29.72	38.45	PASS
GPRS850	128	5	2	30.63	-1.1	27.38	38.45	PASS
GPRS850	128	5	3	28.69	-1.1	25.44	38.45	PASS
GPRS850	128	5	4	26.77	-1.1	23.52	38.45	PASS
GPRS850	190	5	1	33.11	-1.1	29.86	38.45	PASS
GPRS850	190	5	2	30.90	-1.1	27.65	38.45	PASS
GPRS850	190	5	3	28.90	-1.1	25.65	38.45	PASS
GPRS850	190	5	4	26.99	-1.1	23.74	38.45	PASS
GPRS850	251	5	1	33.07	-1.1	29.82	38.45	PASS
GPRS850	251	5	2	30.98	-1.1	27.73	38.45	PASS
GPRS850	251	5	3	28.96	-1.1	25.71	38.45	PASS
GPRS850	251	5	4	26.97	-1.1	23.72	38.45	PASS
GPRS1900	512	0	1	29.67	0.2	29.87	33.00	PASS
GPRS1900	512	0	2	27.90	0.2	28.1	33.00	PASS
GPRS1900	512	0	3	26.50	0.2	26.7	33.00	PASS
GPRS1900	512	0	4	24.43	0.2	24.63	33.00	PASS
GPRS1900	661	0	1	29.98	0.2	30.18	33.00	PASS
GPRS1900	661	0	2	27.99	0.2	28.19	33.00	PASS
GPRS1900	661	0	3	26.60	0.2	26.8	33.00	PASS
GPRS1900	661	0	4	24.52	0.2	24.72	33.00	PASS
GPRS1900	810	0	1	29.72	0.2	29.92	33.00	PASS
GPRS1900	810	0	2	27.53	0.2	27.73	33.00	PASS
GPRS1900	810	0	3	26.13	0.2	26.33	33.00	PASS
GPRS1900	810	0	4	24.12	0.2	24.32	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	Antenna Gain (dBi)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	25.76	-1.1	22.51	38.45	PASS
EGPRS850	128	8	2	24.57	-1.1	21.32	38.45	PASS
EGPRS850	128	8	3	22.47	-1.1	19.22	38.45	PASS
EGPRS850	128	8	4	20.22	-1.1	16.97	38.45	PASS
EGPRS850	190	8	1	25.95	-1.1	22.7	38.45	PASS
EGPRS850	190	8	2	24.87	-1.1	21.62	38.45	PASS
EGPRS850	190	8	3	22.71	-1.1	19.46	38.45	PASS
EGPRS850	190	8	4	20.38	-1.1	17.13	38.45	PASS
EGPRS850	251	8	1	25.64	-1.1	22.39	38.45	PASS
EGPRS850	251	8	2	24.57	-1.1	21.32	38.45	PASS
EGPRS850	251	8	3	22.40	-1.1	19.15	38.45	PASS
EGPRS850	251	8	4	20.06	-1.1	16.81	38.45	PASS
EGPRS1900	512	2	1	26.82	0.2	27.02	33.00	PASS
EGPRS1900	512	2	2	25.49	0.2	25.69	33.00	PASS
EGPRS1900	512	2	3	23.92	0.2	24.12	33.00	PASS
EGPRS1900	512	2	4	21.88	0.2	22.08	33.00	PASS
EGPRS1900	661	2	1	27.03	0.2	27.23	33.00	PASS
EGPRS1900	661	2	2	25.63	0.2	25.83	33.00	PASS
EGPRS1900	661	2	3	24.18	0.2	24.38	33.00	PASS
EGPRS1900	661	2	4	22.03	0.2	22.23	33.00	PASS
EGPRS1900	810	2	1	26.67	0.2	26.87	33.00	PASS
EGPRS1900	810	2	2	25.32	0.2	25.52	33.00	PASS
EGPRS1900	810	2	3	23.79	0.2	23.99	33.00	PASS
EGPRS1900	810	2	4	21.83	0.2	22.03	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.6	13	PASS
EGPRS850	190	8	5.74	13	PASS
GSM1900	661	0	2.7	13	PASS
EGPRS1900	661	2	5.59	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24245	0.3172	---	PASS
GSM850	190	5	0.24447	0.3136	---	PASS
GSM850	251	5	0.24456	0.3150	---	PASS
EGPRS850	128	8	0.24234	0.3078	---	PASS
EGPRS850	190	8	0.24207	0.3090	---	PASS
EGPRS850	251	8	0.24366	0.3102	---	PASS
GSM1900	512	0	0.24351	0.3119	---	PASS
GSM1900	661	0	0.24413	0.3117	---	PASS
GSM1900	810	0	0.24301	0.3075	---	PASS
EGPRS1900	512	2	0.24437	0.3100	---	PASS
EGPRS1900	661	2	0.24361	0.3158	---	PASS
EGPRS1900	810	2	0.24606	0.3106	---	PASS

Test Graphs







Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	823.98	-15.66	-13	PASS
GSM850	251	5	849.02	-14.56	-13	PASS
EGPRS850	128	8	823.99	-21.77	-13	PASS
EGPRS850	251	8	849.01	-24.94	-13	PASS
GSM1900	512	0	1850.00	-16.37	-13	PASS
GSM1900	810	0	1910.02	-17.00	-13	PASS
EGPRS1900	512	2	1849.97	-27.14	-13	PASS
EGPRS1900	810	2	1910.02	-24.08	-13	PASS

Test Graphs






Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-54.97	-33	PASS
GSM850	128	5	0.15~30MHz	0.16	-42.99	-13	PASS
GSM850	128	5	30~1000MHz	931.49	-45.55	-13	PASS
GSM850	128	5	1000~10000MHz	1648.3	-28.89	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-54.41	-33	PASS
GSM850	190	5	0.15~30MHz	0.16	-44.33	-13	PASS
GSM850	190	5	30~1000MHz	965.02	-46.06	-13	PASS
GSM850	190	5	1000~10000MHz	1673.2	-28.53	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-53.21	-33	PASS
GSM850	251	5	0.15~30MHz	0.15	-42.05	-13	PASS
GSM850	251	5	30~1000MHz	469.38	-45.37	-13	PASS
GSM850	251	5	1000~10000MHz	1697.5	-28.81	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-54.68	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-41.44	-23	PASS
GSM1900	512	0	30~1000MHz	394.59	-46.98	-13	PASS
GSM1900	512	0	1000~18000MHz	16468.87	-22.22	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-54.74	-43	PASS
GSM1900	661	0	0.15~30MHz	0.15	-43.33	-23	PASS
GSM1900	661	0	30~1000MHz	390.13	-46.33	-13	PASS
GSM1900	661	0	1000~18000MHz	16199.13	-21.75	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-54.48	-43	PASS
GSM1900	810	0	0.15~30MHz	0.15	-40.16	-23	PASS
GSM1900	810	0	30~1000MHz	954.73	-46.77	-13	PASS
GSM1900	810	0	1000~18000MHz	16995.87	-22.05	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2504067







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	15.98	0.019101	±2.5	Pass
	-20	13.20	0.015778		
	-10	12.37	0.014786		
	0	14.08	0.016830		
	10	8.62	0.010304		
	20	12.59	0.015049		
	30	10.33	0.012348		
	40	9.91	0.011846		
	50	11.91	0.014236		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.50	14.46	0.017284	±2.5	Pass
	3.85	12.75	0.015240		
	4.40	13.62	0.016280		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	13.85	0.016555	±2.5	Pass
	-20	18.79	0.022460		
	-10	9.98	0.011929		
	0	11.46	0.013698		
	10	13.20	0.015778		
	20	15.98	0.019101		
	30	12.43	0.014858		
	40	11.95	0.014284		
	50	12.43	0.014858		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.50	12.40	0.014822	±2.5	Pass
	3.85	14.63	0.017487		
	4.40	14.40	0.017213		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	-2.42	-0.001287	Within authorized band for PCS 1900	Pass
	-20	12.62	0.006713		
	-10	14.72	0.007830		
	0	8.94	0.004755		
	10	19.50	0.010372		
	20	12.30	0.006543		
	30	9.46	0.005032		
	40	7.33	0.003899		
	50	3.84	0.002043		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.50	6.36	0.003383	Within authorized band for PCS 1900	Pass
	3.85	8.75	0.004654		
	4.40	5.78	0.003074		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	11.33	0.006027	Within authorized band for PCS 1900	Pass
	-20	6.75	0.003590		
	-10	3.94	0.002096		
	0	4.78	0.002543		
	10	-2.20	-0.001170		
	20	6.62	0.003521		
	30	9.14	0.004862		
	40	15.43	0.008207		
	50	12.33	0.006559		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.50	9.85	0.005239	Within authorized band for PCS 1900	Pass
	3.85	11.49	0.006112		
	4.40	2.20	0.001170		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

