

TEST REPORT

Applicant Name: Xiamen Longstar Lighting Co., Ltd
Address: NO. 4431, Min'an Avenue, Neicuo Town, Xiang'an District, Xiamen, China
Factory Name : LONGSTAR LIGHTING THAI BINH VIETNAM COMPANY LIMITED
Address: Lot D3, Lien Ha Thai Industrial Park (Green iP-1), Thai Binh Economic Zone, Thai Thuy Commune, Hung Yen Province, Vietnam
Report Number: 2601Q45975E-RF-00
FCC ID: 2A7EA-005RD

Test Standard (s)
FCC PART 15.249

Sample Description

Product Type: LED Lamp
Model No.: L14-PAR38GK5NS-12W
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2026/02/10
Issue Date: 2026/03/24

Test Result:

Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Wills Yu

Wills Yu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
SUPPORT CABLE DESCRIPTIONS	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
§1.1307 (B) (3) & §2.1091 - RF EXPOSURE.....	10
APPLICABLE STANDARD	10
FCC§15.203 - ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (A) - AC LINE CONDUCTED EMISSIONS.....	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER SETUP	12
TEST PROCEDURE.....	13
FACTOR & OVER LIMIT CALCULATION.....	13
TEST DATA.....	13
FCC§15.205, §15.209 & §15.249(A)(C)(D) - RADIATED EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE.....	20
FACTOR & OVER LIMIT/MARGIN CALCULATION.....	21
TEST DATA.....	21
FCC§15.215(C) - 20DB EMISSION BANDWIDTH	45
APPLICABLE STANDARD	45
TEST PROCEDURE.....	45
TEST DATA.....	46
EUT PHOTOGRAPHS	49
TEST SETUP PHOTOGRAPHS	50

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2601Q45975E-RF-00	Original Report	2026/03/24

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	5730-5870MHz
Maximum E-field strength	87.08dBuV/m@3m
Modulation Technique	CW
Antenna Specification [#]	3.5dBi (provided by the applicant)
Voltage Range	AC120V, 60Hz
Sample serial number	3HF3-1(5730MHz), 3HF3-2(5800MHz), 3HF3-3 (5870MHz) (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Objective

This test report is in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.215 and 15.249 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		52.29kHz(k=1.96, 95% level of confidence)
RF Frequency		81.235Hz(k=1.96, 95% level of confidence)
RF output power, conducted		1.57dB(k=1.96, 95% level of confidence)
Conducted Spurious Emission		2.48dB(k=1.96, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.46dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.72dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.66dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Horizontal)	5.10dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Vertical)	6.28dB(k=2, 95% level of confidence)
	1GHz - 6GHz	6.18dB(k=2, 95% level of confidence)
	6GHz - 18GHz	6.62dB(k=2, 95% level of confidence)
	18GHz - 40GHz	6.66dB(k=2, 95% level of confidence)
Temperature		$\pm 0.4^{\circ}\text{C}$
Humidity		$\pm 2\%$
Supply voltages		DC $\pm 0.4\%$; AC $\pm 1\%$

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, test firm registration No.: 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing by manufacturer.

Frequency Channel List#:

Channel No.	Frequency (MHz)
1	5730
2	5800
3	5870

EUT Exercise Software

No exercise software was used.

Equipment Modifications

No modifications were made to the unit tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Lamp holder	Unknown	Unknown

Support Cable Descriptions


Cable Description	Length (m)	From/Port	To
Un-shielding Un-Detachable AC Cable	1.2	Receptacle	AC Mains
Un-shielding Un-Detachable AC Cable	1.2	Lamp holder	LISN/Receptacle

Block Diagram of Test Setup

For AC Line Conducted Emissions:



For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) (3) & §2.1091	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
15.205, §15.209, §15.249(a)(c)(d)	Radiated Emissions& Outside of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2025/09/01	2026/08/31
Rohde & Schwarz	LISN	ENV216	101613	2025/09/18	2026/09/17
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2025/09/18	2026/09/17
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2025/09/18	2026/09/17
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR
Radiated Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2025/09/01	2026/08/31
Sonoma instrument	Pre-amplifier	310 N	186238	2025/09/08	2026/09/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Chamber A Cable	Cable A1	Cable A1	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A2	Cable A2	2025/09/08	2026/09/07
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Chamber A Cable	Cable A3	Cable A3	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A4	Cable A4	2025/09/08	2026/09/07
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
TDK	Chamber	Chamber A	2#	2023/07/12	2026/07/11
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2025/09/01	2026/08/31
A.H.System	Preamplifier	PAM-0118P	489	2025/09/08	2026/09/07
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	Chamber B Cable	Cable B1	Cable B1	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B2	Cable B2	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B3	Cable B3	2025/09/08	2026/09/07
JD	Filter Switch Unit	DT7220FSU	DS79906	2025/08/12	2026/08/11
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2025/08/12	2026/08/11
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/09/08	2026/09/07
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
Unknown	Chamber B Cable	Cable B4	Cable B4	2025/09/17	2026/09/16
Unknown	Chamber B Cable	Cable B5	Cable B5	2025/09/17	2026/09/16
TDK	Chamber	Chamber B	1#	2023/07/14	2026/07/13

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

§1.1307 (b) (3) & §2.1091 - RF EXPOSURE

Applicable Standard

According to FCC §2.1091 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance

1-mW Test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

Result

For worst case:

Mode	Frequency (MHz)	Maximum E-Field (dBuV/m@3m)	Maximum EIRP		1-mW Test Exemption
			(dBm)	(mW)	
SRD	5730-5870MHz	87.08	-8.12	0.15	Yes

Note: EIRP = E-Field – 95.2 @3m

Result: Compliant

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached and the antenna gain[#] is 3.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	Antenna Gain [#]	Impedance	Frequency Range
Microstrip patch	3.5dBi	50Ω	5730-5870MHz


Result: Compliant.

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data

Environmental Conditions


Temperature:	25.6 °C
Relative Humidity:	36 %
ATM Pressure:	101.6 kPa

The testing was performed by Macy Shi on 2026-03-13.

EUT operation mode: Transmitting

Note: The maximum E-Field strength channel: Middle Channel was tested.

AC 120V/60 Hz, Line



Condition: Line

Project : 2601Q45975E-RF


tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.150	24.28	43.90	9.60	10.02	56.00	-12.10	Average
2	0.150	41.40	61.02	9.60	10.02	66.00	-4.98	QP
3	0.156	20.28	39.90	9.60	10.02	55.67	-15.77	Average
4	0.156	40.11	59.73	9.60	10.02	65.67	-5.94	QP
5	0.170	15.95	35.57	9.60	10.02	54.95	-19.38	Average
6	0.170	34.98	54.60	9.60	10.02	64.95	-10.35	QP
7	0.186	9.11	28.74	9.60	10.03	54.22	-25.48	Average
8	0.186	33.67	53.30	9.60	10.03	64.22	-10.92	QP
9	0.212	8.30	27.93	9.60	10.03	53.12	-25.19	Average
10	0.212	28.03	47.66	9.60	10.03	63.12	-15.46	QP
11	0.229	5.89	25.52	9.60	10.03	52.48	-26.96	Average
12	0.229	30.71	50.34	9.60	10.03	62.48	-12.14	QP
13	0.253	1.17	20.80	9.60	10.03	51.65	-30.85	Average
14	0.253	29.22	48.85	9.60	10.03	61.65	-12.80	QP
15	0.292	3.11	22.74	9.60	10.03	50.47	-27.73	Average
16	0.292	26.60	46.23	9.60	10.03	60.47	-14.24	QP

	Freq	Read Level	Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
17	0.338	2.02	21.65	9.60	10.03	49.26	-27.61	Average
18	0.338	23.94	43.57	9.60	10.03	59.26	-15.69	QP

AC 120V/60 Hz, Neutral



Condition: neutral

Project : 2601Q45975E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.151	23.44	43.06	9.60	10.02	55.93	-12.87	Average
2	0.151	41.22	60.84	9.60	10.02	65.93	-5.09	QP
3	0.163	13.83	33.45	9.60	10.02	55.32	-21.87	Average
4	0.163	34.72	54.34	9.60	10.02	65.32	-10.98	QP
5	0.173	12.58	32.20	9.60	10.02	54.81	-22.61	Average
6	0.173	30.08	49.70	9.60	10.02	64.81	-15.11	QP
7	0.194	8.03	27.66	9.60	10.03	53.85	-26.19	Average
8	0.194	32.20	51.83	9.60	10.03	63.85	-12.02	QP
9	0.212	6.48	26.11	9.60	10.03	53.13	-27.02	Average
10	0.212	31.03	50.66	9.60	10.03	63.13	-12.47	QP
11	0.233	4.01	23.64	9.60	10.03	52.35	-28.71	Average
12	0.233	29.29	48.92	9.60	10.03	62.35	-13.43	QP
13	0.256	0.42	20.05	9.60	10.03	51.55	-31.50	Average
14	0.256	28.41	48.04	9.60	10.03	61.55	-13.51	QP
15	0.290	1.87	21.50	9.60	10.03	50.53	-29.03	Average
16	0.290	26.56	46.19	9.60	10.03	60.53	-14.34	QP

	Freq	Read Level	Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
17	0.313	0.74	20.37	9.60	10.03	49.88	-29.51	Average
18	0.313	24.98	44.61	9.60	10.03	59.88	-15.27	QP
19	0.356	-1.15	18.48	9.60	10.03	48.82	-30.34	Average
20	0.356	22.25	41.88	9.60	10.03	58.82	-16.94	QP

FCC§15.205, §15.209 & §15.249(a)(c)(d) - RADIATED EMISSIONS

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500



As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC§15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:**Above 1GHz:**

The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	PK
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	PK
Above 1 GHz	1MHz	3 MHz	/	PK	PK
	1MHz	≥10 Hz	/	Average	PK

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

According to ANSI C63.10-2020,9.2.1: For field strength measurements made at other than the distance specified by the limit, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance)

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dBμV/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dBμV/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB, for 18-40GHz range, the limit of 1m distance was added by 9.5dB from limit of 3m to compared with the result measurement at 1m distance.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit}; \text{Margin} = \text{Limit} - \text{Corrected Amplitude} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23.5~24.8 °C
Relative Humidity:	46~56 %
ATM Pressure:	100.9~101.6 kPa

The testing was performed by Anson Su on 2026-03-18 for below 1GHz and Wing K Ji on 2026-03-06 for above 1GHz.

EUT operation mode: Transmitting


Note:

For 9 kHz-30MHz, after pre-scan in the ground-parallel, perpendicular and parallel of orientation, the worst case parallel of orientation were recorded.

For 9 kHz-1GHz, when the test result of peak was less than the limit of QP/Average more than 6dB, just peak value was recorded.


After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.

9 kHz-30MHz: (The maximum E-Field strength channel: Middle Channel was tested.)



Site : Chamber A
Condition : 3m
Project Number : 2601Q45975E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	MHz	dB/m	Level			
			dBuV	dBuV/m	dBuV/m	dB
1	0.010	32.28	23.61	55.89	127.51	-71.62 Peak
2	0.019	30.57	23.79	54.36	121.99	-67.63 Peak
3	0.033	28.19	34.67	62.86	117.25	-54.39 Peak
4	0.066	24.82	30.67	55.49	111.25	-55.76 Peak
5	0.099	22.10	28.71	50.81	107.73	-56.92 Peak
6	0.131	20.15	28.00	48.15	105.24	-57.09 Peak




Site : Chamber A
Condition : 3m
Project Number : 2601Q45975E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.536	5.96	38.32	44.28	73.01	-28.73	Peak
2	0.605	5.10	38.40	43.50	71.93	-28.43	Peak
3	0.663	4.39	37.69	42.08	71.12	-29.04	Peak
4	0.817	2.57	38.16	40.73	69.27	-28.54	Peak
5	0.987	1.30	36.06	37.36	67.59	-30.23	Peak
6	1.198	0.65	33.56	34.21	65.87	-31.66	Peak

30MHz-1GHz: (The maximum E-Field strength channel: Middle Channel was tested.)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2601Q45975E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	Level	Level	Line	Limit	
			dBuV	dBuV/m	dBuV/m	dB	
1	30.80	-6.28	30.71	24.43	40.00	-15.57	Peak
2	120.70	-11.77	39.63	27.86	43.50	-15.64	Peak
3	131.41	-11.67	38.19	26.52	43.50	-16.98	Peak
4	192.67	-13.89	40.78	26.89	43.50	-16.61	Peak
5	307.56	-11.47	44.99	33.52	46.00	-12.48	Peak
6	365.86	-10.08	39.74	29.66	46.00	-16.34	Peak

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2601Q45975E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	MHz	dB/m	Level	Level	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	32.69	-7.36	42.51	35.15	40.00	-4.85 QP
2	35.64	-9.21	45.39	36.18	40.00	-3.82 QP
3	36.96	-10.21	44.20	33.99	40.00	-6.01 QP
4	38.36	-11.20	45.00	33.80	40.00	-6.20 QP
5	40.95	-13.04	46.29	33.25	40.00	-6.75 QP
6	43.66	-14.98	48.40	33.42	40.00	-6.58 QP

Above 1GHz:

Frequency (MHz)	Reading (dBμV)	PK/AV	Polar (H/V)	Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
11460.00	53.55	PK	H	3.53	57.08	74	-16.92
11460.00	39.05	AV	H	3.53	42.58	54	-11.42
11460.00	53.41	PK	V	3.53	56.94	74	-17.06
11460.00	39.18	AV	V	3.53	42.71	54	-11.29
Middle Channel							
11600.00	54.10	PK	H	3.19	57.29	74	-16.71
11600.00	39.67	AV	H	3.19	42.86	54	-11.14
11600.00	54.25	PK	V	3.19	57.44	74	-16.56
11600.00	40.11	AV	V	3.19	43.30	54	-10.70
High Channel							
11740.00	54.75	PK	H	3.95	58.70	74	-15.30
11740.00	40.16	AV	H	3.95	44.11	54	-9.89
11740.00	54.58	PK	V	3.95	58.53	74	-15.47
11740.00	39.95	AV	V	3.95	43.90	54	-10.10


Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit

The other spurious emission which is 20dB to the limit or in noise floor level was not recorded.


Test plots for Band Edge Measurements (Radiated):

Test Channel:

5730MHz

Ant. Polar. :

Horizontal-Average



Condition : Horizontal

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Average reading: RBW:1MHz VBW:10Hz Detector:Peak

Note : SRD_5730MHz


Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5723.885	-5.54	52.11	46.57	54.00	-7.43 Average
2 5725.000	-5.54	51.98	46.44	54.00	-7.56 Average
3 5730.342	-5.48	92.25	86.77	94.00	-7.23 Average

Test Channel:

5730MHz

Ant. Polar. :

Vertical-Peak



Condition : Vertical

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : SRD_5730MHz


	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5687.210	-5.80	66.26	60.46	74.00	-13.54	Peak
2	5725.000	-5.54	63.50	57.96	74.00	-16.04	Peak
3	5730.342	-5.48	91.85	86.37	114.00	-27.63	Peak

Test Channel:

5730MHz

Ant. Polar. :

Vertical-Average



Condition : Vertical

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Average reading: RBW:1MHz VBW:10Hz Detector:Peak

Note : SRD_5730MHz


	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5723.750	-5.54	52.08	46.54	54.00	-7.46	Average
2	5725.000	-5.54	51.95	46.41	54.00	-7.59	Average
3	5730.342	-5.48	90.92	85.44	94.00	-8.56	Average

Test Channel:

5800MHz

Ant. Polar. :

Horizontal



Condition : Horizontal

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : SRD_5800MHz


Freq Factor		Read Level	Level	Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5800.362	-5.09	92.17	87.08	114.00	-26.92	Peak

Test Channel:

5800MHz

Ant. Polar. :

Vertical



Condition : Vertical

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : SRD_5800MHz


Freq Factor		Read Level	Level	Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5800.313	-5.09	90.57	85.48	114.00	-28.52	Peak

Test Channel:

5870MHz

Ant. Polar. :

Horizontal-Peak



Condition : Horizontal

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : SRD_5870MHz


		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5870.388	-4.62	90.91	86.29	114.00	-27.71	Peak
2 5875.000	-4.61	64.69	60.08	74.00	-13.92	Peak
3 5876.763	-4.60	66.98	62.38	74.00	-11.62	Peak

Test Channel:

5870MHz

Ant. Polar. :

Horizontal-Average



Condition : Horizontal

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Average reading: RBW:1MHz VBW:10Hz Detector:Peak

Note : SRD_5870MHz


Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5870.350	-4.62	90.01	85.39	94.00	-8.61 Average
2 5875.000	-4.61	52.32	47.71	54.00	-6.29 Average
3 5948.275	-4.49	52.40	47.91	54.00	-6.09 Average

Test Channel:

5870MHz

Ant. Polar. :

Vertical-Peak



Condition : Vertical

Project No. : 2601Q45975E-RF

Tester : Wing K Ji

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : SRD_5870MHz


	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5870.388	-4.62	90.06	85.44	114.00	-28.56	Peak
2	5875.000	-4.61	64.07	59.46	74.00	-14.54	Peak
3	5886.700	-4.55	67.63	63.08	74.00	-10.92	Peak

Test Channel:

5870MHz

Ant. Polar. :

Vertical-Average



Condition : Vertical

Project No. : 2601Q45975E-RF


Tester : Wing K Ji


Spectrum setting: Average reading: RBW:1MHz VBW:10Hz Detector:Peak


Note : SRD_5870MHz


	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5870.350	-4.62	89.80	85.18	94.00	-8.82	Average
2	5875.000	-4.61	52.35	47.74	54.00	-6.26	Average
3	5942.744	-4.49	52.42	47.93	54.00	-6.07	Average


Listed with the worst case test plot:




















FCC§15.215(c) - 20dB EMISSION BANDWIDTH

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


Test Procedure

Test Method: ANSI C63.10-2020 Clause 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max-hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Environmental Conditions

Temperature:	23.5 °C
Relative Humidity:	56 %
ATM Pressure:	101.6 kPa


The testing was performed by Wing K Ji on 2026-03-06.

EUT operation mode: Transmitting

Please refer to the following table and plots.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	5730	0.1325
Middle	5800	0.1350
High	5870	0.1325


Low channel



ProjectNo.:2601Q45975E-RFTester:Wing K Ji

Date: 6.MAR.2026 11:13:09


Middle Channel



ProjectNo.:2601Q45975E-RFTester:Wing K Ji

Date: 6.MAR.2026 11:30:15

High Channel



ProjectNo.:2601Q45975E-RFTester:Wing K Ji
Date: 6.MAR.2026 11:42:08

Note: The TDF is the parameter of the Multiplex Switch Test Control Set and does not include the antenna factor, cable loss and amplifier factor.

EUT PHOTOGRAPHS

Please refer to the attachment 2601Q45975E-RF-EXP External photo and 2601Q45975E-RF-INP Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2601Q45975E-RF-00-TSP Test Setup photo.

******* END OF REPORT *******