


2.4G-2.48G 频段板载 PIFA 天线测试报告


SPECIFICATIONS

Frequency (MHz)	2400-2480
Peak Gain (dBi)	2.499
Average Gain (dBi)	>-4
VSWR	<3.2
Impedance (Ω)	50 Ω
Antenna Type	Plannar Inverted F Antenna on board
Polarization	Linear

测试环境：中科国技暗室测试系统




天线实物及物理尺寸



Manufacturer: Zhuhai senlee Electronic Technology co., Ltd
Address: 2nd Floor, Building 1, Yifeng Industrial Park, No. 19, Yongtian Road, Xiangzhou District, Zhuhai City, Guangdong, China


天线无源 S 参数：
驻波比（VSWR）、回波损耗（Return Loss）及史密斯圆图



天线效率及增益

Frequency (MHz)	Gain (dBi)	Effciency (%)	AverageGain (dBi)	Efficiency (dB)
2400	1.433	59.329%	-2.717	-2.267
2410	0.927	51.861%	-3.416	-2.852


2420	0.829	52.112%	-3.166	-2.831
2430	0.881	49.299%	-3.258	-3.072
2440	1.192	50.672%	-3.144	-2.952
2450	1.688	53.067%	-2.735	-2.752
2460	2.194	59.423%	-2.276	-2.260
2470	2.118	56.680%	-2.438	-2.466
2480	2.499	61.727%	-2.112	-2.095
Average	1.529	54.908%	-2.806	-2.616
Peak	2.499	61.727%	-2.112	-2.095





1.192
0.58
-0.13
-1.05
-1.96
-2.87
-3.78
-4.69
-5.61
-6.52
-7.43
-8.34
-9.26
-10.2
-11.1
-12
-12.9

2440MHz



2.499
1.69
0.78
-0.13
-1.05
-1.96
-2.87
-3.78
-4.69
-5.61
-6.52
-7.43
-8.34
-9.26
-10.2
-11.1
-12
-12.9

2480MHz

