RF Exposure Estimation

1. Introduction

Product: Bluetooth voice remote control
Model no.: NPA-RCU2
FCC ID: 2A7GQ-NPA-RCU2
The EUT is a Bluetooth voice remote control which contain BLE 1Mbps function inside.
Reference Report: 709502403575-00B

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to§15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation25
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

3. Calculation method

[(max. power of` channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·[√f(GHz)] ≤ 3.0

Conducted Power + tune up tolerance = 3.35dBm= 2.16mW
Distance = 5 mm
f = 2.402 GHz

[2.16/5] * SQRT (2.402) =0.6704
0.6704≤ 3.0
Therefore, excluded from SAR testing.

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:	Prepared by:	Tested by:
Hui TONG	Jiaxi XU	Chengjie GUO
EMC Section Manager	EMC Project Engineer	EMC Test Engineer
Date: 2024-06-11	Date: 2024-06-11	Date: 2024-06-11