



# FCC Test Report

Report No: FCS202206146W01

Issued for

|                                                                                                                                                                                                                                                                          |                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Applicant:                                                                                                                                                                                                                                                               | Commbax Sdn Bhd                                                                      |
| Address:                                                                                                                                                                                                                                                                 | E-01-03, Sekitar 26 Enterprise, Seksyen 26 40400 Shah Alam, Selangor Darul, Malaysia |
| Product Name:                                                                                                                                                                                                                                                            | Speaker System                                                                       |
| Brand Name:                                                                                                                                                                                                                                                              | EIKI                                                                                 |
| Model Name:                                                                                                                                                                                                                                                              | EBS10                                                                                |
| Series Model:                                                                                                                                                                                                                                                            | EIKI-SPK01,EIKI-SPK02,EIKI-SP01,EIKI-SP02,<br>EIKI-SS01,EBS20,EBS30,EBS40            |
| FCC ID:                                                                                                                                                                                                                                                                  | 2A7I3-EBS10                                                                          |
| Issued By: Flux Compliance Service Laboratory<br>Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan<br>Tel: 769-27280901 Fax:769-27280901 <a href="http://www.FCS-lab.com">http://www.FCS-lab.com</a> |                                                                                      |

## TEST RESULT CERTIFICATION

Applicant's Name.....: Commbax Sdn Bhd

Address.....: E-01-03, Sekitar 26 Enterprise, Seksyen 26 40400 Shah Alam, Selangor Darul, Malaysia

Manufacture's Name.....: Commbax Sdn Bhd

Address.....: E-01-03, Sekitar 26 Enterprise, Seksyen 26 40400 Shah Alam, Selangor Darul, Malaysia

### Product Description

Product Name.....: Speaker System

Brand Name.....: EIKI

Model Name.....: EBS10

Series Model.....: EIKI-SPK01,EIKI-SPK02,EIKI-SP01,EIKI-SP02,  
EIKI-SS01,EBS20,EBS30,EBS40

Test Standards.....: FCC Rules and Regulations Part 15 Subpart C, Section 247

Test Procedure.....: ANSI C63.10:2013

This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document..

### Date of Test.....:

Date (s) of performance of tests.: June 21, 2022 ~ July 07, 2022

Date of Issue.....: July 07, 2022

Test Result.....: Pass

Tested by : Scott shen  
(Scott Shen)

Reviewed by : Duke Qian  
(Duke Qian)

Approved by : Jack Wang  
(Jack Wang)



| Table of Contents                                                 | Page      |
|-------------------------------------------------------------------|-----------|
| <b>1. SUMMARY OF TEST RESULTS .....</b>                           | <b>6</b>  |
| 1.1 TEST FACTORY .....                                            | 7         |
| 1.2 MEASUREMENT UNCERTAINTY .....                                 | 7         |
| <b>2. GENERAL INFORMATION .....</b>                               | <b>8</b>  |
| 2.1 GENERAL DESCRIPTION OF THE EUT .....                          | 8         |
| 2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED ..... | 10        |
| 2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS .....  | 11        |
| 2.4 EQUIPMENTS LIST .....                                         | 12        |
| <b>3 CONDUCTED EMISSION MEASUREMENT .....</b>                     | <b>13</b> |
| <b>4. 20 DB BANDWIDTH .....</b>                                   | <b>17</b> |
| 4.1 Limit .....                                                   | 17        |
| 4.2 Test Procedure .....                                          | 17        |
| 4.3 Test setup .....                                              | 17        |
| 4.4 Test results .....                                            | 17        |
| 4.5 Original Test Data .....                                      | 18        |
| <b>5. CONDUCTED OUTPUT POWER .....</b>                            | <b>20</b> |
| 5.1 LIMIT .....                                                   | 20        |
| 5.3 TEST SETUP .....                                              | 20        |
| 5.5 TEST RESULTS .....                                            | 20        |
| <b>6 NUMBER OF HOPPING CHANNEL .....</b>                          | <b>23</b> |
| 6.1 LIMIT .....                                                   | 23        |
| 6.2 TEST PROCEDURE .....                                          | 23        |
| 5.3 TEST SETUP .....                                              | 23        |
| 6.4 EUT OPERATION CONDITIONS .....                                | 23        |
| 6.5 TEST RESULTS .....                                            | 24        |
| <b>7. BAND EDGE AND SPURIOUS(CONDUCTED) .....</b>                 | <b>24</b> |
| 7.1 LIMIT .....                                                   | 24        |
| 7.2 TEST PROCEDURE .....                                          | 25        |
| 7.3 TEST SETUP .....                                              | 25        |
| 7.4 TEST RESULTS .....                                            | 26        |
| 7.5 Original test data .....                                      | 26        |

| Table of Contents                                      | Page      |
|--------------------------------------------------------|-----------|
| 7.6 For Hopping Band edge .....                        | 29        |
| <b>8. RADIATED EMISSION MEASUREMENT .....</b>          | <b>30</b> |
| 8.1 RADIATED EMISSION LIMITS .....                     | 30        |
| 8.2 TEST PROCEDURE .....                               | 31        |
| 8.3 TESTSETUP .....                                    | 32        |
| 8.4. TEST RESULTS .....                                | 34        |
| 8.5 (30MHZ-1000MHZ) .....                              | 35        |
| ■ 8.6 ABOVE 1GHZ .....                                 | 37        |
| 8.7 RADIATED BAND EDGE DATA .....                      | 40        |
| <b>9. AVERAGE TIME OF OCCUPANCY .....</b>              | <b>41</b> |
| 9.1 LIMIT .....                                        | 41        |
| 9.2 TEST PROCEDURE .....                               | 41        |
| 9.3 TEST SETUP .....                                   | 41        |
| 9.4 TEST RESULTS .....                                 | 42        |
| 9.5 ORIGINAL TEST DATA .....                           | 42        |
| <b>10. HOPPING CHANNEL SEPARATION MEASUREMEN .....</b> | <b>46</b> |
| 10.1 LIMIT .....                                       | 46        |
| 10.2 TEST PROCEDURE .....                              | 46        |
| 10.3 TEST SETUP .....                                  | 46        |
| 10.4 EUT OPERATION CONDITIONS .....                    | 46        |
| 10.5 TEST RESULTS .....                                | 47        |
| <b>11. ANTENNA REQUIREMENT .....</b>                   | <b>49</b> |
| 11.1 STANDARD REQUIREMENT .....                        | 49        |
| 11.2 RESULT .....                                      | 49        |

**Revision History**

| Rev. | Issue Date    | Effect Page | Contents |
|------|---------------|-------------|----------|
| 00   | July 07, 2022 | N/A         | N/A      |
|      |               |             |          |

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:  
KDB 558074 D01 15.247 Meas Guidance v05r02

| FCC Part 15.247,Subpart C        |                                         |          |        |
|----------------------------------|-----------------------------------------|----------|--------|
| Standard Section                 | Test Item                               | Judgment | Remark |
| 15.207                           | Conducted Emission                      | PASS     | --     |
| 15.247(a)(1)                     | Hopping Channel Separation              | PASS     | --     |
| 15.247 (b)(2)                    | Output Power                            | PASS     | --     |
| 15.209                           | Radiated Spurious Emission              | PASS     | --     |
| 15.247(d)                        | Conducted Spurious & Band Edge Emission | PASS     | --     |
| 15.247(a)(1 )(i)                 | Number of Hopping Frequency             | PASS     | --     |
| 15.247(a)(1)(i)                  | Dwell Time                              | PASS     | --     |
| 15.247(a)(1)                     | 20dB Bandwidth<br>99% Bandwidth         | PASS     | --     |
| 15.205                           | Restricted bands of operation           | PASS     | --     |
| Part 15.247(d)/part<br>15.209(a) | Band Edge Emission                      | PASS     | --     |
| 15.203                           | Antenna Requirement                     | PASS     | --     |

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.10-2013

## 1.1 TEST FACTORY

|                                                                                                                                                            |                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Company Name:                                                                                                                                              | Flux Compliance Service Laboratory                                                                               |
| Address:                                                                                                                                                   | Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan |
| Telephone:                                                                                                                                                 | +86-769-27280901                                                                                                 |
| Fax:                                                                                                                                                       | +86-769-27280901                                                                                                 |
| Laboray Accreditations                                                                                                                                     |                                                                                                                  |
| FCC Test Firm Registration Number: 514908<br>CNAS Number: L15566<br>Designation number: CN0127<br>A2LA accreditation number: 5545.01<br>ISED Number: 25801 |                                                                                                                  |

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

| No. | Item                                      | Uncertainty           |
|-----|-------------------------------------------|-----------------------|
| 1   | RF output power, conducted                | $\pm 0.71\text{dB}$   |
| 2   | Unwanted Emissions, conducted             | $\pm 2.988\text{ dB}$ |
| 3   | Conducted Emission (9KHz-150KHz)          | $\pm 4.13\text{ dB}$  |
| 4   | All emissions radiated (9KHz -30MHz)      | $\pm 3.1\text{ dB}$   |
| 5   | Conducted Emission (150KHz-30MHz)         | $\pm 4.74\text{ dB}$  |
| 6   | All emissions,radiated(<1G) 30MHz-1000MHz | $\pm 5.2\text{ dB}$   |
| 7   | All emissions,radiated 1GHz -18GHz        | $\pm 4.66\text{ dB}$  |
| 8   | All emissions,radiated 18GHz -40GHz       | $\pm 4.31\text{ dB}$  |

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF THE EUT

|                         |                                                                                                                                                                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name            | Speaker System                                                                                                                                                                                                                                              |
| Trade Name              | EIKI                                                                                                                                                                                                                                                        |
| Model Name              | EBS10                                                                                                                                                                                                                                                       |
| Series Model            | EIKI-SPK01,EIKI-SPK02,EIKI-SP01,EIKI-SP02,<br>EIKI-SS01,EBS20,EBS30,EBS40                                                                                                                                                                                   |
| Model Difference        | The above product with same circuit, PCB layout, electrical parts, materials and wiring structures, the materials of decorative accessories is same, For the product appearance difference, the size is the same, but the color of the product is different |
| Channel List            | Please refer to the Note 2.                                                                                                                                                                                                                                 |
| Operation frequency     | 2402MHz-2480MHz                                                                                                                                                                                                                                             |
| Modulation:             | GFSK                                                                                                                                                                                                                                                        |
| Channel number          | 79 CH                                                                                                                                                                                                                                                       |
| Transmitter rate:       | 1MHz                                                                                                                                                                                                                                                        |
| Power Supply            | DC 5V 2A                                                                                                                                                                                                                                                    |
| Battery                 | DC 7.4V                                                                                                                                                                                                                                                     |
| Hardware version number | LZ-A8MAIN-V1.0                                                                                                                                                                                                                                              |
| Software version number | 3.1.0                                                                                                                                                                                                                                                       |
| Connecting I/O Port(s)  | Please refer to the User's Manual                                                                                                                                                                                                                           |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 1       | 2402MHz   | 21      | 2422MHz   | 41      | 2442MHz   | 61      | 2462MHz   |
| 2       | 2403MHz   | 22      | 2423MHz   | 42      | 2443MHz   | 62      | 2463MHz   |
| ⋮       | ⋮         | ⋮       | ⋮         | ⋮       | ⋮         | ⋮       | ⋮         |
| 19      | 2420MHz   | 39      | 2440MHz   | 59      | 2460MHz   | 79      | 2480MHz   |
| 20      | 2421MHz   | 40      | 2441MHz   | 60      | 2461MHz   |         |           |

3. Table for Filed Antenna

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | NOTE    |
|------|-------|------------|--------------|-----------|------------|---------|
| 1    | NA    | N/A        | PCB Antenna  | N/A       | 1.0        | Antenna |

## 2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Block diagram of EUT configuration for test



Test software: the

 FCC Assist 1.0.2.2

— □ ×

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

| No. | Test model description |
|-----|------------------------|
| 1   | Low channel GFSK       |
| 2   | Middle channel GFSK    |
| 3   | High channel GFSK      |
| 4   | Hopping GFSK           |

Note:

1. All the test modes can be supply by battery, only the result of the worst case recorded in the report. GFSK mode is worst mode.
2. For radiated emission, 3 axis were chosen for testing for each applicable mode.
3. The EUT used fully charge battery when tested.
4. During the test, the dutycycle>98%, the test voltage was tuned from 85% to 115% of the Nominal rate supply votage, and found that the worst case was the nominal rated supply condition, So the report just shows that condition's data

### 2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

#### Necessary accessories

| Item | Equipment | Mfr/Brand | Model/Type No. | Serial No. | Note                                      |
|------|-----------|-----------|----------------|------------|-------------------------------------------|
| 1    | Adapter   |           |                | N/A        | this adapter is for testing only in repor |
|      |           |           |                |            |                                           |

#### Support units

| Item | Equipment | Mfr/Brand | Model/Type No. | Serial No. | Note |
|------|-----------|-----------|----------------|------------|------|
| N/A  | N/A       | N/A       | N/A            | N/A        | N/A  |
|      |           |           |                |            |      |

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

## 2.4 EQUIPMENTS LIST

### Radiation Test equipment

| Kind of Equipment                | Manufacturer               | Type No.     | Company No. | Last calibration | Calibrated until |
|----------------------------------|----------------------------|--------------|-------------|------------------|------------------|
| EMI Test Receiver                | R&S                        | ESRP 3       | FCS-E001    | 2022.02.10       | 2023.02.09       |
| Signal Analyzer                  | R&S                        | FSV40-N      | FCS-E012    | 2022.02.10       | 2023.02.09       |
| Active loop Antenna              | ZHINAN                     | ZN30900C     | FCS-E013    | 2022.02.10       | 2023.02.09       |
| Bilog Antenna                    | SCHWARZBECK                | VULB 9168    | FCS-E002    | 2022.02.10       | 2023.02.09       |
| Horn Antenna                     | SCHWARZBECK                | BBHA 9120D   | FCS-E003    | 2022.02.10       | 2023.02.09       |
| SHF-EHF Horn Antenna (18G-40GHz) | A-INFO                     | LB-180400-KF | FCS-E018    | 2022.02.10       | 2023.02.09       |
| Pre-Amplifier(0.1M-3G Hz)        | EMCI                       | EM330N       | FCS-E004    | 2022.02.10       | 2023.02.09       |
| Pre-Amplifier (1G-18GHz)         | N/A                        | TSAMP-0518SE | FCS-E014    | 2022.02.10       | 2023.02.09       |
| Pre-Amplifier (18G-40GHz)        | TERA-MW                    | TRLA-0400    | FCS-E019    | 2022.02.10       | 2023.02.09       |
| Temperature & Humidity           | HTC-1                      | victor       | FCS-E005    | 2022.02.10       | 2023.02.09       |
| Testing Software                 | EZ-EMC(Ver.STSLAB 03A1 RE) |              |             |                  |                  |

### Conduction Test equipment

| Kind of Equipment      | Manufacturer              | Type No. | Company No. | Last calibration | Calibrated until |
|------------------------|---------------------------|----------|-------------|------------------|------------------|
| EMI Test Receiver      | R&S                       | ESPI     | FCS-E020    | 2022.02.10       | 2023.02.09       |
| LISN                   | R&S                       | ENV216   | FCS-E007    | 2022.02.10       | 2023.02.09       |
| LISN                   | ETS                       | 3810/2NM | FCS-E009    | 2022.02.10       | 2023.02.09       |
| Temperature & Humidity | HTC-1                     | victor   | FCS-E008    | 2022.02.10       | 2023.02.09       |
| Testing Software       | EZ-EMC(Ver.EMC-CON 3A1.1) |          |             |                  |                  |

### RF Connected Test

| Kind of Equipment   | Manufacturer               | Type No. | Company No. | Last calibration | Calibrated until |
|---------------------|----------------------------|----------|-------------|------------------|------------------|
| MXA SIGNAL Analyzer | Keysight                   | N9020A   | FCS-E015    | 2022.02.10       | 2023.02.09       |
| Spectrum Analyzer   | Agilent                    | E4447A   | MY50180039  | 2022.02.10       | 2023.02.09       |
| Spectrum Analyzer   | R&S                        | FSV-40   | 101499      | 2022.02.10       | 2023.02.09       |
| Power Sensor        | Agilent                    | UX2021XA | FCS-E021    | 2022.02.10       | 2023.02.09       |
| Testing Software    | EZ-EMC(Ver.STSLAB 03A1 RE) |          |             |                  |                  |

### 3 CONDUCTED EMISSION MEASUREMENT

#### 3.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

| FREQUENCY (MHz) | Conducted Emission limit (dBuV) |           |
|-----------------|---------------------------------|-----------|
|                 | Quasi-peak                      | Average   |
| 0.15 -0.5       | 66 - 56 *                       | 56 - 46 * |
| 0.50 -5.0       | 56.00                           | 46.00     |
| 5.0 -30.0       | 60.00                           | 50.00     |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


#### 3.2 TEST PROCEDURE

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.3 TEST SETUP




Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


### 3.4 TEST RESULTS

|              |      |                    |                  |
|--------------|------|--------------------|------------------|
| Temperature: | 25°C | Relative Humidity: | 50%              |
| Test Mode:   | GFSK | Test Voltage:      | DC 5V by adapter |
| Result:      | L    | Result:            | Pass             |



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| 1   | 0.2355             | 49.17             | 9.53                  | 58.70            | 62.25           | 3.55           | QP     |
| 2   | 0.2355             | 18.65             | 9.53                  | 28.18            | 52.25           | 24.07          | AVG    |
| 3   | 0.3435             | 43.47             | 9.54                  | 53.01            | 59.12           | 6.11           | QP     |
| 4   | 0.3435             | 13.95             | 9.54                  | 23.49            | 49.12           | 25.63          | AVG    |
| 5   | 0.6134             | 35.57             | 9.56                  | 45.13            | 56.00           | 10.87          | QP     |
| 6   | 0.6134             | 24.36             | 9.56                  | 33.92            | 46.00           | 12.08          | AVG    |
| 7   | 0.6134             | 24.36             | 9.56                  | 33.92            | 46.00           | 12.08          | QP     |
| 8   | 1.2885             | 30.07             | 9.57                  | 39.64            | 56.00           | 16.36          | AVG    |
| 9   | 1.2885             | 6.95              | 9.57                  | 16.52            | 46.00           | 29.48          | QP     |
| 10  | 8.5155             | 31.86             | 9.62                  | 41.48            | 60.00           | 18.52          | AVG    |
| 11  | 8.5155             | 11.81             | 9.62                  | 21.43            | 50.00           | 28.57          | QP     |
| 12  | 17.6190            | 34.53             | 9.73                  | 44.26            | 60.00           | 15.74          | AVG    |

|              |      |                    |                  |
|--------------|------|--------------------|------------------|
| Temperature: | 25°C | Relative Humidity: | 50%              |
| Test Mode:   | GFSK | Test Voltage:      | DC 5V by adapter |
| Result:      | N    | Result:            | Pass             |



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| 1   | 0.1590             | 36.99             | 9.51                  | 46.50            | 65.52           | 19.02          | QP     |
| 2   | 0.1590             | 18.72             | 9.51                  | 28.23            | 55.52           | 27.29          | AVG    |
| 3   | 0.5865             | 38.13             | 9.56                  | 47.69            | 56.00           | 8.31           | QP     |
| 4   | 0.5865             | 22.32             | 9.56                  | 31.88            | 46.00           | 14.12          | AVG    |
| 5   | 1.5945             | 22.07             | 9.58                  | 31.65            | 56.00           | 24.35          | QP     |
| 6   | 1.5945             | 9.69              | 9.58                  | 19.27            | 46.00           | 26.73          | AVG    |
| 7   | 4.2810             | 21.59             | 9.63                  | 31.22            | 56.00           | 24.78          | QP     |
| 8   | 4.2810             | 8.51              | 9.63                  | 18.14            | 46.00           | 27.86          | AVG    |
| 9   | 11.8860            | 26.22             | 9.80                  | 36.02            | 60.00           | 23.98          | QP     |
| 10  | 11.8860            | 12.36             | 9.80                  | 22.16            | 50.00           | 27.84          | AVG    |
| 11  | 15.5130            | 32.86             | 9.80                  | 42.66            | 60.00           | 17.34          | QP     |
| 12  | 15.5130            | 18.68             | 9.80                  | 28.48            | 50.00           | 21.52          | AVG    |

Remark:

1. All readings are Quasi-Peak and Average values

## 4. 20 DB BANDWIDTH

### 4.1 Limit

| FCC Part15 (15.247) , Subpart C |                |       |                       |
|---------------------------------|----------------|-------|-----------------------|
| Section                         | Test Item      | Limit | Frequency Range (MHz) |
| 15.247a(1)                      | 20dB bandwidth | N/A   | 2400-2483.5           |

### 4.2 Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows

RBW: 30kHz

VBW: 100kHz

Detector Mode: AVG

Sweep time: auto

Trace mode Max hold

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.3 Test setup




### 4.4 Test results


| TestMode | Channel (MHz) | 20dB Bandwidth (KHz) | Verdict |
|----------|---------------|----------------------|---------|
| Lowest   | 2402MHz       | 920.4                | Pass    |
| Middle   | 2441MHz       | 1.007                | Pass    |
| Highest  | 2480MHz       | 1.029                | Pass    |

## 4.5 Original Test Data


### Low



### Middle



## High



## 5. CONDUCTED OUTPUT POWER


### 5.1 LIMIT

| FCC Part 15 Subpart C |                   |                  |                 |
|-----------------------|-------------------|------------------|-----------------|
| Section               | Test Item         | Limit            | Frequency Range |
| 15.247(b)(3)          | Peak output power | Power <1W(30dBm) | 2400-2483.5     |

§§

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)  
RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.


### 5.3 TEST SETUP



### 5.5 TEST RESULTS

| TestMode | Channel (MHz) | Result (dBm) | Limit (dBm) | Verdict |
|----------|---------------|--------------|-------------|---------|
| Lowest   | 2402MHz       | -10.38       | 21          | Pass    |
| Middle   | 2441MHz       | -13.436      | 21          | Pass    |
| Highest  | 2480MHz       | -15.085      | 21          | Pass    |


Low



Middle



High



## 6 NUMBER OF HOPPING CHANNEL

### 6.1 LIMIT


| FCC Part 15.247, Subpart C<br>RSS-247 Issue 2 |                           |       |                       |        |
|-----------------------------------------------|---------------------------|-------|-----------------------|--------|
| Section                                       | Test Item                 | Limit | Frequency Range (MHz) | Result |
| 15.247<br>(a)(1)(iii) RSS-247                 | Number of Hopping Channel | >15   | 2400-2483.5           | PASS   |

### 6.2 TEST PROCEDURE

a The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b Spectrum Setting: RBW= 100kHz, VBW=300kHz, Sweep time = Auto

### 5.3 TEST SETUP




### 6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 6.5 TEST RESULTS

|              |                         |                    |         |
|--------------|-------------------------|--------------------|---------|
| Temperature: | 25 °C                   | Relative Humidity: | 60%     |
| Test Mode:   | Hopping Mode -GFSK Mode | Test Voltage:      | DC 3.7V |



## 7. BAND EDGE AND SPURIOUS(CONDUCTED)

### 7.1 LIMIT

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

## 7.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

|                  |                              |
|------------------|------------------------------|
| Center frequency | DTS Channel center frequency |
| RBW:             | 100kHz                       |
| VBW:             | 300kHz                       |
| Span             | 1.5times the DTS bandwidth   |
| Detector Mode:   | Peak                         |
| Sweep time:      | auto                         |
| Trace mode       | Max hold                     |


(3) Establish Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

|                              |                                          |
|------------------------------|------------------------------------------|
| RBW:                         | 100kHz                                   |
| VBW:                         | 300kHz                                   |
| Span                         | Encompass frequency range to be measured |
| Number of measurement points | $\geq \text{span}/\text{RBW}$            |
| Detector Mode:               | Peak                                     |
| Sweep time:                  | auto                                     |
| Trace mode                   | Max hold                                 |

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

## 7.3 TEST SETUP




## 7.4 TEST RESULTS


|              |                 |        |
|--------------|-----------------|--------|
| Eut set mode | CH or Frequency | Result |
| GFSK         | CH1             | Pass   |
|              | CH79            | Pass   |

## 7.5 Original test data

### CH1 2402MHZ




### CH79 2480MHZ




## Spurious emissions


### Low Channel 30MHz-25GHz





### Middle Channel 30MHz-25GHz



# High Channel 30MHz-25GHz



## 7.6 For Hopping Band edge



## 8. RADIATED EMISSION MEASUREMENT

### 8.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

| FREQUENCY (MHz) | (dBuV/m) (at 3M) |         |
|-----------------|------------------|---------|
|                 | PEAK             | AVERAGE |
| Above 1000      | 74               | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

| Spectrum Parameter                    | Setting                         |
|---------------------------------------|---------------------------------|
| Attenuation                           | Auto                            |
| Detector                              | Peak/AV                         |
| Start Frequency                       | 1000 MHz(Peak/AV)               |
| Stop Frequency                        | 10th carrier hamonic(Peak/AV)   |
| RB / VB (emission in restricted band) | PK=1MHz / 1MHz, AV=1 MHz /10 Hz |