

< **Shenzhen Cnstar Electronic CO., LTD** >**Modular Transmitter Approval Request**

Federal Communications Commission  
 Equipment Authorization Branch  
 7435 Oakland Mills Road  
 Columbia, MD 21046

**Company name:** Shenzhen Cnstar Electronic CO., LTD  
**FCC ID:** 2A7I8HC03RFM

Gentlemen,

In accordance with 47CFR 15.212 Modular Transmitters and KDB 996369 D01 'Module Certification Guide v02'. FCC ID: 2A7I8HC03RFM has been examined against the following requirements.

Items to be covered by Single modular transmitters.

| <b>Requirement per 15.212 and KDB 996369 D01<br/>'Modular Certification Guide v02</b>                                                                                                                                        | <b>Explanation from Grantee</b><br>(do not write yes/no, but explain why product complies/how it is achieved)                                                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly                                | Yes, the products have a shield, Physical components and tuning capacitor(s) are assembly to the module and located internal to the shield.                          |
| 2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal                                                                        | Yes, The module has buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.                   |
| 3. The module must contain power supply regulation on the module                                                                                                                                                             | Yes, The modular transmitter has its own power supply regulation (LDOs circuit integrated in chipset CMT2300A).                                                      |
| 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) | Yes, The module contains a PR-SMA antenna.                                                                                                                           |
| 5. The module must demonstrate compliance in a stand-alone configuration                                                                                                                                                     | Yes, The module demonstrates compliance in a stand-alone configuration.                                                                                              |
| 6. The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements)                                                             | Yes, The module is labelled with its permanently affixed FCC ID label.                                                                                               |
| 7. The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee                                                         | Yes, The module complies with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee. |
| 8. The module must comply with RF exposure requirements                                                                                                                                                                      | Yes, The module complies with RF exposure requirements.                                                                                                              |

Items to be covered by Split modular transmitters.

| <b>Requirement per 15.212 and KDB 996369 D01<br/>'Modular Certification Guide v02</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <b>Explanation from Grantee</b><br>(do not write yes/no, but explain why product complies/how it is achieved) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| 9. Split modular transmitters must meet all the requirements of a single modular in above item1 and 5 for single modular approval requirements.                                                                                                                                                                                                                                                                                                                                                                                                                           | Not applicable                                                                                                |
| 10. Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signaling amplitude of 150 mV peak-to-peak.                                                                                                                                                                                                                                                                               | Not applicable                                                                                                |
| 11. Control information and other data may be exchanged between the transmitter control elements and radio front end.                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Not applicable                                                                                                |
| 12. The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.                                                                                                                                                                                                                                                                                                                                                                                                 | Not applicable                                                                                                |
| 13. Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization. | Not applicable                                                                                                |

**A limited modular approval (LMA) may be granted for single or split modular transmitters that comply partially with requirements above.**

**Name:** Ben Liao

**Date:** 2022-07-19

**Title:** Business Leader

**Signature of applicant**

