

|                                              |                                      |
|----------------------------------------------|--------------------------------------|
| Receive Sensitivity<br>(11n,20MHz) @10% PER  | - 54Mbps PER @ -74 dBm, typical      |
|                                              | - MCS=0 PER @ -92 dBm, typical       |
|                                              | - MCS=1 PER @ -89 dBm, typical       |
|                                              | - MCS=2 PER @ -86 dBm, typical       |
|                                              | - MCS=3 PER @ -83 dBm, typical       |
|                                              | - MCS=4 PER @ -80 dBm, typical       |
|                                              | - MCS=5 PER @ -77 dBm, typical       |
|                                              | - MCS=6 PER @ -74 dBm, typical       |
|                                              | - MCS=7 PER @ -72 dBm, typical       |
| Receive Sensitivity<br>(11n,40MHz) @10% PER  | - MCS=0 PER @ -90 dBm, typical       |
|                                              | - MCS=1 PER @ -87 dBm, typical       |
|                                              | - MCS=2 PER @ -84 dBm, typical       |
|                                              | - MCS=3 PER @ -81 dBm, typical       |
|                                              | - MCS=4 PER @ -78 dBm, typical       |
|                                              | - MCS=5 PER @ -75 dBm, typical       |
|                                              | - MCS=6 PER @ -72 dBm, typical       |
|                                              | - MCS=7 PER @ -70 dBm, typical       |
| Receive Sensitivity<br>(11ac,20MHz) @10% PER | - MCS=0, NSS1 PER @ -91 dBm, typical |
|                                              | - MCS=1, NSS1 PER @ -88 dBm, typical |
|                                              | - MCS=2, NSS1 PER @ -85 dBm, typical |
|                                              | - MCS=3, NSS1 PER @ -82 dBm, typical |
|                                              | - MCS=4, NSS1 PER @ -79 dBm, typical |
|                                              | - MCS=5, NSS1 PER @ -76dBm, typical  |
|                                              | - MCS=6, NSS1 PER @ -73 dBm, typical |
|                                              | - MCS=7, NSS1 PER @ -70 dBm, typical |
|                                              | - MCS=8, NSS1 PER @ -68 dBm, typical |
| Receive Sensitivity<br>(11ac,40MHz) @10% PER | - MCS=0, NSS1 PER @ -89 dBm, typical |
|                                              | - MCS=1, NSS1 PER @ -86 dBm, typical |
|                                              | - MCS=2, NSS1 PER @ -83 dBm, typical |
|                                              | - MCS=3, NSS1 PER @ -80 dBm, typical |
|                                              | - MCS=4, NSS1 PER @ -77 dBm, typical |
|                                              | - MCS=5, NSS1 PER @ -74 dBm, typical |
|                                              | - MCS=6, NSS1 PER @ -71 dBm, typical |
|                                              | - MCS=7, NSS1 PER @ -68 dBm, typical |
|                                              | - MCS=8, NSS1 PER @ -65 dBm, typical |
|                                              | - MCS=9, NSS1 PER @ -63 dBm, typical |