

RF EXPOSURE Test Report

Report No. : MTi260511003-0107E2
Date of issue : 2026-05-25
Applicant : CG Mobile SAS
Product : Wireless Headphones
Model(s) : SP-B04
Series model : Please refer to the remark
FCC ID : 2A7J2-GUBHB04

Shenzhen Microtest Co., Ltd.

TEST REPORT

Report No.: MTi260511003-0107E2

Series model : SP-B04 GUOBHP10HMBSK, SP-B04 GUOBHP10HMBSB,**Remark**

SP-B04 GUBHP10HMBSK, SP-B04 GUBHP10HMBSB,
SP-B04 GUBHP10HMBSP, SP-B04 GUBHP10HMBSU,
SP-B04 GUOBHP10HMBSP, SP-B04 GUOBHP10HMBSU,
SP-B04 GUOBHP10HMBSW, SP-B04 GUOBHP10HMBSS,
SP-B04 GUOBHP10HMBSD, SP-B04 GUOBHP10HMBSE,
SP-B04 GUOBHP10HMBST, SP-B04 GUOBHP10HMBSO,
SP-B04 GUOBHP10HMBSLB, SP-B04 GUBHP10HMBSW,
SP-B04 GUBHP10HMBSS, SP-B04 GUBHP10HMBSD,
SP-B04 GUBHP10HMBSE, SP-B04 GUBHP10HMBST,
SP-B04 GUBHP10HMBSO, SP-B04 GUBHP10HMBSLB,
SP-B04 GUOBHP10HMBTK, SP-B04 GUOBHP10HMBTB,
SP-B04 GUBHP10HMBTK, SP-B04 GUBHP10HMBTB,
SP-B04 GUBHP10HMBTP, SP-B04 GUBHP10HMBTU,
SP-B04 GUOBHP10HMBTP, SP-B04 GUOBHP10HMBTU,
SP-B04 GUOBHP10HMBTW, SP-B04 GUOBHP10HMBTS,
SP-B04 GUOBHP10HMBTD, SP-B04 GUOBHP10HMBTE,
SP-B04 GUOBHP10HMBTT, SP-B04 GUOBHP10HMBTO,
SP-B04 GUOBHP10HMBTLB, SP-B04 GUBHP10HMBTW,
SP-B04 GUBHP10HMBTS, SP-B04 GUBHP10HMBTD,
SP-B04 GUBHP10HMBTE, SP-B04 GUBHP10HMBTT,
SP-B04 GUBHP10HMBTO, SP-B04 GUBHP10HMBTLB,
SP-B04 GUOBHP10HMBCK, SP-B04 GUOBHP10HMBCB,
SP-B04 GUBHP10HMBCK, SP-B04 GUBHP10HMBCB,
SP-B04 GUBHP10HMBCP, SP-B04 GUBHP10HMBCU,
SP-B04 GUOBHP10HMBCP, SP-B04 GUOBHP10HMBCU,
SP-B04 GUOBHP10HMBCW, SP-B04 GUOBHP10HMBCS,
SP-B04 GUOBHP10HMBCD, SP-B04 GUOBHP10HMBCE,
SP-B04 GUOBHP10HMBCT, SP-B04 GUOBHP10HMBCO,
SP-B04 GUOBHP10HMBCLB, SP-B04 GUBHP10HMBCW,
SP-B04 GUBHP10HMBCS, SP-B04 GUBHP10HMBCD,
SP-B04 GUBHP10HMBCE, SP-B04 GUBHP10HMBCT,
SP-B04 GUBHP10HMBCO, SP-B04 GUBHP10HMBCLB,
SP-B04 DKOBHP10HMBHK, SP-B04 DKOBHP10HMBHB,
SP-B04 DKBHP10HMBHK, SP-B04 DKBHP10HMBHB,
SP-B04 DKBHP10HMBHP, SP-B04 DKBHP10HMBHU,
SP-B04 DKOBHP10HMBHP, SP-B04 DKOBHP10HMBHU,
SP-B04 DKOBHP10HMBHW, SP-B04 DKOBHP10HMBHS,

TEST REPORT

Report No.: MTi260511003-0107E2

SP-B04 DKOBHP10HMBHD, SP-B04 DKOBHP10HMBHE,
SP-B04 DKOBHP10HMBHT, SP-B04 DKOBHP10HMBHO,
SP-B04 DKOBHP10HMBHLK, SP-B04 DKOBHP10HMBHLB,
SP-B04 DKBHP10HMBHW, SP-B04 DKBHP10HMBHS,
SP-B04 DKBHP10HMBHD, SP-B04 DKBHP10HMBHE,
SP-B04 DKBHP10HMBHT, SP-B04 DKBHP10HMBHO,
SP-B04 DKBHP10HMBHLB, SP-B04 BMBHP10HMBHW,
SP-B04 BMBHP10HMBHS, SP-B04 BMBHP10HMBHD,
SP-B04 BMBHP10HMBHE, SP-B04 BMBHP10HMBHT,
SP-B04 BMBHP10HMBHO, SP-B04 BMBHP10HMBHLB,
SP-B04 BMBHP10HMBHLK, SP-B04 RBBHP10HMBHLK,
SP-B04 RBBHP10HMBHLV, SP-B04 HKBHP10HMBSK,
SP-B04 HKBHP10HMBSB, SP-B04 HKBHP10HMBSP,
SP-B04 HKBHP10HMBSU, SP-B04 HKBHP10HMBSE,
SP-B04 HKBHP10HMBST, SP-B04 LCBHP10HMBHW,
SP-B04 LCBHP10HMBHS, SP-B04 LCBHP10HMBHD,
SP-B04 LCBHP10HMBHE, SP-B04 LCBHP10HMBHT,
SP-B04 LCBHP10HMBHO, SP-B04 LCBHP10HMBHLB,
SP-B04 LCBHP10HMBHLK, SP-B04 KLBHP10HMBHW,
SP-B04 KLBHP10HMBHS, SP-B04 KLBHP10HMBHD,
SP-B04 KLBHP10HMBHE, SP-B04 KLBHP10HMBHT,
SP-B04 KLBHP10HMBHO, SP-B04 KLBHP10HMBHLB,
SP-B04 KLBHP10HMBHLK

Table of contents

1	Standalone SAR test exclusion considerations	6
2	SAR Test Exclusion Thresholds	7

TEST REPORT

Report No.: MTi260511003-0107E2



Test Result Certification

Applicant	CG Mobile SAS
Applicant Address	39 rue de Courcelles, 75008 Paris - France
Manufacturer	Shenzhen Jsound Technologies Co., Limited
Manufacturer Address	RM 401,601, Building 13, No.23,Songshanzai Rd, Xinhe Community, Fucheng Street, Longhua,Shenzhen,China
Factory	Shenzhen Jsound Technologies Co., Limited
Factory Address	RM 401,601, Building 13, No.23,Songshanzai Rd, Xinhe Community, Fucheng Street, Longhua,Shenzhen,China

Product description

Product name	Wireless Headphones
Trademark	GUESS/DKNY/BMW/ HELLO KITTY/KARL LAGERFELD/RED BULL /LACOSTE
Model name	SP-B04
Series Model(s)	Please refer to the remark
Standards	47 CFR Part 2.1093
Test method	KDB 447498 D01 v06

Testing Information

Date of test	2026-05-14 to 2026-05-18	
Test Result	Pass	
Prepared by:	James Qin	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

1 Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures.

When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion.

When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions.

- a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

- b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):

- 1) $\{[\text{Power allowed at } \textit{numeric threshold} \text{ for } 50 \text{ mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$ mW, for 100 MHz to 1500 MHz
- 2) $\{[\text{Power allowed at } \textit{numeric threshold} \text{ for } 50 \text{ mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$ mW, for > 1500 MHz and ≤ 6 GHz

- c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$

- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

2 SAR Test Exclusion Thresholds

We use 5mm as separation distance to calculated.

BR&EDR:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up	Result	1g SAR test exclusion threshold
				power(dBm)	calculation	
2402	GFSK	0.25	0 $\pm$ 1	1	0.3902	3
2441		0.96	0 $\pm$ 1	1	0.3934	3
2480		2.04	2 $\pm$ 1	3	0.6284	3
2402	$\pi/4$ -DQPSK	1.13	1 $\pm$ 1	2	0.4913	3
2441		1.68	1 $\pm$ 1	2	0.4952	3
2480		2.77	2 $\pm$ 1	3	0.6284	3

Conclusion:

For the max result: $0.6284 \leq 3.0$ for 1g SAR test exclusion threshold, No SAR is required.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****