

RF EXPOSURE Test Report

Report No. : MTi260430003-0108E2
Date of issue : 2026-07-28
Applicant : CG Mobile SAS
Product : Wireless Earphones
Model(s) : TP103B
Series model : Please refer to the remark
FCC ID : 2A7J2-TWS03B

Shenzhen Microtest Co., Ltd.

Series model : TP103B DKTWST3PUCPSLW, TP103B DKTWST3PUCPSLT,
TP103B DKTWST3PUCPSLE, TP103B DKTWST3PUCPSLK,
TP103B DKTWST3PUSPSLK, TP103B DKTWST3PUSPSLE,
TP103B DKTWST3PUSPSLH, TP103B DKTWST3PUSPSLW,
TP103B DKTWST3PUSPSLB, TP103B DKTWST3PUSPSLV,
TP103B DKTWST3PUSPSLBU, TP103B DKTWST3PUSPSLLB,
TP103B DKTWST3PUSPSLU, TP103B DKTWST3PUSPSLP,
TP103B DKTWST3PULPSLK, TP103B DKTWST3PULPSLE,
TP103B DKTWST3PULPSLH, TP103B DKTWST3PULPSLW,
TP103B DKTWST3PULPSLB, TP103B DKTWST3PULPSLV,
TP103B DKTWST3PULPSLBU, TP103B DKTWST3PULPSLLB,
TP103B DKTWST3PULPSLU, TP103B DKTWST3PULPSLP,
TP103B GUTWST3PUSPSLK, TP103B GUTWST3PUSPSLE,
TP103B GUTWST3PUSPSLH, TP103B GUTWST3PUSPSLW,
TP103B GUTWST3PUSPSLB, TP103B GUTWST3PUSPSLV,
TP103B GUTWST3PUSPSLBU, TP103B GUTWST3PUSPSLLB,
TP103B GUTWST3PUSPSLU, TP103B GUTWST3PUSPSLP,
TP103B GUTWST3PULPSLK, TP103B GUTWST3PULPSLE,
TP103B GUTWST3PULPSLH, TP103B GUTWST3PULPSLW,
TP103B GUTWST3PULPSLB, TP103B GUTWST3PULPSLV,
TP103B GUTWST3PULPSLBU, TP103B GUTWST3PULPSLLB,
TP103B GUTWST3PULPSLU, TP103B GUTWST3PULPSLP,
TP103B GUOTWST3PUSPSLK, TP103B GUOTWST3PUSPSLE,
TP103B GUOTWST3PUSPSLH, TP103B GUOTWST3PUSPSLW,
TP103B GUOTWST3PUSPSLB, TP103B GUOTWST3PUSPSLV,
TP103B GUOTWST3PUSPSLBU,
TP103B GUOTWST3PUSPSLLB, TP103B GUOTWST3PUSPSLU,
TP103B GUOTWST3PUSPSLP, TP103B GUOTWST3PULPSLK,
TP103B GUOTWST3PULPSLE, TP103B GUOTWST3PULPSLH,
TP103B GUOTWST3PULPSLW, TP103B GUOTWST3PULPSLB,
TP103B GUOTWST3PULPSLV, TP103B GUOTWST3PULPSLBU,
TP103B GUOTWST3PULPSLLB, TP103B GUOTWST3PULPSLU,
TP103B GUOTWST3PULPSLP, TP103B KLTWST3PUSPSLK,
TP103B KLTWST3PUSPSLE, TP103B KLTWST3PUSPSLH,
TP103B KLTWST3PUSPSLW, TP103B KLTWST3PUSPSLB,
TP103B KLTWST3PUSPSLV, TP103B KLTWST3PUSPSLP,
TP103B BMTWST3PUSPSLK, TP103B BMTWST3PUSPSLE,
TP103B BMTWST3PUSPSLH, TP103B BMTWST3PUSPSLW,
TP103B BMTWST3PUSPSLB, TP103B BMTWST3PUSPSLV,




**TP103B BMTWST3PUSPSLBU, TP103B LCTWST3PUSPSLK,
TP103B LCTWST3PUSPSLE, TP103B LCTWST3PUSPSLH,
TP103B LCTWST3PUSPSLW, TP103B LCTWST3PUSPSLB,
TP103B LCTWST3PUSPSLV, TP103B LCTWST3PUSPSLBU,
TP103B LCTWST3PUSPSLBN**

Table of contents

1	Standalone SAR test exclusion considerations	6
2	SAR Test Exclusion Thresholds	7

TEST REPORT

Report No.: MTi260430003-0108E2

Test Result Certification		
Applicant	CG Mobile SAS	
Applicant Address	39 rue de Courcelles, 75008 Paris - France	
Manufacturer	Shenzhen Jsound Technologies Co., Limited	
Manufacturer Address	RM 401, 601, Building 13, No.23, Songshanzai Rd, Xinhe Community, Fucheng Street, Longhua, Shenzhen, China	
Product description		
Product name	Wireless Earphones	
Trademark	DKNY/GUESS/KARL LAGERFELD /BMW/LACOSTE	
Model name	TP103B	
Series Model(s)	Please refer to the remark	
Standards	47 CFR Part 2.1093	
Test method	KDB 447498 D01 v06	
Testing Information		
Date of test	2026-05-11 to 2026-05-13	
Test Result	Pass	
Prepared by:	James Qin	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

1 Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures.

When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion.

When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions.

- a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

- b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):

- 1) $\{[\text{Power allowed at } \textit{numeric threshold} \text{ for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$ mW, for 100 MHz to 1500 MHz
- 2) $\{[\text{Power allowed at } \textit{numeric threshold} \text{ for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$ mW, for > 1500 MHz and ≤ 6 GHz

- c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$

- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

2 SAR Test Exclusion Thresholds

We use 5mm as separation distance to calculated.

BR&EDR:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up	Result	1g SAR test exclusion threshold
				power(dBm)	calculation	
2402	GFSK	-2.53	-2 $\pm$ 1	-1	0.2462	3
2441		-3.17	-3 $\pm$ 1	-2	0.1972	3
2480		-2.91	-2 $\pm$ 1	-1	0.2502	3
2402	$\pi/4$ -DQPSK	-1.75	-1 $\pm$ 1	0	0.3100	3
2441		-2.36	-2 $\pm$ 1	-1	0.2482	3
2480		-2.03	-2 $\pm$ 1	-1	0.2502	3

Conclusion:

For the max result: $0.3100 \leq 3.0$ for 1g SAR test exclusion threshold, No SAR is required.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****