



RF TEST REPORT

Report No.:SHATBL2510016W04

Applicant : Shenzhen Jiutong Zhichuang Technology Co., Ltd.

Product Name : Wireless gaming headset

Brand Name : N/A

Model Name : Captain 200

Series Model : Captain 560,Axis 100,Axis 200,Axis 300,Axis 400,Axis 500,
Axis 600,Axis 700,Axis800,Axis900,Commander 1000,
Commander 2000,Commander 3000,Commander 4000,
Commander 5000,Commander 6000,Commander 7000,
Commander 8000,Commander 9000

FCC ID : 2A7JV-CT200

Test Standard : FCC CFR Title 47 Part 2.1093

Date of Receipt : Oct.23, 2025

Date of Test : Oct.23, 2025~Nov.05, 2025

Issue Date : Nov.05, 2025

Report Prepared by :

Emily

(Emily)

Report Approved by :

Guozheng Li

(Guozheng Li)

Authorized Signatory :

Terry Yang

(Terry Yang)



"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards, or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

Tel:+86(0)21-51298625

Web:www.atbl-lab.com

Email:atbl@atbl-lab.com

TABLE OF CONTENTS

DECLARATION OF REPORT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Factory	5
1.4. General Information of EUT	6
1.5. Laboratory Information	6
2. FCC 47CFR §2.1093 Requirement	7
2.1. Test Standards	7
2.2. Requirement	7
2.3. MPE Calculation Method	8
2.4. Antenna Information	8
2.5. Manufacturing Tolerance	8
2.6. Test Result	9

REVISION HISTORY

Rev.	Issue Date	Report No.	Effect Page	Contents
00	Nov.05, 2025	SHATBL2510016W04	ALL	Initial Release

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2.1093. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '☐' indicates that EUT does not support content after '☐', and '☑' indicates that it supports content after '☑'

1. GENERAL DESCRIPTION

1.1. Applicant

Name : Shenzhen Jiutong Zhichuang Technology Co., Ltd.
Address : Room 615, Building B, Xinshiyi Maker Park, No.111 Pingshan 1st Road,
Taoyuan Subdistrict, Nanshan District, Shenzhen, Guangdong Province, China

1.2. Manufacturer

Name : Shenzhen Jiutong Zhichuang Technology Co., Ltd.
Address : Room 615, Building B, Xinshiyi Maker Park, No.111 Pingshan 1st Road,
Taoyuan Subdistrict, Nanshan District, Shenzhen, Guangdong Province, China

1.3. Factory

Name : Dongguan Chilang Electronic Technology Co., Ltd.
Address : Room 202, Building 1, No. 19, Hengli Sugar Factory Road, Hengli Town,
Dongguan City, Guangdong Province

1.4. General Information of EUT

General Information	
Equipment Name	Wireless gaming headset
Brand Name	N/A
Model Name	Captain 200
Series Model	Captain 560,Axis 100,Axis 200,Axis 300,Axis 400,Axis 500, Axis 600,Axis 700,Axis 800,Axis 900,Commander 1000, Commander 2000,Commander 3000,Commander 4000, Commander 5000,Commander 6000,Commander 7000, Commander 8000,Commander 9000
Model Difference	Only model name and color are different.
Operation Frequency	BR/EDR:2402MHz~2480MHz LE_1Mbps :2402MHz~2480MHz 2.4G:2402MHz~2480MHz
Modulation Type	BR/EDR:GFSK/ π /4-DQPSK/8-DPSK LE 1Mbps :GFSK 2.4G :GFSK
Antenna gain	-0.58dBi
Antenna Designation	PCB Antenna
Power Source	DC 3.7V From Battery
Sample No	202510150011011
Battery	Rated Voltage:3.7V Charge Limit Voltage:4.2V Capacity:1000mAh
Hardware Version	V07
Software Version	V23

1.5. Laboratory Information

Company Name:	Shanghai ATBL Technology Co., Ltd.
Address:	Building 8, No. 160, Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone:	+86(0)21-51298625
FCC-Registration Number:	485917
Designation Number:	CN1306
A2LA-Lab Cert. No.:	6184.01

2. FCC 47CFR §2.1093 Requirement

2.1. Test Standards

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure requirement

KDB447498 v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

2.2. Requirement

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ "

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

2.4. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
Antenna0	/	PCB Antenna	-0.58dBi	2402MHz-2480MHz

2.5. Manufacturing Tolerance

Frequency (MHz)	ANT0_2.4GHz (Max Peak)		
	2402	2440	2480
Target (dBm)	-0.49	-0.22	-2.79
Tolerance ± (dB)	1.0	1.0	1.0

Note:

Maximum power Calculation(dBm) :P=Field strength-95.2

Frequency (MHz)	ANT0_Bluetooth LE(1Mbps)(Max Peak)		
	2402	2440	2480
Target (dBm)	4.54	3.79	2.74
Tolerance ± (dB)	1.0	1.0	1.0

Frequency (MHz)	ANT0_Bluetooth DR(Max Peak)		
	2402	2441	2480
Target (dBm)	4.69	3.76	3.56
Tolerance ± (dB)	1.0	1.0	1.0

2.6. Test Result

Mode	f (GHz)	Antenna Distance (mm)	Max.RF output power (including tune-up tolerance)		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
2.4GHz	2.402	5	0.78	1.19	0.37<3	Yes
Bluetooth LE	2.402	5	5.54	3.58	1.11<3	Yes
Bluetooth BR	2.402	5	5.69	3.70	1.14<3	Yes

Note:

- 1.The Maximum power is less than the limit, complies with the exemption requirements.
- 2.Output power (Peak) including turn-up tolerance.
- 3.The calculated distance is 5mm.
- 4.Simultaneous emission is not supported.

*****END OF THE REPORT*****