


2 in 3 Magnetic Charging Cable



iWatch Magentic Charger Manual

Technical Parameters

Length of Wire: 120CM MODEL: W9 FCC ID: 2A7KE-W9
External Material Quality : ABS+Nylon weave
Input Voltage & Current: 5V/3A
Output power : Type-C: 10W Lightning: 12W iWatch 2.5W (Max)
Effective transformation distance: 2mm
working frequency: 328KHz
Charging speed: Offer a fast charging speed about 2.5 hours.

Features

It can charge an iPhone (AirPods) and Apple Watch at the same time, compatible with the latest system of Apple Watch Ultra2\Ultra\SE\10\9\8\7\6\5\4\3\2 generation of the latest system, iPhone series 5-16 All Series



NOTE: To better protect from getting too hot, Please use the original adapter

FCC Statement

1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including interference that may cause undesired operation.

2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body.