# TEST REPORT

| | | |
|---|---|---|
| **Product Name** | : | VIBRATION PLATE |
| **Brand Name** | : | JOROTO |
| **Model** | : | JV80 |
| **Series Model** | : | N/A |
| **FCC ID** | : | 2A7MN-JV80 |
| **Applicant** | : | **Li'ang jian kang ke ji bei jing you xian gong si** |
| **Address** | : | beijing, fengtaiqu xijubeijie 26haoyuan 2 haolou 1ceng 1-4(01), beijing, China |
| **Manufacturer** | : | **Li'ang jian kang ke ji bei jing you xian gong si** |
| **Address** | : | beijing, fengtaiqu xijubeijie 26haoyuan 2 haolou 1ceng 1-4(01), beijing, China |
| **Standard(s)** | : | FCC CFR Title 47 Part 15 Subpart C Section 15.247 |
| **Date of Receipt** | : | Nov. 07, 2025 |
| **Date of Test** | : | Nov. 08, 2025~ Nov. 24, 2025 |
| **Issued Date** | : | Nov. 25, 2025 |

**Issued By:** **Guangdong Asia Hongke Test Technology Limited**
B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

**Reviewed by:** Aalen.Ye **Approved by:** Allen Wang

Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited. If there is a need to alter or revise this document, the right belongs to Guangdong Asia Hongke Test Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.

## Report Revise Record

| Report Version | Issued Date | Notes |
|---|---|---|
| M0 | Nov. 25, 2025 | Initial Release |

# Contents


**1 TEST SUMMARY ..... 4**

1.1 TEST STANDARDS ..... 4
1.2 TEST SUMMARY ..... 4
1.3 TEST FACILITY ..... 5
1.4 MEASUREMENT UNCERTAINTY ..... 5

**2 GENERAL INFORMATION ..... 6**

2.1 ENVIRONMENTAL CONDITIONS ..... 6
2.2 GENERAL DESCRIPTION OF EUT ..... 6
2.3 DESCRIPTION OF TEST MODES AND TEST FREQUENCY ..... 7
2.4 SPECIAL ACCESSORIES ..... 8
2.5 EQUIPMENT LIST FOR THE TEST ..... 8

**3 TEST CONDITIONS AND RESULTS ..... 10**

3.1 CONDUCTED EMISSIONS TEST ..... 10
3.2 RADIATED EMISSIONS AND BAND EDGE ..... 13
3.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER ..... 20
3.4 POWER SPECTRAL DENSITY ..... 21
3.5 6DB BANDWIDTH ..... 22
3.6 OUT-OF-BAND EMISSIONS ..... 23
3.7 ANTENNA REQUIREMENT ..... 25

**4 TEST SETUP PHOTOGRAPHS OF EUT ..... 错误!未定义书签。**

**5 EXTERNAL PHOTOGRAPHS OF EUT ..... 错误!未定义书签。**

**6 INTERNAL PHOTOGRAPHS OF EUT ..... 错误!未定义书签。**

# 1 TEST SUMMARY

## 1.1 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10: 2020: American National Standard for Testing Unlicensed Wireless Devices

KDB558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spreda Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules

## 1.2 Test Summary

| Test Item | Section in 47 CFR | Result |
|---|---|---|
| Antenna requirement | §15.203 | Pass |
| On Time and Duty Cycle | / | / |
| AC Power Line Conducted Emission | § 15.207(a) | Pass |
| Conducted Peak Output Power | §15.247 (b)(3) | Pass |
| Channel Bandwidth | §15.247 (a)(2) | Pass |
| Power Spectral Density | §15.247 (e) | Pass |
| Transmitter Radiated Spurious Emission | §15.205/15.209 | Pass |
| Restricted Bands | §15.205/15.209 | Pass |
| Conducted Unwanted emissions and Bandedge | §15.205, §15.247(d) | Pass |

## 1.3 Test Facility

**Test Laboratory:**
**Guangdong Asia Hongke Test Technology Limited**
B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:
**FCC-Registration No.: 251906 Designation Number: CN1376**
Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

**IC —Registration No.: 31737 CAB identifier: CN0165**
The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

**A2LA-Lab Cert. No.: 7133.01**
Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

## 1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the Guangdong Asia Hongke Test Technology Limited’s quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.
Hereafter the best measurement capability for Asia Hongke laboratory is reported:

| Test | Measurement Uncertainty | Notes |
|---|---|---|
| Power Line Conducted Emission | 9KHz~30MHz ±1.20 dB | (1) |
| Radiated Emission | 9KHz~30MHz ±3.10dB | (1) |
| Radiated Emission | 30MHz~1GHz ±3.75dB | (1) |
| Radiated Emission | 1GHz~18GHz ±3.88 dB | (1) |
| Radiated Emission | 18GHz-40GHz ±3.88dB | (1) |
| RF power, conducted | 30MHz~6GHz ±0.16dB | (1) |
| RF power density, conducted | ±0.24dB | (1) |
| Spurious emissions, conducted | ±0.21dB | (1) |
| Temperature | ±1℃ | (1) |
| Humidity | ±3% | (1) |
| DC and low frequency voltages | ±1.5% | (1) |
| Time | ±2% | (1) |
| Duty cycle | ±2% | (1) |

The report uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

# 2 GENERAL INFORMATION

## 2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|---|---|
| Normal Temperature: | 25°C |
| Relative Humidity: | 55 % |
| Air Pressure: | 101 kPa |

## 2.2 General Description of EUT

| | |
|---|---|
| Product Name: | VIBRATION PLATE |
| Model/Type reference: | JV80 |
| Serial Model: | N/A |
| Power Rating: | 100-240V~ 50/60Hz |
| Hardware Version: | N/A |
| Software Version: | N/A |
| Sample(s) Status: | AiTSZ-251107012-1(Normal sample)<br>AiTSZ-251107012-2(Engineer sample) |
| **Bluetooth LE:** | |
| Supported type: | Bluetooth LE 1M/2M |
| Modulation: | GFSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 40 |
| Channel separation: | 2MHz |
| Antenna type: | PCB antenna |
| Antenna gain: | 2.83dBi |
| **Remark:**<br>The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.. | |

## 2.3 Description of Test Modes and Test Frequency

There are 40 channels provided to the EUT and Channel 00/19/39 were selected to test.

**Operation Frequency List:**

| Channel | Frequency (MHz) |
|---|---|
| **00** | **2402** |
| 02 | 2404 |
| 03 | 2406 |
| ⋮ | ⋮ |
| **19** | **2440** |
| ⋮ | ⋮ |
| 37 | 2476 |
| 38 | 2478 |
| **39** | **2480** |

Note: The line display in grey were the channel selected for testing

Exploratory testing was performed under each mode combination test channel; only the final measurement of the worst combination was made and recorded in this report.

| **Test case** | **Exploratory measurement** | | | **Final measurement Recorded In Report** | | |
|---|---|---|---|---|---|---|
| | **Mode** | **Date rate** | **Channel** | **Mode** | **Date rate** | **Channel** |
| Maximum output power | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest |
| Power spectral density | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest |
| -6dB bandwidth | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest |
| Conducted Spurious Emissions | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest |
| Conducted Band edge | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Highest | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Highest |
| Radiated Band edge | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Highest | GFSK | LE 2M | ☒ Lowest<br>☒ Highest |
| Radiated Emissions Above 1GHz | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest |
| Radiated Emissions Below 1GHz | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 2M | ☒ Middle |
| Conducted Emissions 9KHz-30 MHz | GFSK | LE 1M<br>LE 2M | ☒ Lowest<br>☒ Middle<br>☒ Highest | GFSK | LE 2M | ☒ Middle |

**Power setting during the test:**

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters:

| Test Software Version | FCC_assist.exe | | |
|---|---|---|---|
| Frequency | 2402MHz | 2440MHz | 2480MHz |
| BLE | default | default | default |

## 2.4 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

| Description | Manufacturer | Model | Serial No. | Provided by | Other |
|---|---|---|---|---|---|
| / | / | / | / | / | / |
| / | / | / | / | / | / |

## 2.5 Equipment List for the Test

| Conducted Emission measurement | | | | | | |
|---|---|---|---|---|---|---|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal.Due |
| ☒1 | EMI Test Receiver | R&S | ESPI | 100771 | 2025.09.23 | 2026.09.22 |
| ☒2 | LISN | R&S | NNLK 8129 | 8130179 | 2025.09.23 | 2026.09.22 |
| ☒3 | ISN | TESEQ | T800 | 29429 | 2025.09.23 | 2026.09.22 |
| ☒4 | Pulse Limiter | R&S | ESH3-Z2 | 102789 | 2025.09.23 | 2026.09.22 |
| ☒5 | CE Software | EZ | EZ-EMC_CE | Ver.AIT-03A | N/A | N/A |

| Radiation Emission measurement | | | | | | |
|---|---|---|---|---|---|---|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal.Due |
| ☒1 | EMI Measuring Receiver | R&S | ESR | 101160 | 2025.09.23 | 2026.09.22 |
| ☒2 | Low Noise Pre Amplifier | SCHWARZBECK | BBV 9745 | 00282 | 2025.09.23 | 2026.09.22 |
| ☒3 | Low Noise Pre Amplifier | CESHENG | CSKJLNA231 016A | CSKJLNA23 1016A | 2025.09.23 | 2026.09.22 |
| ☒4 | Spectrum Analyzer | R&S | FSV40 | 101470 | 2025.09.23 | 2026.09.22 |
| ☒5 | Passive Loop | ETS | 6512 | 00165355 | 2024.08.29 | 2026.08.28 |
| ☒6 | TRILOG Super Broadband test Antenna | SCHWARZBECK | VULB9168 | 01434 | 2024.08.29 | 2027.08.28 |
| ☒7 | Broadband Horn Antenna | Schwarzbeck | BBHA 9120D | 452 | 2024.08.29 | 2027.08.28 |
| ☒8 | Horn Antenna 15-40GHz | SCHWARZBECK | BBHA9170 | BBHA91703 67 | 2024.08.28 | 2027.08.27 |
| ☒9 | 6dB Attenuator | JFW | 50FPE-006 | 4360846-949-1 | 2025.09.23 | 2026.09.22 |
| ☒10 | RE Software | EZ | EZ-EMC_RE | Ver.AIT-03A | N/A | N/A |

| RF Conducted measurement | | | | | | |
|---|---|---|---|---|---|---|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal.Due |
| ☒1 | Spectrum Analyzer | Agilent | N9020A | MY53421570 | 2025.09.23 | 2026.09.22 |
| ☐2 | Power Sensor | Agilent | 8481A | MY41097697 | 2025.09.23 | 2026.09.22 |
| ☐3 | Vector Signal Generator | Agilent | N5182A | MY50143009 | 2025.09.23 | 2026.09.22 |
| ☐4 | Analog signal generator | Agilent | E8257 | MY51554256 | 2025.09.23 | 2026.09.22 |
| ☐5 | Const Temp. & Humidity Chamber | Eastlab | YH-HW-408L | 23051109 | 2025.09.23 | 2026.09.22 |
| ☐6 | Wideband Radio communication tester | R&S | CMW500 | 1201.0002K50 | 2025.09.23 | 2026.09.22 |
| ☐7 | DC power supply | ZHAOXIN | RXN-305D-2 | 28070002559 | 2025.09.23 | 2026.09.22 |
| ☒8 | RF Test box | TST | TSTPASS | 21033016 | 2025.09.23 | 2026.09.22 |
| ☒9 | RF Software | TST | TSTPASS | Version 2.0 | N/A | N/A |
| ☐10 | RF Software | Cesheng | WCN Regulary | Ver 25.03.2901 | N/A | N/A |

Note: ☐ is not applicable in this Test Report. ☒ is applicable in this Test Report.

# 3 TEST CONDITIONS AND RESULTS

## 3.1 Conducted Emissions Test

**LIMIT**

| Frequency range (MHz) | Limit (dBuV) | |
|---|---|---|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

**TEST CONFIGURATION**




**TEST PROCEDURE**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a Floor-standing system; EUT is placed on the ground plane as per ANSI C63.10:2020
2. Support equipment, if needed, was placed as per ANSI C63.10:2020.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2020.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

## TEST RESULTS

Remark: Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

| Test Mode | BLE | Line: | L |
|---|---|---|---|




Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;
Measurement Result = Reading Level +Correct Factor;
Margin = Measurement Result- Limit

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|
| 1 | 0.1995 | 36.39 | 10.70 | 47.09 | 63.63 | -16.54 | QP |
| 2 | 0.1995 | 30.61 | 10.70 | 41.31 | 53.63 | -12.32 | AVG |
| 3 | 0.4425 | 19.19 | 10.69 | 29.88 | 47.01 | -17.13 | AVG |
| 4 | 0.4560 | 29.19 | 10.69 | 39.88 | 56.77 | -16.89 | QP |
| 5 | 0.6090 | 30.82 | 10.69 | 41.51 | 56.00 | -14.49 | QP |
| 6 | 0.6225 | 19.92 | 10.69 | 30.61 | 46.00 | -15.39 | AVG |
| 7 | 1.3560 | 31.56 | 10.69 | 42.25 | 56.00 | -13.75 | QP |
| 8 | 1.3560 | 26.34 | 10.69 | 37.03 | 46.00 | -8.97 | AVG |
| 9 | 7.2420 | 17.36 | 11.05 | 28.41 | 50.00 | -21.59 | AVG |
| 10 | 7.6560 | 28.47 | 11.05 | 39.52 | 60.00 | -20.48 | QP |
| 11 | 25.9980 | 29.32 | 11.79 | 41.11 | 50.00 | -8.89 | AVG |
| 12 | 26.0025 | 33.79 | 11.79 | 45.58 | 60.00 | -14.42 | QP |

| Test Mode | BLE | Line: | N |
|---|---|---|---|




Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;
Measurement Result = Reading Level +Correct Factor;
Margin = Measurement Result- Limit

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|
| 1 | 0.2006 | 28.29 | 10.69 | 38.98 | 53.59 | -14.61 | AVG |
| 2 | 0.2040 | 36.54 | 10.69 | 47.23 | 63.45 | -16.22 | QP |
| 3 | 0.2760 | 29.27 | 10.69 | 39.96 | 60.94 | -20.98 | QP |
| 4 | 0.2805 | 20.64 | 10.69 | 31.33 | 50.80 | -19.47 | AVG |
| 5 | 0.6180 | 19.94 | 10.68 | 30.62 | 46.00 | -15.38 | AVG |
| 6 | 0.6270 | 30.37 | 10.67 | 41.04 | 56.00 | -14.96 | QP |
| 7 | 1.3560 | 28.22 | 10.68 | 38.90 | 56.00 | -17.10 | QP |
| 8 | 1.3560 | 25.09 | 10.68 | 35.77 | 46.00 | -10.23 | AVG |
| 9 | 8.8932 | 29.30 | 11.07 | 40.37 | 60.00 | -19.63 | QP |
| 10 | 8.9923 | 19.16 | 11.07 | 30.23 | 50.00 | -19.77 | AVG |
| 11 | 25.9980 | 33.57 | 11.71 | 45.28 | 60.00 | -14.72 | QP |
| 12 | 26.0025 | 29.37 | 11.71 | 41.08 | 50.00 | -8.92 | AVG |

## 3.2 Radiated Emissions and Band Edge

**Limit**

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits

| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m) | Radiated (μV/m) |
|---|---|---|---|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

**TEST CONFIGURATION**

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz




Below 30MHz

(B) Radiated Emission Test Set-Up, Frequency below 1000MHz




Below 1GHz

(C) Radiated Emission Test Set-Up, Frequency above 1000MHz




Above 1GHz

## Test Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a Floor-standing system; EUT is placed on the ground plane as per ANSI C63.10:2020.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|---|---|---|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Bilog Antenna | 3 |
| 1GHz-18GHz | Horn Antenna | 3 |
| 18GHz-25GHz | Horn Anternna | 1 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|---|---|---|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz,Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz,Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz,Sweep time=Auto | QP |
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

## TEST RESULTS

Remark:
1. For below 1GHz testing recorded worst at BLE 2M middle channel.
2. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and The emission levels from 9kHz to 30MHz are attenuated 20dB below the limit and not recorded in report.

**For 30MHz-1GHz**

| Test mode: | BLE | Polarization: | Horizontal |
|---|---|---|---|




Remark:
Emission Level = Reading + Factor;
Factor = Antenna Factor + Cable Loss – Pre-amplifier;
Margin= Emission Level - Limit.

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|---|---|---|---|---|---|---|---|
| 1 | 79.8002 | 52.34 | -20.89 | 31.45 | 40.00 | -8.55 | peak |
| 2 | 152.6640 | 39.15 | -16.51 | 22.64 | 43.50 | -20.86 | peak |
| 3 | 181.9200 | 41.63 | -18.54 | 23.09 | 43.50 | -20.41 | peak |
| 4 | 304.6099 | 49.10 | -16.82 | 32.28 | 46.00 | -13.72 | peak |
| 5 | 390.7225 | 44.61 | -14.77 | 29.84 | 46.00 | -16.16 | peak |
| 6 | 922.5157 | 36.11 | -4.23 | 31.88 | 46.00 | -14.12 | peak |

| Test mode: | BLE | Polarization: | Vertical |
|---|---|---|---|




Remark:
Emission Level = Reading + Factor;
Factor = Antenna Factor + Cable Loss – Pre-amplifier;
Margin= Emission Level - Limit.

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|---|---|---|---|---|---|---|---|
| 1 | 78.4133 | 55.45 | -20.61 | 34.84 | 40.00 | -5.16 | peak |
| 2 | 135.9821 | 48.16 | -17.48 | 30.68 | 43.50 | -12.82 | peak |
| 3 | 187.0955 | 43.21 | -19.12 | 24.09 | 43.50 | -19.41 | peak |
| 4 | 309.9977 | 46.68 | -16.66 | 30.02 | 46.00 | -15.98 | peak |
| 5 | 570.6100 | 41.64 | -10.52 | 31.12 | 46.00 | -14.88 | peak |
| 6 | 689.5643 | 44.52 | -8.39 | 36.13 | 46.00 | -9.87 | peak |

***For 1GHz to 25GHz***

***BLE 2M GFSK (above 1GHz)***

| **Frequency(MHz):** | | **2402** | | **Polarity:** | **Horizontal** | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 4803.50 | 52.34 | -7.56 | 44.78 | 74 | -29.22 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 7206.00 | 45.38 | -1.64 | 43.74 | 74 | -30.26 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| **Frequency(MHz):** | | **2402** | | **Polarity:** | **VERTICAL** | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 4803.50 | 52.97 | -7.56 | 45.41 | 74 | -28.59 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 7206.00 | 45.42 | -1.64 | 43.78 | 74 | -30.22 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| **Frequency(MHz):** | | **2440** | | **Polarity:** | **Horizontal** | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 4879.25 | 51.29 | -6.76 | 44.53 | 74 | -29.47 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 7319.70 | 43.08 | -0.53 | 42.55 | 74 | -31.45 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| **Frequency(MHz):** | | **2440** | | **Polarity:** | **VERTICAL** | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 4879.25 | 51.76 | -6.76 | 45.00 | 74 | -29.00 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 7319.70 | 43.13 | -0.53 | 42.60 | 74 | -31.40 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| Frequency(MHz): | | 2480 | | Polarity: | Horizontal | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 4959.80 | 47.02 | -5.77 | 46.94 | 74 | -27.06 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 7439.65 | 46.47 | -0.51 | 44.03 | 74 | -29.97 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| Frequency(MHz): | | 2480 | | Polarity: | VERTICAL | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 4959.80 | 45.63 | -5.77 | 47.16 | 74 | -26.84 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 7439.65 | 45.02 | -0.51 | 44.11 | 74 | -29.89 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

REMARKS:

1. Emission level (dBuV/m) = Reading (dBuV)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Emission level- Limit value.
4. -- Mean the PK detector measured value is below average limit.
5. Other emission levels are attenuated 20dB below the limit and not recorded in report.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

***Radiation Restricted band***

***BLE 2M GFSK***

| Frequency(MHz): | | 2402 | | Polarity: | Horizontal | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2387.68 | 51.97 | -4.07 | 47.90 | 74 | -26.10 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 2390.00 | 40.62 | -4.10 | 45.61 | 74 | -28.39 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| Frequency(MHz): | | 2402 | | Polarity: | Vertical | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2389.23 | 52.26 | -4.09 | 48.17 | 74 | -25.83 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 2390.00 | 49.92 | -4.10 | 45.82 | 74 | -28.18 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| Frequency(MHz): | | 2480 | | Polarity: | Horizontal | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2483.50 | 53.02 | -3.09 | 49.93 | 74 | -24.07 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 2485.12 | 50.37 | -3.07 | 47.30 | 74 | -26.70 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

| Frequency(MHz): | | 2480 | | Polarity: | Vertical | |
|---|---|---|---|---|---|---|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
| (MHz) | (dBμV) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2483.50 | 53.32 | -3.09 | 50.23 | 74 | -23.77 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |
| 2487.36 | 50.89 | -3.04 | 47.85 | 74 | -26.15 | PEAK |
| -- | -- | -- | -- | -- | -- | AVG |

REMARKS:

1. Emission level (dBuV/m) = Reading (dBuV)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Emission level- Limit value.
4. -- Mean the PK detector measured value is below average limit.
5. Other emission levels are attenuated 20dB below the limit and not recorded in report.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

## 3.3 Maximum Peak Conducted Output Power

**Limit**

The maximum peak conducted output power shall not exceed 1.0 W.

**Test Procedure**

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

a) Set the RBW ≥ DTS bandwidth.

b) Set VBW ≥ 3×RBW

c) Set span ≥3×RBW

d) Sweep time = auto couple.

e) Detector = peak.

f) Trace mode = max hold.

g) Allow trace to fully stabilize.

h) Use peak marker function to determine the peak amplitude level.

**Test Configuration**




Note: For Conducted Measurement the final Conducted value (dBm) = Measurement value (dBm) + RF cable loss (dB)(the short RF cable connect EUT antenna port to the test equipment)
For example: the measurement value is 10 dBm and the short RF cable loss 0.5dB used (Provided by Applicant), then the final result of EUT: Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm

Input the cable Compensation value to the test software before test, then the software will calculate the final result automatically.

**Test Results**

☒ **Pass** ☐ **Not Applicable**

Note:
For test data, please refer to Appendix RF test data for BLE.

## 3.4 Power Spectral Density

**Limit**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

**Test Procedure**

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW ≥ 3× RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

**Test Configuration**




**Test Results**

☒ **Pass** ☐ **Not Applicable**

Note:
For test data, please refer to Appendix RF test data for BLE.

## 3.5 6dB Bandwidth

**Limit**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

**Test Procedure**

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Set EUT in transmitting mode.

a) Set Spectrum Analyzer to OBW measurement mode and set bandwidth mode with X set to 6 dB.

b) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.

c) Set the VBW ⩾ [3 ×RBW].

d) Detector = peak.

e) Sweep time = auto couple.

f) Trace mode = max hold.

Allow trace to fully stabilize

**Test Configuration**




**Test Results**

☒ **Pass** ☐ **Not Applicable**

Note:
For test data, please refer to Appendix RF test data for BLE.

## 3.6 Out-of-band Emissions

**Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF con-ducted or a radiated measurement, pro-vided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter com-plies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

**Test Procedure**

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Place the EUT on the table and set it in transmitting mode.

**Step 1: Reference level measurement using the following procedure:**

g) Set instrument center frequency to DTS channel center frequency.

h) Set the span to ⩾1.5 times the DTS bandwidth.

i) Set the RBW = 100 kHz.

j) Set the VBW ⩾ [3 ×RBW].

k) Detector = peak.

l) Sweep time = auto couple.

m) Trace mode = max hold.

n) Allow trace to fully stabilize.

o) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

**Step 2: Emission level measurement using the following procedure:**

a) Set the center frequency and span to encompass frequency range to be measured.

b) Set the RBW = 100 kHz.

c) Set the VBW ⩾ [3 × RBW].

d) Detector = peak.

e) Sweep time = auto couple.

f) Trace mode = max hold.

g) Allow trace to fully stabilize.

h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements of PSD level measured in step 1 Reference level measurement.

## Test Configuration




## Test Results

☒ **Pass** ☐ **Not Applicable**

Note:
For test data, please refer to Appendix RF test data for BLE.

## 3.7 Antenna Requirement

**Standard Applicable**

**For intentional device, according to FCC 47 CFR Section 15.203:**
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(b) (4):**
(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**Test Result**

The EUT use an integrated PCB antenna, the maximum gain is less than 6dBi.

# 4 Test Setup Photographs of EUT







# 5 Photos of EUT

Please refer to test Report No.: AiTSZ-251107012FW1.

********** **End of Report** **********