

承认书
APPROVAL

客 户

Shenzhen Excelland Technology Co. Ltd.

CUSTOMER

品 名 规 格

DESCRIPTION: 2.4G Antenna Internal Antenna

料 号

PART NO.: YG-TX2.4GM012

客 户 料 号

CUS PART NO.: NXX0000004306

日 期

DATE: 2022-09-01

深圳市圆规科技有限公司呈样签章

(Shenzhen Compass Technology Co., Ltd)

工 程 ENGINEERING DEPARTMENT	品 保 Q C DEPARTMENT	业 务 SALES DEPARTMENT
陈远平	王丰	肖尊元

客户承认签章

(Customer First Article Inspection Approval)


工 程 ENGINEERING DEPARTMENT	品 保 QC DEPARTMENT	采 购 PURCHASING DEPARTMENT
Hunter Wang	Dylan Liu	Winson Su

Shenzhen Compass Technology Co., Ltd

Contents

Cover page	1
Catalogue	2
1.Product 2D Drawing	3
2.Product Physical Picture.....	4
3.Electrical Performance.....	5
4.Environmental Performance Test	6
5.RF Coaxial Connector	7

1.Product 2D drawing



Shenzhen Compass Technology Co., Ltd


1. Pictures of products



2. Electrical performance


Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHIS (%)	Max (dB)	Min (dB)	irectivity (dBi)
2400	51.56	-2.88	1.01	-1.14	19.828	31.729	1.01	-11.4	3.88
2410	51.76	-2.86	1.21	-0.94	19.667	32.09	1.21	-11.1	4.07
2420	49.63	-3.04	1.06	-1.09	18.959	30.671	1.06	-10.6	4.1
2430	47	-3.28	0.88	-1.27	18.181	28.821	0.88	-10.42	4.16
2440	49.8	-3.03	1.15	-1	19.643	30.16	1.15	-11.76	4.18
2450	49.68	-3.04	1.16	-0.99	19.894	29.784	1.16	-15.74	4.2
2460	48.38	-3.15	1.08	-1.07	19.535	28.841	1.08	-20.03	4.23
2470	43.85	-3.58	0.68	-1.47	17.752	26.1	0.68	-18.57	4.26
2480	42.03	-3.76	0.46	-1.69	16.873	25.16	0.46	-14.23	4.23
2490	41.7	-3.8	0.42	-1.73	16.509	25.187	0.42	-11.35	4.22
2500	40.68	-3.91	0.3	-1.85	15.78	24.895	0.3	-9.43	4.21

2400.00MHz - 2500.00MHz Gain




Shenzhen Compass Technology Co., Ltd


2400.000MHz H




2400.000MHz E1




2400.000MHz E2




2410.000MHz H




2410.000MHz E1




2410.000MHz E2



2400.000MHz



2410.000MHz



Shenzhen Compass Technology Co., Ltd

Environmental Performance Test Items	Test Conditions	Specifications
Storage environment	The test temperature, humidity and air pressure without specification are as follows: 1. Temperature: - 40 °C ~ + 80 °C 2. Relative humidity: 45% - 85% 3. The air pressure is 86kpa-106kpa	Normal electrical and mechanical performance
High and low temperature test	Conduct 5 cycles between 70 °C and 40 °C, and then check the appearance quality under normal conditions for 1-2h.	The dimension shall meet the requirements and meet the mechanical and electrical performance
Constant damp heat resistance test	The relative humidity was $95 \pm 3\%$ and the test temperature was 40 °C. After 2 hours, The electrical performance shall be measured within 5 mins after the test article is taken out, and the test article shall be in normal condition Check the appearance quality for 1-2h under the part	The dimension shall meet the requirements and meet the mechanical and electrical performance
Vibration test	Vibration frequency range: 10-55Hz, displacement amplitude: 0.35mm, acceleration amplitude: 50.0m/s, frequency sweep cycle times: 30 times	Normal electrical and mechanical performance
Drop test	Free fall for 3 times in the direction of mutually perpendicular axes at a height of 1m	Normal electrical and mechanical performance

SMA射频同轴连接器

RF COAXIAL CONNECTORS

编号: 1101

主要技术特性 (TECHNICAL SPECIFICATIONS) :

温度范围 (Temp.range) :	-55~+155° C	
特性阻抗 (Impedance) :	50 Ω	
频率范围 (Frequency Range) :	DC~12.4GHz	
工作电压 (Working Voltage) :	335Vmax (有效值)	
耐压 (Withstand Voltage) :	1000V rms (海平面最小值)	
接触电阻 (Contact resistance) :		
	内导体之间 (Center Contact)	≤3m Ω
	外导体之间 (Outer Contact)	≤2m Ω
绝缘电阻 (Insulationresistance) :	≥5000mΩ	
电压驻波比 (VSWR) :	直式 (Right angle)	≤1.10
耐用性 (Durability) :	≥500次	

材料与涂覆 (MATERIAL AND PLATING) :

壳体 (Shell) :	黄铜 (Brass)	镀硬金 (Gold plated)
插针 (contact pin) :	黄铜 (brass)	镀硬金 (Gold plated)
插孔 (socket contact)	铍青铜 (brylliumbrass)	镀硬金 (Gold plated)
绝缘体 (Insulator) :	聚四氟乙烯 (PTFE)	
压接套 (Crimping suite) :	铜合金 (Copper alloy)	镀金 (Gold plated)
O型密封件 (O-ring sealing) :	硅橡胶 (6146 silastic)	