

RF Exposure Evaluation Report

Product : Wireless Smart Camera
Trade mark : ZWO
Model/Type reference : ASI585MC Air
Serial Number : N/A
Report Number : EED32Q81338805
FCC ID : 2A7R3-ASICA78
Date of Issue : Jul. 05, 2025
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1091
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF
Exposure Guidance v01
Test result : PASS

Prepared for:

SUZHOU ZWO CO., LTD.

**Building 2, Peninsula Life Plaza, Moon bay road 6 SuZhou
Industrial Park, JiangSu, China**

Prepared by:

Centre Testing International Group Co., Ltd.

**Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Keven Tan.

Keven Tan

Reviewed by:

Frazer. Li

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Date:

Jul. 05, 2025



Check No.: 7150290824

1 Version

Version No.	Date	Description
00	Jul. 05, 2025	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
3.4 TEST LOCATION	5
3.5 DEVIATION FROM STANDARDS	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
4 SAR EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure	6
4.1.3 EUT RF Exposure Evaluation	7

3 General Information

3.1 Client Information

Applicant:	SUZHOU ZWO CO., LTD.
Address of Applicant:	Building 2, Peninsula Life Plaza, Moon bay road 6 SuZhou Industrial Park, JiangSu, China
Manufacturer:	SUZHOU ZWO CO., LTD.
Address of Manufacturer:	Building 2, Peninsula Life Plaza, Moon bay road 6 SuZhou Industrial Park, JiangSu, China
Factory:	SUZHOU ZWO CO., LTD.
Address of Factory:	Building #2, DongJing Workshop, Suzhou Industrial Park

3.2 General Description of EUT

Product Name:	Wireless Smart Camera
Model No.(EUT):	ASI585MC Air
Trade Mark:	ZWO

3.3 Product Specification subjective to this standard

Frequency Range:	BLE/BT: 2402MHz~2480MHz 2.4G Wi-Fi: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz 5G Wi-Fi: U-NII-1: 5150-5250MHz U-NII-3:5745-5825MHz	
Modulation Type:	BLE: GFSK BT: GFSK, $\pi/4$ DQPSK, 8DPSK 2.4G Wi-Fi: IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM,QPSK,BPSK) 5G Wi-Fi: IEEE 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11n(HT20/HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac(VHT20/VHT40/VHT80): OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)	
Test Power Grade:	Default	
Test Software of EUT:	MobaXterm	
Antenna Type:	External Antenna	
Antenna Gain:	BLE/BT/2.4G Wi-Fi: 4.75dBi 5G Wi-Fi: U-NII-1: 5150-5250MHz 3.33 dBi U-NII-3:5745-5825MHz 3.72 dBi	
Power Supply:	Adapter:	Model: KPL-060F-VI INPUT:100~240V,50/60Hz OUTPUT:12V/5A
Sample Received Date:	Feb. 26, 2025	
Sample tested Date:	Feb. 26, 2025 to Mar. 21	

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

For Stand alone:

BLE:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
@2.4GHz	20	5.17	4.75	7.77	5.9841	3060	0.0020	Pass

BT:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
@2.4GHz	20	2.44	4.75	5.04	3.1915	3060	0.0010	Pass

2.4G Wi-Fi:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
@2.4GHz	20	12.85	4.75	15.45	35.0752	3060	0.0115	Pass

5G Wi-Fi:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
@5GHz	20	13.68	3.33	14.86	30.6196	3060	0.0100	Pass

Note:

- ① EIRP=conducted power+antenna gain;
- ② $ERP = EIRP - 2.15$;
- ③ $EIRP(dBm) = \text{Field strength of the fundamental signal}(dBuV/m@3m) - 95.23$;
- ④ $ERP(mW) = 10^{(ERP(dBm)/10)}$;
- ⑤ The estimation distance is 20cm;
- ⑥ The test data please refer to the report of EED32Q81338801, EED32Q81338802, EED32Q81338803, EED32Q81338804 and only the worst case data was recorded in the report.

For Simultaneous Transmission:

As MPE ratio (BLE+2.4G Wi-Fi)= 0.0044+0.0220=0.0264 < 1, it's deemed to fulfil the RF exposure requirement.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***