


# TEST REPORT

**Report No.** .....: **KS2206S2655E01**  
**FCC ID**.....: **2A7U3PROV2**  
**Applicant**.....: **RPG Brands, LLC**  
**Address**.....: 3515 East Atlanta Avenue Phoenix, Arizona, 85040, USA  
**Manufacturer**.....: RPG Brands, LLC  
**Address**.....: 3515 East Atlanta Avenue Phoenix, Arizona, 85040, USA  
**Product Name**.....: **Electric Fireplace**  
**Trade Mark**.....: MODERN FLAMES  
**Model/Type reference**.....: LPS-4414 V2  
**Standard**.....: **FCC CFR Title 47 Part 15 Subpart C Section 15.247**  
**Date of receipt of test sample**...: June 22, 2022  
**Date of testing**.....: June 22, 2022~July 09, 2022  
**Date of issue**.....: July 09, 2022  
**Result**.....: **PASS**

**Prepared by:**  
 ( Printed name+ signature)

Pai Zheng



**Approved by:**  
 ( Printed Name + Signature)

Sky Dong



**Testing Laboratory Name**.....: **KSIGN(Guangdong) Testing Co., Ltd.**

**Address**.....: West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by KSIGN. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to KSIGN within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely corresponds to the test sample.

| TABLE OF CONTENTS                                      | Page      |
|--------------------------------------------------------|-----------|
| <b>1.TEST SUMMARY .....</b>                            | <b>3</b>  |
| 1.1. TEST STANDARDS .....                              | 3         |
| 1.2. REPORT VERSION .....                              | 3         |
| 1.3. TEST DESCRIPTION .....                            | 4         |
| 1.4. TEST FACILITY .....                               | 5         |
| 1.5. MEASUREMENT UNCERTAINTY .....                     | 5         |
| 1.6. ENVIRONMENTAL CONDITIONS .....                    | 6         |
| <b>2. GENERAL INFORMATION .....</b>                    | <b>7</b>  |
| 2.1. GENERAL DESCRIPTION OF EUT .....                  | 7         |
| 2.2. OPERATION STATE .....                             | 8         |
| 2.3. MEASUREMENT INSTRUMENTS LIST .....                | 9         |
| 2.4. TEST SOFTWARE .....                               | 10        |
| <b>3. TEST ITEM AND RESULTS .....</b>                  | <b>11</b> |
| 3.1. ANTENNA REQUIREMENT .....                         | 11        |
| 3.2. PEAK OUTPUT POWER .....                           | 12        |
| 3.3. POWER SPECTRAL DENSITY .....                      | 14        |
| 3.4. BANDWIDTH .....                                   | 21        |
| 3.5. BAND EDGE AND SPURIOUS EMISSION (CONDUCTED) ..... | 34        |
| 3.6. BAND EDGE EMISSIONS(RADIATED) .....               | 40        |
| 3.7. SPURIOUS EMISSION (RADIATED) .....                | 45        |
| 3.8. CONDUCTED EMISSION .....                          | 56        |
| <b>4. EUT TEST PHOTOS .....</b>                        | <b>59</b> |
| <b>5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL .....</b>      | <b>61</b> |

## 1.TEST SUMMARY

### 1.1. TEST STANDARDS

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**KDB 558074 D01 :** The measurement guidance provided herein is applicable only to Digital Transmission System (DTS) devices operating in the 902-928 MHz. 2400-2483.5 MHz and/or 5725-5850 MHz bands under §15.247 of the FCC rules (Title 47 of the Code of Federal Regulations).

### 1.2. REPORT VERSION

| Revised No. | Date of issue | Description |
|-------------|---------------|-------------|
| 01          | July 09, 2022 | Original    |

### 1.3. TEST DESCRIPTION

| FCC Part 15 Subpart C(15.247)              |                  |        |               |
|--------------------------------------------|------------------|--------|---------------|
| Test Item                                  | Standard Section | Result | Test Engineer |
|                                            | FCC              |        |               |
| Antenna Requirement                        | 15.203           | Pass   | Tom Chen      |
| Conducted Emission                         | 15.207           | Pass   | Tom Chen      |
| 6dB&99% Bandwidth                          | 15.247(a)(2)     | Pass   | Tom Chen      |
| Peak Output Power                          | 15.247(b)        | Pass   | Tom Chen      |
| Power Spectral Density                     | 15.247(e)        | Pass   | Tom Chen      |
| Restricted Band                            | 15.247(d)/15.205 | Pass   | Tom Chen      |
| Band Edge and Spurious Emission(Conducted) | 15.247(d)        | Pass   | Tom Chen      |
| Spurious Emission(Radiated)                | 15.247(d)&15.209 | Pass   | Tom Chen      |

Note: The measurement uncertainty is not included in the test result.

## 1.4. TEST FACILITY

### Address of the report laboratory

#### **KSIGN(Guangdong) Testing Co., Ltd.**

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China

### Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### **CNAS-Lab Code: L13261**

KSIGN(Guangdong) Testing Co., Ltd. has been assessed and proved to be in Compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### **A2LA-Lab Cert. No.: 5457.01**

KSIGN(Guangdong) Testing Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### **ISED#: 25693 CAB identifier.: CN0096**

KSIGN(Guangdong) Testing Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

#### **FCC-Registration No.: 294912 Designation Number: CN1328**

KSIGN(Guangdong) Testing Co., Ltd. EMC Laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

## 1.5. MEASUREMENT UNCERTAINTY

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the KSIGN(Guangdong) Testing Co., Ltd. system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device. Below is the best measurement capability for KSIGN(Guangdong) Testing Co., Ltd.

| Test Items                              | Measurement Uncertainty | Notes |
|-----------------------------------------|-------------------------|-------|
| Transmitter power conducted             | 0.42 dB                 | (1)   |
| Transmitter power Radiated              | 2.14 dB                 | (1)   |
| Conducted spurious emissions 9kHz~40GHz | 1.60 dB                 | (1)   |
| Radiated spurious emissions 9kHz~40GHz  | 2.20 dB                 | (1)   |
| Conducted Emissions 9kHz~30MHz          | 3.20 dB                 | (1)   |
| Radiated Emissions 30~1000MHz           | 4.70 dB                 | (1)   |
| Radiated Emissions 1~18GHz              | 5.00 dB                 | (1)   |
| Radiated Emissions 18~40GHz             | 5.54 dB                 | (1)   |
| Occupied Bandwidth                      | 2.80 dB                 | (1)   |

**Note (1):** This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

## 1.6. ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

|                    |             |
|--------------------|-------------|
| Temperature:       | 15~35°C     |
| Relative Humidity: | 30~60 %     |
| Air Pressure:      | 950~1050mba |

## 2. GENERAL INFORMATION

### 2.1. GENERAL DESCRIPTION OF EUT

|                        |                                                                                                                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Sample Number:    | 1-1-1(Normal Sample),1-1-2(Engineering Sample )                                                                                                                                                                                                                                                                          |
| Product Name:          | Electric Fireplace                                                                                                                                                                                                                                                                                                       |
| Trade Mark:            | MODERN FLAMES                                                                                                                                                                                                                                                                                                            |
| Model/Type reference:  | LPS-4414 V2                                                                                                                                                                                                                                                                                                              |
| Listed Model(s):       | LPS-5614 V2, LPS-6814 V2, LPS-8014 V2, LPS-9614 V2, SPM-2426 V2, SPM-3026 V2, SPM-3626 V2, SPM-4226 V2, SPM-5426 V2, LPM-4416 V2, LPM-5616 V2, LPM-6816 V2, LPM-8016 V2, LPM-9616 V2, LPM-12016 V2                                                                                                                       |
| Model Different:       | The difference between the product model is only Dimensions and power of the machine is not the same, the different model name is for the market demand. Other power supply mode, internal structure, circuit and key components are the same, does not affect the safety and electromagnetic compatibility performance. |
| Power supply(Adapter): | AC 100V~120V                                                                                                                                                                                                                                                                                                             |
| Hardware version:      | V1.0                                                                                                                                                                                                                                                                                                                     |
| Software version:      | V1.0.0                                                                                                                                                                                                                                                                                                                   |
| <b>2.4GHz WIFI</b>     |                                                                                                                                                                                                                                                                                                                          |
| Modulation:            | 802.11b: DSSS(CCK, DQPSK, DBPSK)<br>802.11g/n: OFDM(BPSK,QPSK,16QAM,64QAM)                                                                                                                                                                                                                                               |
| Operation frequency:   | 802.11b/g/n(HT20): 2412MHz~2462MHz                                                                                                                                                                                                                                                                                       |
| Max Peak Output Power: | 802.11b: 15.98 dBm<br>802.11g: 21.07 dBm<br>802.11n (HT20): 19.25 dBm                                                                                                                                                                                                                                                    |
| Channel number:        | 802.11b/g/n(HT20):11 channels                                                                                                                                                                                                                                                                                            |
| Test frequency:        | CH01/03: 2412MHz/2422MHz; CH06: 2437MHz;<br>CH09/11: 2452MHz/2462MHz                                                                                                                                                                                                                                                     |
| Channel separation:    | 5MHz                                                                                                                                                                                                                                                                                                                     |
| Antenna type:          | Intenal Antenna                                                                                                                                                                                                                                                                                                          |
| Antenna gain:          | 2.5dBi                                                                                                                                                                                                                                                                                                                   |

## 2.2. OPERATION STATE

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

Operation Frequency List:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 01      | 2412            |
| 02      | 2417            |
| 03      | 2422            |
| 04      | 2427            |
| 05      | 2432            |
| 06      | 2437            |
| 07      | 2442            |
| 08      | 2447            |
| 09      | 2452            |
| 10      | 2457            |
| 11      | 2462            |

Note:

- 1.CH 01~CH 11 for 802.11b/g/n(HT20).
- 2.The display in grey were the channel selected for testing.

### Test mode

|                                                                                                                                                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For RF test items                                                                                                                                                                                                                        |
| The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).                                                                                                                                  |
| For AC power line conducted emissions:                                                                                                                                                                                                   |
| The EUT was set to connect with the WLAN AP under large package sizes transmission.                                                                                                                                                      |
| For Radiated spurious emissions test item:                                                                                                                                                                                               |
| The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report. |

## 2.3. MEASUREMENT INSTRUMENTS LIST

| Tonscend JS0806-2 Test system |                                     |              |           |            |            |
|-------------------------------|-------------------------------------|--------------|-----------|------------|------------|
| Item                          | Test Equipment                      | Manufacturer | Model No. | Serial No. | Cal. Until |
| 1                             | Spectrum Analyzer                   | R&S          | FSV40-N   | 101798     | 03/04/2023 |
| 2                             | Vector Signal Generator             | Agilent      | N5182A    | MY50142520 | 03/04/2023 |
| 3                             | Analog Signal Generator             | HP           | 83752A    | 3344A00337 | 03/04/2023 |
| 4                             | Power Sensor                        | Agilent      | E9304A    | MY50390009 | 03/04/2023 |
| 5                             | Power Sensor                        | Agilent      | E9300A    | MY41498315 | 03/04/2023 |
| 6                             | Wideband Radio Communication Tester | R&S          | CMW500    | 157282     | 03/04/2023 |
| 7                             | Climate Chamber                     | Angul        | AGNH80L   | 1903042120 | 03/04/2023 |
| 8                             | Dual Output DC Power Supply         | Agilent      | E3646A    | MY40009992 | 03/04/2023 |
| 9                             | RF Control Unit                     | Tonscend     | JS0806-2  | /          | 03/04/2023 |

| Transmitter spurious emissions & Receiver spurious emissions |                                            |                     |              |            |            |
|--------------------------------------------------------------|--------------------------------------------|---------------------|--------------|------------|------------|
| Item                                                         | Test Equipment                             | Manufacturer        | Model No.    | Serial No. | Cal. Until |
| 1                                                            | EMI Test Receiver                          | R&S                 | ESR          | 102525     | 03/04/2023 |
| 2                                                            | High Pass Filter                           | Chengdu E-Microwave | OHF-3-18-S   | 0E01901038 | 03/04/2023 |
| 3                                                            | High Pass Filter                           | Chengdu E-Microwave | OHF-6.5-18-S | 0E01901039 | 03/04/2023 |
| 4                                                            | Spectrum Analyzer                          | HP                  | 8593E        | 3831U02087 | 03/04/2023 |
| 5                                                            | Ultra-Broadband logarithmic period Antenna | Schwarzbeck         | VULB 9163    | 01230      | 12/04/2023 |
| 6                                                            | Loop Antenna                               | Beijin ZHINAN       | ZN30900C     | 18050      | 03/04/2023 |
| 7                                                            | Spectrum Analyzer                          | R&S                 | FSV40-N      | 101798     | 03/04/2023 |
| 8                                                            | Horn Antenna                               | Schwarzbeck         | BBHA 9120 D  | 2023       | 03/29/2023 |
| 9                                                            | Pre-Amplifier                              | Schwarzbeck         | BBV 9745     | 9745#129   | 03/04/2023 |
| 10                                                           | Pre-Amplifier                              | EMCI                | EMC051835 SE | 980662     | 03/04/2023 |
| 11                                                           | Pre-Amplifier                              | Schwarzbeck         | BBV-9721     | 57         | 03/04/2023 |
| 12                                                           | Horn Antenna                               | Schwarzbeck         | BBHA 9170    | 00939      | 03/04/2023 |

| Item | Test Equipment    | Manufacturer | Model No. | Serial No.   | Calibrated until |
|------|-------------------|--------------|-----------|--------------|------------------|
| 1    | LISN              | R&S          | ENV432    | 1326.6105.02 | 03/04/2023       |
| 2    | EMI Test Receiver | R&S          | ESR       | 102524       | 03/04/2023       |
| 3    | Manual RF Switch  | JS TOYO      | /         | MSW-01/002   | 03/04/2023       |

Note:

1)The Cal. Interval was one year.

2)The cable loss has calculated in test result which connection between each test instruments.

TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

## 2.4. TEST SOFTWARE

| Software name                           | Model    | Version       |
|-----------------------------------------|----------|---------------|
| Conducted emission Measurement Software | EZ-EMC   | EMC-Con 3A1.1 |
| Radiated emission Measurement Software  | EZ-EMC   | FA-03A.2.RE   |
| Bluetooth and WIFI Test System          | JS1120-3 | 2.5.77.0418   |

### 3. TEST ITEM AND RESULTS

#### 3.1. ANTENNA REQUIREMENT

##### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

##### Test Result


The directional gain of the antenna less than 6dBi, please refer to the EUT internal photographs antenna photo.

## 3.2. PEAK OUTPUT POWER

### Limit

| Test Item         | Limit            | Frequency Range(MHz) |
|-------------------|------------------|----------------------|
| Peak Output Power | 1 Watt or 30 dBm | 2400~2483.5          |

### Test Configuration



### Test Procedure

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator.
2. The measurement is according to ANSI C63.10 (2013) for compliance to FCC 47CFR 15.247 requirements.
3. Spectrum Setting:  
Set analyser center frequency to DTS channel center frequency.  
Set the RBW to: 1MHz  
Set the VBW to: 3MHz  
Detector: peak  
Sweep time: auto  
Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.
4. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

### Test Mode

Please refer to the clause 2.2

### Test Result


| Mode           | Channel frequency (MHz) | Test Result (dBm) | Limit (dBm) |
|----------------|-------------------------|-------------------|-------------|
| 802.11b        | 2412                    | 15.98             | 30          |
|                | 2437                    | 15.83             |             |
|                | 2462                    | 15.42             |             |
| 802.11g        | 2412                    | 21.07             |             |
|                | 2437                    | 20.98             |             |
|                | 2462                    | 20.38             |             |
| 802.11n (HT20) | 2412                    | 18.94             |             |
|                | 2437                    | 19.25             |             |
|                | 2462                    | 18.70             |             |
| Result : PASS  |                         |                   |             |

### 3.3. POWER SPECTRAL DENSITY

#### Limit

| FCC Part 15 Subpart C(15.247) |                    |                      |
|-------------------------------|--------------------|----------------------|
| Test Item                     | Limit              | Frequency Range(MHz) |
| Power Spectral Density        | 8dBm(in any 3 kHz) | 2400~2483.5          |

#### Test Configuration




#### Test Procedure

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to ANSI C63.10 (2013) for compliance to FCC 47CFR 15.247 requirements.
3. Spectrum Setting:  
 Set analyser center frequency to DTS channel center frequency.  
 Set the span to 1.5 times the DTS bandwidth.  
 Set the RBW to: 3 kHz  
 Set the VBW to: 10 kHz  
 Detector: peak  
 Sweep time: auto  
 Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

#### Test Mode

Please refer to the clause 2.2

# Test Result




TRF No. FCC Part 15.247\_R1


Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

### 2437 MHz




### 2462 MHz




TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com







TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com





TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

### 3.4. BANDWIDTH

#### Limit

| Test Item | Limit                             | Frequency Range(MHz) |
|-----------|-----------------------------------|----------------------|
| Bandwidth | $\geq 500$ KHz<br>(6dB bandwidth) | 2400~2483.5          |

#### Test Configuration



#### Test Procedure


1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator:  
6db Bandwidth
  - (1) Set RBW = 100 kHz.
  - (2) Set the video bandwidth (VBW)  $\geq 3$  RBW.
  - (3) Detector = Peak.
  - (4) Trace mode = Max hold.
  - (5) Sweep = Auto couple.

NOTE: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

#### Test Mode

Please refer to the clause 2.2.


## Test Results



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com









TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com










TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com



### 2437 MHz




### 2462 MHz



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

### 2437 MHz



Date: 6.JUL.2022 15:53:11

### 2462 MHz



Date: 6.JUL.2022 15:56:05

TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com


### 3.5. BAND EDGE AND SPURIOUS EMISSION (CONDUCTED)

#### Limit

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### Test Configuration



#### Test Procedure

1. Connect EUT RF Output port to the Spectrum Analyzer through an RF attenuator.
2. Spectrum Setting:
  - RBW=100KHz
  - VBW=300KHz.
  - Detector function: Peak.
  - Trace: Max hold.
  - Sweep = Auto couple.

Allow the trace to stabilize.

#### Test Mode

Please refer to the clause 2.2.

#### Test Results


TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com

## 802.11b

## CH01-Bandedge





## CH11-Bandedge





## 802.11b



## CH01-SE



### CH06-SE




### CH11-SE




### 802.11g

#### CH01-Bandedge



#### CH11-Bandedge





TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China



Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

802.11g



CH01-SE



CH06-SE



CH11-SE




TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

## 802.11n(HT20)

## CH01-Bandedge





## CH11-Bandedge



## 802.11n(HT20)

## CH01-SE




TRF No. FCC Part 15.247\_R1


Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

### CH06-SE



### CH11-SE





TRF No. FCC Part 15.247\_R1


Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com











### 3.7. SPURIOUS EMISSION (RADIATED)

#### Limit

**Radiated Emission Limits (9 kHz~1000 MHz)**

| Frequency (MHz) | Field Strength (microvolt/meter) | Measurement Distance (meters) |
|-----------------|----------------------------------|-------------------------------|
| 0.009~0.490     | 2400/F(KHz)                      | 300                           |
| 0.490~1.705     | 24000/F(KHz)                     | 30                            |
| 1.705~30.0      | 30                               | 30                            |
| 30~88           | 100                              | 3                             |
| 88~216          | 150                              | 3                             |
| 216~960         | 200                              | 3                             |
| Above 960       | 500                              | 3                             |


**Radiated Emission Limit (Above 1000MHz)**

| Frequency (MHz) | Distance Meters(at 3m) |         |
|-----------------|------------------------|---------|
|                 | Peak                   | Average |
| Above 1000      | 74                     | 54      |


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m).


#### Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

### Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;

(2) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

(3) From 1 GHz to 10<sup>th</sup> harmonic:

RBW=1MHz, VBW=1MHz Peak detector for Peak value.

RBW=1MHz, VBW=10Hz Peak detector for Peak value.

### **Test Mode**

Please refer to the clause 2.2.

### **Test Result**

#### **9 KHz~30 MHz and 18GHz~25GHz**

: Conclusion: PASS

Note:

1) Measurement = Reading level + Correct Factor

Correct Factor=Antenna Factor + Cable Loss -Preamplifier Factor


2) **From 9 KHz~30 MHz and 18GHz~25GHz,the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.**

3) Pre-scan 802.11b/g/n(HT20) modulation, and found the 802.11b modulation which it is worse case for above 1GHz, 2412MHz channel which it is worse case for below 1GHz, so only show the test data for worse case. Pre-scan LPM series,SPM series and LPS series,LPS series worst test data was listed in report as representative.

### **BELOW 30MHz**

the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


## 30MHz-1GHz




TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com




Adobe 1GHz





TRF No. FCC Part 15.247\_R1


Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com











### 3.8.CONDUCTED EMISSION

#### Limit


Conducted Emission Test Limit

| Frequency     | Maximum RF Line Voltage (dB $\mu$ V) |               |
|---------------|--------------------------------------|---------------|
|               | Quasi-peak Level                     | Average Level |
| 150kHz~500kHz | 66 ~ 56 *                            | 56 ~ 46 *     |
| 500kHz~5MHz   | 56                                   | 46            |
| 5MHz~30MHz    | 60                                   | 50            |

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### Test Configuration



#### Test Procedure


1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 0.1m above the conducting ground plane. The vertical conducting plane was located 80 cm to the rear of the EUT. All other surfaces of EUT were at least 0.8m from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.


#### Test Mode:

Please refer to the clause 2.2.

## Test Results

Pre-scan 802.11b/g/n(HT20) modulation, and found the 802.11b modulation 2412MHz which it is worse case, so only show the test data for worse case. Pre-scan LPM series,SPM series and LPS series,LPS series worst test data was listed in report as representative.





## 4.EUT TEST PHOTOS

Radiated Emissions (30MHz~1000MHz)



Radiated Emissions (Above 1GHz)




Conducted Emission





## 5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL













TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China



Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China



Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com



TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China



Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdkesign.cn Web: www.gdkesign.com






TRF No. FCC Part 15.247\_R1

Add : West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com







**The end**