

FCC TEST REPORT

FCC ID: 2A7VA-MFT1204

Report Number..... : ZKT-220707L4647

Date of Test..... : Jun. 29, 2022 -- Jul. 12, 2022

Date of issue : Jul. 12, 2022

Total number of pages : 49

Test Result : PASS

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Shenzhen Meevt Technology Co.,Ltd.

Address : Room 203-X08, Building C, Jinhu Building, Industrial East Road, Xinniu Community, Minzhi Street, Longhua District, Shenzhen

Manufacturer's name : Shenzhen Meevt Technology Co.,Ltd.

Address : Room 203-X08, Building C, Jinhu Building, Industrial East Road, Xinniu Community, Minzhi Street, Longhua District, Shenzhen

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : LED Strip Light


Trademark :  meevt


Model/Type reference : MF-T1204RGBIC, MF-T1204RGB, MF-T1204RGBCW,
MF-T1204WIC, MF-T1004CW, MF-T1004W, MF-TXXXXRGB,
MF-TXXXXCW, MF-TXXXXW

Ratings..... : DC 24V 2A from adapter

Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.
Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Alen He 

Reviewer (name + signature).....: Joe Liu 

Approved (name + signature).....: Lake Xie 

Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULT	14
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	16
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS	18
4.2.6 TEST RESULTS	19
5.RADIATED BAND EMISSIONMEASUREMENT	23
5.1 TEST REQUIREMENT:	23
5.2 TEST PROCEDURE	23
5.3 DEVIATION FROM TEST STANDARD	23
5.4 TEST SETUP	24
5.5 EUT OPERATING CONDITIONS	24
5.6 TEST RESULT	25
6.POWER SPECTRAL DENSITY TEST	26
6.1 APPLIED PROCEDURES / LIMIT	26
6.2 TEST PROCEDURE	26
6.3 DEVIATION FROM STANDARD	26
6.4 TEST SETUP	26
6.5 EUT OPERATION CONDITIONS	26

6.6 TEST RESULT	27
7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH	29
7.1 APPLIED PROCEDURES / LIMIT	29
7.2 TEST PROCEDURE	29
7.3 DEVIATION FROM STANDARD	29
7.4 TEST SETUP	29
7.5 EUT OPERATION CONDITIONS	29
7.6 TEST RESULT	30
8. PEAK OUTPUT POWER TEST	32
8.1 APPLIED PROCEDURES/LIMIT	32
8.2 TEST PROCEDURE	32
8.3 DEVIATION FROM STANDARD	32
8.4 TEST SETUP	32
8.5 EUT OPERATION CONDITIONS	32
8.6 TEST RESULT	32
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	33
9.1 APPLICABLE STANDARD	33
9.2 TEST PROCEDURE	33
9.3 DEVIATION FROM STANDARD	33
9.4 TEST SETUP	33
9.5 EUT OPERATION CONDITIONS	33
9.6 TEST RESULTS	33
10. ANTENNA REQUIREMENT	42
11. TEST SETUP PHOTO	43
12. EUT CONSTRUCTIONAL DETAILS	45

1. VERSION

Report No.	Version	Description	Approved
ZKT-220707L4647	Rev.01	Initial issue of report	Jul. 12, 2022

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth& 99% OCB	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	LED Strip Light
Model No.:	MF-T1204RGBIC
Serial No.:	MF-T1204RGB, MF-T1204RGBCW, MF-T1204WIC, MF-T1004CW, MF-T1004W, MF-TXXXXRGB, MF-TXXXXCW, MF-TXXXXW
Model difference	Their electrical circuit design, layout, components used and internal wiring are identical, Only the name will be different . Test sample model: MF-T1204RGBIC
Hardware Version:	C.10.0028
Software Version:	Lekit_200927
Sample(s) Status:	Engineer sample
Channel numbers:	40
Channel separation:	2402MHz~2480MHz
Modulation technology:	GFSK
Rate	1Mbps/2Mbps
Antenna Type:	PCB antenna
Antenna gain:	0dBi
Power supply:	DC 24V from adapter


Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402	11	2422	21	2442	31	2462
2	2404	12	2424	22	2444	32	2464
3	2406	13	2426	23	2446	33	2466
4	2408	14	2428	24	2448	34	2468
5	2410	15	2430	25	2450	35	2470
6	2412	16	2432	26	2452	36	2472
7	2414	17	2434	27	2454	37	2474
8	2416	18	2436	28	2456	38	2476
9	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	

Test Software	BT Test Tool 
Power level setup	<10dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	adapter	/	Model:MYX-2402000US INPUT:110-240V AC 50/60Hz 1.2A Output: 24V 2A	/	Provide by client
2					

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 21, 2021	Sep. 22, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 21, 2021	Sep. 22, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESC17	101169	Sep. 21, 2021	Sep. 22, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 21, 2021	Sep. 22, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 21, 2021	Sep. 22, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 21, 2021	Sep. 22, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 21, 2021	Sep. 22, 2022
8	Amplifier (1GHz-40GHz)	QUANJUDA	DLE-161	097	Sep. 21, 2021	Sep. 22, 2022
9	Loop Antenna (9KHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 21, 2021	Sep. 22, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 21, 2021	Sep. 22, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 21, 2021	Sep. 22, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 21, 2021	Sep. 22, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 21, 2021	Sep. 22, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 21, 2021	Sep. 22, 2022
2	LISN	CYBERTEK	EM5040A	E185040014 9	Sep. 21, 2021	Sep. 22, 2022
3	Test Cable	N/A	C01	N/A	Sep. 21, 2021	Sep. 22, 2022
4	Test Cable	N/A	C02	N/A	Sep. 21, 2021	Sep. 22, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 21, 2021	Sep. 22, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 21, 2021	Sep. 22, 2022

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	48.88	-0.13	48.75	65.99	-17.24	QP	
2		0.1539	25.88	-0.13	25.75	55.78	-30.03	AVG	
3		1.0620	13.67	-0.13	13.54	46.00	-32.46	AVG	
4		1.0740	24.71	-0.13	24.58	56.00	-31.42	QP	
5		1.6700	10.69	-0.20	10.49	46.00	-35.51	AVG	
6		2.1780	24.82	-0.24	24.58	56.00	-31.42	QP	
7		6.4740	32.23	-0.26	31.97	50.00	-18.03	AVG	
8		6.5900	38.58	-0.27	38.31	60.00	-21.69	QP	
9	*	13.5300	52.26	-0.17	52.09	60.00	-7.91	QP	
10		14.4700	42.24	-0.21	42.03	50.00	-7.97	AVG	
11		26.4660	32.14	-0.43	31.71	60.00	-28.29	QP	
12		27.5260	24.90	-0.38	24.52	50.00	-25.48	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	49.57	-0.13	49.44	65.78	-16.34	QP	
2		0.1539	29.65	-0.13	29.52	55.78	-26.26	AVG	
3		0.4060	24.87	-0.01	24.86	47.73	-22.87	AVG	
4		0.4140	35.93	-0.01	35.92	57.57	-21.65	QP	
5		1.3180	31.20	-0.17	31.03	56.00	-24.97	QP	
6		1.5260	16.68	-0.19	16.49	46.00	-29.51	AVG	
7		6.5900	44.16	-0.27	43.89	60.00	-16.11	QP	
8		6.5900	35.15	-0.27	34.88	50.00	-15.12	AVG	
9	*	13.4100	42.66	-0.16	42.50	50.00	-7.50	AVG	
10		13.5300	52.64	-0.17	52.47	60.00	-7.53	QP	
11		27.5260	31.92	-0.38	31.54	60.00	-28.46	QP	
12		27.5260	24.00	-0.38	23.62	50.00	-26.38	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. when charging, BT can not transmit

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different from above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 metre to 1.5 metre (Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



1GHz~25GHz

BLE-1Mbps

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Low Channel:2402MHz									
V	4804.00	55.22	30.55	5.77	24.66	55.10	74.00	-18.90	PK
V	4804.00	42.17	30.55	5.77	24.66	42.05	54.00	-11.95	AV
V	7206.00	54.22	30.33	6.32	24.55	54.76	74.00	-19.24	PK
V	7206.00	41.42	30.33	6.32	24.55	41.96	54.00	-12.04	AV
V	9608.00	52.59	30.85	7.45	24.69	53.88	74.00	-20.12	PK
V	9608.00	37.11	30.85	7.45	24.69	38.40	54.00	-15.60	AV
H	4804.00	55.35	31.02	5.77	25.57	55.67	74.00	-18.33	PK
H	4804.00	41.08	31.02	5.77	25.57	41.40	54.00	-12.60	AV
H	7206.00	54.40	30.55	6.32	24.66	54.83	74.00	-19.17	PK
H	7206.00	41.48	30.55	6.32	24.66	41.91	54.00	-12.09	AV
H	9608.00	50.03	30.33	7.45	24.55	51.70	74.00	-22.30	PK
H	9608.00	36.69	30.33	7.45	24.55	38.36	54.00	-15.64	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Middle Channel:2440MHz									
V	4880.00	55.19	30.55	5.77	24.66	55.07	74.00	-18.93	PK
V	4880.00	41.13	30.55	5.77	24.66	41.01	54.00	-12.99	AV
V	7320.00	52.77	30.33	6.32	24.55	53.31	74.00	-20.69	PK
V	7320.00	40.29	30.33	6.32	24.55	40.83	54.00	-13.17	AV
V	9760.00	50.80	30.85	7.45	24.69	52.09	74.00	-21.91	PK
V	9760.00	37.88	30.85	7.45	24.69	39.17	54.00	-14.83	AV
H	4880.00	56.33	31.02	5.77	25.57	56.65	74.00	-17.35	PK
H	4880.00	39.42	31.02	5.77	25.57	39.74	54.00	-14.26	AV
H	7320.00	52.86	30.55	6.32	24.66	53.29	74.00	-20.71	PK
H	7320.00	40.84	30.55	6.32	24.66	41.27	54.00	-12.73	AV
H	9760.00	51.95	30.33	7.45	24.55	53.62	74.00	-20.38	PK
H	9760.00	36.59	30.33	7.45	24.55	38.26	54.00	-15.74	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:2480MHz									
V	4960.00	56.12	30.55	5.77	24.66	56.00	74.00	-18.00	PK
V	4960.00	41.63	30.55	5.77	24.66	41.51	54.00	-12.49	AV
V	7440.00	54.51	30.33	6.32	24.55	55.05	74.00	-18.95	PK
V	7440.00	38.83	30.33	6.32	24.55	39.37	54.00	-14.63	AV
V	9920.00	50.50	30.85	7.45	24.69	51.79	74.00	-22.21	PK
V	9920.00	36.74	30.85	7.45	24.69	38.03	54.00	-15.97	AV
H	4960.00	54.65	31.02	5.77	25.57	54.97	74.00	-19.03	PK
H	4960.00	39.81	31.02	5.77	25.57	40.13	54.00	-13.87	AV
H	7440.00	54.04	30.55	6.32	24.66	54.47	74.00	-19.53	PK
H	7440.00	41.02	30.55	6.32	24.66	41.45	54.00	-12.55	AV
H	9920.00	50.58	30.33	7.45	24.55	52.25	74.00	-21.75	PK
H	9920.00	38.74	30.33	7.45	24.55	40.41	54.00	-13.59	AV

BLE-2Mbps

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Low Channel:2402MHz									
V	4804.00	54.12	30.55	5.77	24.66	54.00	74.00	-20.00	PK
V	4804.00	41.36	30.55	5.77	24.66	41.24	54.00	-12.76	AV
V	7206.00	54.71	30.33	6.32	24.55	55.25	74.00	-18.75	PK
V	7206.00	40.61	30.33	6.32	24.55	41.15	54.00	-12.85	AV
V	9608.00	50.79	30.85	7.45	24.69	52.08	74.00	-21.92	PK
V	9608.00	37.65	30.85	7.45	24.69	38.94	54.00	-15.06	AV
H	4804.00	55.32	31.02	5.77	25.57	55.64	74.00	-18.36	PK
H	4804.00	41.33	31.02	5.77	25.57	41.65	54.00	-12.35	AV
H	7206.00	54.51	30.55	6.32	24.66	54.94	74.00	-19.06	PK
H	7206.00	41.58	30.55	6.32	24.66	42.01	54.00	-11.99	AV
H	9608.00	50.99	30.33	7.45	24.55	52.66	74.00	-21.34	PK
H	9608.00	36.59	30.33	7.45	24.55	38.26	54.00	-15.74	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Middle Channel:2440MHz									
V	4880.00	56.17	30.55	5.77	24.66	56.05	74.00	-17.95	PK
V	4880.00	41.79	30.55	5.77	24.66	41.67	54.00	-12.33	AV
V	7320.00	53.05	30.33	6.32	24.55	53.59	74.00	-20.41	PK
V	7320.00	40.02	30.33	6.32	24.55	40.56	54.00	-13.44	AV
V	9760.00	50.80	30.85	7.45	24.69	52.09	74.00	-21.91	PK
V	9760.00	38.07	30.85	7.45	24.69	39.36	54.00	-14.64	AV
H	4880.00	56.26	31.02	5.77	25.57	56.58	74.00	-17.42	PK
H	4880.00	40.38	31.02	5.77	25.57	40.70	54.00	-13.30	AV
H	7320.00	53.58	30.55	6.32	24.66	54.01	74.00	-19.99	PK
H	7320.00	40.13	30.55	6.32	24.66	40.56	54.00	-13.44	AV
H	9760.00	52.48	30.33	7.45	24.55	54.15	74.00	-19.85	PK
H	9760.00	38.10	30.33	7.45	24.55	39.77	54.00	-14.23	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:2480MHz									
V	4960.00	54.83	30.55	5.77	24.66	54.71	74.00	-19.29	PK
V	4960.00	41.55	30.55	5.77	24.66	41.43	54.00	-12.57	AV
V	7440.00	54.40	30.33	6.32	24.55	54.94	74.00	-19.06	PK
V	7440.00	38.84	30.33	6.32	24.55	39.38	54.00	-14.62	AV
V	9920.00	52.09	30.85	7.45	24.69	53.38	74.00	-20.62	PK
V	9920.00	38.48	30.85	7.45	24.69	39.77	54.00	-14.23	AV
H	4960.00	55.36	31.02	5.77	25.57	55.68	74.00	-18.32	PK
H	4960.00	41.08	31.02	5.77	25.57	41.40	54.00	-12.60	AV
H	7440.00	53.44	30.55	6.32	24.66	53.87	74.00	-20.13	PK
H	7440.00	39.56	30.55	6.32	24.66	39.99	54.00	-14.01	AV
H	9920.00	49.83	30.33	7.45	24.55	51.50	74.00	-22.50	PK
H	9920.00	36.28	30.33	7.45	24.55	37.95	54.00	-16.05	AV

5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

BLE-1Mbps

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
Low Channel 2402MHz									
H	2390.00	54.12	30.22	4.85	23.98	52.73	74	-21.27	PK
H	2390.00	36.75	30.22	4.85	23.98	35.36	54	-18.64	AV
H	2400.00	54.55	30.22	4.85	23.98	53.16	74	-20.84	PK
H	2400.00	37.84	30.22	4.85	23.98	36.45	54	-17.55	AV
V	2390.00	52.48	30.22	4.85	23.98	51.09	74	-22.91	PK
V	2390.00	42.33	30.22	4.85	23.98	40.94	54	-13.06	AV
V	2400.00	51.12	30.22	4.85	23.98	49.73	74	-24.27	PK
V	2400.00	37.48	30.22	4.85	23.98	36.09	54	-17.91	AV
High Channel: 2480MHz									
H	2483.50	47.33	30.22	4.85	23.98	45.94	74	-28.06	PK
H	2485.50	36.59	30.22	4.85	23.98	35.20	54	-18.80	AV
H	2483.50	48.77	30.22	4.85	23.98	47.38	74	-26.62	PK
H	2485.50	38.58	30.22	4.85	23.98	37.19	54	-16.81	AV
V	2483.50	52.77	30.22	4.85	23.98	51.38	74	-22.62	PK
V	2485.50	40.59	30.22	4.85	23.98	39.20	54	-14.80	AV
V	2483.50	55.34	30.22	4.85	23.98	53.95	74	-20.05	PK
V	2485.50	43.62	30.22	4.85	23.98	42.23	54	-11.77	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level – Limit

BLE-2Mbps

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
Low Channel 2402MHz									
H	2390.00	53.97	30.22	4.85	23.98	52.58	74	-21.42	PK
H	2390.00	37.07	30.22	4.85	23.98	35.68	54	-18.32	AV
H	2400.00	51.88	30.22	4.85	23.98	50.49	74	-23.51	PK
H	2400.00	40.74	30.22	4.85	23.98	39.35	54	-14.65	AV
V	2390.00	50.68	30.22	4.85	23.98	49.29	74	-24.71	PK
V	2390.00	40.78	30.22	4.85	23.98	39.39	54	-14.61	AV
V	2400.00	52.42	30.22	4.85	23.98	51.03	74	-22.97	PK
V	2400.00	37.12	30.22	4.85	23.98	35.73	54	-18.27	AV
High Channel: 2480MHz									
H	2483.50	48.60	30.22	4.85	23.98	47.21	74	-26.79	PK
H	2485.50	36.06	30.22	4.85	23.98	34.67	54	-19.33	AV
H	2483.50	49.83	30.22	4.85	23.98	48.44	74	-25.56	PK
H	2485.50	35.61	30.22	4.85	23.98	34.22	54	-19.78	AV
V	2483.50	57.42	30.22	4.85	23.98	56.03	74	-17.97	PK
V	2485.50	38.03	30.22	4.85	23.98	36.64	54	-17.36	AV
V	2483.50	56.95	30.22	4.85	23.98	55.56	74	-18.44	PK
V	2485.50	40.17	30.22	4.85	23.98	38.78	54	-15.22	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidance v 05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.


6.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V
Test Mode :	GFSK		

Frequency	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	1Mbps	2Mbps		
2402 MHz	-12.840	-15.575	8	PASS
2440 MHz	-13.285	-15.000	8	PASS
2480 MHz	-17.262	-16.472	8	PASS

BLE-1Mbps

TX CH01



BLE-2Mbps

TX CH01



TX CH20



TX CH20



TX CH40



TX CH40



7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP**7.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V
Test Mode :	GFSK		

Test CH	Channel Bandwidth (KHz)		Limit(KHz)	Result
	1Mbps	2Mbps		
Lowest	651.8	1186	>500	Pass
Middle	650.6	1178		
Highest	662.0	1174		

BLE-1Mbps	BLE-2Mbps
TX CH01	TX CH01
 Center Freq 2.40200000 GHz Center Freq 2.40200000 GHz Trig: Free Run #Atten: 30 dB Avg/Hold: 100/100 Radio Device: BTS Ref Offset 5 dB Ref 25.00 dBm Center Freq 2.402 GHz #Res BW 100 kHz #VBW 300 kHz Span 3 MHz Sweep 1 ms CF Step 300.000 kHz Occupied Bandwidth 1.0435 MHz Total Power 5.92 dBm Transmit Freq Error 78.826 kHz % of OBW Power 99.00 % x dB Bandwidth 651.8 kHz x dB -6.00 dB Freq Offset 0 Hz	 Center Freq 2.40200000 GHz Center Freq 2.40200000 GHz Trig: Free Run #Atten: 30 dB Avg/Hold: 100/100 Radio Device: BTS Ref Offset 5 dB Ref 25.00 dBm Center Freq 2.402 GHz #Res BW 100 kHz #VBW 300 kHz Span 5 MHz Sweep 1 ms CF Step 500.000 kHz Occupied Bandwidth 2.0205 MHz Total Power 13.0 dBm Transmit Freq Error 3.306 kHz % of OBW Power 99.00 % x dB Bandwidth 1.186 MHz x dB -6.00 dB Freq Offset 0 Hz
TX CH20	TX CH20



TX CH40



TX CH40



8. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP**8.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V

Test CH	Peak Output Power (dBm)		Limit(dBm)	Result
	1Mbps	2Mbps		
Lowest	1.24	2.22	30.00	Pass
Middle	0.04	2.66		
Highest	-1.53	2.26		

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Highest channel

BLE-2Mbps

Test mode:

GFSK



Lowest channel




Highest channel


Test plot as follows:

BLE-1Mbps


GFSK Lowest channel



GFSK Middle channel




GFSK Highest channel




BLE-2Mbps


GFSK Lowest channel




GFSK Middle channel



GFSK Highest channel




10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna: The antenna is PCB antenna, the best case gain of the antennas is 0dBi, reference to the below photo for details ANT for BT	
	

11. TEST SETUP PHOTO








12. EUT CONSTRUCTIONAL DETAILS




External photos






Internal photos







***** END OF REPORT *****