FCC Test Report

Applicant	:	**Shenzhen Qianyan Technology LTD**
Address	:	**No.3301,Block C,Section 1,Chuangzhi Yuncheng Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China**
Product Name	:	**Govee Smart LED Downlight**
Report Date	:	**Aug. 29, 2023**

Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information 6
1.1. Client Information 6
1.2. Description of Device (EUT) 6
1.3. Auxiliary Equipment Used During Test 7
1.4. Description of Test Configuration 7
1.5. Description Of Test Setup 8
1.6. Test Equipment List 9
1.7. Measurement Uncertainty 10
1.8. Description of Test Facility 10
2. Summary of Test Results 11
3. Conducted Emission Test 12
3.1. Test Standard and Limit 12
3.2. Test Setup 12
3.3. Test Procedure 12
3.4. Test Data 12
4. Radiation Spurious Emission and Band Edge 17
4.1. Test Standard and Limit 17
4.2. Test Setup 17
4.3. Test Procedure 18
4.4. Test Data 19
5. Maximum Peak Output Power Test 32
5.1. Test Standard and Limit 32
5.2. Test Setup 32
5.3. Test Procedure 32
5.4. Test Data 32
6. 6dB Occupy Bandwidth Test 33
6.1. Test Standard and Limit 33
6.2. Test Setup 33
6.3. Test Procedure 33
6.4. Test Data 33
7. Power Spectral Density Test 34
7.1. Test Standard and Limit 34
7.2. Test Setup 34
7.3. Test Procedure 34
7.4. Test Data 34
8. 100kHz Bandwidth of Frequency Band Edge Requirement 35
8.1. Test Standard and Limit 35

8.2. Test Setup 35
8.3. Test Procedure 35
8.4. Test Data 35
9. Antenna Requirement 36
9.1. Test Standard and Requirement 36
9.2. Antenna Connected Construction 36
APPENDIX I -- TEST SETUP PHOTOGRAPH 37
APPENDIX II -- EXTERNAL PHOTOGRAPH 37
APPENDIX III -- INTERNAL PHOTOGRAPH 37

TEST REPORT

Applicant	:	Shenzhen Qianyan Technology LTD
Manufacturer	:	Shenzhen Qianyan Technology LTD
Product Name	:	Govee Smart LED Downlight
Test Model No.	:	H601C
Reference Model No.	:	H601D
Trade Mark	:	Govee
Rating(s)	:	H601C: Input: AC 100-132V, 50/60Hz, 13W H601D: Input: AC 100-132V, 50/60Hz, 11W
Test Standard(s)	:	**FCC Part15 Subpart C, Section 15.247**
Test Method(s)	:	**ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt	Aug. 14, 2023
Date of Test	Aug. 14 ~ 23, 2023
Prepared By	Nian xiu Chen (Nianxiu Chen)
Approved & Authorized Signer	Edward pan (Edward Pan)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Aug. 29, 2023

Address:1/F.,Building D,Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 0755-26066440 Fax:(86) 0755-26014772 Email:service@anbotek.com
Hotline 400-003-0500
www.anbotek.com.cn

1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qianyan Technology LTD
Address	:	No.3301,Block C,Section 1,Chuangzhi Yuncheng Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China
Manufacturer	:	Shenzhen Qianyan Technology LTD
Address	:	No.3301,Block C,Section 1,Chuangzhi Yuncheng Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China

1.2. Description of Device (EUT)

Product Name	:	Govee Smart LED Downlight
Test Model No.	:	H601C
Reference Model No.	:	H601D (For models differences: Model H601C is 6-inch, with 13W power; Model H601D is 4-inch, with 11W power; and the light board layout is different. According to their differences, we prepared all models for conducted emission and radiation spurious emission testing, other items are only tested for “H601C”.)
Trade Mark	:	Govee
Test Power Supply	:	AC 120V, 60Hz
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Mode	:	☒ BT BLE
Support Rate	:	☒ 1Mbps ☐ 2Mbps
Operation Frequency	:	2402~2480MHz
Number of Channel	:	40 Channels
Modulation Type	:	GFSK
Antenna Type	:	FPC Antenna
Antenna Gain(Peak)	:	5.12dBi (Provided by customer)
Remark: 1) For a more detailed features description, please refer to the manufacturer’s specifications or the User’s Manual.		

1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	**2402**	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	**19**	**2440**	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	**39**	**2480**
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 19 and 39.

1.5. Description Of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	SKET-PA-002	Oct. 13, 2022	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Oct. 23, 2022	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 19, 2022	1 Year
18.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: “N/A” is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark:(1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data

Model: H601C

Test Site: 1# Shielded Room

Operating Condition: 2480MHz

Test Specification: AC 120V, 60Hz

Comment: Live Line

Temp.(℃)/Hum.(%RH): 26.1℃/69%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	35.35	19.82	55.17	65.99	-10.82	QP	
2	0.1500	21.77	19.82	41.59	55.99	-14.40	AVG	
3	0.1860	30.82	19.82	50.64	64.21	-13.57	QP	
4	0.1860	16.76	19.82	36.58	54.21	-17.63	AVG	
5	0.3420	23.03	19.83	42.86	59.15	-16.29	QP	
6	0.8180	22.15	19.87	42.02	56.00	-13.98	QP	
7	1.2260	12.81	19.85	32.66	46.00	-13.34	AVG	
8	1.3740	23.98	19.86	43.84	56.00	-12.16	QP	
9	1.5780	10.39	19.85	30.24	46.00	-15.76	AVG	
10	1.9460	7.75	19.85	27.60	46.00	-18.40	AVG	
11	28.4460	28.86	20.66	49.52	60.00	-10.48	QP	
12	29.9620	15.61	20.73	36.34	50.00	-13.66	AVG	

Conducted Emission Test Data

Model: H601C

Test Site: 1# Shielded Room

Operating Condition: 2480MHz

Test Specification: AC 120V, 60Hz

Comment: Neutral Line

Temp.(℃)/Hum.(%RH): 26.1℃/69%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	35.39	19.82	55.21	65.99	-10.78	QP	
2	0.1500	20.53	19.82	40.35	55.99	-15.64	AVG	
3	0.1819	32.85	19.82	52.67	64.39	-11.72	QP	
4	0.1819	17.89	19.82	37.71	54.39	-16.68	AVG	
5	0.7780	12.53	19.87	32.40	46.00	-13.60	AVG	
6	1.2660	23.34	19.86	43.20	56.00	-12.80	QP	
7	1.3460	12.87	19.86	32.73	46.00	-13.27	AVG	
8	1.6260	20.21	19.85	40.06	56.00	-15.94	QP	
9	1.7020	9.98	19.85	29.83	46.00	-16.17	AVG	
10	1.9500	18.46	19.85	38.31	56.00	-17.69	QP	
11	2.0340	7.10	19.85	26.95	46.00	-19.05	AVG	
12	28.7140	22.56	20.67	43.23	60.00	-16.77	QP	

Conducted Emission Test Data

Model: H601D

Test Site: 1# Shielded Room

Operating Condition: 2480MHz

Test Specification: AC 120V, 60Hz

Comment: Live Line

Temp.(℃)/Hum.(%RH): 26.1℃/69%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1620	30.62	19.83	50.45	65.36	-14.91	QP	
2	0.1660	19.42	19.83	39.25	55.15	-15.90	AVG	
3	0.4940	20.65	19.86	40.51	56.10	-15.59	QP	
4	0.9980	23.67	19.86	43.53	56.00	-12.47	QP	
5	0.9980	13.04	19.86	32.90	46.00	-13.10	AVG	
6	1.3300	23.47	19.86	43.33	56.00	-12.67	QP	
7	1.3540	12.40	19.86	32.26	46.00	-13.74	AVG	
8	1.7140	9.34	19.85	29.19	46.00	-16.81	AVG	
9	1.9900	19.68	19.85	39.53	56.00	-16.47	QP	
10	2.0420	6.72	19.85	26.57	46.00	-19.43	AVG	
11	28.7180	25.14	20.67	45.81	60.00	-14.19	QP	
12	29.8500	14.87	20.72	35.59	50.00	-14.41	AVG	

Conducted Emission Test Data

Model: H601D

Test Site: 1# Shielded Room

Operating Condition: 2480MHz

Test Specification: AC 120V, 60Hz

Comment: Neutral Line

Temp.(℃)/Hum.(%RH): 26.1℃/69%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1660	30.43	19.83	50.26	65.15	-14.89	QP	
2	0.1660	18.16	19.83	37.99	55.15	-17.16	AVG	
3	0.5780	21.81	19.86	41.67	56.00	-14.33	QP	
4	0.7780	12.84	19.87	32.71	46.00	-13.29	AVG	
5	0.9980	24.00	19.86	43.86	56.00	-12.14	QP	
6	1.3099	23.51	19.86	43.37	56.00	-12.63	QP	
7	1.3340	12.90	19.86	32.76	46.00	-13.24	AVG	
8	1.6820	9.92	19.85	29.77	46.00	-16.23	AVG	
9	1.7740	19.81	19.86	39.67	56.00	-16.33	QP	
10	1.9940	9.30	19.85	29.15	46.00	-16.85	AVG	
11	2.3380	5.46	19.85	25.31	46.00	-20.69	AVG	
12	2.5540	16.65	19.85	36.50	56.00	-19.50	QP	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =3MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

–VBW=3*RBW, Detector= RMS, When duty cycle is no less than 98 percent

–VBW=3*RBW, Detector= RMS, When duty cycle is less than 98 percent and dutycycle is constant, average=peak level+correction factor(20log(dutycycle)).

–VBW≥1/T, when duty cycle is less than 98 percent and dutycycle is not constant, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.

Test Results (30~1000MHz)

Model: H601C

Test Mode: 2480MHz

Power Source: AC 120V, 60Hz

Polarization: Horizontal

Temp.(℃)/Hum.(%RH): 22.5℃/56%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	77.5928	50.35	-22.70	27.65	40.00	-12.35	QP			
2	224.5193	50.77	-21.92	28.85	46.00	-17.15	QP			
3	286.9823	51.37	-18.29	33.08	46.00	-12.92	QP			
4	330.1949	49.07	-16.46	32.61	46.00	-13.39	QP			
5	351.7079	48.96	-16.00	32.96	46.00	-13.04	QP			
6	394.8545	48.01	-16.13	31.88	46.00	-14.12	QP			

Test Results (30~1000MHz)

Model: H601C

Test Mode: 2480MHz

Power Source: AC 120V, 60Hz

Polarization: Vertical

Temp.(℃)/Hum.(%RH): 22.5℃/56%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	44.7433	38.40	-15.02	23.38	40.00	-16.62	QP			
2	78.4133	53.02	-19.49	33.53	40.00	-6.47	QP			
3	131.2965	46.33	-21.56	24.77	43.50	-18.73	QP			
4	155.9101	48.91	-21.83	27.08	43.50	-16.42	QP			
5	346.8092	42.75	-15.08	27.67	46.00	-18.33	QP			
6	379.9141	41.59	-14.66	26.93	46.00	-19.07	QP			

Test Results (30~1000MHz)

Model: H601D

Test Mode: 2480MHz

Power Source: AC 120V, 60Hz

Polarization: Horizontal

Temp.(℃)/Hum.(%RH): 22.5℃/56%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	77.5926	51.35	-22.70	28.65	40.00	-11.35	QP			
2	224.5192	51.77	-21.92	29.85	46.00	-16.15	QP			
3	286.9823	52.37	-18.29	34.08	46.00	-11.92	QP			
4	330.1949	50.07	-16.46	33.61	46.00	-12.39	QP			
5	351.7078	49.96	-16.00	33.96	46.00	-12.04	QP			
6	394.8543	48.51	-16.13	32.38	46.00	-13.62	QP			

Test Results (30~1000MHz)

Model: H601D

Test Mode: 2480MHz

Power Source: AC 120V, 60Hz

Polarization: Vertical

Temp.(℃)/Hum.(%RH): 22.5℃/56%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	44.7433	39.40	-15.02	24.38	40.00	-15.62	QP			
2	78.4133	53.02	-19.49	33.53	40.00	-6.47	QP			
3	131.2965	47.83	-21.56	26.27	43.50	-17.23	QP			
4	155.9096	50.41	-21.83	28.58	43.50	-14.92	QP			
5	291.0360	44.40	-16.56	27.84	46.00	-18.16	QP			
6	346.8091	43.25	-15.08	28.17	46.00	-17.83	QP			

Model: H601C

Test Results (1GHz-25GHz)

Test Mode: CH00			Test channel: Lowest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	28.68	15.27	43.95	74.00	-30.05	Vertical
7206.00	28.71	18.09	46.80	74.00	-27.20	Vertical
9608.00	29.63	23.76	53.39	74.00	-20.61	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	28.33	15.27	43.60	74.00	-30.40	Horizontal
7206.00	29.32	18.09	47.41	74.00	-26.59	Horizontal
9608.00	28.21	23.76	51.97	74.00	-22.03	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	16.95	15.27	32.22	54.00	-21.78	Vertical
7206.00	17.76	18.09	35.85	54.00	-18.15	Vertical
9608.00	19.10	23.76	42.86	54.00	-11.14	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	16.66	15.27	31.93	54.00	-22.07	Horizontal
7206.00	18.35	18.09	36.44	54.00	-17.56	Horizontal
9608.00	17.72	23.76	41.48	54.00	-12.52	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH19			Test channel: Middle			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	28.23	15.42	43.65	74.00	-30.35	Vertical
7320.00	28.68	18.02	46.70	74.00	-27.30	Vertical
9760.00	29.13	23.80	52.93	74.00	-21.07	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	28.14	15.42	43.56	74.00	-30.44	Horizontal
7320.00	29.19	18.02	47.21	74.00	-26.79	Horizontal
9760.00	27.93	23.80	51.73	74.00	-22.27	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	17.04	15.42	32.46	54.00	-21.54	polarization
7320.00	17.62	18.02	35.64	54.00	-18.36	Vertical
9760.00	18.95	23.80	42.75	54.00	-11.25	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	16.77	15.42	32.19	54.00	-21.81	Vertical
7320.00	18.70	18.02	36.72	54.00	-17.28	Horizontal
9760.00	18.02	23.80	41.82	54.00	-12.18	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH39			Test channel: Highest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	28.36	15.58	43.94	74.00	-30.06	Vertical
7440.00	28.84	17.93	46.77	74.00	-27.23	Vertical
9920.00	29.83	23.83	53.66	74.00	-20.34	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	28.28	15.58	43.86	74.00	-30.14	Horizontal
7440.00	29.40	17.93	47.33	74.00	-26.67	Horizontal
9920.00	28.31	23.83	52.14	74.00	-21.86	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	18.16	15.58	33.74	54.00	-20.26	Vertical
7440.00	18.89	17.93	36.82	54.00	-17.18	Vertical
9920.00	19.60	23.83	43.43	54.00	-10.57	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	17.95	15.58	33.53	54.00	-20.47	Horizontal
7440.00	19.50	17.93	37.43	54.00	-16.57	Horizontal
9920.00	18.17	23.83	42.00	54.00	-12.00	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor

2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Model: H601D

Test Results (1GHz-25GHz)

Test Mode: CH00			Test channel: Lowest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	28.60	15.27	43.87	74.00	-30.13	Vertical
7206.00	28.64	18.09	46.73	74.00	-27.27	Vertical
9608.00	29.54	23.76	53.30	74.00	-20.70	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	28.26	15.27	43.53	74.00	-30.47	Horizontal
7206.00	29.22	18.09	47.31	74.00	-26.69	Horizontal
9608.00	28.17	23.76	51.93	74.00	-22.07	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	16.87	15.27	32.14	54.00	-21.86	Vertical
7206.00	17.69	18.09	35.78	54.00	-18.22	Vertical
9608.00	19.01	23.76	42.77	54.00	-11.23	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	16.59	15.27	31.86	54.00	-22.14	Horizontal
7206.00	18.25	18.09	36.34	54.00	-17.66	Horizontal
9608.00	17.68	23.76	41.44	54.00	-12.56	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH19			Test channel: Middle			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	28.15	15.42	43.57	74.00	-30.43	Vertical
7320.00	28.61	18.02	46.63	74.00	-27.37	Vertical
9760.00	29.04	23.80	52.84	74.00	-21.16	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	28.07	15.42	43.49	74.00	-30.51	Horizontal
7320.00	29.09	18.02	47.11	74.00	-26.89	Horizontal
9760.00	27.89	23.80	51.69	74.00	-22.31	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	16.96	15.42	32.38	54.00	-21.62	polarization
7320.00	17.55	18.02	35.57	54.00	-18.43	Vertical
9760.00	18.86	23.80	42.66	54.00	-11.34	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	16.70	15.42	32.12	54.00	-21.88	Vertical
7320.00	18.60	18.02	36.62	54.00	-17.38	Horizontal
9760.00	17.98	23.80	41.78	54.00	-12.22	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH39			Test channel: Highest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	28.28	15.58	43.86	74.00	-30.14	Vertical
7440.00	28.77	17.93	46.70	74.00	-27.30	Vertical
9920.00	29.74	23.83	53.57	74.00	-20.43	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	28.21	15.58	43.79	74.00	-30.21	Horizontal
7440.00	29.30	17.93	47.23	74.00	-26.77	Horizontal
9920.00	28.27	23.83	52.10	74.00	-21.90	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	18.08	15.58	33.66	54.00	-20.34	Vertical
7440.00	18.82	17.93	36.75	54.00	-17.25	Vertical
9920.00	19.51	23.83	43.34	54.00	-10.66	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	17.88	15.58	33.46	54.00	-20.54	Horizontal
7440.00	19.40	17.93	37.33	54.00	-16.67	Horizontal
9920.00	18.13	23.83	41.96	54.00	-12.04	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor

2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Test Mode: Lowest (CH00)



Peak Value(Vertical)



Peak Value(Horizontal)

Test Mode: Highest (CH39)



Peak Value(Vertical)



Peak Value(Horizontal)

Average:

Test Channel	Peak Value (dBuV/m)	Correction factor	Average Value (dBuV/m)	Limit (dBuV/m)	Polarization	Verdict
CH00	38.807	-3.95	34.861	54.00	Vertical	Pass
	38.946	-3.95	35.000	54.00	Horizontal	Pass
CH39	43.572	-3.95	39.626	54.00	Vertical	Pass
	42.724	-3.95	38.778	54.00	Horizontal	Pass

Remark:

1. Correction factor=20log(Duty Cycle)
2. Average Value=Peak Value+Correction factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW ≥DTS bandwidth.
2. Set the VBW≥3*RBW.
3. Set the span≥ 3*RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Pass

Please refer to Appendix C of the Appendix Test Data.

Additional test for duty cycle.

Please refer to Appendix G of the Appendix Test Data.

6. 6dB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	≥500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
   RBW = 100kHz, VBW≥3*RBW
   Detector= Peak
   Trace mode= Max hold.
   Sweep- auto couple.
4. Mark the peak frequency and –6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data

Pass

Please refer to Appendix A of the Appendix Test Data.

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3kHz

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW ≥ 3*RBW, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Pass

Please refer to Appendix D of the Appendix Test Data.

8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to Appendix E & Appendix F of the Appendix Test Data.

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

9.2. Antenna Connected Construction

The antenna is a FPC Antenna which permanently attached, and the best case gain of the antenna is 5.12dBi . It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

---------- End of Report ----------